


## Klean-Strip MEK Substitute



HEALTH	-	1
FLAMMABILITY	3	
PHYSICAL	0	
PPE	X	



Printed: 07/05/2011  
Revision: 06/01/2011

### 1. Product and Company Identification

**Product Code:** 1636

**Product Name:** Klean-Strip MEK Substitute

**Manufacturer Information**

**Company Name:** W. M. Barr  
2105 Channel Avenue  
Memphis, TN 38113

**Phone Number:** (901)775-0100

**Emergency Contact:** 3E 24 Hour Emergency Contact (800)451-8346

**Information:** W.M. Barr Customer Service (800)398-3892

**Web site address:** www.wmbarr.com

**Preparer Name:** W.M. Barr EHS Dept (901)775-0100

**Synonyms**  
GME71SUB, QME71SUB, CME71SUB

### 2. Composition/Information on Ingredients

Hazardous Components (Chemical Name)	CAS #	Concentration	OSHA PEL	ACGIH TLV	Other Limits
1. Acetic acid, ethyl ester {Ethyl acetate}	141-78-6	100.0 %	400 ppm	400 ppm	No data.
Hazardous Components (Chemical Name)	RTECS #	OSHA STEL	OSHA CEIL	ACGIH STEL	ACGIH CEIL
1. Acetic acid, ethyl ester {Ethyl acetate}	AH5425000	No data.	No data.	No data.	No data.

### 3. Hazards Identification

#### Emergency Overview

Warning! Flammable Liquid and Vapor.

High vapor concentrations may cause drowsiness and irritation of the eyes or respiratory tract.

Prolonged or repeated skin contact may cause drying, cracking, or irritation.

**Route(s) of Entry:** Inhalation? Yes Skin? Yes Eyes? Yes Ingestion? Yes

#### Potential Health Effects (Acute and Chronic)

No data available.

#### LD 50 / LC 50

Oral LD50 (rat) - 5,600 mg/kg

Inhalation LC50 (rat) - 6 h: 16,000 ppm

Dermal LD50 (rabbit) - >20 ml/kg (highest dose tested)

Skin irritation (rabbit) - very slight

Eye irritation (rabbit) - slight

Skin sensitization (human) - none

### Signs and Symptoms Of Exposure

No data available.

### Medical Conditions Generally Aggravated By Exposure

None known.

### OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

## 4. First Aid Measures

### Emergency and First Aid Procedures

Skin:

Immediately begin washing the skin thoroughly with large amounts of water and mild soap, if available, while removing contaminated clothing. Seek medical attention if irritation persists.

Eyes:

Immediately begin to flush eyes with water, remove any contact lens. Continue to flush the eyes for at least 15 minutes, then seek immediate medical attention.

Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

Ingestion:

If swallowed, do NOT induce vomiting. Seek immediate medical attention. Call a physician, hospital emergency room, or poison control center immediately. Never give anything by mouth to an unconscious person.

## 5. Fire Fighting Measures

**Flammability Classification:** NFPA Class 1B

**Flash Pt:** 24 F (-4.4 C) Method Used: TAG Closed Cup

**Explosive Limits:** LEL: 2.2 UEL: 9

**Autoignition Pt:** 490 C (905.0 F)

### Fire Fighting Instructions

Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up.

Water spray may be ineffective in fighting the fire.

### Flammable Properties and Hazards

Vapors may form explosive mixtures with air.

Vapors may travel to source of ignition and flash back.

Prevent buildup of vapors or gases to explosive concentrations.

### Hazardous Combustion Products

Decomposition may produce carbon monoxide and carbon dioxide.

### Extinguishing Media

Water spray, dry chemical, carbon dioxide or foam.

### Unsuitable Extinguishing Media

None known.

## 6. Accidental Release Measures

### Steps To Be Taken In Case Material Is Released Or Spilled

Clean up: Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources; keep flares, smoking or flames out of hazard area. Use non-sparking tools. Use proper bonding and grounding methods for all equipment and processes. Keep out of waterways and bodies of water. Be cautious of vapors collecting in small enclosed spaces, sewers, low lying areas, confined spaces, etc.

Small spills: Take up with sand, earth or other noncombustible absorbent material and place in a plastic container where applicable.

Large spills: Dike far ahead of spill for later disposal.

Waste Disposal: Dispose in accordance with applicable local, state and federal regulations.

## 7. Handling and Storage

### Precautions To Be Taken in Handling

AVOID BREATHING VAPOR

Avoid prolonged or repeated contact with skin.

Use with adequate ventilation.

Wash thoroughly with soap and water after handling.

Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.

Do not use this product near any source of heat or open flame, furnace areas, pilot lights, stoves, etc.

Do not use in small enclosed spaces, such as basements and bathrooms. Vapors can accumulate and explode if ignited.

Do not spread this product over large surface areas because fire and health safety risks will increase dramatically.

### Precautions To Be Taken in Storing

Keep away from heat, sparks and flame.

Keep container tightly closed.

Keep from contact with oxidizing materials.

## 8. Exposure Controls/Personal Protection

### Respiratory Equipment (Specify Type)

For use in areas with inadequate ventilation or fresh air, wear a properly maintained and properly fitted NIOSH approved respirator for organic solvent vapors.

For OSHA controlled work places and other regular users - Use only with adequate ventilation under engineered air control systems designed to prevent exceeding the appropriate TLV.

A dust mask does not provide protection against vapors.

### Eye Protection

Safety glasses should be worn during normal handling of this material.

Where contact with the eyes or face is likely, a faceshield or chemical splash goggles should be worn to prevent eye contact.

### Protective Gloves

Wear gloves with as much resistance to the chemical ingredients as possible. Glove materials such as nitrile rubber may provide protection. Glove selection should be based on chemicals being used and conditions of use. Consult your glove supplier for additional information. Gloves contaminated with product should be discarded and not reused.

### Other Protective Clothing

Various application methods can dictate use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure.

### Engineering Controls (Ventilation etc.)

Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

Use only with adequate ventilation to prevent buildup of vapors. Do not use in areas where vapors can accumulate and concentrate, such as basements, bathrooms or small enclosed areas. Whenever possible, use outdoors in an open air area. If using indoors open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering -- STOP -- ventilation is inadequate. Leave area immediately and move to fresh air.

### Work/Hygienic/Maintenance Practices

Clothing that becomes soiled with product should be removed as soon as possible and laundered separately.

Wash hands thoroughly after use and before eating, drinking, or smoking.

Do not eat, drink, or smoke in the work area.

Discard any clothing or other protective equipment that cannot be decontaminated.

Facilities storing or handling this material should be equipped with an emergency eyewash and safety shower.

# MATERIAL SAFETY DATA SHEET

## Klean-Strip MEK Substitute

Page: 5  
Printed: 07/05/2011  
Revision: 06/01/2011

### 9. Physical and Chemical Properties

**Physical States:** [ ] Gas [ X ] Liquid [ ] Solid

**Melting Point:** 83 C (181.4 F)

**Boiling Point:** 78 C (172.4 F)

**Autoignition Pt:** 490 C (905.0 F)

**Flash Pt:** 24 F (-4.4 C) Method Used: TAG Closed Cup

**Explosive Limits:** LEL: 2.2 UEL: 9

**Specific Gravity (Water = 1):** .8955 - .8985

**Density:** 7.44 - 7.468 LB/GL

**Vapor Pressure (vs. Air or mm Hg):** 75 MM HG at 68 F (20.0 C)

**Vapor Density (vs. Air = 1):** 3.04 (Air=1)

**Evaporation Rate (vs Butyl Acetate=1):** 4.1

**Solubility in Water:** 64 g/l at 25 C (77.0 F)

**Percent Volatile:** 100 % by weight.

**VOC / Volume:** 900 G/L

**HAP / Volume:** NP

**Viscosity:** .44 CP at 25 C (77.0 F)

**Octanol/Water Partition Coefficient:** 0.73

**Appearance and Odor**  
Clear liquid, sweet odor

### 10. Stability and Reactivity

**Stability:** Unstable [ ] Stable [ X ]

**Conditions To Avoid - Instability**  
No data available.

**Incompatibility - Materials To Avoid**  
Incompatible with strong oxidizing agents.

**Hazardous Decomposition Or Byproducts**  
No data available.

**Hazardous Polymerization:** Will occur [ ] Will not occur [ X ]

**Conditions To Avoid - Hazardous Polymerization**  
No data available.

### 11. Toxicological Information

Refer to Hazards Section

#### Chronic Toxicological Effects

No data available.

Hazardous Components (Chemical Name)	CAS #	NTP	IARC	ACGIH	OSHA
1. Acetic acid, ethyl ester {Ethyl acetate}	141-78-6	n.a.	n.a.	n.a.	n.a.

### 12. Ecological Information

Oxygen Demand Data

BOD-5 1,240 mg/g

BOD-20 1,240 mg/g

# MATERIAL SAFETY DATA SHEET

## Klean-Strip MEK Substitute

Page: 6  
Printed: 07/05/2011  
Revision: 06/01/2011

BOD-20 1,430 mg/g

COD 1,540 mg/g

ThBOD 1,820 mg/g

Acute Aquatic Effects Data

48 h LC-50 (golden orfe) 270 mg/l

48 h LC-50 (golden orfe) 333 mg/l

24 h LC-50 (daphnid) 3,090 mg/l

24 h EC-50 (daphnid) 3,090 mg/l

### 13. Disposal Considerations

#### Waste Disposal Method

Dispose in accordance with applicable local, state and federal regulations.

**RCRA Waste ID Code:** D001

### 14. Transport Information

#### LAND TRANSPORT (US DOT)

**DOT Proper Shipping Name** Ethyl acetate  
**DOT Hazard Class:** 3  
**DOT Hazard Label:** FLAMMABLE LIQUID  
**UN/NA Number:** UN1173  
**Packing Group:** II

#### Additional Transport Information

For D.O.T. information, contact W.M. Barr Technical Services at 1-800-398-3892.

The shipper/supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

### 15. Regulatory Information

#### US EPA SARA Title III

Hazardous Components (Chemical Name)	CAS #	Sec.302 (EHS)	Sec.304 RQ	Sec.313 (TRI)	Sec.110
1. Acetic acid, ethyl ester {Ethyl acetate}	141-78-6	No	Yes 5000 LB	No	No

#### US EPA CAA, CWA, TSCA

Hazardous Components (Chemical Name)	CAS #	EPA CAA	EPA CWA NPDES	EPA TSCA	CA PROP 65
1. Acetic acid, ethyl ester {Ethyl acetate}	141-78-6	HAP, ODC ()	No	Inventory	No

#### SARA (Superfund Amendments and Reauthorization Act of 1986) Lists:

**Sec.302:** EPA SARA Title III Section 302 Extremely Hazardous Chemical with TPQ. \* indicates 10000 LB TPQ if not volatile.

# MATERIAL SAFETY DATA SHEET

## Klean-Strip MEK Substitute

Page: 7  
Printed: 07/05/2011  
Revision: 06/01/2011

**Sec.304:** EPA SARA Title III Section 304: CERCLA Reportable + Sec.302 with Reportable Quantity. \*\* indicates statutory RQ.

**Sec.313:** EPA SARA Title III Section 313 Toxic Release Inventory. Note: -Cat indicates a member of a chemical category.

**Sec.110:** EPA SARA 110 Superfund Site Priority Contaminant List

### TSCA (Toxic Substances Control Act) Lists:

**Inventory:** Chemical Listed in the TSCA Inventory.

**5A(2):** Chemical Subject to Significant New Rules (SNURS)

**6A:** Commercial Chemical Control Rules

**8A:** Toxic Substances Subject To Information Rules on Production

**8A CAIR:** Comprehensive Assessment Information Rules - (CAIR)

**8A PAIR:** Preliminary Assessment Information Rules - (PAIR)

**8C:** Records of Allegations of Significant Adverse Reactions

**8D:** Health and Safety Data Reporting Rules

**8D TERM:** Health and Safety Data Reporting Rule Terminations

**12(b):** Notice of Export

### Other Important Lists:

**CWA NPDES:** EPA Clean Water Act NPDES Permit Chemical

**CAA HAP:** EPA Clean Air Act Hazardous Air Pollutant

**CAA ODC:** EPA Clean Air Act Ozone Depleting Chemical (1=CFC, 2=HCFC)

**CA PROP 65:** California Proposition 65

### International Regulatory Lists:

### EPA Hazard Categories:

This material meets the EPA 'Hazard Categories' defined for SARA Title III Sections 311/312 as indicated:

☒ Yes ☐ No Acute (immediate) Health Hazard

☐ Yes ☒ No Chronic (delayed) Health Hazard

☒ Yes ☐ No Fire Hazard

☐ Yes ☒ No Sudden Release of Pressure Hazard

☐ Yes ☒ No Reactive Hazard

## 16. Other Information

### Company Policy or Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

**N.A.=Not available, N.P.=Not applicable, N.D.=Not determined, N.E.=Not established, N.R.=Not required**