

ITW Permatex  
 10 Columbus Blvd.  
 Hartford, CT 06106 USA  
 Telephone: 1-87-Permatex  
 (877) 376-2839  
 Emergency: 800-255-3924 (ChemTel)  
 International Emergency: +01-813-248-0585

## Material Safety Data Sheet

### 1. PRODUCT IDENTIFICATION

**Product Name:** SA-8 BATTERY CLEANER 5 OZ AE  
**Item No:** 80369  
**Product Type:** Aerosol cleaner

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	ACGIH; TLV-TWA	OSHA PEL
WATER 7732-18-5	>75	Not listed	Not listed
BUTANE 106-97-8	<7	1000 ppm	800 ppm; 1900 mg/m <sup>3</sup>
2-BUTOXYETHANOL 111-76-2	<5	20 ppm	50 ppm; 240 mg/m <sup>3</sup>
PROPANE 74-98-6	<5	1000 ppm	1000 ppm; 1800 mg/m <sup>3</sup>

### 3. HAZARDS IDENTIFICATION

**Toxicity:** Exposure to 2-butoxyethanol can cause nausea, dizziness, vomiting, malaise, incoordination, diarrhea, weakness, eye redness and swelling of conjunctiva.  
**Primary Routes of Entry:** Eye and skin contact, ingestion, inhalation  
**Signs and Symptoms of Exposure:** Excessive accidental exposure may cause headache, dizziness, nausea and mild respiratory irritation. May cause pain, redness or swelling of the eyes and excessive blinking and tear production. Skin: Exposure may cause mild skin irritation. Prolonged or repeated exposure may dry the skin. Symptoms may include redness, burning, drying, cracking and skin burns. Preexisting skin disorders may be aggravated by exposure. .

Component	Weight%	NTP	ACGIH Carcinogens	IARC Carcinogen
2-BUTOXYETHANOL 111-76-2	<5	male rat-no evidence; female rat-equivocal evidence; male mice- some evidence; female mice-some evidence	A3	Group 3; Monograph 88, 2006

**Aggravated Medical Condition:** Persons with preexisting respiratory, liver, kidney, eye or skin diseases may be adversely affected.

### 4. FIRST AID MEASURES

**Ingestion:** If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention.  
**Inhalation:** Move to fresh air in case of accidental inhalation of vapours. If not breathing, give artificial respiration. Obtain medical attention.  
**Skin Contact:** Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. If skin irritation persists, call a physician.  
**Eye Contact:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

### 5. FIRE FIGHTING MEASURES

**Flash Point °F(C°):** No flame projection  
**Recommended Extinguishing Media:** Carbon Dioxide, Dry Chemicals, Foam.  
**Special Fire-Fighting Procedures:** Firefighters should wear self-contained breathing apparatus. Keep containers cool. Use equipment or shielding required to protect against bursting or venting of containers. Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool.  
**Hazardous Products of Combustion:** Oxides of carbon

**5. FIRE FIGHTING MEASURES****Unusual Fire/Explosion Hazards:**

Contents under pressure. Exposure to temperatures over 120 degrees F. may cause bursting or venting. Keep containers cool. Use equipment or shielding to protect personnel from bursting containers.

**Lower Explosive Limit:**

Not determined

**Upper Explosive Limit:**

Not determined

**6. ACCIDENTAL RELEASE MEASURES****Spill Procedures:**

Eliminate all sources of ignition. Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

**7. HANDLING AND STORAGE****Storage:**

Store away from heat, sparks or open flame. Do not store at temperatures above 100°F (38°C).

**Handling:**

Do not use near heat, sparks or open flame. Do not inhale vapors. Avoid contact with skin and eyes. Wash hands before eating and smoking.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Eyes:**

Safety glasses.

**Skin:**

Neoprene or nitrile gloves recommended.

**Ventilation:**

General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.

**Respiratory Protection:**

An approved organic vapor respirator should be worn when exposures are expected to exceed the applicable limits.

**9. PHYSICAL AND CHEMICAL PROPERTIES****Appearance:**

White foam

**Odor:**

Solvent

**Boiling Point:**

>200°F

**pH:**

7.5-8.5

**Solubility in Water:**

Soluble

**Specific Gravity:**

0.95-1.05

**VOC(Wt.%):**

13%

**Vapor Pressure:**

Not determined

**Vapor Density (Air=1):**

>1

**Evaporation Rate:**

<1 (butyl acetate = 1)

**10. STABILITY AND REACTIVITY****Chemical Stability:**

Stable at normal conditions

**Hazardous Polymerization:**

Will not occur

**Incompatibilities:**

Strong oxidizers

**Conditions to Avoid:**

Keep away from heat, sparks and open flame.

**Hazardous Products of Combustion:**

Oxides of carbon

**11. TOXICOLOGICAL INFORMATION**

See Section 3

**12. ECOLOGICAL INFORMATION**

No data available

**13. DISPOSAL CONSIDERATIONS****Recommended Method of Disposal:**

Disposal should be made in accordance with federal, state and local regulations. This container may be recycled in aerosol recycling centers. Before offering for recycling, empty the can by using the product according to the label. If recycling is not available, wrap the container and discard in the trash.

**US EPA Waste Number:**

D001 as per 40CFR 261.21

**14. TRANSPORTATION INFORMATION****DOT (49CFR 172)****U.S. Department of Transportation - DOT - 49 CFR (Ground)****DOT Shipping Name:**

Aerosols, Limited Quantity

**Hazard Class:**

Class 2.2

**UN/ID Number:**

UN 1950

## 14. TRANSPORTATION INFORMATION

### IATA (Air)

**Proper Shipping Name:** Consumer Commodity (Not more than 1 liter)  
**Class or Division:** Class 9  
**UN/ID Number:** ID 8000

### IMDG (Vessel)

**Proper Shipping Name:** Aerosols, Limited Quantity  
**Hazard Class:** Class 2.2  
**UN Number:** UN 1950

**Marine Pollutant:** None

## 15. REGULATORY INFORMATION

**SARA 313 Chemicals:** The following component(s) is listed as a SARA Section 313 Toxic Chemical.

2-Butoxyethanol

**California Proposition 65:** WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm

**TSCA Inventory Status:** All components of this product are listed (or exempt) on the EPA TSCA inventory.

## 16. OTHER INFORMATION

**Estimated NFPA Rating:** HEALTH 1, FLAMMABILITY 2, REACTIVITY 0.

**Estimated HMIS Classification:** HEALTH 1, FLAMMABILITY 2, PHYSICAL HAZARD 0

(NFPA is a registered trademark of the National Fire Protection Association)

HMIS is a registered trademark of the National Paint and Coatings Association

**Prepared By:** Denise Boyd, Manager-Environmental, Health & Safety  
**Company:** ITW Permatex 10 Columbus Blvd. Hartford, CT USA 06106  
**Telephone No.:** 1-87-Permatex (877) 376-2839

**Revision Date:** March 29, 2012  
**Revision Number:** 3