

Permatex, Inc.  
 10 Columbus Blvd.  
 Hartford, CT 06106 USA  
 Telephone: 1-87-Permatex  
 (877) 376-2839  
 Emergency: 800-255-3924  
 International Emergency: +01-813-248-0585

## Material Safety Data Sheet

### 1. PRODUCT IDENTIFICATION

**Product Name:** SA9 BATTERY PROTECTOR & SEALER 5 OZ AE  
**Item No:** 80370  
**Product Type:** Aerosol coating

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	ACGIH; TLV-TWA	OSHA PEL
XYLENE 1330-20-7	15-40	100 ppm	100 ppm; 435 mg/m <sup>3</sup>
ACETONE 67-64-1	15-40	500 ppm	1000 ppm; 2400 mg/m <sup>3</sup>
PROPANE 74-98-6	15-40	1000 ppm	1000 ppm; 1800 mg/m <sup>3</sup>
MINERAL OIL 8042-47-5	<10	5 mg/m <sup>3</sup> TWA (oil mist) ACGIH	Not listed
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT 64742-47-8	<10	Not listed	Not listed
ETHYL BENZENE 100-41-4	<5	100 ppm	100 ppm; 435 mg/m <sup>3</sup>

### 3. HAZARDS IDENTIFICATION

**Toxicity:** Exposure to vapors or mist may result in irritation of the respiratory tract. Long term exposure to high concentrations of vapor may cause lung, liver or kidney damage. May cause eye and skin irritation. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage (sometimes referred to as "solvent" or "painter's syndrome"). Symptoms include fatigue, concentration difficulties, anxiety, depression, rapid mood swings, and short-term memory loss. Deliberately concentrating and inhaling the vapor may be harmful or fatal.

**Primary Routes of Entry:** Eye and skin contact, ingestion, inhalation

**Signs and Symptoms of Exposure:** Excessive overexposure may cause giddiness, dizziness, headache, nausea and in extreme cases, unconsciousness and respiratory depression. May cause redness to eyes and irritation to nasal passages.

Component	Weight%	NTP	ACGIH Carcinogens	IARC
XYLENE 1330-20-7	15-40	male rat-no evidence; female rat-no evidence; male mice- no evidence; female mice-no evidence	A4 - Not Classifiable as a Human Carcinogen	Group 3: Monograph 71, 1999; Monograph 47, 1989
ACETONE 67-64-1	15-40	Not known	A4 - Not Classifiable as a Human Carcinogen	
ETHYL BENZENE 100-41-4	<5	male rat-clear evidence; female rat- some evidence; male mice-some evidence; female mice-some evidence	A3 Confirmed animal carcinogen with unknown relevance to humans	Group 2B Monograph 77, 2000

**Medical Conditions Recognized as Being Aggravated by Exposure:** Heart disease, respiratory disorders, liver and kidney diseases, anemia, rhythm disorders of the heart. Preexisting eye, skin and respiratory disorders may be aggravated by overexposure to this product.

### 4. FIRST AID MEASURES

**Ingestion:** Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.

#### 4. FIRST AID MEASURES

<b>Inhalation:</b>	Move to fresh air in case of accidental inhalation of vapours. Oxygen or artificial respiration if needed. Obtain medical attention.
<b>Skin Contact:</b>	Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
<b>Eye Contact:</b>	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

#### 5. FIRE FIGHTING MEASURES

<b>Flash Point °F(C°):</b>	<0°F
<b>Recommended Extinguishing Media:</b>	Carbon Dioxide, Dry Chemicals, Foam.
<b>Special Fire-Fighting Procedures:</b>	Firefighters should wear self-contained breathing apparatus. Keep containers cool. Use equipment or shielding required to protect against bursting or venting of containers. Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool.
<b>Hazardous Products of Combustion:</b>	Oxides of carbon, Irritating vapors
<b>Unusual Fire/Explosion Hazards:</b>	Contents under pressure Exposure to temperatures over 120 degrees F. may cause bursting or venting Use equipment or shielding to protect personnel from bursting containers
<b>Lower Explosive Limit:</b>	1.0%
<b>Upper Explosive Limit:</b>	12.8%

#### 6. ACCIDENTAL RELEASE MEASURES

<b>Spill Procedures:</b>	Eliminate all sources of ignition. Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.
--------------------------	--

#### 7. HANDLING AND STORAGE

<b>Storage:</b>	Store away from heat, sparks or open flame. Do not store at temperatures above 100°F (38°C). Exposure to high temperatures may cause container to burst.
<b>Handling:</b>	Avoid contact with skin and eyes. Do not inhale vapors. Intentionally concentrating and inhaling the vapor may be harmful or fatal. Use only in a well ventilated area. Extinguish all flames, pilot lights and heaters. Turn off stoves, electric tools and appliances, and other sources of ignition. Vapors may accumulate readily and may ignite explosively. Do not puncture or incinerate container. Wash thoroughly after handling.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

<b>Eyes:</b>	Safety glasses.
<b>Skin:</b>	Neoprene or nitrile gloves recommended.
<b>Ventilation:</b>	General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.
<b>Respiratory Protection:</b>	An approved organic vapor respirator should be worn when exposures are expected to exceed the applicable limits.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance:</b>	Purple liquid
<b>Odor:</b>	Solvent
<b>Boiling Point:</b>	>100°F
<b>pH:</b>	Does not apply
<b>Solubility in Water:</b>	Nil
<b>Specific Gravity:</b>	0.835
<b>VOC(Wt.%):</b>	45%
<b>Vapor Pressure:</b>	Not determined
<b>Vapor Density (Air=1):</b>	>1
<b>Evaporation Rate:</b>	>1 (butyl acetate = 1)

#### 10. STABILITY AND REACTIVITY

<b>Chemical Stability:</b>	Stable at normal conditions
<b>Hazardous Polymerization:</b>	Will not occur
<b>Incompatibilities:</b>	Strong oxidizers
<b>Conditions to Avoid:</b>	Heat
<b>Hazardous Products of Combustion:</b>	Oxides of carbon, Irritating vapors

## 11. TOXICOLOGICAL INFORMATION

See Section 3

## 12. ECOLOGICAL INFORMATION

No data available

## 13. DISPOSAL CONSIDERATIONS

**Recommended Method of Disposal:** Disposal should be made in accordance with federal, state and local regulations.. This container may be recycled in aerosol recycling centers. Before offering for recycling, empty the can by using the product according to the label. If recycling is not available, wrap the container and discard in the trash.

**US EPA Waste Number:** D001 as per 40CFR 261.21

## 14. TRANSPORTATION INFORMATION

### DOT (49CFR 172)

#### Ground Transport (DOT)

**DOT Shipping Name:** Consumer Commodity (not more than one liter)  
**Hazard Class:** ORM-D  
**UN/ID Number:** None

### IATA

**Proper Shipping Name:** Consumer Commodity (Not more than 1 liter)  
**Class or Division:** Class 9  
**UN/ID Number:** ID 8000

### IMDG

**Proper Shipping:** Aerosols, Limited Quantity  
**Hazard Class:** Class 2.1  
**UN Number:** UN 1950

**Marine Pollutant:** None

## 15. REGULATORY INFORMATION

**SARA 313 Chemicals:** The following component(s) is listed as a SARA Section 313 Toxic Chemical.

XYLENE, ETHYL BENZENE

**California Proposition 65:** WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm

**TSCA Inventory Status:** All components of this product are listed (or exempt) on the EPA TSCA inventory.

## 16. OTHER INFORMATION

**Estimated NFPA Rating:** HEALTH 2, FLAMMABILITY 4, REACTIVITY 0.

**Estimated HMIS Classification:** HEALTH 2, FLAMMABILITY 4, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

**Prepared By:** Denise Boyd, Manager-Environmental, Health & Safety  
**Company:** Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA 06106

**Revision Date:** May 27, 2010

**Revision Number:** 5

**Telephone No.:** 1-87-Permatex (877) 376-2839