

LG - White Lithium Grease

MSDS Number: LG - aerosol Revision Date: 05/01/12

Page 1 of 6

PRODUCT AND COMPANY IDENTIFICATION

Product Name: LG - White Lithium Grease

Revision Date: 05/01/12
MSDS Number: LG - aerosol
Product Code: 16-LG, 16LG-THD

Manufacturer: The Blaster Corporation

8500 Sweet Valley Drive Valley View, Ohio 44125

(216) 901-5800 (216) 901-5801 fax

www.blasterproducts.com

24 Hour emergency contact: Chemtrec (800) 424-9300

CHEMICAL	CAS #	OSHA PEL	ACGIH TLV	Wt %	
Heptane	142-82-5	400ppm	400ppm	20 - 30	
Liquefied Petroleum Gas (Propellant)	68476-86-8	1000ppm	1000ppm	10 - 20	
Lubricating Oils, Petroleum Mixture**		N/A	N/A	10 - 20	
Castor Oil, Hydrogenated,	64754-95-6	N/A	N/A	1 - 5	
Titanium Dioxide	13463-67-7	N/A	N/A	<1	
Zinc Oxide	1314-13-2	N/A	N/A	<1	

**The base oil for this product can be a mixture of any of the following highly refined petroleum streams:

CAS 64741-88-4; CAS 64741-89-5; CAS 64741-95-3; CAS 64741-96-4; CAS64741-97-5; CAS64742-01-4; CAS 64742-52-5; CAS 64742-53-6; CAS 64742-54-7; CAS 64742-55-8; CAS 64742-56-9; CAS 64742-57-0; CAS 64742-62-7; CAS64742-63-8; CAS 64742-65-0; CAS 72623-83-7; CAS 72623-85-9; CAS 72623-86-0; CAS 72623-87-1



LG - White Lithium Grease

MSDS Number: LG - aerosol Revision Date: 05/01/12

Page 2 of 6

3 HAZARDS IDENTIFICATION

Route of Entry: Eyes, skin, inhalation, ingestion

Target Organs:

Inhalation: Inhalation of vapors or spray mist may cause headaches, and/or nose and throat irritation.

Skin Contact: Repeated or prolonged contact with skin may produce redness, irritation and/or dryness. May

cause or aggravate dermatitis or other existing skin condition.

Eye Contact: May cause immediate or delayed irritation. Irritation may show up as redness and/or swelling. May

cause corneal damage.

Ingestion: Ingestion may cause irritation to the mouth, esophagus, and/or stomach.

Signs or Overexposure: Irritation of eyes, nose, throat, digestive tract.

Pre-existing Conditions Aggravated: Skin and respiratory disorders. Alcoholism,

kidney, liver, cardiovascular and nervous system

CAUTION! CONTENTS UNDER PRESSURE EXTREMELY FLAMMABLE

4 FIRST AID MEASURES

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

Continue to monitor. Get medical attention.

Skin Contact: Remove contaminated clothing immediately! Wash skin with soap and water. If irritation develops,

seek medical attention.

Eye Contact: Flush eye(s) with water for 15 minutes. Get medical attention. If eye irritation persists, obtain

medical treatment.

Ingestion: Do not induce vomiting. Get medical attention immediately.

5 FIRE FIGHTING MEASURES

Flash point: <0°F*

Extinguishing Media: Dry chemical, carbon dioxide or foam is recommended. Water spray may be used to cool containers or structures.

General Fire and Explosion Hazards: This material may be ignited by heat, sparks (static electricity), flame or other ignition sources. Vapors are heavier than air and will collect in low areas (sewers) and can travel considerable distances. If containers are not cooled in a fire, they may explode.

Fire Fighting Procedures: Emergency responders should wear self-contained breathing apparatus. Wear other protective gear as conditions warrant. Keep unauthorized people out. Try to contain spills or leaks if it can be done safely. Material will float on water. Avoid spreading.

Unusual Fire & Explosion Hazard: Level 3 Aerosols - Contents Under Pressure

Special Fire Fighting Procedures:

At elevated temperatures (over 130F) aerosol container may burst, vent or rupture; use equipment or shielding to protect personnel. Cooling exposed containers with streams of water may be helpful.



LG - White Lithium Grease

MSDS Number: LG - aerosol Revision Date: 05/01/12

Page 3 of 6

6

ACCIDENTAL RELEASE MEASURES

Eliminate all sources of ignition and ventilate the area. Aerosol cans should be handled with caution. Sudden release of pressure could produce projectiles and atomized liquid. Leaking aerosol cans should be put into suitable container until the internal pressure has dissipated. Take precautions to prevent contamination of ground and surface waters. Do not flush into sewers or storm drains. Use suitable absorbents to collect liquid product. Consult regulations for the proper disposal of the container, liquid and absorbents.

7 HANDLING AND STORAGE

Handling Precautions: Use in accordance with good industrial workplace practices. Avoid unnecessary contact.

Wash thoroughly after handling. Use with good ventilation.

Storage Requirements: Store in a dry place away from excessive heat. Store containers with lids on and properly

labeled.

Do not store at temperatures above 120 degrees F.

8

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Protective Equipment:

Eye wash stations and emergency showers should be immediately available.

Eyes and Face: Standard safety glasses with splash shields typically offer adequate protection. Where excessive splashing or spraying is possible, a face shield should be

used.

Skin and clothing: Excessive contact should be avoided. Nitrile gloves, boots and aprons will provide adequate protection when contact cannot be avoided. Remove and wash any contaminated clothing immediately. Wash thoroughly after handling.

Respiratory: Good general ventilation should be sufficient to control airborne levels. Maintain airborne concentrations below OSHA established exposure limits of ingredients in Section 2.

Exposure Guidelines/Other:

The Blaster Corporation takes no responsibility for determining what measures are required for personal protection in any specific application. This information should be used with discretion.



LG - White Lithium Grease

MSDS Number: LG - aerosol Revision Date: 05/01/12

Page 4 of 6

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: white cream colored grease

Physical State:aerosolBoiling Point:180 - 200 FOdor:typical petroleumFreezing/Melting Pt.:not determined

pH: not determined Solubility: Slight

Vapor Pressure: not determined Spec Grav./Density: 0.7 (water = 1)

Vapor Density: >1 (air = 1)

Heat Value: not determined VOC: not determined Evap. Rate: >1 [NBA=1] **Bulk Density:** not determined Octanol: not determined Molecular Weight: not determined Particle Size: not applicable **Softening Point:** not applicable Viscosity: not determined **Percent Volatile:** not determined Sat. Vap. Concentrat.: not determined Molecular Formula: not determined

10 STABILITY AND REACTIVITY

Stability: This product is stable.

Conditions to avoid: Avoid excessive heat, sources of ingition and excessive water.

Materials to avoid (incompatability): Avoid strong oxidizers

Hazardous Decomposition products: Carbon monoxide, carbon dioxide and various hydrocarbons

Hazardous Polymerization: Will not occur.

11 TOXICOLOGICAL INFORMATION

Acute oral toxicity

Heptane LD 50 Rat: > 15,000 mg

Acute inhalation toxi

Heptane LC 50 Rat: 103 g/m3, 4 h

Acute dermal toxic

Heptane LD 50 Rabbit: > 2,001 mg/kg

No other toxicological information is available for this product or its components.



LG - White Lithium Grease

MSDS Number: LG - aerosol Revision Date: 05/01/12

Page 5 of 6

12

ECOLOGICAL INFORMATION

Ecological information on this product as a mixture has not been determined.

13

DISPOSAL CONSIDERATIONS

Used or unused product should be disposed of in accordance with local, state and federal regulations. Some special regulations may exist for the disposal of aerosol containers.

Empty containers may contain residual pressure and contents. They should be handled with the same precautions as the product.

14

TRANSPORT INFORMATION

Dept. of Transportation (DOT):

This product, as it leaves Blaster's facilities, meets the definitions set forth in CFR 49 part 173.150c as a "consumer commodity." Allowing for certain exceptions (173.156) for domestic surface (ground) shipments.

Proper shipping name: Consumer Commodity

Hazard class: ORM-D

International (IMO-IATA):

Proper shipping name: Aerosols, Limited Quantities **Hazard class:** 2.1 Flammable Compressed Gas

UN Number: 1950



LG - White Lithium Grease

MSDS Number: LG - aerosol Revision Date: 05/01/12

Page 6 of 6

15

REGULATORY INFORMATION

SARA 311/312:

Immediate (x) Delayed () Fire (x) Reactive () Sudden Release of Pressure (x)

Section 313

This product contains: Zinc Oxide 1314-13-2 <1% Heptane 142-82-5 20-30%

EPA Toxic Substances Control Act (TSCA) Status: All of the components of this product are listed on the TSCA inventory.

California Safe Drinking Water and Toxic Enforcement Act (Proposition 65): This product is not known to contain any chemicals currently listed as carcinogens or reproductive toxins under California Proposition 65.

VOC Regulations: This product complies with the consumer product VOC limits of CARB, the US EPA and states adopting the OTC VOC rules.

Consumer Product Safety Act General Conformity Certification: This product was evaluated by The Blaster Corporation, and is certified to be in compliance with the provisions of the Consumer Product Safety Act, the Federal Hazardous Substances Act and the Poison Prevention Packaging Act, as applicable. This product was manufactured at the location listed in Section 1 of this MSDS. The date of manufacture is stamped on the product container. No testing is required to certify compliance with the above.

16

OTHER INFORMATION

Manufacturer's Disclaimer:

To the best of our knowledge, the information contained herein is accurate. However, neither The Blaster Corporation nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exists.

HMIS Ratings

Health: 1 Fire: 4 Reactivity 0

END OF MSDS DOCUMENT