

## DESIGNER METALLIC Sprays

<b>DESCRIPTION</b>	Brilliant durable, metallic finishes for both indoor and outdoor use. Will not rub off. May be used on wood, metal, wicker, masonry, unglazed ceramics, plaster and clay.
<b>APPEARANCE</b>	High luster
<b>RECOMMENDED PRIMERS</b>	For superior adhesion and hiding and for bare wood or metal, apply a coat of American Accents Primer Spray.
<b>FILL WEIGHT</b>	11 oz. (312 g)
<b>SURFACE PREPARATION</b>	Remove loose paint and rust with a wire brush or sandpaper. Lightly sand glossy surfaces. Clean with soap and water, rinse and let fully dry.
<b>APPLICATION</b>	Use in a well ventilated area. Spraying can produce a fog that will travel. Protect surrounding area, clothing and skin from overspray. Shake can vigorously for one minute after the mixing ball begins to rattle. Shake often during use. Hold can upright 10-16 inches for the surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance for the surface and in motion while spraying. For best appearance, apply one light coat followed by one wet coat.
<b>CLEAN-UP</b>	When finished spraying, clear spray valve by turning can upside down and pushing spray button for 5 seconds. If valve clogs, twist and pull off spray tip and rinse it in a solvent such as mineral spirits. Do not stick a pin or other object into the stem. Throw away empty can in trash pickup. Do not burn or place in home trash compactor.

### PHYSICAL PROPERTIES (Calculated values are shown and may vary slightly from the actual manufactured material)

RESIN TYPE	Solvent Acrylic	
SOLVENTS	Xylene, Acetone, Toluene	
PRACTICAL COVERAGE	Approximately 10-12 sq. ft./can (.9-1.1 m <sup>2</sup> /can)	
DRY TIMES @70°F (21°C) and 50% RH		
	Touch	10 minutes
	Handle	30 minutes
	Recoat	Anytime
VOLATILE ORGANIC COMPOUND	<80%	
SHELF LIFE	5 years	

### SAFETY (For additional information, see MSDS)

FLASH POINT	-156° F (-144° C)
LEAD FREE	