HENKEL ADHESIVES CORPANI 740 TOLLGATE ROAD ELGIN IL 60 123 708-931-1100

VICTOR AUTOMOTIVE 501 S. WOLF RD. IL 60016 DES PLAINES

RUBBER DEMENT 652 + 651 erc Pro Parch INVOICE#: Kit

DATE 08/03/48

PAGE

24-HOUR EMERGENCY PHONE NO: CHEMTREC, 800/424-9300

MATERIAL SAFETY DATA SHEET

CHEMICAL NAME: NONE

TRADE NAME: HENKEL# RC-7818

CHEMICAL FAMILY:

FORMULAI

FOLYMER SOLUTION (FLAMMABLE)

MIXTURE

NAME! HEPTANE

CAS NUMBER:

142-82-5

OSHA PELI

ACGIH TLV: 400 PPM 500 PPM

OSHA STEL: 500 PPM

NAME: ETHYL ALCOHOL

CAS NUMBER:

64-17-5

ACBIH TLVI

1000 PPM

OSHA PEL:

1000 PFM

OSHA STEL:

% BY WEIGHT: 1.00

% BY WEIGHT:

92.00

并并并并并并并并并并并并并并并并并并并 PHYSICAL PROPERTIES DATA 并并并并并并并并并并并并并并并并并并并

BOILING POINT: 200 F SPECIFIC GRAVITY: 0.7 VAPOR PRESSURE (mm HG AT 20 DEG C): 76 PERCENT VOLATILE: 89% VAPOR DENSITY: 3.5 EVAPORATION RATE: 5.6 SOLUBILITY IN WATER: NIL

MATERIAL SAFETY DATA SHEET

SH: N/A
APPEARANCE AND ODOR: LIGHT YELLOW LIQUID WITH SOLVENT ODOR.

长效的铁铁铁铁头头头头头头头头头 FIRE AND EXPLOSION HAZARD DATA 米米米特特米米米米米米米米米

FLASH POINT & METHOD: 25 F
FLAMMABLE LIMITS: N/A
LEL%: 1.2
UEL%: 7.5
EXTINGUISHING MEDIA: CARBON DIOXIDE, DRY CHEMICAL, FOAM.
SPECIAL FIRE FIGHTING PROCEDURES:
WEAR SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACE MASK.
UNUSUAL FIRE & EXPLOSION HAZARDS:
VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL ALONG THE GROUND.
THIS COULD CAUSE IGNITION BY PILOT LIGHT, SPARKS, HEATERS,
SMOKING, ELECTRIC MOTOR, STATIC DISCHARGE OR OTHER IGNITION
SOURCES. NEVER WELD OR CUT EMPTY DRUMS.

经运动减长 英英英英英英英英英英英英英英英英 HEALTH HAZARD INFORMATION 美非美美英英英英英英英英英英英英英英英英英

THRESHOLD LIMIT VALUE: NOT KNOWN
PRIMARY ROUTES OF EXPOSURE:
EYE CONTACT: TEARING, BLURRED VISION
SKIN CONTACT: DRIED SKIN, IRRITATION POSSIBLE
INHALATION: HEADACHE, NAUSEA, VOMITING, NARCOSIS
INGESTION: NAUSEA
CHRONIC EFFECTS OF EXPOSURE:
ANEMIA, LIVER ABNORMALITIES, KIDNEY DAMAGE, LUNG DAMAGE

EYE FIRST AID:
FLUSH WITH WATER FOR 15 MINUTES. SEEK MEDICAL ATTENTION.
SKIN FIRST AID: WASH THOROUGHLY WITH SCAP AND WATER.
IF IRRITATION PERSISTS, SEEK MEDICAL ATTENTION.
INHALATION FIRST AID: REMOVE TO FRESH AIR. IF BREATHING IS
DIFFICULT, SEEK MEDICAL ATTENTION.
INGESTION FIRST AID:
IF CONSCIOUS, INDUCE VOMITING - SEEK MEDICAL ATTENTION.

STABLE OR UNSTABLE: STABLE
CONDITIONS TO AVOID: OPEN FLAME AND EXCESSIVE HEAT
INCOMPATIBILITY: STRONG DXIDIZING AGENTS
HAZARDOUS DECOMPOSITION PRODUCTS:
CARBON MONOXIDE, CARBON DIOXIDE, HYDROCARBONS
AND OTHER ACRID PRODUCTS OF COMBUSTION.

MATERIAL SAFETY DATA SHEET

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR CONDITIONS TO AVOID:

SPILL PROCEDURES: EXTINGUISH ALL SOURCES OF IGNITION. COLLECT ON SAFETY ABSORBENTS AND DISPOSE OF PROPERTY. DISPOSAL PROCEDURES: TREAT AS A FLAMMABLE WASTE IN COMPLIANCE WITH THE EPA REGULATIONS. DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

来来被要求关系来来来来来来来来来来来来来来,PROTECTIVE EQUIPMENT 和米特莱米斯基共和共共和共共和共共和共和共和共和

VENTILATION: RECOMMENDED RESPIRATORY PROTECTION: CHEMICAL FILTER MASK CARTRIDGE TYPE IS REQUIRED IF TLY IS EXCEEDED. PROTECTIVE CLOTHING: CHEMICALLY RESISTANT GLOVES SUCH AS NEOPRENE RUBBER. EYE PROTECTION: OSHA APPROVED FULL FACE MASK.

HANDLING & STORAGE PRECAUTIONS: TREAT AS A FLAMMABLE LIQUID, STORE IN ACCORDANCE WITH FEDERAL, STATE, LOCAL AND INSURANCE REBULATIONS AS PRESCRIBED CLASS I/GROUP D FLAMMABLE LIQUIDS. KEEP AWAY FROM SOURCES OF HEAT SUCH AS DIRECT SUN, BOILERS ETC. AVOID SPARKS AND OPEN FLAMES. SPECIAL COMMENTS: NON-HAZARDOUS INGREDIENTS WITHHELD UNDER PA TRADE SECRET STATUS.

EPA SARA TITLE III HAZARD CLASSI FLAMMABLE

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICALS SUBJECT TO THE REPORTING REQUIREMENTS OF EPA SARA TITLE III SECTION 313 (40CFR372):

CHEMICAL ETHYL ALCOHOL 64-17-5

CAS NUMBER WEIGHT PERCENT 1.00

THE INFORMATION SUPPLIED HEREIN RELATES TO THE PRODUCT NAMED AND IS BASED UPON INFORMATION HENKEL ADHESIVES BELIEVES TO BE ACCURATE. NO WARRANTY, EXPRESS OF IMPLIED, IS INTENDED. THIS INFORMATION IS OFFERED SOLELY FOR YOUR CONSIDERATION AND INTERPRETATION.

PREPARED BY: RONALKO LEONHARDT

DATE: 12/10/92