

*Estimate N/A-Not Applicable N/R-Not Restricted N/E-Not Established

MATERIAL SAFETY DATA SHEET

NOTE: BLANK SPACES ARE NOT PERMIT	ITED.	IF ANY ITEM	I IS NOT APPLIC	ABLE, TH	E SPACE MUS	T BE MARKED	TO INDICATE THAT.		
IDENTITY						PART NO.			
(As shown on Label or package) F971 & F975 RUBBER DIP SPRAY						IF APPLICABLE			
SECTION I									
MANUFACTURER'S						EMERGENCY			
NAME Plasti Dip International, Inc.						PHONE No. 1-800-424-9300			
ADDRESS (NUMBER, STREET, CITY, STATE AND ZIP CODE)						REVISION #			
3920 Pheasant Ridge Drive									
Dhina MNI 55440					MANUFACTURER'S PHONE No. FOR INFORMATION 1-763-785-2156				
Blaine, MN 55449						NO. FOR INFORMATION 1-763-783-2136			
						WAS PREPARED July 4, 2012			
SECTION II - HAZARDOUS INGREDIENTS INFORMATION. All Health Hazards which comprise 1% or greater of the composition and all									
carcinogens if 0.1% of the composition or greater.									
HAZARDOUS COMPONENTS CHEMICAL		% Wt.	CAS	NO	OSHA	ACGIH	OTHER LIMITS		
IDENTITY AND COMMON NAME (S)	una	(OPTIONAL			PEL	TLV	RECOMMEND		
Toluene		35-45	108-8	8-3	200 ppm	50 ppm	None		
VM&P Naphtha		30-40	64742-		300 ppm	300 ppm	None		
Hexane		8-12	110-5		500 ppm	50 ppm	None		
Methyl Ethyl Ketone		1-4	78-9	3-3	200 ppm	200 ppm	None		
Resins		12-15	N/.	1	N/A	N/A	None		
SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS									
BOILING	SPECIFIC GRAVITY (H ₂ 0 =1)				APPROXIMATE WEIGHT PER GALLON (LBS)				
POINT 149 - 285°F	0.8081				6.68 - 6-74				
VAPOR PRESSURE		R DENSITY			EVAPORATION RATE				
125 mmHg @ 20°C	(AIR = 1) Heavier than air				(BUTYL ACETATE =1) > 1.0				
SOLUBILITY IN WATER	% VOLATILE 85-88 %				OTHER				
Insoluble	VOC LBS./GAL 5.67 - 5.93				(IF ANY) None				
APPEARANCE									
AND ODOR Various Colors, Honey Like Substance - Characteristic Odor									
SECTION IV-FIRE AND EXPLOSION HAZARD DATA									
FLASH POINT -10.0°F		1	FLAMMABLE LI		LEL		UEL		
(METHOD USED) TCC			0.9 – 1	.5		0.9	11.5		
EXTINGUISHING									
MEDIA Carbon Dioxide, Dry Chemical, or Foam									
SPECIAL FIRE									
FIGHTING PROCEDURES Self contained breathing apparatus with a full face piece, operated in pressure demand or other positive pressure mode.									
EXPLOSION HAZARDS This material is flammable and may be ignited by heat, sparks, flame or static electricity.									
HAZARDOUS PRODUCTS FORMED BY									
FIRE OR THERMAL DECOMPOSITION Carbon Dioxide and/or Carbon Monoxide.									
EXPLOSIVE LIMITS									
(% BY VOLUME IN AIR) 0.9 - 11.5									
SECTION V - OPTIONAL HAZARD RATINGS IDENTIFICATION									
HAZARD RATING	National Fir	National Fire Protection Association (NFPA)							
4-EXTREME		FIRE <u>3</u> REACTIVITY <u>0</u> .							
3-HIGH	FIRE <u>3</u>								
2-MODERATE									
1-SLIGHT 0-INSIGNIFICANT	HEAT TH	HEALTH 2 SPECIAL HAZARDS None .							
**SEE SECTION IV		HEALTH <u>2</u> SI ECIAL HALAKUS <u>None</u> .							
			1						

This is the "front" when printed in duplex. Page 1 of 2 pages if not duplex.



SECTION VI - REACTIVITY AND STABILITY DATA							
STABILITY UNSTABLE STABLE X CONDITIONS TO AVOID None							
INCOMPATIBILITY (Materials to Avoid) Strong acids, bases, oxidizing agents, selected amines with alkali metals and halogens.							
HAZARDOUS DECOMPOSITION OR BY PRODUCTS Carbon Monoxide, Carbon Dioxide							
HAZARDOUS		ONS TO AVOID					
POLYMERIZATION	WILL NOT OCCUR X	None					
SECTION VII - HEALTH HAZARD DATA							
ROUTES OF ENTRY INHALATION? Yes SKIN? Yes INGESTION? Yes EYES? Yes							
HEALTH ACUTE							
HAZARDS CHRONIC	X Brain and Nervous System Damage (Referred to as solvents or painters syndrome). Drying or Cracking skin.						
CARCINOGENICITY: No							
SIGNS AND							
SYMPTOMS OF	Headache, Dizziness, Drowsiness, Fatigue, Irregular Heartbeat, Skin and Eye Irritation.						
EXPOSURE	Target Organs: CNS, CVS, PNS, Liver, Kidneys, Lungs	, Respiratory System, Skin.					
MEDICAL CONDITIONS GENE	RALLY AGGRAVATED BY EXPOSURE Pre-existing	Heart, Liver, Kidney and Lung disorders.					
EMERGENCY AND	Ingestion: Contact Physician or Poison Control Immedi						
FIRST AID	Inhalation: Remove to fresh air. Administer Oxygen or						
PROCEDURES	Eye Contact: Flush with large amounts of water. If irrit	ation persists, contact Physician.					
	Skin: Wash with soap and water.						
SECTION VIII - PRECAUTIONS	S FOR SAFE HANDLING AND USE						
STEPS TO BE TAKEN	Wipe up with floor absorbent. Transfer to hood. Prevent run-off to sewers. Eliminate all sources of ignition. Ventilate to maintain exposure below PEL's. Use sand or other material to dam						
IN CASE MATERIAL IS							
RELEASED OR SPILLED	or contain spills. If large spill, notify appropriate state a	nd local agencies.					
WASTE DISPOSAL METHODS	Dispose of product in accordance with local, county, state	and federal regulations					
WASTE DISCOSAL METHODS	Dispose of product in accordance with local, county, state						
PRECAUTIONS TO BE	BE Keep away from sparks, flame and heat sources. Do not store above 120°F and use adequate ventilation.						
TAKEN IN HANDLING	Avoid inhalation of vapors and contact with liquid prod						
AND STORAGE	Avoid initiation of vapors and contact with right product. Ose good personal hygicite.						
OTHER	ER Keep Container Closed When Not In Use. Containers should be disposed of in an environmentally safe manner						
PRECAUTIONS in accordance with Governmental Regulations.							
SECTION IX - CONTROL MEASURES							
RESPIRATORY PROTECTION	(SPECIFY TYPE) Depending on the Airborne concentrati	on, PROTECTIVE GLOVES					
use a Respirator with appropriate N	OSH approved cartridge or supplied air equipment.	Impervious					
VENTILATION LOCAL EX	KHAUST Supplemental (if needed)	SPECIAL None					
MECHANI	CAL (GENERAL) To maintain exposure below PEL's	OTHER None					
EYE PROTECTION		OTHER PROTECTIVE CLOTHING OR EQUIPMENT					
Chemical splash goggles or approve		Impervious Clothing/Boots as needed.					
WORK HYGIENIC PRACTICES Wash thoroughly after handling.							
SECTION X - TRANSPORTATION INFORMATION (Optional)							
D.O.T. PROPER SHIPPING NAME Coating Solution (UN 1139) D.O.T. HAZARD CLASS 3, PG II							
IATA PROPER SHIPPING NAME Coating Solution (UN 1139) IATA HAZARD CLASS 3, PG II							
DOT EXCEPTION See DOT 49CFR 172.102, New Special Provision 149 AND DOT 49CFR 171.8 FOR CONSUMER COMMODITY, ORM-D							
SECTION XI - 313 SUPPLIER NOTIFICATION							
	THIS PRODUCT CONTAINS THE FOLLOWING CHEMICALS SUBJECT TO REPORTING REQUIREMENTS OF SECTION 313 OF THE						
	· · · · · · · · · · · · · · · · · · ·	CFR 372 , (see table on page 1 for CAS # and percent by weight).					
Hexane, Toluene and Methyl Ethyl							
WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS, OR OTHER REPRODUCTIVE HARM							
DEFECTS, OR OTHER REPRODUCTIVE HARM. This is the "back" when printed in dupley. Page 2 of 2 pages if not dupley							

This is the "back" when printed in duplex. Page 2 of 2 pages if not duplex.

Prepared By: Mark Kenow

THE INFORMATION PROVIDED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THE DATA OR THE RESULTS OBTAINED FROM ITS USE. SINCE THE INFORMATION CONTAINED HEREIN MAY BE APPLIED UNDER CONDITIONS BEYOND THE VENDORS CONTROL AND SINCE SUBSEQUENT DATA MAY SUGGEST MODIFICATION OF THE INFORMATION, VENDOR ASSUMES NO RESPONSIBILITY FOR THE RESULTS OF ITS USE.