

MATERIAL SAFETY DATA SHEET

LevelQuik Latex Primer

Section 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: LevelQuik Latex Primer
Product Use: Primer.
Manufacturer/Supplier: Custom Building Products
13001 Seal Beach Blvd
Seal Beach, CA 90740
Phone Number: (562) 598-8808
Emergency Phone: INFOTRAC 1-800-535-5053 (US and Canada)
INTERNATIONAL + 1-352-323-3500
Date of Preparation: February 1, 2010 **Revision Date:** August 31, 2012

Section 2: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

CAUTION

MAY CAUSE EYE IRRITATION. MAY CAUSE SKIN IRRITATION.

Potential Health Effects: See Section 11 for more information.

Likely Routes of Exposure: Skin contact, eye contact, inhalation, and ingestion.

Eye: May cause eye irritation.

Skin: May cause skin irritation.

Ingestion: May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

Inhalation: May cause respiratory tract irritation.

Chronic Effects: Prolonged or repeated contact may dry skin and cause irritation.

Signs and Symptoms: Symptoms may include discomfort, excess blinking and tear production. Symptoms may include redness, drying, and cracking of the skin.

Medical Conditions Aggravated By Exposure: Asthma. Allergies.

Target Organs: Skin, eyes, gastrointestinal tract, respiratory system.

Potential Environmental Effects: May cause long-term adverse effects in the aquatic environment. See Section 12 for more information.

Section 3: COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	CAS #	Wt. %
None by WHMIS/OSHA criteria.		

Section 4: FIRST AID MEASURES

Eye Contact: In case of contact, immediately flush eyes with plenty of water. If easy to do, remove contact lenses, if worn.

Skin Contact: If irritation occurs, flush skin with plenty of water. Call a physician if irritation persists.

Inhalation: Remove person to fresh air. If symptoms persist, obtain medical attention.

Ingestion: If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.

MATERIAL SAFETY DATA SHEET

LevelQuik Latex Primer

General Advice: In case of accident or if you feel unwell, seek medical advice immediately (show the label or MSDS where possible).

Note to Physicians: Symptoms may not appear immediately.

Section 5: FIRE FIGHTING MEASURES

Flammability: Not flammable by WHMIS/OSHA criteria.

Means of Extinction:

Suitable Extinguishing Media: Powder, water spray, foam, carbon dioxide.

Unsuitable Extinguishing Media: Not available.

Products of Combustion: May include, and are not limited to: oxides of carbon.

Explosion Data:

Sensitivity to Mechanical Impact: Not available.

Sensitivity to Static Discharge: Not available.

Protection of Firefighters: Containers may explode when heated. Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

Section 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental Precautions: Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

Methods for Containment: Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for Clean-Up: Scoop up material and place in a disposal container.

Other Information: Not available.

Section 7: HANDLING AND STORAGE

Handling:

Avoid contact with skin and eyes. Do not swallow. Do not breathe gas/fumes/vapor/spray. Use only in well-ventilated areas. Handle and open container with care. When using do not eat or drink. Wash hands before eating, drinking, or smoking.

Storage:

Keep out of the reach of children. Keep container tightly closed in a cool place. Keep from freezing. Store away from light. Contents may develop pressure upon prolonged storage.

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Ingredient

Exposure Limits
OSHA-PEL ACGIH-TLV

Not applicable.

Engineering Controls: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

MATERIAL SAFETY DATA SHEET

LevelQuik Latex Primer

Personal Protective Equipment:

Eye/Face Protection: Wear eye/face protection.

Hand Protection: Wear suitable gloves.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: In case of insufficient ventilation, wear suitable respiratory equipment.

General Hygiene Considerations: Handle according to established industrial hygiene and safety practices.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Opaque.
Color:	White.
Odor:	Mild acrylic or SBR odor.
Odor Threshold:	Not available.
Physical State:	Liquid.
pH:	9.0-10.0
Viscosity:	Not available.
Freezing Point:	~ 0 °C (~ 32 °F).
Boiling Point:	~ 100 °C (~ 212 °F).
Flash Point:	Not available.
Evaporation Rate:	Not available.
Lower Flammability Limit:	Not available.
Upper Flammability Limit:	Not available.
Vapor Pressure:	Not available.
Vapor Density:	Not available.
Relative Density:	~ 1 g/mL.
Solubility in Water:	Miscible.
Coefficient of Water/Oil Distribution:	Not available.
Auto-ignition Temperature:	Not available.
Percent Volatile, wt. %:	~70%.
VOC content:	8 g/L (Calculated).

Section 10: STABILITY AND REACTIVITY

Stability: Stable under normal storage conditions. Protect from freezing.

Conditions of Reactivity: Heat. Incompatible materials.

Incompatible Materials: Oxidizers.

Hazardous Decomposition Products: May include, and are not limited to: oxides of carbon.

Possibility of Hazardous Reactions: No dangerous reaction known under conditions of normal use. Heat may cause pressure build-up in closed containers.

MATERIAL SAFETY DATA SHEET

LevelQuik Latex Primer

Section 11: TOXICOLOGY INFORMATION

EFFECTS OF ACUTE EXPOSURE

Component Analysis

Ingredient	LD ₅₀ (oral)	LC ₅₀
	Not applicable.	
Eye:	May cause eye irritation. Symptoms may include discomfort, excess blinking and tear production.	
Skin:	May cause skin irritation. Symptoms may include redness, drying, and cracking of the skin.	
Ingestion:	May be harmful if swallowed. May cause stomach distress, nausea or vomiting.	
Inhalation:	May cause respiratory tract irritation.	

EFFECTS OF CHRONIC EXPOSURE

Target Organs: Not available.

Chronic Effects: Not hazardous by WHMIS/OSHA criteria.

Carcinogenicity: Not hazardous by WHMIS/OSHA criteria.

Ingredient	Chemical Listed as Carcinogen or Potential Carcinogen *
	Not applicable.

* See Section 15 for more information.

Mutagenicity: Not hazardous by WHMIS/OSHA criteria.

Reproductive Effects: Not hazardous by WHMIS/OSHA criteria.

Developmental Effects:

Teratogenicity: Not hazardous by WHMIS/OSHA criteria.

Embryotoxicity: Not hazardous by WHMIS/OSHA criteria.

Respiratory Sensitization: Not hazardous by WHMIS/OSHA criteria.

Skin Sensitization: Not hazardous by WHMIS/OSHA criteria.

Toxicologically Synergistic Materials: Not available.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity: May cause long-term adverse effects in the aquatic environment.

Persistence / Degradability: Not available.

Bioaccumulation / Accumulation: Not available.

Mobility in Environment: Not available.

Section 13: DISPOSAL CONSIDERATIONS

Disposal Instructions:

This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

MATERIAL SAFETY DATA SHEET

LevelQuik Latex Primer

Section 14: TRANSPORTATION INFORMATION

DOT Classification

Not regulated

TDG Classification

Not regulated

Section 15: REGULATORY INFORMATION

Federal Regulations

Canadian: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

US: MSDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200).

SARA Title III

Ingredient

**Section 302
(EHS) TPQ (lbs.)**

**Section 304
EHS RQ (lbs.)**

**CERCLA
RQ (lbs.)**

**Section
313**

Not applicable.

State Regulations

California Proposition 65:

This product contains a chemical known to the state of California to cause cancer.

Global Inventories

Ingredient

**Canada
DSL/NDSL**

**USA
TSCA**

All ingredients are on DSL/NDSL & TSCA inventories.

HMIS - Hazardous Materials Identification System

Health - 1

Flammability - 0

Physical Hazard - 0

PPE - B

NFPA - National Fire Protection Association:

Health - 1

Fire - 0

Reactivity - 0

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

WHMIS Classification(s):

Not controlled.

SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

OSHA (O) Occupational Safety and Health Administration.

ACGIH (G) American Conference of Governmental Industrial Hygienists.

A1 - Confirmed human carcinogen.

A2 - Suspected human carcinogen.

A3 - Animal carcinogen.

A4 - Not classifiable as a human carcinogen.

A5 - Not suspected as a human carcinogen.

IARC (I) International Agency for Research on Cancer.

1 - The agent (mixture) is carcinogenic to humans.

2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.

2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.

3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.

4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.

NTP (N) National Toxicology Program.

MATERIAL SAFETY DATA SHEET

LevelQuik Latex Primer

- 1 - Known to be carcinogens.
- 2 - Reasonably anticipated to be carcinogens.

Section 16: OTHER INFORMATION

Disclaimer:

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Expiry Date: August 31, 2015

Version #: 1.1

Prepared by: Nexreg Compliance Inc.
Phone: (519) 488-5126
www.nexreg.com