

*Estimated N/A-Not Applicable N/R-Not Restricted N/E-Not Established

MATERIAL SAFETY DATA SHEET

NOTE: BLANK SPACES ARE NOT PERMITTED. IF ANY ITEM IS NOT APPLICABLE, THE SPACE MUST BE MARKED TO INDICATE THAT.						
IDENTITY				PART NO.		
(As shown on Label or package) F-886 Re-Rack				IF APPLICABLE		
SECTION I						
MANUFACTURER'S				EMERGENCY PHONE No.		
NAME Plasti Dip Internationa				USA only: 1-800-424-9300 INT'L: 703-527-3887		
ADDRESS (NUMBER, STREET, CITY, ST	ΓATE AND	ZIP CODE)		REVISION # 0001		
3920 Pheasant Ridge Drive				ļ		
Diaina MN 55440				MANUFACTURER'S PHONE No. FOR INFORMATION 1-763-785-2156		
Blaine, MN 55449				DATE MSDS		
				WAS PREPARED May 25, 2007		
SECTION II - HAZARDOUS INGREDIEN	TS INFOR	MATION. All He	alth Hazards which c			
carcinogens if 0.1% of the composition or g	greater.					<u> </u>
HAZARDOUS COMPONENTS CHEMI		% Wt.	CAS NO.	OSHA	ACGIH	OTHER LIMITS
IDENTITY AND COMMON NAME	L (S)	(OPTIONAL)		PEL	TLV	RECOMMEND
Xylene		53%	1330-20-7	100 ppm	100 ppm	None
Methyl Ethyl Ketone		10%	78-93-3	200 ppm	200 ppm	None
Ethylbenzene		13%	100-41-4	100 ppm	100 ppm	None
	'	 		1		
CECTION III DINCICAL / CHEMICAL	CILADACT	PRICENCE				
SECTION III - PHYSICAL / CHEMICAL			2 1)	A DDD OVIMA	TE MEIGHT	PED CALLON (LDC)
BOILING POINT 175 - 279°F	SPECIFIC	C GRAVITY (H ₂ C 0.85	= 1) APPROXIMATE WEIGHT PER GALLON (LBS) 7.05			
VAPOR PRESSURE	VADORD			EVAPORATION RATE		
78 mmHg @ 20°C	VAPOR DENSITY (AIR = 1) Heavier than air			(BUTYL ACETATE =1) >1.0		
SOLUBILITY IN WATER	, ,	FILE 76%	-	OTHER		
Insoluble	1 1 1 2			(IF ANY) None		
APPEARANCE					-	
AND ODOR Clear syrupy liquid, strong						
SECTION IV-FIRE AND EXPLOSION HA	AZARD DA'	ГА				
FLASH POINT 23°F		FLAMM	IABLE LIMITS	LEL		UEL
(METHOD USED) TCC						11.5
EXTINGUISHING						
MEDIA Carbon Dioxide, Dry Che	mical, or Foa	<u>.m</u>				
SPECIAL FIRE	1 1		C 11 C	1	141	
FIGHTING PROCEDURES Self conta UNUSUAL FIRE AND	inea breatnin	ig apparatus with a	full face piece, operate	ed in pressure den	and or other po	sitive pressure mode.
UNUSUAL FIRE AND EXPLOSION HAZARDS This material is flammable and may be ignited by heat, sparks, flame or static electricity.						
HAZARDOUS PRODUCTS FORMED BY						
FIRE OR THERMAL DECOMPOSITION Carbon Dioxide and/or Carbon Monoxide, Hydrogen Chloride and organic hydrocarbons.						
EXPLOSIVE LIMITS						
(% BY VOLUME IN AIR) 1.0 - 11.5						
SECTION V - OPTIONAL HAZARD RATINGS IDENTIFICATION						
HAZARD RATING				National Fire Protection Association (NFPA)		
3-HIGH	4-EXTREME 3-HIGH					
2-MODERATE			FIRE 3 REA	ACTIVITY	<u>) .</u>	
1-SLIGHT 0-INSIGNIFICANT						
**SEE SECTION IV HEALTH 2 SH			SPECIAL HA	ZARDS None	_	
III.			HEADTH	SIECIAL IIA	ZARDS None	<u>~ •</u>

This is the "front" when printed in duplex. Page 1 of 2 pages if not duplex.



SECTION VI - REACTIVITY AND	STARII ITV DATA					
STABILITY UNSTAB		CONDITIONS	2500F C 10 ' 1			
	-		O AVOID Temperatures over 350°F for over 10 minutes.			
	Avoid) Oxidizing Materials, strong acids,					
HAZARDOUS DECOMPOSITION OR BY PRODUCTS Carbon Monoxide, Carbon Dioxide, Hydrogen Chloride and some hydrocarbons. HAZARDOUS MAY OCCUR CONDITIONS TO AVOID						
HAZARDOUS		CONDITIONS 10				
POLYMERIZATION WILL NOT OCCUR X None						
SECTION VII - HEALTH HAZARD DATA						
ROUTES OF ENTRY INHALATION? Yes SKIN? Yes INGESTION? Yes EYES? Yes						
HEALTH ACUTE	X See Signs and Symptoms of Expos	ure below.				
HAZARDS CHRONIC	X					
CARCINOGENICITY: IARC 2B						
	SIGNS AND					
SYMPTOMS OF		on of nose, throat and lungs. Skin: Irritation upon repeat or				
EXPOSURE	prolonged contact. Eyes: Slightly irritation	i to eyes.				
MEDICAL CONDITIONS GENERA	ALLY AGGRAVATED BY EXPOSURE	None known				
EMERGENCY AND	Ingestion: Contact Physician or Poison C					
FIRST AID			er Oxygen or Artificial Respiration if Necessary.			
PROCEDURES Eye Contact: Flush with large amounts of water. If irritation persists, contact Physician.						
	Skin: Wash with soap and water.					
SECTION VIII - PRECAUTIONS F	OR SAFE HANDLING AND USE					
STEPS TO BE TAKEN	S TO BE TAKEN Wipe up with floor absorbent. Transfer to hood. Prevent run-off to sewers.					
IN CASE MATERIAL IS		e to maintain exposure below PEL's. Use sand or other material				
RELEASED OR SPILLED	to dam or contain spills. If large spill, app					
		*				
WASTE DISPOSAL METHODS D	ispose of product in accordance with local,	county, state and	federal regulations.			
		•				
PRECAUTIONS TO BE	Avoid contact with eyes. Keep container	closed. Use with adequate ventilation. Keep away from sparks,				
TAKEN IN HANDLING	flame and heat sources and store in cool a	area. Avoid inhalation of vapors and personal contact with liquid				
AND STORAGE	product. Use good personal hygiene prac	tices.				
OTHER	Keep from freezing - product may coagula	ate. Keep containe	e. Keep container closed when not in use. All containers should be			
PRECAUTIONS	disposed of in an environmentally safe ma					
SECTION IX - CONTROL MEASURES						
RESPIRATORY PROTECTION (SPECIFY TYPE) Depending on the Airborne co			PROTECTIVE GLOVES			
	SH approved cartridge or supplied air equip		Rubber gloves			
	UST Supplemental (if needed)		SPECIAL None			
	L (GENERAL) To maintain exposure bel	ow PEL's.	OTHER None			
EYE PROTECTION	,		OTHER PROTECTIVE CLOTHING OR EQUIPMENT			
Chemical splash goggles or approved of	eye protection.		Chemical Apron/Eye bath/Safety shower			
WORK HYGIENIC PRACTICES Wash thoroughly after handling.						
SECTION X - TRANSPORTATION INFORMATION (Optional)						
DOT PROPER SHIPPING NAME Coating Solution DOT HAZARD CLASS 3						
DOT UN NUMBER UN 1139		DOT PACKING GROUP II				
IATA PROPER SHIPPING NAME Coating Solution		IATA HAZARD CLASS 3				
IATA UN NUMBER UN 1139		IATA PACKING GROUP II				
THIS PRODUCT CONTAINS THE FOLLOWING CHEMICALS SUBJECT TO REPORTING REQUIREMENTS OF SECTION 313 OF THE						
			R 372, (see table on page 1 for CAS # and percent by weight).			
Xylene, Methyl Ethyl Ketone, Ethylber		OF 1700, 40 CF	1. 27. (see those on page 1 for CAS π and percent by weight).			
WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH						
DEFECTS, OR OTHER REPRODUCTIVE HARM.						

This is the "back" when printed in duplex. Page 2 of 2 pages if not duplex.

Prepared By:	Mark Kenow	