

MATERIAL SAFETY DATA SHEET

MSDS Name: GS-121 VOC Compliant GUTTER & SEAM SEALANT  
MSDS Number: 1117415  
Version Number 0  
Revision Date: DEC-06-2007  
Page Number: 1

-----

SECTION I - PRODUCT AND COMPANY INFORMATION

Product Name: GS-121 VOC Compliant GUTTER & SEAM SEALANT  
HMIS Hazard Rating: Health: 1 Fire: 3 Reactivity: 0 PPE: B

Company Identification: HENKEL CORPORATION  
7405 PRODUCTION DRIVE  
MENTOR OH 44060

Contact (24 hour): Customer Affairs (800)321-0253  
Information phone/Fax: (440) 255-8900 / (440) 974-8358  
CHEMTREC Emergency (24 hour): (703) 527-3887 (International)  
(800) 424-9300  
in Canada CANUTEC 613-996-6666

Product Class SEALANT  
Trade Name PRO-SERIES  
Product Code See above

SECTION II - INGREDIENT AND HAZARD INFORMATION

Hazardous Ingredient Name	CAS Number	Percent	TSCA
Chloro,fluoro Solvent	TSRN7010S01	10 - 15	Y
Light Petroleum Distillates	TSRN0029S01	5 - 10	Y
Methyl Acetate	0079-20-9	5 - 10	Y
Toluene	108-88-3	< 5.0	Y

Ingredient Notes:

Remaining ingredients are not considered OSHA hazardous.  
Contains ingredients whose specific chemical identity has been withheld as a trade secret.

-----

SECTION III - PHYSICAL AND CHEMICAL PROPERTIES

Form: High viscosity Caulk  
Appearance/Color: White OR Aluminum  
Solubility (in water): insoluble  
pH Value, +/- .3: Not Applicable  
Boiling Range: 140.°F - 300.°F (60.°C - 148.89°C)

-----

**MATERIAL SAFETY DATA SHEET**

MSDS Name: GS-121 VOC Compliant GUTTER & SEAM SEALANT  
MSDS Number: 1117415  
Version Number 0  
Revision Date: DEC-06-2007  
Page Number: 2

-----  
Vapor Pressure (mmHg): 80.@ 68.°F (20.°C)  
Evaporation Rate: 2. times Faster than n-Butyl Acetate  
  
Vapor Density: Heavier than air  
  
% Volatile, Weight approx. 30.%  
% Volatile, Volume Not Available  
Specific Gravity: 1.42386  
VOC (less H2O or exempt) 45 Gr/l, (4 %)

**NOTE:**

\*BOIL RANGE, EVAP RATE, VAPOR DENSITY AND PRESSURE FOR SOLVENT ONLY!

-----  
**SECTION IV - FIRE FIGHTING MEASURES**

Flammability Class IB  
Flash Point: 9.°F (-12.78°C)  
Tag Closed Cup  
Explosive Range (LEL/UEL): 1.%  
7.%

**EXTINGUISHING MEDIA:**

Carbon Dioxide---Dry Chemical---Foam  
Use water fog to cool material in vicinity of fire.

**SPECIAL FIRE-FIGHTING PROCEDURES:**

Use self-contained breathing apparatus with full facepiece  
operated in pressure demand with full protective equipment.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:**

Any closed container may rupture when exposed to extreme heat.  
Solvent vapors are heavier than air and travel along the ground.  
Vapors given off are flammable and may be ignited in air explosively.

-----  
**SECTION V - HEALTH HAZARD DATA**

Route	Species	Exposure and Dose
Methyl Acetate		LD50 5000. mg/kg

**ROUTES OF ENTRY:**

ENTRY THROUGH... Inhalation and skin most likely

**CARCINOGENICITY...**

NTP? N/E | IARC Monographs? N/E | OHSA? NO

**EFFECTS OF OVEREXPOSURE**

Eyes: Can cause irritation, redness, tearing and blurred vision.  
Skin: Prolonged or repeated contact can cause moderate  
irritation, drying of the skin, and dermatitis.

-----

**MATERIAL SAFETY DATA SHEET**

MSDS Name: GS-121 VOC Compliant GUTTER & SEAM SEALANT

MSDS Number: 1117415

Version Number 0

Revision Date: DEC-06-2007

Page Number: 3

-----  
Inhalation: Excessive inhalation of vapors can cause respiratory irritation, headache, drowsiness and fatigue. High concentrations of vapors are anesthetic and may cause central nervous system effects such as dizziness.

Ingestion: Can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

**FIRST AID MEASURES**

Eyes: Flush eyes gently with water for at least 15 minutes lifting eyelids occasionally; get prompt medical attention

Skin: Wash thoroughly with soap and water; apply a mild skin cream. Remove contaminated clothing.

Inhalation: Move affected person to fresh air; if breathing is difficult, administer oxygen; if breathing has stopped, give artificial respiration. Get medical attention.

Ingestion: DO NOT INDUCE VOMITING! Get immediate medical attention.

**CHRONIC HAZARDS**

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain, nervous system, liver or kidney damage or may cause cardiac arrhythmia. INTENTIONAL misuse of this product by deliberately inhaling its vapors may be harmful or fatal.

Repeated overexposure to TOLUENE may cause liver damage.

Toluene has been found to cause Kidney, Lung and Spleen damage in laboratory animals.

Repeated overexposure to Chloro, fluoro Solvent, by breathing or ingestion has been found to cause Liver and Kidney damage in laboratory animals.

May also produce symptoms of central nervous system depression.

-----  
**SECTION VI - STABILITY AND REACTIVITY**

Stability: Product is stable under normal storage conditions

Hazardous Polymerization: Will not occur under normal conditions

**INCOMPATIBILITY:**

Keep away from strong oxidizing agents.

**CONDITIONS TO AVOID:**

Keep away from heat, spark, open flames and any ignition source.

**HAZARDOUS DECOMPOSITION PRODUCTS:**

Will produce fumes and smoke containing carbon monoxide and dioxide under fire conditions.

-----  
**SECTION VII - ACCIDENTAL RELEASE AND DISPOSAL MEASURES:**

**STEPS TO BE TAKEN IN CASE OF SPILL:**

Eliminate all ignition sources. Ventilate confined areas.

(Open windows and doors). Wear appropriate protective clothing.

-----

MATERIAL SAFETY DATA SHEET

MSDS Name: GS-121 VOC Compliant GUTTER & SEAM SEALANT
MSDS Number: 1117415
Version Number 0
Revision Date: DEC-06-2007
Page Number: 4

Cover with absorbent. Scoop into sealable safety container.

WASTE DISPOSAL METHOD:

Dispose of following local, state, and federal regulations.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

Table with 5 columns: ACGIH TLV, ACGIH TLV-C, ACGIH STEL, OSHA STEL, OSHA PEL. Rows include Chloro,fluoro Solvent, Light Petroleum Distillates, Methyl Acetate, and Toluene.

RESPIRATORY PROTECTION:

If TLV of the product is exceeded, a NIOSH/MSHA jointly approved air supply respirator is advised in the absence of proper ventilation. OSHA regulations also permit the use of other types of NIOSH/MSHA respirators under specified conditions. (See your safety equipment supplier for more information)

VENTILATION:

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV. Ventilate during application and curing of this product.

PROTECTIVE CLOTHING:

Rubber gloves should be worn where skin contact is likely. Wear impervious clothing and shoes.

EYE PROTECTION:

Chemical goggles or safety glasses should be worn.

HANDLING AND STORAGE PRECAUTIONS:

Keep away from heat, spark and flame. Keep out of reach of children. Keep container closed while not in use. Do not cut or burn recepticals that have contained a solvent based product. Do not reuse this container. Use only in a well ventilated area.

N/A=NOT APPLICABLE N/AV=NOT AVAILABLE N/E, N/est=NOT ESTABLISHED

**MATERIAL SAFETY DATA SHEET**

MSDS Name: GS-121 VOC Compliant GUTTER & SEAM SEALANT  
MSDS Number: 1117415  
Version Number 0  
Revision Date: DEC-06-2007  
Page Number: 5

-----  
**SECTION IX - TRANSPORT INFORMATION: (not all sizes available)**

**GROUND TRANSPORT (DOT) - DOMESTIC**

Units less than 5L (1.3 gallons liquid) i.e. 4oz,7oz, 10.2oz tubes

Proper Shipping Name: CONSUMER COMMODITY  
Classification: ORM-D  
DOT Label Required: ORM-D  
Shipping Document: CONSUMER COMMODITY, ORM-D  
ERG Code: 171

**AIR TRANSPORT (DOT) - DOMESTIC**

Units less than 5L (1.3 gallons liquid) i.e. 4oz,7oz,10.2 oz.tubes

Proper Shipping Name: CONSUMER COMMODITY  
Classification: ORM-D  
DOT Label Required: ORM-D-AIR  
Shipping Document: Consumer Commodity, ORM-D  
ERG Code: 171

**AIR TRANSPORT ( IATA ) - INTERNATIONAL**

Units less than 5L (1.3 gallons liquid) i.e. 4oz,7oz,10.2oz.tubes

Proper Shipping Name: CONSUMER COMMODITY  
Classification: class 9  
Label Required: ID8000  
Shipping Document: Consumer Commodity,9, ID8000  
ERG Code: 9L

**MARINE - OCEAN TRANSPORT ( IMDG )**

Units less than 5L (1.3 gallons liquid) i.e. 4oz,7oz,10.2oz.tubes

Proper Shipping Name: ADHESIVE  
Classification: Class 3  
Label Required: Flammable Liquid, UN1133, Class 3, Ltd. Qty.  
(on Ocean container only, not required on cartons)  
Shipping Document: ADHESIVE,3, UN1133, PG III, LTD.QTY.  
EMS Code: F-E, S-D

-----  
**SECTION X - REGULATORY INFORMATION:**

SARA TITLE III SECTION 313:

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right to Know Act of 1986 and of 40 CFR 372:

Ingredient Name	CAS Number	Percent
Toluene	108-88-3	< 5.0

-----

**MATERIAL SAFETY DATA SHEET**

MSDS Name: GS-121 VOC Compliant GUTTER & SEAM SEALANT

MSDS Number: 1117415

Version Number 0

Revision Date: DEC-06-2007

Page Number: 6

---

SARA Section 311/312 Hazard Categories met: Fire Hazard,  
Immediate (Acute) and Delayed (Chronic) Health Hazards.

Chemical ingredients are listed on the TSCA inventory.

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

**DISCLAIMER:**

The information contained herein is based on data available as of the date of preparation of this MSDS and which we believe to be reliable. However, no warranty is expressed or implied regarding the accuracy of the data. We shall not be responsible for the use of this information, or of any product, method, apparatus mentioned, and user must make his own investigation to determine the suitability of the information or products for his particular purpose, for the protection of the environment, and the health & safety of the users of this material.