

# Material Safety Data Sheet

**24 Hour Assistance:**  
1-847-367-7700

Rust-Oleum Corp.  
[www.rustoleum.com](http://www.rustoleum.com)

## 1. Identification

**Product Name:** BIN 5-GL ADVANCED CLEAR **Revision Date:** 4/18/2013

**Identification Number:** 271461

**Product Use/Class:** Primer/Latex

**Supplier:** Rust-Oleum Corporation  
11 Hawthorn Parkway  
Vernon Hills, IL 60061  
USA

**Manufacturer:** Rust-Oleum Corporation  
11 Hawthorn Parkway  
Vernon Hills, IL 60061  
USA

**Preparer:** Regulatory Department

## 2. Hazard Identification

**EMERGENCY OVERVIEW:** Use ventilation necessary to keep exposures below recommended exposure limits, if any.

**EFFECTS OF OVEREXPOSURE - EYE CONTACT:** Causes eye irritation.

**EFFECTS OF OVEREXPOSURE - SKIN CONTACT:** Substance may cause slight skin irritation.

**EFFECTS OF OVEREXPOSURE - INHALATION:** Low hazard for usual industrial handling or commercial handling by trained personnel.

**EFFECTS OF OVEREXPOSURE - INGESTION:** Substance may be harmful if swallowed.

**EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:** No Information

**PRIMARY ROUTE(S) OF ENTRY:** Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

## 3. Composition/Information On Ingredients

Chemical Name	CAS-No.	Weight % Less Than	ACGIH TLV- TWA	ACGIH TLV- STEL	OSHA PEL-TWA	OSHA PEL- CEILING
Talc	14807-96-6	15.0	2 mg/m3	N.E.	0.1 mg/m3 [Respirable]	N.E.

## 4. First-aid Measures

**FIRST AID - EYE CONTACT:** Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

**FIRST AID - SKIN CONTACT:** Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

**FIRST AID - INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation.

**FIRST AID - INGESTION:** Swallowing less than an ounce will not cause significant harm. For larger amounts, do not induce vomiting, but give one or two glasses of water to drink and get medical attention.

## 5. Fire-fighting Measures

**Flash Point, °F** >200 (Setaflash)

**Extinguishing Media:** Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Fog

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** FLASH POINT IS TESTED TO BE GREATER THAN 200 DEGREES F.

**SPECIAL FIREFIGHTING PROCEDURES:** Water may be used to cool closed containers to prevent buildup of steam.

## 6. Accidental Release Measures

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** Dispose of according to local, state (provincial) and federal regulations. Do not incinerate closed containers.

## 7. Handling and Storage

**HANDLING:** Wash thoroughly after handling. Wash hands before eating. Avoid contact with eyes.

**STORAGE:** Keep from freezing. Keep container closed when not in use.

## 8. Exposure Controls/Personal Protection

**ENGINEERING CONTROLS:** Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

**RESPIRATORY PROTECTION:** A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

**SKIN PROTECTION:** Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

**EYE PROTECTION:** Use safety eyewear designed to protect against splash of liquids.

**OTHER PROTECTIVE EQUIPMENT:** Refer to safety supervisor or industrial hygienist for further information regarding personal protective equipment and its application.

**HYGIENIC PRACTICES:** Wash thoroughly with soap and water before eating, drinking or smoking.

## 9. Physical and Chemical Properties

<b>Vapor Density</b>	Heavier than Air	<b>Odor:</b>	Mild
<b>Appearance:</b>	Liquid	<b>Evaporation Rate:</b>	Slower than Ether
<b>Solubility in Water:</b>	Miscible	<b>Freeze Point:</b>	N.D.
<b>Specific Gravity:</b>	1.092	<b>pH:</b>	7.5
<b>Physical State:</b>	Liquid		

(See section 16 for abbreviation legend)

## 10. Stability and Reactivity

**CONDITIONS TO AVOID:** Avoid contact with strong acid and strong bases.

**INCOMPATIBILITY:** Incompatible with strong oxidizing agents, strong acids and strong alkalis.

**HAZARDOUS DECOMPOSITION:** By open flame, carbon monoxide and carbon dioxide. When heated to decomposition, it emits acrid smoke and irritating fumes.

**HAZARDOUS POLYMERIZATION:** Will not occur under normal conditions.

**STABILITY:** This product is stable under normal storage conditions.

## 11. Toxicological Information

<u>Chemical Name</u>	<u>LD50</u>	<u>LC50</u>
Talc	N.E.	TCLo: 11 mg/m3 (Inhalation)

## 12. Ecological Information

**ECOLOGICAL INFORMATION:** Product is a mixture of listed components.

## 13. Disposal Information

**DISPOSAL INFORMATION:** Dispose of material in accordance to local, state and federal regulations and ordinances. Do not allow to enter waterways, wastewater, soil, storm drains or sewer systems.

## 14. Transport Information

	<u>Domestic (USDOT)</u>	<u>International (IMDG)</u>	<u>Air (IATA)</u>
<b>Proper Shipping Name:</b>	Not Regulated	Not Regulated	Not Regulated
<b>Hazard Class:</b>	N.A.	N.A.	N.A.
<b>UN Number:</b>	N.A.	N.A.	N.A.
<b>Packing Group:</b>	N.A.	N.A.	N.A.
<b>Limited Quantity:</b>	No	No	No

## 15. Regulatory Information

### U.S. Federal Regulations:

#### CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Acute Health Hazard, Chronic Health Hazard

#### Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>
Ethylene Glycol	107-21-1

#### Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

<u>Chemical Name</u>	<u>CAS-No.</u>
5-chloro-2-methyl-4-isothiazolin-3-one	26172-55-4
Methyl-4-isothiazolin-3-one	2682-20-4

**International Regulations:****CANADIAN WHMIS:**

This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

Canadian WHMIS Class: D2A

**16. Other Information****HMIS Ratings:**

**Health:** 2\*      **Flammability:** 1      **Physical Hazard:** 0      **Personal Protection:** X

**NFPA Ratings:**

**Health:** 2      **Flammability:** 1      **Instability:** 0

**Volatile Organic Compounds, g/L:** 12

**REASON FOR REVISION:** Regulatory Update

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

Rust-Oleum Corporation believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. Rust-Oleum Corporation makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.