MATERIAL SAFETY DATA SHEET

L-06566 Page: 1

PREPARED FOR: W.J. HAGERTY & SONS

====== SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION =========

PRODUCT NAME: HAGERTY SILVERSMITH SPRAY POLISH

PRODUCT CODE: L-06566

MANUFACTURER'S NAME: W.J. HAGERTY & SONS
ADDRESS : 3801 Linden Ave

South Bend, IN 46619

EMERGENCY PHONE : 574-288-4991 INFORMATION PHONE : 574-288-4991

======= SECTION 2 - HAZARDS IDENTIFICATION ============

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE RESPIRATORY IRRITATION, HEADACHE, NAUSEA, FATIGUE, DROWSINESS, IMPAIRED CO-ORDINATION.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE SKIN: CONTACT MAY DRY THE SKIN; PROLONGED CONTACT MAY CAUSE IRRITATION. EYES: LIQUID OR VAPOR CAN IRRITATE; PROLONGED CONTACT MAY LEAD TO CORNEAL DAMAGE.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
NOT EASILY ABSORBED. SOLVENT ACTION CAN DRY AND DEFAT THE SKIN CAUSING THE SKIN
TO CRACK, LEADING TO DERMATITIS.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
NOT A LIKELY ROUTE OF EXPOSURE. IF SWALLOWED, DO NOT INDUCE VOMITING. SEEK
IMMEDIATE MEDICAL ADVICE AND/OR ATTENTION.

HEALTH HAZARDS (ACUTE AND CHRONIC)

ACUTE: EYE IRRITANT. SKIN IRRITANT. NARCOTIC IN HIGH CONCENTRATIONS. CHRONIC: LIVER AND KIDNEY DISEASE. SKIN IRRITATION AND DERMATITIS. CHRONIC OVEREXPOSURES HAVE CAUSED LIVER AND KIDNEY TOXIC EFFECTS IN EXPERIMENTAL ANIMALS. CAN CAUSE CENTRAL NERVOUS SYSTEM EFFECTS, IRREGULAR HEARTBEAT AND POSSIBLE DEATH IF TOO MUCH IS BREATHED. DELIBERATE CONCENTRATION AND INHALATION OF CONTENTS MAY BE HARMFUL OR FATAL.

CARCINOGENICITY: NTP CARCINOGEN: NO IARC MONOGRAPHS: NO OSHA REGULATED: No

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE ACUTE AND CHRONIC LIVER AND KIDNEY DISEASE, ANEMIA, CORONARY DISEASE OR RHYTHM DISORDERS OF THE HEART.

====== SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS ========

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRE		WEIGHT PERCENT
BENZENE, 1-CHLORO-4 (TRIFLUOROMETHYL)	98-56-6	5.3	68	24
OSHA PEL: NOT ESTABLISHED; ACGIH TLV: NOT ESTABLISHED				
2-PROPANOL, ISOPROPYL ALCOHOL	67-63-0	33	68	15
OSHA PEL: 400 PPM, ACGIH TLV: 400	PPM			
ACETONE	67-64-1	181	68	14
OSHA PEL: 750 PPM, ACGIH TLV: 750	PPM			
DIFLUOROETHANE	75-37-6	47500	70	44
OSHA TLV: 1000 PPM				

^{***} No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. ***

L-06566 Page: 2

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: REMOVE TO FRESH AIR. ADMINISTER OXYGEN IF NEEDED. APPLY ARTIFICIAL RESPIRATION IF BREATHING HAS STOPPED. GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING; CALL A DOCTOR. IF CONDITIONS REMAIN, GET MEDICAL ATTENTION. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. SKIN: WIPE OFF WITH TOWEL. WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF IRRITATION PERSISTS. EYES: WASH IMMEDIATELY WITH LARGE VOLUMES OF FRESH WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION.

FLASH POINT: -58 F METHOD USED: ESTIMATED FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 0.9 UPPER: 16.9

EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIREFIGHTING PROCEDURES

WATER MAY BE USED TO COOL CONTAINERS TO PREVENT PRESSURE BUILD-UP AND EXPLOSION WHEN EXPOSED TO EXTREME HEAT. IF WATER IS USED, FOG NOZZLES ARE PREFERRED. WEAR GOGGLES AND SELF-CONTAINED BREATHING APPARATUS.

UNUSUAL FIRE AND EXPLOSION HAZARDS

KEEP CONTAINERS FROM HEAT AND OPEN FLAME. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH HAZARD. SYMPTOMS MAY NOT BE READILY APPARENT. OBTAIN MEDICAL ATTENTION. CONTAINS A FLAMMABLE SOLVENT THAT MAY UNDER SOME CONDITIONS OF USE ALLOW THE ENTIRE MIXTURE TO BURN IF IGNITED.

======= SECTION 6 - ACCIDENTAL RELEASE MEASURES ==========

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED AVOID BREATHING VAPORS. VENTILATE AREA. DIKE AREA TO CONTAIN SPILL. CLEAN UP AREA WITH ABSORBENT MATERIAL AND PLACE IN CLOSED CONTAINERS FOR DISPOSAL.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING STORE AND USE IN COOL, DRY, WELL-VENTILATED AREAS.

STORE AND USE IN COOL, DRY, WELL-VENTILATED AREAS. AVOID CONTACT WITH HOT METAL SURFACES. KEEP AWAY FROM EXCESSIVE HEAT OR OPEN FLAME. CONTENTS UNDER PRESSURE. DO NOT PUNCTURE OR INCINERATE CONTAINER OR STORE ABOVE 120 DEGREES F.

====== SECTION 8 - EXPOSURE CONTROL/PERSONAL PROTECTION =========

PRECAUTIONS

SMALL PRESSURIZED CONTAINERS OF FLAMMABLE PRODUCTS MAY BE STORED IN AREAS SUITABLE FOR ORDINARY COMBUSTIBLES WITH RESPECT TO CONSTRUCTION, DRAINAGE, CONTROL OF IGNITION SOURCES, AND VENTILATION EXCEPT THAT THEY SHOULD NOT BE STORED IN BASEMENTS.

RESPIRATORY PROTECTION

IN RESTRICTED AREAS, USE APPROVED CHEMICAL/MECHANICAL FILTERS DESIGNED TO REMOVE A COMBINATION OF PARTICLES AND VAPOR. IN CONFINED AREAS, USE APPROVED AIR LINE TYPE RESPIRATOR OR HOOD. SELF-CONTAINED BREATHING APPARATUS IS REQUIRED FOR VAPOR CONCENTRATIONS ABOVE PEL/TLV LIMITS.

VENTILATION

SUFFICIENT TO PREVENT INHALATION OF SOLVENT VAPORS. GENERAL DILUTION AND/OR LOCAL EXHAUST VENTILATION IN VOLUME OR PATTERN TO KEEP PEL/TLV OF MOST HAZARDOUS INGREDIENT BELOW ACCEPTABLE LIMIT AND LEL BELOW STATED LIMIT.

L-06566 Page: 3

SOLVENT RESISTANT REQUIRED FOR PROLONGED OR REPEATED CONTACT.

EYE PROTECTION

SAFETY GLASSES WITH SPLASH GUARDS OR FULL FACE SHIELD.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT SOLVENT RESISTANT APRON.

WORK/HYGIENIC PRACTICES

EYE WASHES AND SAFETY SHOWERS IN THE WORKPLACE ARE RECOMMENDED.

======= SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES ========

BOILING RANGE: -13 F - 282 F SPECIFIC GRAVITY (H2O=1): 0.95 VAPOR DENSITY: HEAVIER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER

SOLUBILITY IN WATER: SLIGHT

APPEARANCE AND ODOR: AEROSOL PRODUCT; LIGHT RED LIQUID; MILDLY SWEET

STABILITY: STABLE CONDITIONS TO AVOID

APPLICATION TO HOT SURFACES.

INCOMPATIBILITY (MATERIALS TO AVOID) UNKNOWN.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS
MAY PRODUCE FUMES WHEN HEATED TO DECOMPOSITION. FUMES MAY CONTAIN CARBON
MONOXIDE AND OTHER TOXIC FUMES.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

====== SECTION 11 - TOXICOLOGICAL INFORMATION =============

LONG-TERM TOXICOLOGICAL STUDIES HAVE NOT BEEN CONDUCTED FOR THIS PRODUCT.

======= SECTION 12 - ECOLOGICAL INFORMATION ===========

LONG-TERM ECOLOGICAL STUDIES HAVE NOT BEEN CONDUCTED FOR THIS PRODUCT.

======= SECTION 13 - DISPOSAL CONSIDERATIONS ===========

WASTE DISPOSAL METHOD

DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS. BEFORE ATTEMPTING CLEAN UP, REFER TO OTHER SECTIONS OF THIS MSDS FOR HAZARD CAUTION INFORMATION.

BY LAND: SHIPPING NAME: CLEANING COMPOUND, NOI

BY WATER: DOT PROPER SHIPPING NAME: UN 1950, Aerosols, 2.1, LTD QTY BY AIR: DOT PROPER SHIPPING NAME: UN1950, Aerosols, flammable, 2.1, LTD QTY

(Packing instruction Y203 applies)

======= SECTION 15 - REGULATORY INFORMATION ===========

ALL INGREDIENTS ARE EITHER LISTED ON THE TSCA INVENTORY OR ARE EXEMPT.

DATE PRINTED: 09/04/13 NAME OF PREPARER: ESP

L-06566 Page: 4

HMIS CODES: H-1 F-3 R-0 P-

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. BECAUSE THE INFORMATION CONTAINED HEREIN MAY BE APPLIED UNDER CONDITIONS BEYOND OUR CONTROL, WE ASSUME NO RESPONSIBILITY FOR ITS USE.