



Revision Number: 002.1

Issue date: 07/25/2012

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:	Loctite Professional Performance Spray Adhesive	IDH number:	1629134
Product type:	Adhesive	Region:	United States
Company address:	Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067		
	Contact information: Telephone: 800.624.7767 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887		

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Physical state:	liquid	HEALTH:	1
Color:	Off white	FLAMMABILITY:	4
Odor:	Solvent	PHYSICAL HAZARD:	0
		Personal Protection:	See MSDS Section 8

DANGER: EXTREMELY FLAMMABLE.
 VAPOR MAY CAUSE FLASH FIRE.
 HARMFUL IF INHALED.
 CONTENTS UNDER PRESSURE.
 CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION.

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects

Inhalation:	May be harmful if inhaled. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.
Skin contact:	Prolonged and/or repeated skin contact may result in mild irritation or redness. Repeated or prolonged contact can result in drying of skin. Symptoms may include redness, burning, drying, cracking and skin burns.
Eye contact:	Symptoms can include irritation, redness, scratching of the cornea, and tearing. Mild eye irritation.
Ingestion:	May be harmful if swallowed. Aspiration may occur during swallowing or vomiting, resulting in lung damage.

Existing conditions aggravated by exposure: Other pre-existing skin conditions. Other respiratory disorders (bronchitis, emphysema, bronchial hyperreactivity).

 This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Acetone	67-64-1	10 - 30
Methyl acetate	79-20-9	10 - 30
Solvent naphtha (petroleum), light aliphatic, low benzene content	64742-89-8	5 - 10
Cyclohexane	110-82-7	30 - 60
Propane	74-98-6	10 - 30

4. FIRST AID MEASURES

Inhalation:	Move to fresh air. In case of adverse health effects seek medical advice.
Skin contact:	Wash affected area immediately with soap and water. If symptoms develop and persist, get medical attention. Remove contaminated clothes.
Eye contact:	In case of contact with the eyes, rinse immediately with plenty of water for 15 minutes, and seek immediate medical attention.
Ingestion:	If material is ingested, immediately contact a physician or poison control center. Do not induce vomiting: contains petroleum distillates and/or aromatic solvents. If vomiting occurs, prevent aspiration by keeping the patient's head below the knees.
Notes to physician:	This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting.

5. FIRE FIGHTING MEASURES

Flash point:	Not available.
Flashback:	This product exhibits flashback when tested for flame extension.
Autoignition temperature:	Not available.
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Extinguishing media:	Carbon dioxide. Alcohol-resistant foam Dry powder.
Special firefighting procedures:	Firefighters should wear self-contained breathing apparatus. Water may be ineffective, but may be used to cool exposed containers to prevent pressure build-up and possible auto-ignition or explosion when exposed to extreme heat. If water is used, fog nozzles are preferable.
Unusual fire or explosion hazards:	Contents under pressure. Do not handle or store near an open flame, heat or other sources of ignition. Do not puncture or incinerate pressurized containers. Exposure to temperatures above 49°C (120°F) may cause container to burst.
Hazardous combustion products:	Not available.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways.

Clean-up methods:

Absorb spill with inert material. Shovel material into appropriate container for disposal. Follow all local, state, federal and provincial regulations for disposal.

7. HANDLING AND STORAGE

Handling:

Keep out of the reach of children. Keep in a cool, well ventilated area. Ventilate working rooms thoroughly. Avoid naked flames, sparking and sources of ignition. Switch off electrical devices. Do not smoke, do not weld. Do not empty waste into waste water drains. Avoid skin and eye contact. Avoid breathing vapors or mists of this product. Do not puncture or incinerate pressurized containers.

Storage:

For safe storage, store at or below 48.8 °C (119.8 °F)

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Acetone	500 ppm TWA 750 ppm STEL	1,000 ppm (2,400 mg/m ³) TWA	None	None
Methyl acetate	200 ppm TWA 250 ppm STEL	200 ppm (610 mg/m ³) TWA	None	None
Solvent naphtha (petroleum), light aliphatic, low benzene content	None	None	None	None
Cyclohexane	100 ppm TWA	300 ppm (1,050 mg/m ³) TWA	None	None
Propane	1,000 ppm TWA	1,000 ppm (1,800 mg/m ³) TWA	None	None

Engineering controls:

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Respiratory protection:

Use a NIOSH approved respirator if ventilation is inadequate.

Eye/face protection:

Safety goggles or safety glasses with side shields.

Skin protection:

Use impermeable gloves and protective clothing as necessary to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	liquid
Color:	Off white
Odor:	Solvent
Odor threshold:	Not available.
pH:	Not applicable
Vapor pressure:	Not available.
Boiling point/range:	Not available.
Melting point/ range:	Not available.
Specific gravity:	0.8300 - 0.8400
Vapor density:	Not available.
Flash point:	Not available.
Flashback:	This product exhibits flashback when tested for flame extension.
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Evaporation rate:	> 1 (Butyl acetate = 1)
Solubility in water:	Insoluble
Partition coefficient (n-octanol/water):	Not available.
VOC content:	54.80 %

10. STABILITY AND REACTIVITY

Stability:	Not available.
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Carbon dioxide. Carbon monoxide. Hydrocarbons.
Incompatible materials:	Strong oxidizing agents.
Conditions to avoid:	Heat, flames, sparks and other sources of ignition.

11. TOXICOLOGICAL INFORMATION

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Acetone	No	No	No
Methyl acetate	No	No	No
Solvent naphtha (petroleum), light aliphatic, low benzene content	No	No	No
Cyclohexane	No	No	No
Propane	No	No	No

Hazardous components	Health Effects/Target Organs
Acetone	Blood, Central nervous system, Irritant, Reproductive
Methyl acetate	Blood, Central nervous system, Eyes, Irritant
Solvent naphtha (petroleum), light aliphatic, low benzene content	Irritant
Cyclohexane	Irritant, Central nervous system
Propane	Cardiac, Central nervous system, Irritant

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: It is the responsibility of the user to determine if an item is hazardous as defined in the Resource Conservation and Recovery Act (RCRA) at the time of disposal. Product uses, transformations, mixtures, processes, etc., may render the resulting material hazardous, under the criteria of ignitability, corrosivity, reactivity and toxicity characteristics of the Toxicity Characteristics Leaching Procedure (TCLP) 40 CFR 261.20-24.

14. TRANSPORT INFORMATION

The shipping classification in this section are for bulk packaging only. Shipping classification may be different for non-bulk packaging as exceptions may apply. Refer to shipping documents for package specific transportation classification.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:	Aerosols
Hazard class or division:	2.1
Identification number:	UN 1950
Packing group:	None
DOT Reportable quantity:	Cyclohexane, Acetone

International Air Transportation (ICAO/IATA)

Proper shipping name: Aerosols, flammable
Hazard class or division: 2.1
Identification number: UN 1950
Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: AEROSOLS (Cyclohexane)
Hazard class or division: 2.1
Identification number: UN 1950
Packing group: None
Marine pollutant: Cyclohexane

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

TSCA 12(b) Export Notification: None above reporting de minimus

CERCLA/SARA Section 302 EHS: None above reporting de minimus
CERCLA/SARA Section 311/312: Immediate Health, Delayed Health, Fire, Sudden Release
CERCLA/SARA 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Cyclohexane (CAS# 110-82-7).

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status:
WHMIS hazard class: D.2.B, A, B.5

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: This Material Safety Data Sheet contains changes from the previous version in Section(s): 2, 4, 5, 15

Prepared by: Mary Ellen Roddy, Sr. Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.