LUCAS MATERIAL SAFETY DATA SHEET

Lucas 80/90 Gear Lube Product Code: 10043 & 10046, 10066, 10067, 10069

DIVISION AND LOCATION --- SECTION I

<u>Division:</u> Lucas Oil Products, Inc. • 302 North Sheridan Street • Corona, CA 92880-2067 Emergency Telephone Number: (800) 342-2512

CHEMICAL AND PHYSICAL PROPERTIES --- SECTION II

Chemical Name: Petroleum hydrocarbon plus additives.

Formula: Proprietary information.

<u>Components:</u> Hydrotreated distillate, heavy paraffin, solvent de-waxed distillate, olefin sulfide, antimony compound.

Hazardous Components: Oil mist if generated.

<u>Appearance:</u> Liquid <u>Color:</u> Clear red <u>Odor:</u> Petroleum and strong additive <u>Vapor Density (air = 1 ATM)</u>: Greater than air

Boiling Point: > 500 degrees F

Viscosity cSt @ 100 degrees C: Greater than or equal to 13.5

Density: 7.472 pounds/gallon

Specific Gravity @ 60 degrees F: .8973

Solubility in Water: Negligible @ 25 degrees C

<u>Stability:</u> Stable under normal conditions of storage and handling

Incompatibility: Avoid contact with strong oxidizing agents

FIRE AND EXPLOSION DATA --- SECTION III

<u>Fire Fighting Procedures:</u> Use dry chemical, carbon dioxide, halon, foam or water spray

Flash Point: COC = 395 degrees F

<u>Hazardous Decomposition Products:</u> Combustion may yield smoke, carbon monoxide, oxides of carbon, nitrogen, phosphorus and sulfur

HEALTH HAZARD DATA --- SECTION IV

<u>Chronic Effects of Over-Exposure:</u> Harmful if inhaled - avoid breathing oil mist Acute Toxicological Properties: No data available

<u>Emergency First Aid Procedures:</u> Eyes - Eye irritant, may cause stinging, watering, redness, swelling: flush with large amounts of water

Frequent or Prolonged Skin Contact - May cause irritation. Remove soiled clothing and wash skin with mild soap & water

Inhalation - Remove exposed person to fresh air. If respiratory symptoms develop seek medical attention

Ingestion - Do not induce vomiting. If conscious, give milk or water and seek medical attention

Ventilation Required: None if airborne concentration us minimal

<u>Respiratory Protection:</u> None if not exposed to mist

<u>Gloves/Glasses:</u> Use impermeable gloves and safety goggles for repeated exposure or hot handling

HANDLING OF SPILLS OR LEAKS --- SECTION VI

<u>Spill Control Measure:</u> Eliminate sources of ignition. Prevent additional discharge of material, if possible to do so safely. Contain and/or clean up with sand or earth on land - skimming absorbent on water.

<u>Waste Disposal:</u> Dispose of in accordance with all applicable federal, state, and local regulations. Wear personal protective equipment - gloves, goggles, etc.

SPECIAL PRECAUTIONS --- SECTION VII

<u>Handling and Storage:</u> Keep containers tightly closed. Store in cool, well ventilated place, away from heat and/or incompatible materials.

TRANSPORTATION DATA --- SECTION VIII

D.O.T.: Not regulated.

Freight Classification: Petroleum lubricating oil.

ENVIRONMENTAL/SAFETY REGULATIONS

This product does not contain greater than 1.0% of any chemical substances listed under SARA section 313.

<u>Prepared By:</u> Dell Findley <u>Title:</u> Lab Technician <u>Original Date:</u> 07-15-95 <u>Updated:</u> 01-01-04

We believe the statements, technical information, and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind, express or implied, and we assume no responsibility for any loss, damage, or expense, direct or consequential, arising out of their use.

This product comes in five gallon pails, 16 gallon kegs and 55 gallon drums.