

# **Material Safety Data Sheet**

Revision Date: 14-Feb-2013

**Revision Number:** 4

# **1. PRODUCT AND COMPANY IDENTIFICATION**

**Product Name** 

Product Code Product Class Color SURE-STEP ANTI-SLIP COATING 100% ACRYLIC LATEX FLOOR & CONCRETE PAINT SU-Series WATER THINNED PAINT White

#### Manufacturer

Complementary Coatings Corp. dba Insl-X 101 Paragon Drive Montvale, NJ 07645 Phone: (800)-225-5554 www.insl-x.com Emergency Telephone Number(s) CHEMTREC (US): 800-424-9300 CHEMTREC (outside US): (703)-527-3887

# 2. COMPOSITION INFORMATION ON COMPONENTS

#### Hazardous Components

Chemical Name	CAS-No	Weight % (max)
Silica, crystalline	14808-60-7	35
Titanium dioxide	13463-67-7	10
Glass, oxide	65997-17-3	5
Iron oxide	1309-37-1	5
Carbon black	1333-86-4	0.5

## 3. HAZARDS IDENTIFICATION

### **Emergency Overview**

Vapors may be irritating to eyes, nose, throat, and lungs. May cause skin irritation and/or dermatitis.

Appearance liquid

Odor little or no odor

#### Potential Health Effects

Principal Routes of Exposure Eye contact, skin contact and inhalation.

Acute Effects Eyes Skin Inhalation Ingestion	May cause slight irritation. Substance may cause slight skin irritation. May cause irritation of respiratory tract. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic Effects	Repeated contact may cause allergic reactions in very susceptible persons.
	Contains: Crystalline Silica which has been determined to be carcinogenic to humans by IARC (1) when in respirable form. Risk of cancer depends on duration and level of inhalation exposure to spray mist or dust from sanding the dried paint.

See Section 11 for additional Toxicological information.

Aggravated N	ledical Condition	s None known		
HMIS	Health: 1*	Flammability: 0	Reactivity: 0	PPE: -

#### HMIS Legend

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- \* Chronic Hazard
- X Consult your supervisor or S.O.P. for "Special"
- handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

## 4. FIRST AID MEASURES

General Advice	No hazards which require special first aid measures.
Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
Skin Contact	Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes.
Inhalation	Move to fresh air. If symptoms persist, call a physician.
Ingestion	Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary.
Notes To Physician	Treat symptomatically

# 5. FIRE-FIGHTING MEASURES

5. FIRE-FIGHTING MEASURES			
Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.		
Protective Equipment And Precautions For Firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.		
Specific Hazards Arising From The Chemical	Closed containers may rupture if exposed to fire or extreme heat.		
Sensitivity To Mechanical Impact	No		
Sensitivity To Static Discharge	No		
Flash Point Data Flash Point (°F) Flash Point (°C) Flash Point Method	Not applicable Not applicable Not applicable		
Flammability Limits In Air Lower Explosion Limit Upper Explosion Limit	Not applicable Not applicable		
NFPA Health: 1 Flammability: 0 Inst	ability: 0 Special: -		

\_\_\_\_

- -

#### NFPA Legend

- 0 Not Hazardous
- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

## 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.
<b>Environmental Precautions</b>	Prevent further leakage or spillage if safe to do so.
Methods For Clean-Up	Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.
Other Information	None known

# 7. HANDLING AND STORAGE

Handling

Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.

Storage

Keep container tightly closed. Keep out of the reach of children.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Exposure Limits** 

#### **Hazardous Components**

Chemical Name	ACGIH	OSHA
Silica, crystalline	0.025 mg/m³ - TWA	respirable - (10)/(%SiO2 + 2) mg/m <sup>3</sup> TWA respirable - (250)/(%SiO2 + 5) mppcf TWA
		total dust - (30)/(%SiO2 + 2) mg/m <sup>3</sup> TWA
Titanium dioxide	10 mg/m³ - TWA	15 mg/m <sup>3</sup> - TWA total
Glass, oxide	1 fiber/cm3 - TWA 5 mg/m³ - TWA	N/E
Iron oxide	5 mg/m³ - TWA	10 mg/m <sup>3</sup> - TWA
Carbon black	3.5 mg/m <sup>3</sup> - TWA	3.5 mg/m <sup>3</sup> - TWA

#### Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits OSHA - Occupational Safety & Health Administration Exposure Limits N/E - Not Established

**Engineering Measures** 

Ensure adequate ventilation, especially in confined areas.

#### **Personal Protective Equipment**

Eye/Face Protection	Safety glasses with side-shields.
Skin Protection	Protective gloves and impervious clothing
Respiratory Protection	Effective dust mask. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. In case of insufficient ventilation wear suitable respiratory equipment

Hygiene MeasuresAvoid contact with skin, eyes and clothing. Remove and wash contaminated clothing<br/>before re-use. Wash thoroughly after handling.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

no odor 1.8 .4 ailable ailable ailable ailable ailable
•

## 9. PHYSICAL AND CHEMICAL PROPERTIES

VOC Regulatory Limit (g/L) Boiling Point (°F) Boiling Point (°C) Freezing Point (°F) Flash Point (°F) Flash Point (°C) Flash Point (°C) Flash Point Method Upper Explosion Limit Lower Explosion Limit <250 212 100 32 0 Not applicable Not applicable Not applicable Not applicable Not applicable

# **10. STABILITY AND REACTIVITY**

**Chemical Stability** 

**Conditions To Avoid** 

**Incompatible Materials** 

**Hazardous Decomposition Products** 

Possibility Of Hazardous Reactions

Stable under normal conditions.

Prevent from freezing

No materials to be especially mentioned.

None under normal use.

None under normal conditions of use.

# **11. TOXICOLOGICAL INFORMATION**

### Acute Toxicity

**Product** No information available

### Component

Silica, crystalline LD50 Oral: 500 mg/kg (Rat) vendor data

Titanium dioxide LD50 Oral: > 10000 mg/kg (Rat) LD50 Dermal: > 10000 mg/m<sup>3</sup> (Rabbit) LC50 Inhalation (Dust): > 6.82 mg/L (Rat, 4 hr.)

Iron oxide LD50 Oral: > 5000 mg/kg (Rat) vendor data

Carbon black LD50 Oral: > 15400 mg/kg (Rat) LD50 Dermal: > 3000 mg/kg (Rabbit)

#### **Chronic Toxicity**

#### Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:

Chemical Name	ACGIH	IARC	NTP	OSHA Carcinogen
Silica, crystalline	A2 - Suspected Human Carcinogen	1 - Human Carcinogen	Known Human Carcinogen	Listed
Titanium dioxide		2B - Possible Human Carcinogen		Listed
Carbon black		2B - Possible Human Carcinogen		Listed

• Crystalline Silica has been determined to be carcinogenic to humans by IARC (1) when in respirable form. Risk of cancer depends on duration and level of inhalation exposure to spray mist or dust from sanding the dried paint.

 Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

#### Legend

ACGIH - American Conference of Governmental Industrial Hygienists IARC - International Agency for Research on Cancer NTP - National Toxicity Program OSHA - Occupational Safety & Health Administration

# **12. ECOLOGICAL INFORMATION**

#### **Ecotoxicity Effects**

#### Product

Acute Toxicity to Fish No information available

#### Acute Toxicity to Aquatic Invertebrates

No information available

#### Acute Toxicity to Aquatic Plants

No information available

### Component

Acute Toxicity to Fish No information available

#### Titanium dioxide

LC50: >1000 mg/L (Fathead Minnow - 96 hr.)

## **12. ECOLOGICAL INFORMATION**

#### Acute Toxicity to Aquatic Invertebrates No information available

#### Acute Toxicity to Aquatic Plants

No information available

## **13. DISPOSAL CONSIDERATIONS**

Waste Disposal Method

Dispose of in accordance with federal, state, and local regulations. Dry, empty containers may be recycled in a can recycling program. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

## **14. TRANSPORT INFORMATION**

DOT Not regulated

ICAO / IATA Not regulated

IMDG / IMO Not regulated

## **15. REGULATORY INFORMATION**

### International Inventories

United States TSCA	Yes - All components are listed or exempt.
Canada DSL	Yes - All components are listed or exempt.

### **Federal Regulations**

#### SARA 311/312 hazardous categorization

No
Yes
No
No
No

#### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

This product may contain trace amounts of (other) SARA reportable chemicals. Contact the preparer for further information.

#### Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

This product may contain trace amounts of (other) HAPs chemicals. Contact the preparer for further information.

### State Regulations

#### **California Proposition 65**

This product may contain small amounts of materials known to the state of California to cause cancer or reproductive harm.

#### State Right-to-Know

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Louisiana	Rhode Island
Silica, crystalline	Х	Х	Х		Х
Titanium dioxide	Х	Х	Х		Х
Iron oxide	Х	Х	Х		Х
Carbon black	Х	Х	Х		Х

#### Legend

X - Listed

# **16. OTHER INFORMATION**

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Prepared By	Product Stewardship Department Complementary Coatings Corp. dba Insl-X 101 Paragon Drive Montvale, NJ 07645 Phone: 1-800-225-5554
Revision Date:	14-Feb-2013
Revision Summary	Not available

#### Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

#### End of MSDS