



Energy Efficient Design  
Diseño Eficiente de la Energía  
Conception rationnelle de l'énergie

# Thermoplastic Sump Pump

**High-Output Performance**

**Thermoplastic construction**

Resists corrosion

**Zinc motor housing**

Dissipates heat quickly and extends motor life

**Stainless steel fasteners and hardware**

Superior quality

**Smooth Flow Hydraulics™**

Deliver high performance for demanding applications

**Vertical float switch**

Operates in 10" basins or larger



**1/3 HP 3600 GPH**  
FPZS33V

**1/2 HP 4200 GPH**  
FPZS50V

**3/4 HP 4700 GPH**  
FPZS75V

| PERFORMANCE (GPH)                    |       |       |       |       |       |           | FLOAT SWITCH |     | SOLIDS HANDLING |
|--------------------------------------|-------|-------|-------|-------|-------|-----------|--------------|-----|-----------------|
| DISCHARGE HEIGHT ABOVE PUMPING LEVEL | 0'    | 5'    | 10'   | 15'   | 20'   | MAX. LIFT | ON           | OFF |                 |
| <b>FPZS33V</b>                       | 3,600 | 3,060 | 2,400 | 1,680 | 660   | 22'       | 7.5"         | 3"  | 3/16"           |
| <b>FPZS50V</b>                       | 4,200 | 3,660 | 3,000 | 2,160 | 960   | 22'       | 7.5"         | 3"  | 3/16"           |
| <b>FPZS75V</b>                       | 4,700 | 4,200 | 3,540 | 2,820 | 1,800 | 24'       | 7.5"         | 3"  | 3/16"           |

| MODEL          | WARRANTY | UPC          | CARTON DIMENSIONS | PALLET QTY. | WEIGHT   |
|----------------|----------|--------------|-------------------|-------------|----------|
| <b>FPZS33V</b> | 1 YEAR   | 022315368477 | 8" x 6" x 12.75"  | 105         | 7.7 LBS. |
| <b>FPZS50V</b> | 1 YEAR   | 022315368491 | 8" x 6" x 12.75"  | 105         | 10 LBS   |
| <b>FPZS75V</b> | 1 YEAR   | 022315368507 | 8" x 6" x 12.75"  | 105         | 10 LBS   |

Includes: 1 1/2" NPT discharge, 8' grounded power cord, piggyback-style switch for automatic or manual operation, detailed owner's manual

Check Valve replacement is recommended

293 Wright Street, Delavan, WI 53115

For Questions or Installation Instructions:

[www.flotecwater.com](http://www.flotecwater.com) 1-800-365-6832

