

POWER SERVICE PRODUCTS, INC.  
**MATERIAL SAFETY DATA SHEET**



**SECTION 1 - CHEMICAL COMPANY AND PRODUCT IDENTIFICATION**

**PRODUCT NAME:** DIESEL FUEL SUPPLEMENT +CETANE BOOST

Unless otherwise noted, all sections of this MSDS apply to each of the following products and part numbers.

**PART NUMBERS:**

<b>1:400 Treatment Ratio</b>	1016-06, 1025-06, 1025-12, 1041-04, 1080-06, 11016-06, 11025-06, 11025-12, 11041-04, 11080-06
<b>1:1,000 Treatment Ratio</b>	1000, 1060-01
<b>1:1,500 Treatment Ratio</b>	1050-02, 1055-01, 1260-01

**COMPANY IDENTIFICATION:**

Power Service Products, Inc.  
P.O. Box 1089  
Weatherford, TX 76086  
Email: [psp@powerservice.com](mailto:psp@powerservice.com)  
Phone: 800/643-9089 or 817-599-9486  
Fax: 817-599-4893

**Emergency Phone Number:** Within USA 1-800-424-9300. Outside USA 001-703-527-3887  
(Call Collect).

**SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS**

Specific chemical information is being withheld as a Trade Secret. Specific chemical information will be made available to health professionals in accordance with 29 CFR 1910.1200.

**INGREDIENTS**

Petroleum Distillates  
Aromatic Hydrocarbons

## SECTION 3 - HAZARDS IDENTIFICATION

### POTENTIAL HEALTH EFFECTS:

**EYES:** May cause eye irritation. Effects may include discomfort or pain and redness.

**SKIN:** May be harmful if absorbed through the skin. May cause skin irritation. Prolonged or repeated skin contact may cause drying or defatting of the skin. Symptoms may include pain, itching, discoloration, swelling, and blistering.

**INHALATION:** Do not breathe vapors. Harmful or fatal if inhaled. Breathing of high vapor concentrations may cause dizziness, light-headedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness. The vapor or fumes from this material may cause respiratory irritation and damage auditory system. Breathing this material at elevated concentrations causes central nervous system effects. Central nervous system effects may include headache, dizziness, nausea, vomiting, weakness, loss of coordination, blurred vision, drowsiness, confusion or disorientation. At extreme exposures, central nervous system effects may include respiratory depression, tremors, or convulsions, loss of consciousness, coma or death.

**INGESTION:** Do not take internally. Harmful or fatal if swallowed. If swallowed, may be aspirated and cause lung damage. This material can directly enter the lungs, if swallowed, or if subsequently vomited. Once in the lungs it is very difficult to remove and can cause severe injury or death.

### TARGET ORGANS:

Central nervous system, auditory system, respiratory system, blood, eyes, heart, kidneys, liver, skin, gastrointestinal tract.

## SECTION 4 - FIRST AID MEASURES

As a precaution, exposure to liquids, vapors, mists and fumes should be minimized.

### EYE CONTACT:

Hold eyelids apart and flush eyes with large amounts of water for at least 15 minutes. Remove contact lenses, if present, after first 5 minutes of rinsing. If irritation persists, call a physician.

### SKIN CONTACT:

Wash contact area with soap and water. Discard contaminated clothing and shoes or thoroughly clean before reuse. If irritation persists, call a physician.

### INHALATION:

If overcome by vapors, move the exposed person to fresh air. If breathing is labored, administer oxygen. If breathing has stopped, apply artificial respiration. Seek medical attention if breathing difficulties continue.

Revised: March 8, 2010

Supersedes: December 16, 2009

POWER SERVICE DIESEL FUEL SUPPLEMENT +CETANE BOOST

**INGESTION:**

If swallowed, do NOT induce vomiting. If vomiting occurs, have person lean forward. Keep at rest. Give the person a glass of water or milk to drink and get immediate medical attention. Never give anything by mouth to an unconscious person.

<b>SECTION 5 - FIRE AND EXPLOSION HAZARD DATA</b>
---

**FLAMMABLE PROPERTIES:****FLASH POINT:**

<b>Treatment Ratio</b>	<b>Part Numbers:</b>	<b>Flash Point:</b>
<b>1:400 Treatment Ratio</b>	1016-06, 1025-06, 1025-12, 1041-04, 1080-06, 11016-06, 11025-06, 11025-12, 11041-04, 11080-06	105°F (40.6°C)
<b>1:1,000 Treatment Ratio</b>	1000, 1060-01	130°F (54.4°C)
<b>1:1,500 Treatment Ratio</b>	1050-02, 1055-01, 1260-01	142°F (61.1°C)

**FLAMMABLE LIMITS:** lower: Not Determined upper: Not Determined

**AUTOIGNITION TEMPERATURE:** Not Determined

**EXTINGUISHING MEDIA:**

Use water fog, foam dry chemical or carbon dioxide (CO<sub>2</sub>) to extinguish flames.

**FIRE FIGHTING:**

**FIRE FIGHTING INSTRUCTIONS:** Use standard protective equipment including self-contained breathing apparatus (SCBA).

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Vapors are heavier than air and may travel along the ground to a distant ignition source and flash back. See Section 10 for Stability and Reactivity.

**NOTE:** EMPTY CONTAINERS CONTAIN COMBUSTIBLE VAPORS. DO NOT USE CUTTING TORCH EQUIPMENT OR ANY OTHER FLAME OR OTHER SOURCES OF IGNITION ON ANY EMPTY CONTAINER.

<b>SECTION 6 - ACCIDENTAL RELEASE MEASURES</b>
--

**PROTECTIVE MEASURES:**

Avoid contact with spilled material. Warn or evacuate occupants in surrounding and downwind areas. Eliminate all sources of ignition in the vicinity of the spill or released vapor. See Section 3

Revised: March 8, 2010

Supersedes: December 16, 2009

POWER SERVICE DIESEL FUEL SUPPLEMENT +CETANE BOOST

for Hazards Identification. See Section 4 for First Aid Measures. See Section 5 for Fire Fighting Information. See Section 8 for Personal Protective Equipment.

**SPILL MANAGEMENT:**

Eliminate potential sources of ignition. Stop leak if it can be done without risk. Dike and contain spill. Do not touch or walk through spilled material. Prevent entry into waterways, sewer, basements or confined areas. Remove with vacuum trucks or pump to storage/salvage vessels. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly. A vapor suppressing foam may be used to reduce vapors. Local, state and federal laws and/or regulations may apply to releases and disposal of this material, as well as those materials and items employed in the clean-up releases. The user/responder will need to determine which local, state and federal laws and/or regulations are applicable. The National Response Center can be reached at 1-800-424-8802.

**SECTION 7 - HANDLING AND STORAGE**

**HANDLING:** Avoid contact with eyes and skin. Use only with adequate ventilation. Use proper bonding and/or grounding procedures. Prevent small spills and leakage to avoid slip hazard. Material can accumulate static charges which may cause an electrical spark (ignition source). Keep away from ignition sources such as heat, sparks and open flame. No smoking.

**STORING:** DO NOT USE OR STORE near heat, sparks or open flames. USE AND STORE ONLY IN A WELL VENTILATED AREA. Handle containers with care. Keep container closed when not in use.

**STORAGE TEMPERATURE:**

<u>Treatment Ratio</u>	<u>Part Numbers:</u>	<u>Storage Temperature:</u>
<b>1:400 Treatment Ratio</b>	1016-06, 1025-06, 1025-12, 1041-04, 1080-06, 11016-06, 11025-06, 11025-12, 11041-04, 11080-06	-20°F to 104°F (-28.8°C to 40°C)
<b>1:1,000 Treatment Ratio</b>	1000, 1060-01	0°F to 104°F (-17.8°C to 40°C)
<b>1:1,500 Treatment Ratio</b>	1050-02, 1055-01, 1260-01	10°F to 104°F (-12.2°C to 40°C)

**NOTE:** CONTAINERS ARE STRICTLY SINGLE TRIP CONTAINERS. THEY ARE NOT TO BE USED FOR ANY REASON AFTER BEING EMPTIED. EMPTY CONTAINERS CONTAIN COMBUSTIBLE VAPORS. DO NOT USE CUTTING TORCH EQUIPMENT OR ANY OTHER FLAME OR OTHER SOURCES OF IGNITION ON ANY EMPTY CONTAINER.

## SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

### EXPOSURE GUIDELINES:

	CAS #	OSHA	ACGIH		NIOSH			Note
		PEL	TLV	STEL	REL	STEL	IDLH	
vinyl acetate	108-05-4	not est.	10 ppm	15 ppm	not est.	4 ppm	not est.	n/a
ethylbenzene	100-41-4	100 ppm	100 ppm	125 ppm	100 ppm	125 ppm	800 ppm	n/a
naphthalene	91-20-3	10 ppm	10 ppm	15 ppm	10 ppm	15 ppm	250 ppm	skin
xylene	1330-20-7	100 ppm	100 ppm	150 ppm	100 ppm	150 ppm	900 ppm	n/a
1,2,4-trimethylbenzene	95-63-6	not est.	25 ppm	not est.	25 ppm	not est.	not est.	n/a
petroleum distillates	n/a	500 ppm	not est.	not est.	86 ppm	444 ppm	1100 ppm	n/a

**ENGINEERING CONTROLS:** The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Local exhaust ventilation is recommended to control exposure.

### PERSONAL PROTECTIVE EQUIPMENT (PPE):

**Eyes and Face:** Eye protection such as safety glasses or chemical goggles is recommended if contact is likely.

**Skin:** If prolonged or repeated skin contact is likely, chemical/oil resistant clothing and gloves are recommended. Wear additional protective clothing as appropriate.

**Respiratory:** Wear a NIOSH/MSHA approved respirator as necessary.

**Specific Hygiene Measures:** Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Practice good housekeeping.

**NOTE:** These precautions are for room temperature handling. If used at elevated temperatures or aerosol/spray application added precautions may be necessary.

## SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

	1:400 Treatment Ratio	1:1,000 Treatment Ratio	1:1,500 Treatment Ratio
<b>PHYSICAL FORM</b>	Liquid	Liquid	Liquid
<b>COLOR</b>	Brown	Brown	Brown
<b>ODOR</b>	Aromatic Solvent	Aromatic Solvent	Aromatic Solvent
<b>POUR POINT</b>	-35°F (-37.2°C)	-20 (-28.9°C)	-10 (-23.3°C)

Revised: March 8, 2010

Supersedes: December 16, 2009

POWER SERVICE DIESEL FUEL SUPPLEMENT +CETANE BOOST

<b>BOILING POINT</b>	300°F (148.9°C)	300°F (148.9°C)	300°F (148.9°C)
<b>VAPOR PRESSURE (psi)</b>	0.2 – 0.95	0.2 – 0.95	0.2 – 0.95
<b>VAPOR DENSITY (AIR = 1)</b>	>5.0	>5.0	>5.0
<b>pH</b>	7 – 8 (slightly basic)	7 – 8 (slightly basic)	7 – 8 (slightly basic)
<b>SPECIFIC GRAVITY (at 60°F)</b>	0.925	0.930	0.930

## SECTION 10 - STABILITY AND REACTIVITY

### CHEMICAL STABILITY:

This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

### CONDITIONS TO AVOID:

Open flames, high energy ignition sources, and elevated temperatures.

### MATERIALS TO AVOID:

May react with oxygen, strong acids, strong oxidizing agents, such as; chlorates, nitrates, peroxides, alkalis, etc., nitriles, and chromic anhydride.

### HAZARDOUS DECOMPOSITION:

Carbon oxides, products of incomplete combustion.

### HAZARDOUS POLYMERIZATION:

Hazardous polymerization will not occur.

## SECTION 11 - TOXICOLOGICAL INFORMATION

This product contains the following chemicals classified as carcinogens as indicated:

Chemical	Listed By	Part Numbers
vinyl acetate	IARC	1050-02,1055-01, 1260-01
ethylbenzene	IARC	ALL
naphthalene	IARC, NTP	ALL

## SECTION 12 - ECOLOGICAL INFORMATION

### ECOTOXICITY:

This material is expected to be toxic to aquatic organisms.

Revised: March 8, 2010

Supersedes: December 16, 2009

POWER SERVICE DIESEL FUEL SUPPLEMENT +CETANE BOOST

## SECTION 13 - DISPOSAL CONSIDERATIONS

### RCRA Hazard Class (40CFR 261):

This product, if discarded, may become a hazardous waste under CERCLA. Use the following information:

Proper Shipping Name: **RQ Waste Flammable Liquid, N.O.S., (Petroleum Hydrocarbons)**  
Class: **3**  
I.D. Number: **UN 1993**  
Packing Group: **III**  
RCRA WASTE Number: **D001**

State or local laws may impose additional regulatory requirements regarding disposal.

**EMPTY CONTAINER WARNING:** Empty containers may contain residue and can be dangerous. See Section 5 for Fire and Explosion Hazard Data.

## SECTION 14 - TRANSPORTATION INFORMATION

The following part numbers are Consumer Commodities and are not regulated by DOT:

<b>1:400 Treatment Ratio</b>	1016-06, 1025-06, 1025-12, 1041-04, 1080-06, 11016-06, 11025-06, 11025-12, 11041-04, 11080-06
<b>1:1,500 Treatment Ratio</b>	1050-02, 1055-01

The following part numbers are regulated by DOT:

<b>1:1,000 Treatment Ratio</b>	1000, 1060-01
<b>1:1,500 Treatment Ratio</b>	1260-01

**PROPER SHIPPING NAME:** Combustible Liquid, N.O.S., (Petroleum Hydrocarbons)

**HAZARD CLASS:** Combustible Liquid

**I.D. NUMBER:** NA1993

**PACKING GROUP:** III

**PLACARDING:** Combustible Liquid

## SECTION 15 - REGULATORY INFORMATION

### §14(a) Consumer Product Safety Act General Certificate of Conformity

Power Service Products, Inc. certifies that this product meets the statutory and regulatory requirements of the US Consumer Products Safety Act, the Federal Hazardous Substances Act,

Revised: March 8, 2010

Supersedes: December 16, 2009

POWER SERVICE DIESEL FUEL SUPPLEMENT +CETANE BOOST

and the Poison Prevention Packaging Act of 1970, as applicable. The Power Service products are manufactured in the United States in Weatherford, Texas, unless otherwise indicated on the product label. The product manufacture date is stamped on the product container. This Certification is based upon a reasonable testing program conducted by Power Service Products, Inc. which includes a quality control program incorporating, as necessary, confirmation of compliance by component suppliers. Third-party testing is not required to certify compliance. Further details may be obtained by contacting the Power Service Products, Inc. Compliance Coordinator at 1-800-643-9089.

Contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200

**TSCA STATUS:**

All chemical substances found in this product comply with the Toxic Substances Control Act inventory reporting requirements.

**EPA SARA TITLE III CHEMICAL LISTINGS:**

**Section 302 Extremely Hazardous Substances:** None

**Sections 311/ 312 Hazard Class:**

Acute Health Effects: Yes      Sudden Release of Pressure Hazard: No

Chronic Health Effects: Yes      Reactivity Hazard: No

Fire Hazard: Yes

**NFPA (NATIONAL FIRE PROTECTION ASSOCIATION) RATING:**

HEALTH: **2**

FIRE: **2**

REACTIVITY: **0**

**Section 313:**

This product contains the following chemicals that are subject to the reporting requirements of EPCRA Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (40 CFR Part 372).

<b>Treatment Ratio</b>	<b>CAS Number</b>	<b>Chemical Name</b>	<b>Max %</b>
1:400 Treatment Ratio	100-41-4	ethylbenzene	9.0
	1330-20-7	xylene, mixed isomers	4.5
	91-20-3	naphthalene	1.0
	95-63-6	1,2,4 trimethylbenzene	25.0
1:1000 Treatment Ratio	108-05-4	vinyl acetate	0.5
	100-41-4	ethylbenzene	6.5
	1330-20-7	xylene, mixed isomers	4.0
	91-20-3	naphthalene	1.0
	95-63-6	1,2,4 trimethylbenzene	15.0
1:1,500 Treatment Ratio	108-05-4	vinyl acetate	0.5
	100-41-4	ethylbenzene	5.0

Revised: March 8, 2010

Supersedes: December 16, 2009

POWER SERVICE DIESEL FUEL SUPPLEMENT +CETANE BOOST



	1330-20-7	xylene, mixed isomers	3.5
	91-20-3	naphthalene	1.0
	95-63-6	1,2,4 trimethylbenzene	6.5

**The following components of this material are found on these state regulatory lists.**

**1, 2, 4 trimethylbenzene:** IL RTK, MN Hazardous substance, NJ RTK, PA RTK, RI RTK

**Vinyl acetate:** NDEP HAP, NJ RTK, MN Hazardous substance

**Ethylbenzene:** NDEP HAP, California Prop. 65, MA RTK, NJ RTK, PA RTK, RI RTK, MN Hazardous substance

**Xylene:** NDEP HAP, MA RTK, NJ RTK, PA RTK, RI RTK, MN Hazardous substance

**Napthalene:** California Prop. 65, MA RTK, NJ RTK, PA RTK, MN Hazardous substance

**This product contains a chemical known to the state of California to cause cancer.**

## **SECTION 16 – OTHER INFORMATION**

The information contained herein is offered in good faith and is believed to be accurate based on the data available to us as of the date of MSDS preparation. The information in this document applies to this specific product as supplied. It may not be appropriate for this product if the product is used in combination with other materials. The information in this document is not intended to constitute product performance information. Some of the information presented and conclusions drawn herein are from sources other than direct test data on the product. No statement shall be construed as an endorsement of any product or process. The recommended industrial hygiene and safe handling procedures are believed to be valid in the context of the intended use as described in product labeling. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate. You are urged to obtain material safety data sheets for all products you buy, process, use or distribute, and are encouraged to advise those who may come in contact with such products of the information contained therein. Regulatory requirements are subject to change and may differ between locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. No warranty or guarantee is expressed or implied with respect to this product, the accuracy and sufficiency of the data or recommendations herein, or the results to be obtained from the use of this product. IN NO EVENT SHALL POWER SERVICE PRODUCTS, INC. BE LIABLE FOR ANY LOSS, CLAIM, DAMAGE OR LIABILITY OF ANY KIND, WHICH MAY ARISE FROM OR IN CONNECTION WITH THE INFORMATION CONTAINED IN THIS DOCUMENT OR FROM THE USE, HANDLING OR STORAGE OF THE PRODUCT BY THE BUYER/USER, WHETHER DIRECT, INDIRECT, OR CONSEQUENTIAL, OR FOR ANY CLAIM BY ANY THIRD PARTY, BEYOND THE PURCHASE PRICE OR REPLACEMENT OF THE PRODUCT IN CONNECTION WITH WHICH SUCH LOSS, CLAIM, DAMAGE OR LIABILITY AROSE.

Revised: March 8, 2010

Supersedes: December 16, 2009

POWER SERVICE DIESEL FUEL SUPPLEMENT +CETANE BOOST

THE FOREGOING LIMITATIONS APPLY REGARDLESS OF THE CAUSES OR CIRCUMSTANCES GIVING RISE TO SUCH LOSS, CLAIM, DAMAGE OR LIABILITY, EVEN IF SUCH LOSS, CLAIM, DAMAGE, OR LIABILITY IS BASED ON NEGLIGENCE OR OTHER TORTS OR BREACH OF CONTRACT.