## MATERIAL SAFETY DATA SHEET

## **SECTION 1 - IDENTIFICATION**

Product identifier : Deep Creep

Product Use : For internal and external engine use

Chemical Family : Mixture.

Supplier's name and address: Manufacturer's name and address:

Sea Foam Sales Company Refer to Supplier

12987 Pioneer Trail Eden Prairie, MN, USA

55347

Information Telephone # : (952) 938-4811

24 Hr. Emergency Tel # : INFOTRAC - (800) 535-5053 (Within Continental US); (352) 323-3500 (Outside US)

NOTE: INFOTRAC emergency number is to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.

# SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

<u>Ingredients</u>	CAS#	Wt.%		
Pale Oil	64742-65-0	40 - 70		
Low Odor Base Solvent	64742-96-7 and 64742-47-8	30 - 60		
IPA	67-63-0	10 - 30		
Carbon dioxide	124-38-9	3 - 7		

## **SECTION 3 - HAZARDS IDENTIFICATION**

Classification: OSHA: Hazardous classification: Compressed gas; Flammable aerosol; Acute Health

Hazard

WHMIS classification: Class A (Pressurized containers); Class B5 (Flammable Aerosols);

Class D2B (Materials Causing Other Toxic Effects, Toxic Material)

**Emergency Overview:** Clear liquid, contained in a pressurized aerosol can. Typical odour.

Warning! Flammable aerosol. Vapors may cause flash fire. Harmful or fatal if swallowed. Can enter the

lungs and cause damage. Harmful if inhaled. May cause nausea, vomiting, headache and other central

nervous system effects. Causes eye irritation. May cause skin irritation.

# **POTENTIAL HEALTH EFFECTS:**

Signs and symptoms of short-term (acute) exposure

Inhalation: Inhalation of vapours can cause nasal and respiratory irritation. Exposure to high vapour concentration can

cause dizziness, nausea and central nervous system depression. May be fatal if inhaled. Breathing saturated vapours for a few minutes may be fatal. Saturated vapours can be encountered in confined

spaces and/or under conditions of poor ventilation. Propellant is a simple asphyxiant.

Skin: May cause mild skin irritation. If product is sprayed directly on skin, symptoms of frostbite may be

experienced including numbness, prickling and itching.

*Eyes:* May cause moderate to severe irritation. Spraying the product directly into the eyes may cause freezing,

and could cause eye damage.

Ingestion: Not an expected route of entry under normal conditions of use. However, if the product is sprayed directly

into mouth and large amounts of the liquid concentrate are swallowed, it may cause irritation to the mouth, throat and stomach. May cause central nervous system depression. May be absorbed and cause symptoms similar to those for inhalation. Symptoms may include burning pain, vomiting and diarrhea.

Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which

can be fatal.

### Effects of long-term (chronic) exposure:

Prolonged skin contact may cause dermatitis (rash), characterized by red, dry, itching skin. Prolonged overexposure to product can result in permanent central nervous system

changes.

MSDS Revision Date (dd/mm/yyyy): 28/01/2010 Page 2 of 6

Additional health hazards: See TOXICOLOGICAL INFORMATION, Section 11.

Potential environmental effects: See ECOLOGICAL INFORMATION, Section 12.

# **SECTION 4 - FIRST AID MEASURES**

Inhalation: Immediately remove person to fresh air. If breathing has stopped, give artificial respiration. If

breathing is difficult, give oxygen by qualified medical personnel only. Seek immediate

medical attention/advice.

Skin contact: Remove/Take off immediately all contaminated clothing. Wash exposed area thoroughly

with soap and water for at least 15 minutes. Get medical attention.

Immediately flush eyes with plenty of water for at least 15 minutes. Lift upper and lower lids Eye contact:

during flushing to ensure complete removal of chemical. Remove contact lenses. Seek

immediate medical attention/advice.

Seek immediate medical attention/advice. Do not induce vomiting. Do not give liquids to Ingestion:

drink. Never give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.

**Notes For Physician** Treat symptomatically.

### **SECTION 5 - FIRE FIGHTING MEASURES**

#### Fire hazards/conditions of flammability

: Flammable aerosol. Will ignite when exposed to heat, flame and other sources of ignition. Closed containers are contained under pressure and may explode if exposed to excess heat for a prolonged period of time.

#### Flammability classification (OSHA 29 CFR 1910.1200)

: Flammable aerosol.

**Oxidizing properties** None known.

Explosion data: Sensitivity to mechanical impact / static discharge

: Not available.

Suitable extinguishing media : Dry chemical, foam, carbon dioxide and water fog.

Special fire-fighting procedures/equipment

: Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. Move containers from fire area if safe to do so. Water spray may be useful in cooling equipment exposed to heat and flame. Direct water or foam spray may cause frothing which can increase the intensity and range of the fire.

## **Hazardous combustion products**

Carbon oxides; nitrogen oxides (NOx); Sulphur oxides; Phosphorus compounds; other unidentified organic compounds; irritating fumes and smoke.

# **SECTION 6 - ACCIDENTAL RELEASE MEASURES**

Personal precautions : All persons dealing with clean-up should wear the appropriate protective equipment

including self-contained breathing apparatus. Keep all other personnel upwind and away

from the spill/release. Restrict access to area until completion of clean-up.

**Environmental precautions** Spill response/cleanup

: Ensure spilled product does not enter drains, sewers, waterways, or confined spaces. : Ventilate area of release. Remove all sources of ignition. Stop spill or leak at source if safely

possible. Contain and absorb spilled liquid with non-combustible, inert absorbent material (e.g. sand), then place absorbent material into a container for later disposal (see Section 13). Large spills should be collected mechanically (remove by pumping) for disposal. only non-sparking tools and equipment in the clean-up process. Notify the appropriate

authorities as required.

**Prohibited materials** None known.

## Special spill response procedures

: If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone:

1-800-424-8002).

US CERCLA Reportable quantity (RQ): None.

### SECTION 7 - HANDLING AND STORAGE

Safe Handling procedures

: Use in a well-ventilated area. Wear suitable protective equipment during handling. Do not breathe vapours or spray mist. Avoid contact with skin, eyes and clothing. Keep away from heat and sources of ignition. Use proper bonding and grounding techniques when transferring liquid. Avoid contact with incompatible materials. Wash thoroughly after handling.

Storage requirements

: Store in a cool, dry, well-ventilated area. Keep away from direct sunlight. Store away from areas of excessive heat, open flames, sparks, and other possible sources of ignition. Keep away from incompatibles. Keep containers tightly closed when not in use.

Incompatible materials

: Strong oxidizing agents; Strong acids; Alkali metals; Aluminium.

**Special packaging materials**: Always keep in containers made of the same materials as the supply container.

#### SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure Limits				
	ACGI	H TLV	OSHA PEL	
<u>Ingredients</u>	<u>TWA</u>	<u>STEL</u>	<u>PEL</u>	<u>STEL</u>
Hydrotreated heavy naphthenic distillate	N/Av	N/Av	N/Av	N/Av
Alkanes, C12-14, iso-	N/Av	N/Av	N/Av	N/Av
Isopropyl alcohol	200 ppm	400 ppm	400 ppm	N/Av
Carbon dioxide	5000 ppm	30000 ppm	5000 ppm ; 9000 mg/m³	N/Av

#### Ventilation and engineering measures

: Provide mechanical ventilation in confined spaces. Use explosion-proof equipment.

Respiratory protection

: If the TLV is exceeded, a NIOSH/MSHA-approved respirator is advised. Advice should be sought from respiratory protection specialists.

Skin protection

Impervious gloves must be worn when using this product. Advice should be sought from glove suppliers. Wear long sleeved shirt and pants to minimize exposed skin.

Eye / face protection

Chemical safety glasses with side shields or splash proof goggles. A full face shield may also be necessary.

Other protective equipment

Depending on conditions of use, an impervious apron should be worn. An eyewash station and safety shower should be made available in the immediate working area.

General hygiene considerations

Avoid breathing vapour or mist. Avoid contact with skin, eyes and clothing. Do not eat, drink or smoke when using this product. Upon completion of work, wash hands before eating, drinking, smoking or use of toilet facilities. Remove and wash contaminated clothing before re-use

### **SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

Physical state : Liquid aerosol. Appearance : Colourless aerosol spray.

Odour : Typical odour. Odour threshold : N/Av

pH : N/Av

Boiling point : N/Av Specific gravity : (concentrate) 0.77

Melting/Freezing point : N/Av Coefficient of water/oil distribution

: N/Av

Vapour pressure (mmHg @ 20° C / 68° F) Solubility in water : Complete

: 75-85 psig @ 21°C

Vapour density (Air = 1) : >1 Evaporation rate (n-Butyl acetate = 1)

: (water = 1) >1

Volatile organic Compounds (VOC's) Volatiles (% by weight) : N/Av

: N/Av

Flash point : N/Av

Flash point Method : N/Av Auto-ignition temperature : N/Av Lower flammable limit (% by vol.)

Upper flammable limit (% by vol.)

2.1 (propellant) (Lower explosion limit)

: 8.5 (propellant) (Upper explosion limit)

MSDS Revision Date (dd/mm/yyyy): 28/01/2010 Page 4 of 6

Flame Projection Length : N/Av Flashback observed : N/Av

Section 10: Stability And Reactivity

Stability and reactivity : Stable under the recommended storage and handling conditions prescribed.

Hazardous polymerization : Will not occur.

Conditions to avoid : Keep away from excessive heat, open flames, sparks and other possible sources of ignition.

Materials To Avoid And Incompatibility

: See Section 7 (Handling and Storage) for further details.

**Hazardous decomposition products** 

: None known, refer to hazardous combustion products in Section 5.

### **SECTION 11 - TOXICOLOGICAL INFORMATION**

Target organs : Eyes, skin, respiratory system and digestive system.

Routes of exposure : Inhalation: YES Skin Absorption: NO Skin & Eyes: YES Ingestion: YES

Toxicological data : There is no available data for the product itself, only for the ingredients. See below

for individual ingredient acute toxicity data.

	LCso(4hr)	LD <sub>50</sub>		
<u>Ingredients</u>	<u>inh, rat</u>	(Oral, rat)	(Rabbit, dermal)	
Hydrotreated heavy naphthenic distillate	2.18 mg/L	>5000 mg/kg	>2000 mg/kg	
Alkanes, C12-14, iso-	N/Av	N/Av	N/Av	
Isopropyl alcohol	17000 ppm	4720 mg/kg	12890 mg/kg	
Carbon dioxide	N/Av	N/Av	N/Av	

Carcinogenic status : No components are listed as carcinogens by ACGIH, IARC, OSHA or NTP.

**Reproductive effects**: Not expected to have other reproductive effects.

**Teratogenicity**: Not expected to be a teratogen.

**Mutagenicity**: Not expected to be mutagenic in humans.

**Epidemiology** : Not available.

Sensitization to material: Not expected to be a skin or respiratory sensitizer.Synergistic materials: None known or reported by the manufacturer.Irritancy: May cause eye, skin and respiratory tract irritation.Other important hazards: None known or reported by the manufacturer.

Conditions aggravated by overexposure

: None known or reported by the manufacturer.

### **SECTION 12 - ECOLOGICAL INFORMATION**

Ecotoxicity : No data is available on the product itself.

Mobility : No data is available on the product itself.

Persistence : No data is available on the product itself.

Bioaccumulation potential : No data is available on the product itself.

Other Adverse Environmental effects

The ecological characteristics of this product have not been fully investigated. The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters.

### SECTION 13 - DISPOSAL CONSIDERATIONS

Handling for Disposal : Handle waste according to recommendations in Section 7. Empty containers retain residue (liquid and/or vapour) and can be dangerous.

Methods of Disposal : Dispose in accordance with all applicable federal, state, provincial and local regulations. Contact your local, state, provincial or federal environmental agency for specific rules.

RCRA:

If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental

agencies.

### **SECTION 14: TRANPORTATION INFORMATION**

Regulatory Information	UN Number	Shipping Name	Class	Packing Group	Label	
49CFR/DOT	UN1950	Aerosols	3	none	ORM-D	
49CFR/DOT Additional information		portation information applies only to ground transport and does age size, mode of shipment, or other regulatory descriptors.	not address reg	ulatory variat	ions due to	
TDG	UN1950	AEROSOLS	3	none	ORM-D	
TDG Additional	The listed transportation information applies only to ground transport and does not address regulatory variations due to changes in package size, mode of shipment, or other regulatory descriptors.					

# **SECTION 15 - REGULATORY INFORMATION**

## **US Federal Information:**

This material is classified as hazardous under OSHA regulations (29CFR 1910.1200). See Section 2. TSCA: All listed ingredients appear on the Toxic Substances Control Act (TSCA) inventory.

SARA TITLE III: Sec. 302, Extremely Hazardous Substances, 40 CFR 355: No Extremely Hazardous Substances are present in this material.

SARA TITLE III: Sec. 311 and 312, MSDS Requirements, 40 CFR 370 Hazard Classes: Fire Hazard; Acute Health Hazard. Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds for the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

SARA TITLE III: Sec. 313, Toxic Chemicals Notification, 40 CFR 372: This product may be subject to SARA notification requirements, since it contains Toxic Chemical constituents above their de minimus concentrations. This product contains: Isopropyl alcohol

## **US State Right to Know Laws:**

California Proposition 65: To the best of our knowledge, this product does not contain any chemicals known to the State of California to cause cancer or reproductive harm.

### **International Information:**

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL). This product is a WHMIS Controlled Product. It meets one or more of the criteria for a controlled product provided in Part IV of the Canadian Controlled Products Regulations (CPR). See Section 2.

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

# **SECTION 16 - OTHER INFORMATION**

NFPA/HMIS Rating : \* - Chronic hazard 0 - Minimal 1 - Slight 2 - Moderate 3 - Serious 4 - Severe

> \* 1 Health: Flammability: 3 Reactivity: 0

ACGIH: American Conference of Governmental Industrial Legend :

Hygienists

CAS: Chemical Abstract Services

CERCLA: Comprehensive Environmental Response,

Compensation, and Liability Act of 1980 CFR: Code of Federal Regulations DOT: Department of Transportation

EPA: Environmental Protection Agency HMIS: Hazardous Materials Identification System HSDB: Hazardous Substances Data Bank IARC: International Agency for Research on Cancer

Inh: Inhalation

MSHA: Mine Safety and Health Administration

N/Ap: Not Applicable N/Av: Not Available

NIOSH: National Institute of Occupational Safety and Health

NTP: National Toxicology Program

NFPA: National Fire Protection Association

OSHA: Occupational Safety and Health Administration PEL: Permissible exposure limit

RCRA: Resource Conservation and Recovery Act RTECS: Registry of Toxic Effects of Chemical Substances SARA: Superfund Amendments and Reauthorization Act

STEL: Short Term Exposure Limit

TDG: Canadian Transportation of Dangerous Goods Act &

Regulations

TLV: Threshold Limit Values TPQ: Threshold Planning Quantity TWA: Time Weighted Average TSCA: Toxic Substance Control Act

WHMIS: Workplace Hazardous Materials Identification System

References: 1. ACGIH. Threshold Limit Values and Biological Exposure Indices for 2009

International Agency for Research on Cancer Monographs, searched 2009
 Canadian Centre for Occupational Health and Safety, CCInfoWeb databases

(Chempendium, HSDB and RTECs).

4. Material Safety Data Sheet from manufacturer.

5. US EPA Title III List of Lists6. California Proposition 65 List

**Prepared for:** Direct all enquiries to:

Sea Foam Sales Company, 12987 Pioneer Trail, Eden Prairie, MN, USA 55347

Telephone: (952) 938-4811

Prepared by: ICC The Compliance Center Inc.

## **DISCLAIMER OF LIABILITY**

This Material Safety Data Sheet was prepared by ICC The Compliance Center Inc using information provided by / obtained from Sea Foam Sales Company and CCOHS' Web Information Service. The information in the Material Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and Sea Foam Sales Company expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this MSDS does not apply to use with any other product or in any other process.

This Material Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc and Sea Foam Sales Company.

Preparation Date (dd/mm/yyyy) : 08/11/2007 28/01/2010

Reviewed Date (dd/mm/yyyy)

Revision No. : 2

Revision Information : (M)SDS sections updated: All

END OF DOCUMENT