



Revision Date: 06/28/2006

Issue date: 10/30/2006

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: Naval Jelly® Rust Dissolver
Product type: Rust Dissolver
Company address:
Henkel Corporation
1001 Trout Brook Crossing
Rocky Hill, Connecticut 06067

Item No. : 80276
Region: United States
Contact Information:
Telephone: 860.571.5100
Emergency telephone: 860.571.5100
Internet: www.loctite.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Hazardous components</u>	<u>%</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>OTHER</u>
Phosphoric acid 7664-38-2	10-30	1 mg/m ³ TWA 3 mg/m ³ STEL	1 mg/m ³ TWA	None
Isopropyl alcohol 67-63-0	1-5	200 ppm TWA 400 ppm STEL	400 ppm TWA 980 mg/m ³ TWA	None
Polysaccharide Proprietary	1-5	None	None	None
Sulfuric acid 7664-93-9	0.1-1	0.2 mg/m ³ TWA	1 mg/m ³ TWA	None
2-Oxopropanoic acid 127-17-3	0-0.1	None	None	None

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HMIS:

Physical state: Gel
Color: Pink
Odor: Lime

HEALTH: 1*
FLAMMABILITY: 0
PHYSICAL HAZARD: 0
Personal Protection: See Section 8

CAUTION: MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.
MAY BE HARMFUL IF SWALLOWED.

Relevant routes of exposure: Eye contact, Skin contact, Inhalation, Ingestion

Potential Health Effects

Inhalation: May cause respiratory tract irritation. Prolonged inhalation of large concentrations can be irritating to lungs, and mucous membranes of nose and throat.
Skin contact: May cause skin irritation.
Eye contact: Non-irritating.
Ingestion: May be harmful if swallowed.

Existing conditions aggravated by exposure: Respiratory disorders.

Item No. : 80276

Product name: Naval Jelly® Rust Dissolver

See Section 11 for additional toxicological information.

4. FIRST AID MEASURES

Inhalation:	Remove to fresh air. If discomfort persists seek medical attention.
Skin contact:	Immediately flush skin with plenty of water (using soap, if available). If symptoms persist, obtain medical attention.
Eye contact:	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
Ingestion:	Do not induce vomiting. Keep individual calm. Obtain medical attention.

5. FIRE-FIGHTING MEASURES

Flash point:	None.
Autoignition temperature:	Not applicable
Flammable/Explosive limits-lower %:	Not applicable
Flammable/Explosive limits-upper %:	Not applicable
Extinguishing media:	Foam, dry chemical or carbon dioxide.
Special fire fighting procedures:	None
Unusual fire or explosion hazards:	Not flammable, however Hydrogen gas may be liberated if product contacts powdered metals or metals above 185°F.
Hazardous combustion products:	None known.

6. ACCIDENTAL RELEASE MEASURES

Environmental precautions:	Prevent product from entering drains or open waters.
Clean-up methods:	Ensure adequate ventilation. Neutralize acid using lime or a lime based agent compatible with the product. Soak up with inert absorbent. Flush with water. Store in a closed container until ready for disposal.

7. HANDLING AND STORAGE

Handling:	Avoid contact with eyes, skin and clothing. Avoid breathing vapor and mist. Wash thoroughly after handling.
Storage:	Keep from freezing.
Incompatible products:	Caustics. Powdered metals.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering controls:	General ventilation is acceptable if the exposure to materials in section 2 is maintained below applicable exposure limits. Refer to OSHA standards 1910.94, 1910.107, 1910.108
Respiratory protection:	Not normally required.
Skin protection:	Disposable rubber or plastic gloves.

Item No. : 80276

Product name: Naval Jelly® Rust Dissolver

Eye/face protection: Safety goggles or safety glasses with side shields.

See Section 2 for exposure limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Gel
Color: Pink
Odor: Lime
Vapor pressure: Low
pH: 1.5 - 2.5
Boiling point/range: Approximately 100°C (212°F)
Melting point/range: Not applicable
Specific gravity: 1.191
Vapor density: Not available
Evaporation rate: Not available
Solubility in water: Soluble.
Partition coefficient (n-octanol/water): Not available
VOC content: 5.17%; 60.4 grams/liter

10. STABILITY AND REACTIVITY

Stability: Stable
Hazardous polymerization: Will not occur.
Hazardous decomposition products: Hydrogen, by reaction with metals
Incompatibility: Powdered metals. Caustics.
Conditions to avoid: Storage with incompatible materials.

11. TOXICOLOGICAL INFORMATION

Carcinogen Status

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen
Phosphoric acid 7664-38-2	No	No	No
Isopropyl alcohol 67-63-0	No	No	No
Polysaccharide Proprietary	No	No	No
Sulfuric acid 7664-93-9	Known Carcinogen	Group 1	Yes
2-Oxopropanoic acid 127-17-3	No	No	No

Literature Referenced Target Organ & Other Health Effects

Hazardous components	Health Effects/Target Organs
Phosphoric acid 7664-38-2	Corrosive, Irritant
Isopropyl alcohol 67-63-0	Allergen, Blood, Central nervous system, Irritant, Kidney, Liver, Brain, Spleen
Polysaccharide Proprietary	Irritant
Sulfuric acid 7664-93-9	Corrosive, Irritant, Lung, Human carcinogen
2-Oxopropanoic acid 127-17-3	No data

12. ECOLOGICAL INFORMATION

Ecological information: Not available

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.

EPA hazardous waste number: Not a RCRA hazardous waste. Waste must be tested to determine the applicable EPA hazardous waste numbers.

14. TRANSPORT INFORMATION

The shipping classifications in this section are for non-bulk packaging only (unless otherwise specified). Shipping classification may be different for bulk packaging.

U.S. Department of Transportation Ground (49 CFR):

Proper shipping name: Phosphoric acid Solution
Hazard class or division: 8
Identification number: UN 1805
Packing group: III
Exceptions: (Not more than 4L) Consumer Commodity ORM-D
Marine pollutant: None

International Air Transportation (ICAO/IATA):

Proper shipping name: Phosphoric acid Solution
Hazard class or division: 8
Identification number: UN1805
Packing group: III

Water Transportation (IMO/MDG):

Proper shipping name: Phosphoric acid Solution
Hazard class or division: 8
Identification number: UN1805
Packing group: III
Marine pollutant: None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 5 (a) (2) SNUR: None.
TSCA 12 (b) Export Notification: None.

CERCLA/SARA Section 302 EHS: None above reporting de minimus.
CERCLA/SARA Section 311/312: Immediate Health Hazard
CERCLA/SARA 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Isopropyl alcohol (CAS# 67-63-0).

California Proposition 65: This product contains a chemical known to the State of California to cause cancer.

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Domestic Substances List.
WHMIS hazard class: D.2.A, D.2.B, E

Item No. : 80276

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: This material safety data sheet contains changes from the previous version in section(s): 14

Prepared by: Rajal Dhruva, Health and Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.