

**Material Safety Data Sheet**  
 May be used to comply with  
 OSHA's Hazard Communication Standard,  
 29 CFR 1910.1200. Standard must be  
 consulted for specific requirements.

**U. S. Department of Labor**  
 Occupational Safety and Health Administration  
 (Non-Mandatory Form)  
 Form Approved  
 OMB No. 1218-0072

<b>IDENTITY (As Used on Label and List)</b> READY-STRIP PRO	<i>Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.</i>
--	--

<b>Section I</b>	
<b>Manufacturer's Name</b> Back to Nature Products Co. Div. of Dynacraft Industries Inc.	<b>Emergency Telephone Number</b> (732) 792-2001
<b>Address (Number, Street, City, and ZIP Code)</b> 28 Harrison Ave. Suite 238 Englishtown, New Jersey 07726	<b>Telephone Number for Information</b> (732) 792-2001
	<b>Date Prepared</b> 10/1/01
	<b>Signature of Preparer (optional)</b>

<b>Section II-Hazardous Ingredients/Identity Information</b>				
<b>Hazardous Components ( Specific Chemical Identity; Common Name(s))</b>	<b>OSHA PEL</b>	<b>ACGIH TLV</b>	<b>Other Limits</b>	<b>% (optional)</b>
Benzyl Alcohol (100-51-6)		Not Established		25-30%
N.Methyl-2 Pyrrolidone (873-50-40)				8-12%
Formic Acid (64-18-6)	5 ppm	5 ppm		3-14%
Non Toxic/Non Hazardous Components				55-65%

<b>Section III- Physical/Chemical Characteristics</b>			
<b>Boiling Point</b>	205 <sup>o</sup> c	<b>Specific Gravity (H<sub>2</sub>O=1)</b>	1.1
<b>Vapor Pressure (mm Hg.)</b>	.2 mm Hg at 20 <sup>o</sup> c (68 <sup>o</sup> F)	<b>Melting Point</b>	N/A
<b>Vapor Density (AIR =1)</b>	5.5-6	<b>Evaporation Rate (Butyl Acetate=1)</b>	.06
<b>Solubility in Water</b>	25-40%		
<b>Appearance and Odor</b>	Mild odor		

<b>Section IV- Fire and Explosion Hazard Data</b>				
<b>Flash Point (Method Used)</b>	over 200 <sup>o</sup> F	<b>Flammable Limits</b>	<b>LEL</b> 1.1	<b>UEL</b> 8.5
<b>Extinguishing Media</b>	Water fog, spray, dry chemical C02			
<b>Special Fire Fighting Procedures</b>	Do not enter confined fire space without protective equipment including NIOSH approved SCBA. Use water spray to cool fire exposed surfaces and to protect personnel.			
<b>Unusual Fire and Explosion Hazards</b>	Low when exposed to flames. May react with strong oxidizing materials			
N/A = Not Applicable				

### Section V-Reactivity Data

Stability	Unstable		Conditions to Avoid	Hot or cold Storage
	Stable	X		
Incompatibility ( <i>Materials to Avoid</i> )		Strong oxidizers, acids and alkalis		
Hazardous Decomposition or Byproducts		Thermal decomposition (combustion) will produce carbon monoxide and dioxide		
Hazardous Polymerization	May Occur		Conditions to Avoid	N/A
	Will Not Occur	X		

### Section VI-Health Hazard Data

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?	Eye
	Not Established	Not Established	Not Established	Eye
Health Hazards ( <i>Acute and Chronic</i> ) Direct contact or exposure to mists and vapor may cause slight to moderate eye irritation. Prolonged or repeated exposure to product, vapors, or mists may cause slight skin irritation. Ingestion may cause moderate to severe irritation of the gastrointestinal tract. Inhalation exposure to vapor or mists may cause moderate to severe irritation of the respiratory tract.				
Carcinogenicity:	NTP?	IARC monographs?	OSHA Regulated?	
	Not listed	Not listed	Not regulated	
Signs and Symptoms of Exposure: Eye Contact: a stinging sensation, excess blinking and tear production, redness and swelling of the conjunctive. Skin Contact: redness and a burning sensation. Prolonged or widespread contact may result in the absorption of potentially harmful amounts of material, with identical symptoms as ingestion. Ingestion: nausea, headache, dizziness, and abdominal pain. Inhalation: headache, nausea, coughing, chest pain and vomiting.				
Medical Conditions Generally Aggravated by Exposure		None known		
Emergency and First Aid Procedures Inhalation-remove victim to fresh air and seek medical attention if irritation persists. Eyes-immediately flush exposed areas with large quantities of water for at least 15 minutes. Skin- immediately flush skin with large amounts of water for at least 15 minutes while removing contaminated clothing. If irritation is evident or discoloration persists, seek medical attention. Ingestion-do not induce vomiting unless directed by medical personnel. Drink large quantities of water or milk. Seek medical attention.				

### Section VII-Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled	Remove any source of ignition. Dike spill using soil, sand, or absorbent. Soak up with suitable, non-combustible absorbent material, collect in suitable containers for disposal. Recover free product, if possible. Prevent flow to sewer and public waters. For water spill, notify downstream users of possible contamination.
Waste Disposal Method	Dispose of in accordance with all Local, State and Federal regulations.
Precautions to Be Taken in Handling and Storing	Store at temperatures between 32°F-110°F, keep container tightly closed. Empty containers should be thoroughly rinsed with water and disposed of according to local regulations.

### Section VIII-Control Measures

Respiratory Protection ( <i>Specify Type</i> ) Use NIOSH approved chemical cartridge (organic vapor) respiratory equipment when spraying material (full face respirator is recommended)			
Ventilation	Local Exhaust	Sufficient to maintain air concentration as required by OSHA	Special N/A
	Mechanical (General)	Maintain adequate ventilation	Other N/A
Protective Gloves	Butyl rubber, Neoprene gloves	Eye Protection	Eye protection for application and removal such as chemical splash goggles.
Other Protective Clothing or Equipment	Impervious coveralls, apron, boots, as necessary to prevent skin contact. Eye wash as needed.		
N/A = Not applicable			