

MATERIAL SAFETY DATA SHEET

I. PRODUCT IDENTIFICATION

Name: HENRY Ceramic Tile Repair Adhesive
Description: Thin-Set Mortar

II. DEPARTMENT OF TRANSPORTATION INFORMATION

SHIPPING NAME: Not Classified
EMERGENCY ONLY CONTACT: 1-800-255-3924

III. HMIS (0=Minimal hazard; 4=severe hazard)

Health = 1 Flammability = 0 Reactivity = 0

IV. PRODUCT CONTENT

This product does not contain chemicals subject to the reporting requirements of Section 313 of SARA Title III and 40 CFR 372. All components are on TSCA inventory. This product does not contain asbestos.

V. HAZARDOUS INGREDIENTS

INGREDIENT:	CAS#	PERCENT:	OCCUP. EXPOS. LMT.
Portland Cement	65997-15-1	45-47 %	OSHA PEL ASGIH TLV 10 mg/m ³ .025 mg/m ³
Quartz	14808-60-7	32-34 %	.05 mg/m ³ .1 mg/m ³

VI. PHYSICAL DATA

BOILING POINT: N/A. VAPOR PRESSURE (mmHg): N/A.
VAPOR DENSITY: (AIR=1) N/A. SPECIFIC GRAVITY
(WATER=1): 1.2. MELTING POINT: N/A. EVAPORATION
RATE (BUTYL ACETATE=1): N/A. SOLUBILITY IN
WATER: < 50G/100CM³. APPEARANCE: Fine gray
powder. ODOR: Odorless.

VII. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (METHOD): Non-Flammable. FLAMMABLE
RANGE: LEL: N/A. UEL: N/A. EXTINGUISHING MEDIA:
Will not burn. SPECIAL FIRE FIGHTING PROCEDURES:
Wear a NIOSH/MSHA approved respirator. UNUSUAL
FIRE AND EXPLOSION HAZARDS: None.

VIII. HEALTH HAZARD DATA

PRIMARY ROUTES OF ENTRY: Inhalation, skin and
ingestion. TARGET ORGANS: Upper respiratory system,
skin and eyes. EFFECTS OF OVEREXPOSURE: Exposure
to skin and eyes may cause rash or irritation. Inhalation may
cause cough, shortness of breath, wheezing and reduced
pulmonary function. Excessive or long-term inhalation may
cause irritation to nose, throat, respiratory passages and
may cause silicosis. Carcinogenicity: NTP, YES. IARC
Monographs, YES. OSHA Regulated, NO. MEDICAL
CONDITIONS GENERALLY AGGRAVATED BY
EXPOSURE: Allergies to Portland cement or individuals
with respiratory disease or subject to eye irritation. FIRST
AID PROCEDURES: Seek medical attention. Inhalation:
remove to fresh air. Skin: wash with soap and water. Eyes:
flush with plenty of water. Ingestion: dilute with water.

IX. REACTIVITY DATA

STABILITY: Stable. INCOMPATIBILITY: None.
HAZARDOUS DECOMPOSITION PRODUCTS: None.
HAZARDOUS POLYMERIZATION: Will not occur.

X. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR
SPILLED: Spills should be contained and placed in suitable
containers for disposal. Avoid creating dust. WASTE
DISPOSAL METHOD: Dispose of in accordance with all
Federal, State and Local waste disposal regulations. Do not
flush unused contents or residue down drains. Do not reuse
container.

XI. SAFE HANDLING AND USE INFORMATION

VENTILATION: Normal ambient ventilation should be
sufficient. RESPIRATORY PROTECTION: Wear a
NIOSH/MSHA approved respirator.

XII. SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:
Keep product in dry cool area. Avoid breakage of bagged
material. Prevent dust accumulation. WARNING: Crystalline
silica (Quartz) is classified as a substance known to the state of
California to be a carcinogen. OTHER PRECAUTIONS: Avoid
creating dust. Use coveralls, apron, boots and safety glasses to
prevent contact. Dusty clothing should be laundered before
reuse.

The information presented herein is supplied as a guide to those who
handle or use this product. Safe work practices must be employed when
working with any materials. It is important that the end user makes a
determination regarding the adequacy of the safety procedures employed
during the use of this product.

N/A- Not applicable or not available

N/K- Not known or none known

HENRY

Ceramic Tile Repair Adhesive

Prepared 7/07

The W.W. Henry Company
400 Ardex Park Drive
Aliquippa, PA 15001
(724) 203-8499

Visit our Web site: <http://www.wwhenry.com>