# valspar

## **Material Safety Data Sheet**

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product Identification	
Product ID:	140.0001316
Product Name:	CABOT ST STAIN NEW CEDAR
Product Use:	Paint product.
Print date:	23/Mar/2009
Revision Date:	14/Mar/2009

#### **Company Identification**

The Valspar Corporation - Architectural Coatings Division 1191 Wheeling Road Wheeling, IL 60090

Manufacturer's Phone: 1-847-520-8580
--------------------------------------

24-Hour Medical Emergency	1-888-345-5732
Phone:	

#### 2. HAZARDS IDENTIFICATION

Primary Routes of Exposure: Inhalation Ingestion Skin absorption

#### Eye Contact:

• Moderate eye irritation

Skin Contact: None known.

Ingestion: None known.

#### Inhalation:

• May cause irritation of respiratory tract.

#### This product contains ingredients that may contribute to the following potential chronic health effects:

• Prolonged exposure to respirable crystalline quartz silica may cause delayed chronic injury (silicosis).

#### Carcinogens:

• Possible cancer hazard. Contains material which may cause cancer based on animal data.

## 3. COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS

## 3. COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS

Ingredient Name CAS-No.	Approx. Weight %	Chemical Name
PROPYLENE GLYCOL 57-55-6	1 - 5	1,2-Propylene glycol
HYDRATED ALUMINUM MAGNESIUM SILICATE 12174-11-7	.1 - 1	Palygorskite (attapulgite)
TITANIUM DIOXIDE 13463-67-7	.1 - 1	Titanium dioxide

If this section is blank there are no hazardous components per OSHA guidelines.

## 4. FIRST AID MEASURES

#### Eye Contact:

Get medical attention, if symptoms develop or persist. Immediately flush eye(s) with plenty of water. Remove any contact lenses and open eyes wide apart.

#### Skin Contact:

Wash off with plenty of water.

#### Ingestion:

Get medical attention if symptoms occur

#### Inhalation:

Move to fresh air. Get medical attention, if symptoms develop or persist.

#### Medical conditions aggravated by exposure:

Any respiratory or skin condition.

#### 5. FIRE FIGHTING MEASURES

Flash point (Fahrenheit):	205°F (96°C)
Lower explosive limit:	2 %
Upper explosive limit:	17 %
Autoignition temperature:	not determined -°F (°C)
Sensitivity to impact:	no
Sensitivity to static discharge:	Sensitivity to static discharge is not expected.
Hazardous combustion products:	See Section 10.

#### **Unusual fire and explosion hazards:** None known.

#### Extinguishing media:

Carbon dioxide, dry chemical, foam and/or water fog.

#### Fire fighting procedures:

Firefighters should be equipped with self-contained breathing apparatus and turn out gear. Keep containers and surroundings cool with water spray.

#### 6. ACCIDENTAL RELEASE MEASURES

#### Action to be taken if material is released or spilled:

Ventilate the area. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Avoid contact with eyes.

## 7. HANDLING AND STORAGE

#### Precautions to be taken in handling and storage:

Keep container closed when not in use. Do not freeze. Since emptied containers may contain product residue, follow all label warnings, even after container is emptied. Do not cut, drill, grind, or weld on or near this container.

## 8. PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE CONTROLS

#### **Personal Protective Equipment**

#### Eye and face protection:

Wear safety glasses or goggles to protect against exposure.

#### Skin protection:

Appropriate chemical resistant gloves should be worn.

#### **Respiratory protection:**

If exposure cannot be controlled below applicable limits, use the appropriate NIOSH approved respirator such as an air purifying respirator with organic vapor cartridge and dust/mist filter. Consult the respirator manufacturer's literature to ensure that the respirator will provide adequate protection. Read and follow all respirator manufacturer's instructions.

#### Ventilation

Use only in well-ventilated areas. Ensure adequate ventilation, especially in confined areas.

#### **Exposure Guidelines**

#### **OSHA Permissible Exposure Limits (PEL's)**

0	Approx. Weight %	TWA	(final)	Ceilings limits (final)	Skin designations
TITANIUM DIOXIDE 13463-67-7	.1 - 1	15 mg/m³	Total dust.		

#### ACGIH Threshold Limit Value (TLV's)

0	Approx. Weight %	TWA	STEL	Ceiling limits	Skin designations
TITANIUM DIOXIDE 13463-67-7	.1 - 1	10 mg/m <sup>3</sup>			

## 9. PHYSICAL PROPERTIES

Odor: Physical State: pH: Vapor pressure: Vapor density (air = 1.0): Boiling point: Solubility in water: Coefficient of water/oil distribution: Density (lbs per US gallon): Specific Gravity: Evaporation rate (butyl acetate = 1.0): Flash point (Fahrenheit): Lower explosive limit: Normal for this product type. liquid not determined 24 mmHg @ 77°F (25°C) 2.62 not determined not determined 9.08 1.09 0.1 205°F (96°C) 2 % Upper explosive limit: Autoignition temperature:

## **10. STABILITY AND REACTIVITY**

Stability: Conditions to Avoid: Incompatibility:

Hazardous Polymerization: Hazardous Decomposition Products:

Sensitivity to static discharge:

17 % not determined -°F (°C)

Stable under normal conditions. None known. Avoid water-reactive materials, heat or contact with peroxides or other catalysts. None anticipated. Carbon monoxide and carbon dioxide. Nitrogen compounds.

Sensitivity to static discharge is not expected.

## 11. TOXICOLOGICAL INFORMATION

5	Approx. Weight %	NIOSH - Selected LD50s and LC50s
PROPYLENE GLYCOL	1 - 5	Oral LD50 Rat : 20 gm/kg
57-55-6		Oral LD50 Mouse : 22 gm/kg
		Dermal LD50 Rabbit : 20800 mg/kg

#### Mutagens/Teratogens/Carcinogens:

Possible cancer hazard. Contains material which may cause cancer based on animal data.

Contains TIO2 which is listed by IARC as a possible human carcinogen (Group 2B) based on animal data. Neither long term animal studies, nor human epidemiology studies of workers exposed to TIO2 provide an adequate basis to conclude TIO2 is carcinogenic. TIO2 is not classified as a carcinogen by NTP, U.S. OSHA, or the U.S. EPA.

Ingredient Name	Approx.	California Prop 65 - Reproductive	California Prop 65 - Carcinogen
CAS-No.	Weight %	(Female)	
HYDRATED ALUMINUM MAGNESIUM SILICATE 12174-11-7	.1 - 1		Listed: December 28, 1999 Carcinogenic.

Ingredient Name CAS-No.	Approx. Weight %	IARC Group 1 - Human Evidence	IARC Group 2A - Limited Human Data	IARC Group 2B - Sufficient Animal Data
HYDRATED ALUMINUM MAGNESIUM SILICATE 12174-11-7	.1 - 1			Monograph 68, 1997; (long fibres, >5 micrometers)
TITANIUM DIOXIDE 13463-67-7	.1 - 1			2B Possible Carcinogen

## 12. ECOLOGICAL DATA

No information on ecology is available.

## **13. DISPOSAL CONSIDERATIONS**

Disposal should be made in accordance with federal, state and local regulations.

#### **14. TRANSPORTATION INFORMATION**

Product ID: 140.0001316

#### **U.S. Department of Transportation**

Proper Shipping Name: PAINT, NOT REGULATED UN ID Number: NRPAIN

#### U.S. Highway & Rail Shipments

The supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

#### **Reportable Quantity Description:**

#### International Air Transport Association (IATA):

Proper Shipping Name:	PAINT, NOT REGULATED
UN ID Number:	NRPAIN

## International Maritime Organization (IMO):Proper Shipping Name:PAINT, NOT REGULATEDNon-Bulk UN ID Number:NRPAIN

yes

#### **15. REGULATORY INFORMATION**

#### **U.S. FEDERAL REGULATIONS:**

SARA	311/312	Hazard	Class:	
Acute:				
~ .				

s

#### **U.S. STATE REGULATIONS:**

#### Right to Know:

The specific chemical identity of a component may be withheld as a trade secret under 34 Pennsylvania Code, Chapter 317.

Pennsylvania	Right	то	Know:
--------------	-------	----	-------

PROPYLENE GLYCOL	57-55-6
Additional Non-Hazardous Materials	
WATTER	7732-18-5

WAIDIC			.0 5
PROPRIETARY I	NERT	Trade	Secret
PROPRIETARY R	ESIN	Trade	Secret

#### California Proposition 65:

WARNING! This product contains a chemical known in the State of California to cause cancer.

Rule 66 status of productNot photochemically reactive.

#### **INTERNATIONAL REGULATIONS - Chemical Inventories**

#### **US TSCA Inventory:**

All components of this product are in compliance with U.S. TSCA Chemical Substance Inventory Requirements.

#### Canada Domestic Substances List:

All components of this product are listed on the Domestic Substances List.

## **16. OTHER INFORMATION**

#### **HMIS Codes**

Health:	2*
Flammability:	1
Reactivity:	1
PPE:	X - See Section 8 for Personal Protective Equipment (PPE).

#### Abbreviations:

OSHA - Occupational Safety and Health Administration, IARC - International Agency for Research on Cancer, NIOSH -National Institute of Occupational Safety and Health, NTP - National Toxicology Program, ACGIH - American Conference of Governmental Industrial Hygienists, SCAQMD - South Coast Air Quality Management District, TSCA - Toxic Substances Control Act, IATA - International Air Transport Association, IMO - International Maritime Organization, DOT -Department of Transportation, NA - Not applicable, NOT ESTAB - Not established, N.A.V. - Not available, RQ -Reportable quantity, WT - Weight, MG/CU M - Milligrams per cubic meter, G/L - Grams per liter, MM - Millimeters, MPPCF - Millions of particles per cubic foot, PPM - parts per million, PPT - parts per thousand, TCC/PM - Tag closed cup / Pensky-Martens, PB - Lead, PEL - Permissible exposure level, TWA - Time Weighted Average, STEL - Short term exposure limit, C - Celsius, F - Fahrenheit.

#### **Disclaimer:**

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. This MSDS contains additional information required by the state of Pennsylvania.

#### **Preparation Information:**

Prepared By: Print date: Revision Date: Regulatory Affairs Department 23/Mar/2009 14/Mar/2009