# BAF Industries

### MATERIAL SAFETY DATA SHEET

MSDS NUMBER: 58489 PART NUMBER: BAF-1744-1

PRODUCT NAME: FLITZ LIQUID METAL POLISH

CHEMICAL:

SECTION I						
MANUFACTURER: BAF INDUSTRIES	HMIS RATING:		NFPA			
			RATING:			
ADDRESS: 1910 SO. YALE ST.	HEALTH:	2	2 / \1			
SANTA ANA, CA 92704	FIRE:	1	HEALTH/ FIRE			
EMERGENCY TELEPHONE NUMBER: (800)424-9300	REACTIVITY:	0	0 \ 0			
INFORMATION TELEPHONE NUMBER: (714)540-3850	PERSONAL PROTECTION:	E	SPEC.HAZ. REACT.			
DATE PREPARED: 12/01/05	]		V			

SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION						
CAS NUMBER	HAZARDOUS COMPONENT	NTP IARC SUB-	SAR	A OSHA PEI	ACGIH TLV	OTHER LIMITS %
		PART/Z	313			RECOMMENDED
64742-48-8	ALIPHATIC HYDROCARBONS			N/EST	N/EST	10-30
1344-28-1	ALUMINA			10mg/m3	10mg/m3	10-30
61790-53-2	DIATOMITE*		Y	80mg/m3	80mg/m3	1-5
	*SEE SECTION IX					

SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS					
212° F	SPECIFIC GRAVITY (H2O=1)	1.1291			
N/AV	MELTING POINT	N/AP			
N/AV	EVAPORATION RATE (Butyl Acetate = 1)	N/AV			
MISCIBLE		•			
LIGHT YELL	LIGHT YELLOW GREEN WITH SOLVENT ODOR.				
pH = 8.12					
	212° F N/AV N/AV MISCIBLE LIGHT YELL	212° F SPECIFIC GRAVITY (H2O=1)  N/AV MELTING POINT  N/AV EVAPORATION RATE (Butyl Acetate = 1)  MISCIBLE  LIGHT YELLOW GREEN WITH SOLVENT ODOR.			

SECTION IV - FIRE AND EXPLOSION HAZARD DATA							
FLASH POINT: N/AV	FLAMMABLE LIMITS:	LEL: N/AV	UEL: N/AV				

EXTINGUISHING MEDIA :FOAM, DRY CHEMICAL, CARBON DIOXIDE, WATER.

SPECIAL FIRE FIGHTING PROCEDURES: SELF-CONTAINED BREATHING APPARATUS.

UNUSUAL FIRE FIGHTING PROCEDURES: TOXIC FUMES MAY BE EMITTED IF MATERIAL IS EXPOSED TO EXTREME TEMPERATURE.

## **SECTION V - REACTIVITY DATA**

STABILITY: STABLE

INCOMPATIBILITY (MATERIALS TO AVOID): VERY STRONG OXIDIZING AGENTS.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: SMOKE, CARBON MONOXIDE, CARBON DIOXIDE AND OTHER TOXIC FUMES.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

# SECTION VI - HEALTH HAZARD DATA

ROUTE(S) OF ENTRY: SKIN, EYES, INHALATION.

HEALTH HAZARDS (ACUTE AND CHRONIC): REDDENING AND BURNING OF EYES AND SKIN, EXCESSIVE INHALATION MAY CAUSE DROWSINESS OR NAUSEA..

SIGNS AND SYMPTOMS OF EXPOSURE: SEE ABOVE.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: NONE KNOWN.

**EMERGENCY AND FIRST AID PROCEDURES:** REMOVE TO FRESH AIR. FLUSH AFFECTED AREA WITH PLENTY OF WATER, IF SYMPTONS PERSIST, GET MEDICAL ATTENTION.

OTHER HEALTH WARNINGS: NONE.

MSDS NUMBER: 58489

PRODUCT NAME: BAF-1744 -1 FLITZ LIQUID METAL POLISH

# SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: WIPE UP WITH A NEUTRAL ABSORBANT AND DRUM FOR PROPER DISPOSAL.

WASTE DISPOSAL METHOD: IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: AVOID FREEZING, KEEP AWAY FROM FLAME.

OTHER PRECAUTIONS: NONE

## SECTION VIII - CONTROL MEASURES

VENTILATION REQUIREMENTS: GOOD VENTILATION SHOULD BE MAINTAINED.

PERSONAL PROTECTIVE EQUIPMENT: RUBBER GLOVES AND CHEMICAL SAFETY GLASSES AND NIOSH APPROVED DUST &

VAPOR RESPIRATOR.

### SECTION IX - ADDITIONAL INFORMATION

ADDITIONAL MANUFACTURER WARNINGS: \*THIS PRODUCT CONTAINS CRYSTALLINE SILICA (CS), WHICH IS CONSIDERED A HAZARD BY INHALATION. IARC HAS CLASSIFIED INHALATION OF CS AS CARCINOGENIC FOR HUMANS (GROUP I). CS IS LISTED BY NTP AS A SUBSTANCE WHICH MAY REASONABLY BE ANTICIPATED TO BE A CARCINOGEN. INHALATION IS CS IS ALSO A KNOWN CAUSE OF SILICOSIS, A NONCANCEROUS LUNG DISEASE.

THIS PRODUCT MAY CONTAIN UP TO 1% CRYSTALLINE SILICA, CAS# 61790-53-2

OTHER PRECAUTIONS AND COMMENTS: D.O.T. PROPER SHIPPING NAME = CLEANING LIQUID.

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. BAF INDUSTRIES ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS OR THIRD PARTIES CAUSED BY THE MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF MATERIAL.

N/AV = NOT AVAILABLEN/AP = NOT APPLICABLE

THIS INFORMATION IS PROVIDED TO MEET VARIOUS STATE REGULATORY COMPOSITION REQUIREMENTS:

 1.
 ALIPHATIC HYDROCARBONS
 CAS# 64742-48-8

 2.
 WATER
 CAS# 7732-18-5

 3.
 ALUMINA
 CAS# 1344-28-1

 4.
 DIATOMITE
 CAS# 61790-53-2

 5.
 SURFACTANT
 MIXTURE

.

V.O.C. CONTENT: 0 GRAM PER LITER.