



Material Safety Data Sheet

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identification

Product ID: 140.0000837
Product Name: SLD SIDING CORDOVAN
Product Use: Paint product.
Print date: 12/Jan/2015
Revision Date: 10/Jan/2015

Company Identification

The Valspar Corporation - Architectural Coatings Division
1191 Wheeling Road
Wheeling, IL 60090

Manufacturer's Phone: 1-847-520-8580

24-Hour Medical Emergency Phone: 1-888-345-5732

2. HAZARDS IDENTIFICATION

Primary Routes of Exposure:

Inhalation
Ingestion
Skin absorption

Eye Contact:

- May cause eye irritation.

Skin Contact:

- Causes mild skin irritation.

Ingestion:

- Irritation of the mouth, throat, and stomach.

Inhalation:

- May cause irritation of respiratory tract.

Target Organ and Other Health Effects:

- Kidney injury may occur.

This product contains ingredients that may contribute to the following potential chronic health effects:

- Prolonged exposure over TLV may produce pneumoconiosis.
- Prolonged exposure to respirable crystalline quartz silica may cause delayed chronic injury (silicosis).
- Chronic exposure may cause permanent damage of health.

Carcinogens:

- Possible cancer hazard. Contains material which may cause cancer based on animal data.
- Cancer hazard. Contains material which can cause cancer.

3. COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS

| Ingredient Name CAS-No. | Approx. Weight % | Chemical Name |
|-----------------------------------|---------------------|----------------------------|
| PROPRIETARY COLOR PIGMENT | 1 - 5 | PROPRIETARY COLOR PIGMENT |
| BURNT UMBER PIGMENT 12713-03-0 | 1 - 5 | Umber |
| C.I. PIGMENT BLACK 7 1333-86-4 | .1 - 1 | Carbon black |
| SILICA 14808-60-7 | .1 - 1 | QUARTZ (SiO ₂) |

If this section is blank there are no hazardous components per OSHA guidelines.

4. FIRST AID MEASURES**Eye Contact:**

Get medical attention, if symptoms develop or persist. Immediately flush eye(s) with plenty of water.

Skin Contact:

Wash off with plenty of water.

Ingestion:

Rinse mouth with water. Give one or two glasses of water. Only induce vomiting at the instruction of medical personnel. Get medical attention.

Inhalation:

Move to fresh air. Get medical attention, if symptoms develop or persist.

Medical conditions aggravated by exposure:

Any respiratory or skin condition.

5. FIRE FIGHTING MEASURES

Flash point (Fahrenheit):

205

Flash point (Celsius):

96

Lower explosive limit (%):

not determined

Upper explosive limit (%):

not determined

Autoignition temperature:

not determined

Sensitivity to impact:

no

Sensitivity to static discharge:

Sensitivity to static discharge is not expected.

5. FIRE FIGHTING MEASURES

Hazardous combustion products:

See Section 10.

Unusual fire and explosion hazards:
None known.

Extinguishing media:

Carbon dioxide, dry chemical, foam and/or water fog.

Fire fighting procedures:

Firefighters should be equipped with self-contained breathing apparatus and turn out gear. Keep containers and surroundings cool with water spray.

6. ACCIDENTAL RELEASE MEASURES

Action to be taken if material is released or spilled:

Ventilate the area. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Avoid contact with eyes.

7. HANDLING AND STORAGE

Precautions to be taken in handling and storage:

Keep container closed when not in use. Do not freeze. Since emptied containers may contain product residue, follow all label warnings, even after container is emptied. Do not cut, drill, grind, or weld on or near this container.

8. PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE CONTROLS

Personal Protective Equipment

Eye and face protection:

Wear safety glasses or goggles to protect against exposure.

Skin protection:

Appropriate chemical resistant gloves should be worn.

Respiratory protection:

If exposure cannot be controlled below applicable limits, use the appropriate NIOSH approved respirator such as an air purifying respirator with organic vapor cartridge and dust/mist filter. Consult the respirator manufacturer's literature to ensure that the respirator will provide adequate protection. Read and follow all respirator manufacturer's instructions.

Ventilation

Use only in well-ventilated areas. Ensure adequate ventilation, especially in confined areas.

Exposure Guidelines

OSHA Permissible Exposure Limits (PEL's)

| Ingredient Name CAS-No. | Approx. Weight % | TWA (final) | Ceilings limits (final) | Skin designations |
|-----------------------------------|---------------------|-------------------------------|----------------------------------|-------------------|
| PROPRIETARY COLOR PIGMENT | 1 - 5 | 10 mg/m ³ TWA fume | | |
| BURNT UMBER PIGMENT 12713-03-0 | 1 - 5 | | = 5 mg/m ³ Ceiling Mn | |
| C.I. PIGMENT BLACK 7 1333-86-4 | .1 - 1 | 3.5 mg/m ³ TWA | | |

| Ingredient Name CAS-No. | Approx. Weight % | TWA (final) | Ceilings limits (final) | Skin designations |
|----------------------------|---------------------|--|-------------------------|-------------------|
| SILICA 14808-60-7 | .1 - 1 | (30)/(%SiO ₂ + 2) mg/m ³ TWA, total dust (250)/(%SiO ₂ + 5) mppcf TWA, respirable fraction (10)/(%SiO ₂ + 2) mg/m ³ TWA, respirable fraction | | |

ACGIH Threshold Limit Value (TLV's)

| Ingredient Name CAS-No. | Approx. Weight % | TWA | STEL | Ceiling limits | Skin designations |
|-----------------------------------|---------------------|--|------|----------------|-------------------|
| PROPRIETARY COLOR PIGMENT | 1 - 5 | 5 mg/m ³ TWA respirable fraction | | | |
| C.I. PIGMENT BLACK 7 1333-86-4 | .1 - 1 | 3.5 mg/m ³ TWA | | | |
| SILICA 14808-60-7 | .1 - 1 | 0.025 mg/m ³ TWA respirable fraction | | | |

9. PHYSICAL PROPERTIES

| | |
|---|-------------------------------|
| Odor: | Normal for this product type. |
| Physical State: | liquid |
| pH: | not determined |
| Vapor pressure: | 24 mmHg @ 77°F (25°C) |
| Vapor density (air = 1.0): | 0.6 |
| Boiling point: | 212°F (100°C) |
| Solubility in water: | not determined |
| Coefficient of water/oil distribution: | not determined |
| Density (lbs per US gallon): | 9.69 |
| Specific Gravity: | 1.16 |
| Evaporation rate (butyl acetate = 1.0): | 0.1 |
| Flash point (Fahrenheit): | 205 |
| Flash point (Celsius): | 96 |
| Lower explosive limit (%): | not determined |
| Upper explosive limit (%): | not determined |
| Autoignition temperature: | not determined |

10. STABILITY AND REACTIVITY

| | |
|-----------------------------------|--|
| Stability: | Stable under normal conditions. |
| Conditions to Avoid: | None known. |
| Incompatibility: | Avoid water-reactive materials, heat or contact with peroxides or other catalysts. |
| Hazardous Polymerization: | None anticipated. |
| Hazardous Decomposition Products: | Carbon monoxide and carbon dioxide. Metal oxide fumes. |
| Sensitivity to static discharge: | Sensitivity to static discharge is not expected. |

11. TOXICOLOGICAL INFORMATION

11. TOXICOLOGICAL INFORMATION

| Ingredient Name CAS-No. | Approx. Weight % | NIOSH - Selected LD50s and LC50s |
|-----------------------------------|---------------------|--|
| PROPRIETARY COLOR PIGMENT | 1 - 5 | > 10000 mg/kg Oral LD50 Rat |
| C.I. PIGMENT BLACK 7 1333-86-4 | .1 - 1 | > 15400 mg/kg Oral LD50 Rat > 3 g/kg Dermal LD50 Rabbit |
| SILICA 14808-60-7 | .1 - 1 | = 500 mg/kg Oral LD50 Rat |

Mutagens/Teratogens/Carcinogens:

Possible cancer hazard. Contains material which may cause cancer based on animal data. Cancer hazard. Contains material which can cause cancer.

IARC has classified carbon black as possibly carcinogenic to humans (Group 2B). Contains crystalline silica. The IARC has determined that crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (group 1). Refer to IARC monograph 68 in conjunction with the use of these materials. Risk of cancer depends on the duration and level of exposure. In coatings products, risk is due primarily to inhalation of sanding dusts or respirable particles in spray mists. The NTP has also determined that crystalline silica is a known human carcinogen in the form of fine, breathable particles. Risk of cancer depends on duration and level of exposure in coatings products, risk is due primarily to inhalation of sanding dust or respirable particles in spray mist.

| Ingredient Name CAS-No. | Approx. Weight % | California Prop 65 - Reproductive (Female) | California Prop 65 - Carcinogen |
|----------------------------|---------------------|---|--|
| SILICA 14808-60-7 | .1 - 1 | | Listed. initial date 10/1/88 - carcinogen |

| Ingredient Name CAS-No. | Approx. Weight % | IARC Group 1 - Human Evidence | IARC Group 2A - Limited Human Data | IARC Group 2B - Sufficient Animal Data |
|-----------------------------------|---------------------|----------------------------------|---------------------------------------|---|
| C.I. PIGMENT BLACK 7 1333-86-4 | .1 - 1 | | | Monograph 65 [1996] |
| SILICA 14808-60-7 | .1 - 1 | Monograph 68 [1997] | | |

| Ingredient Name CAS-No. | Approx. Weight % | NTP Known Carcinogens | NTP Suspect Carcinogens |
|----------------------------|---------------------|------------------------|-------------------------|
| SILICA 14808-60-7 | .1 - 1 | Known Human Carcinogen | |

| Ingredient Name CAS-No. | Approx. Weight % | OSHA - Hazard Communication Carcinogens | OSHA - Specifically Regulated Carcinogens | ACGIH Carcinogens |
|-----------------------------------|---------------------|---|--|----------------------------------|
| C.I. PIGMENT BLACK 7 1333-86-4 | .1 - 1 | Present | | |
| SILICA 14808-60-7 | .1 - 1 | Present | | A2 Suspected Human Carcinogen |

12. ECOLOGICAL DATA

No information on ecology is available.

13. DISPOSAL CONSIDERATIONS

Disposal should be made in accordance with federal, state and local regulations.

14. TRANSPORTATION INFORMATION

U.S. Department of Transportation

UN ID Number (msds):

Proper Shipping Name:

NRPAIN

PAINT, NOT REGULATED

U.S. Hazmat and/or International DG shipment exceptions

The supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

Reportable Quantity Description:

International Air Transport Association (IATA):

Proper shipping name:

NOT REGULATED

International Maritime Organization (IMO):

Proper shipping name:

Marine Pollutant

NOT REGULATED

No

15. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

| Ingredient Name CAS-No. | Approx. Weight % | SARA 302 | SARA 313 | CERCLA RQ in lbs. |
|-----------------------------------|---------------------|----------|----------|-------------------|
| BURNT UMBER PIGMENT 12713-03-0 | 1 - 5 | | YES | |

SARA 311/312 Hazard Class:

Acute: yes
 Chronic: yes
 Flammability: no
 Reactivity: no
 Sudden Pressure: no

U.S. STATE REGULATIONS:

Right to Know:

The specific chemical identity of a component may be withheld as a trade secret under 34 Pennsylvania Code, Chapter 317.

Pennsylvania Right To Know:

PROPRIETARY COLOR PIGMENT
 BURNT UMBER PIGMENT

Trade Secret
 12713-03-0

Additional Non-Hazardous Materials

PROPRIETARY RESIN
 PROPRIETARY RESIN
 WATER
 PROPRIETARY INERT

Trade Secret
 Trade Secret
 7732-18-5
 Trade Secret

California Proposition 65:

WARNING! This product contains a chemical known in the State of California to cause cancer.

Rule 66 status of product

Not photochemically reactive.

INTERNATIONAL REGULATIONS - Chemical Inventories

TSCA Inventory:

All components of this product are in compliance with U.S. TSCA Chemical Substance Inventory Requirements.

Canada Domestic Substances List:

All components of this product are listed on the Domestic Substances List.

16. OTHER INFORMATION

HMIS Codes

| | |
|---------------|--|
| Health: | 1* |
| Flammability: | 0 |
| Reactivity: | 1 |
| PPE: | X - See Section 8 for Personal Protective Equipment (PPE). |

Abbreviations:

OSHA - Occupational Safety and Health Administration, IARC - International Agency for Research on Cancer, NIOSH - National Institute of Occupational Safety and Health, NTP - National Toxicology Program, ACGIH - American Conference of Governmental Industrial Hygienists, SCAQMD - South Coast Air Quality Management District, TSCA - Toxic Substances Control Act, IATA - International Air Transport Association, IMO - International Maritime Organization, DOT - Department of Transportation, NA - Not applicable, NOT ESTAB - Not established, N.A.V. - Not available, RQ - Reportable quantity, WT - Weight, MG/CU M - Milligrams per cubic meter, G/L - Grams per liter, MM - Millimeters, MPPCF - Millions of particles per cubic foot, PPM - parts per million, PPT - parts per thousand, TCC/PM - Tag closed cup / Pinsky-Martens, PB - Lead, PEL - Permissible exposure level, TWA - Time Weighted Average, STEL - Short term exposure limit, C - Celsius, F - Fahrenheit.

Disclaimer:

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information.

UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. This MSDS contains additional information required by the state of Pennsylvania.

Preparation Information:

| | |
|----------------|-------------------------------|
| Prepared By: | Regulatory Affairs Department |
| Print date: | 12/Jan/2015 |
| Revision Date: | 10/Jan/2015 |