



MATERIAL SAFETY DATA SHEET

Name of Material	
Super Patch	
1	HEALTH
0	FLAMMABILITY
0	REACTIVITY
J	PROTECTIVE EQUIPMENT

Section I - PRODUCT IDENTIFICATION

PRODUCT NAME: Latexite® Super Patch
MANUFACTURER NAME: Dalton Enterprises, Inc.
ADDRESS: 131 Willow Street Cheshire, CT 06410
EMERGENCY PHONE NUMBER: (203) 272-3221
AFTER 5 PM AND ON WEEKENDS: (203) 272-3221
ORIGINATOR: D.H.
TRADE NAMES & SYNONYMS: Pavement Patch
CHEMICAL FAMILY: Mixture
EFFECTIVE DATE: 06/9/2009

Section II - Hazards Identification

Emergency Overview

Contact with molten product can cause severe thermal burns. Exposure to vapors may irritate the eyes, skin and respiratory tract.

Potential Health Effects: Eyes

Vapors can irritate the eyes.

Potential Health Effects: Skin

Contact with molten product can cause severe thermal burns. Vapors may irritate the skin.

Potential Health Effects: Ingestion

Not considered a likely route of exposure during normal product use conditions.

Potential Health Effects: Inhalation

Low concentrations (50-100 ppm) can irritate the eye and respiratory tract and may cause nervousness, cough, nausea and headache. Prolonged exposure to concentrations between 250 and 600 ppm may cause pulmonary edema (fluid on the lungs) and bronchial pneumonia. Brief exposure to concentrations above 500 ppm can cause unconsciousness and may be fatal.

Medical Conditions Aggravated by Exposure

Inhalation of respirable dust may aggravate existing respiratory tract diseases. Exposure may aggravate existing skin conditions.

HMIS Ratings: Health: 1 Fire: 0 HMIS Reactivity 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

Section III - Composition

CAS #	Component	Percent
Not Available	Course and Fine aggregate	90-95
8052-42-4	Asphalt	3-6
Not Available	Proprietary Softening Agent	1-5
Trade Secret	Proprietary Additive	0.1-2.5

Section IV – First Aid Measures

First Aid: Eyes

If hot material splashes into eyes, immediately flush eyes with water. Do not attempt to remove particles from eyes. Take victim to physician at once.

First Aid: Skin

If molten asphalt contacts skin, cool immediately with cold water. For extensive burns obtain medical attention immediately. Do not use solvents to remove asphalt from skin.

First Aid: Ingestion

If the material is swallowed, get immediate medical attention or advice – Do not induce vomiting.

First Aid: Inhalation

Remove to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Seek medical attention.

Section V – Fire Fighting Measures

General Fire Hazards

See Section 9 for Flammability Properties.
Irritating and highly toxic gases and fumes can evolve.

Hazardous Combustion Products

Oxides of carbon, hydrogen sulfide and sulfur oxides.

Extinguishing Media

Dry chemical, carbon dioxide, foam and water fog. Water may cause frothing.

Fire Fighting Equipment/Instructions

Firefighters should wear full protective clothing including self contained breathing apparatus.

NFPA Ratings: Health: 1 Fire: 0 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Section VI – Accidental Release Measures

Containment Procedures

Contain spilled material and do not allow to flow into public sewers or water systems.

Clean-Up Procedures

Shut off all ignitions sources. Allow material to harden and transfer into container for proper disposal.

Evacuation Procedures

Isolate area. Keep unnecessary personnel away.

Special Procedures

Unused material can be recycled. Landfill wastes at approved sites. Dispose of in accordance with Federal, State, and local regulations.

Section VII – Handling and Storage

Handling Procedures

Avoid breathing fumes. Contact can cause severe burns. Use in well ventilated areas. Dusts created by drilling or grinding cured asphalt may irritate the eyes and respiratory tract. For such operations, use approved respirators and avoid breathing dusts.

Storage Procedures

Highly flammable and toxic fumes may build up in vapor spaces of storage tanks and transport compartments. Avoid breathing gases and keep ignition sources away from vents.

Section VIII – Exposure Controls / Personal Protection

A: Component Exposure Limits

Asphalt (8052-42-4)

ACGIH: 0.5 mg/m³ TWA (fume, inhalable fraction, as benzene soluble aerosol)

NIOSH: 5 mg/m³ Ceiling (15 min, fumes)

Engineering Controls

Use only in well ventilated areas.

PERSONAL PROTECTIVE EQUIPMENT

Personal Protective Equipment: Eyes/Face

Chemical safety goggles or full face mask.

Personal Protective Equipment: Skin

Use impervious gloves.

Personal Protective Equipment: Respiratory

If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection.

Personal Protective Equipment: General

Eye wash fountain and emergency showers are recommended.

Section IX – PHYSICAL & Chemical Properties

Appearance: Black viscous fluid mixed with coarse and fine aggregate

Physical State: Liquid

Vapor Pressure: NA

Boiling Point: 900°F

Solubility (H₂O): Insoluble

Evaporation Rate: NA

Octanol/H₂O Coeff.: ND

Flash Point Method: ND

Lower Flammability Limit (LFL): ND

Auto Ignition: ND

Odor: Asphalt

pH: ND

Vapor Density: >1

Melting Point: ND

Specific Gravity: 1.041

VOC: <0.1 (By weight)

Flash Point: >400°F

Upper Flammability Limit (UFL): ND

Burning Rate: ND

Section X – Chemical Stability & Reactivity Information

Chemical Stability

This is a stable material.

Chemical Stability: Conditions to Avoid

Heat approaching flash and open flames

Incompatibility

Strong oxidizers.

Hazardous Decomposition

Carbon monoxide, hydrogen sulfide, sulfur oxides.

Possibility of Hazardous Reactions

Will not occur.

Section XI – Disposal Considerations

US EPA Waste Number & Descriptions

Component Waste Numbers

No EPA Waste Numbers are applicable for this product's components.

Disposal Instructions

All wastes must be handled in accordance with local, state and federal regulations.

See Section 7 for Handling Procedures. See Section 8 for Personal Protective Equipment recommendations.

Section XII – Transportation Information

US DOT Information

Shipping Name: Not Regulated

Section XIII – Regulatory Information

US Federal Regulations

Component Analysis

None of these products components are listed under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), or CERCLA (40 CFR 302.4).

State Regulations

Component Analysis – State

The following components appear on one or more of the following state hazardous substances lists:

Component	CA	MA	MN	NJ	PA	RI
Asphalt	Yes	Yes	Yes	Yes	Yes	Yes
Proprietary Additive	No	Yes	No	Yes	Yes	No

Component Analysis – WHMIS IDL

No components are listed in the WHMIS IDL.

Additional Regulatory Information

Component Analysis – Inventory

Component	TSCA	CAN	EEC
Asphalt	Yes	DSL	EINECS
Proprietary Additive	Yes	DSL	EINECS

Section XIV – Other Information

Other Information

Keep out of reach of children.

For professional and industrial use only.

Always read label plus precautions and follow directions carefully.

Do not breathe vapor or spray mist.

Use only with adequate ventilation.

Do not take internally.

Avoid contact with eyes and skin.

Wash thoroughly after using.

Additional Technical Data Sheets and/or MSDS are available upon request.

THE INFORMATION AND RECOMMENDATIONS PROVIDED HEREIN ARE BELIEVED TO BE ACCURATE AS OF THE DATE HEREOF. HOWEVER, SUCH INFORMATION AND RECOMMENDATIONS ARE PROVIDED WITHOUT WARRANTY OF ANY KIND AND THIS CORPORATION DISCLAIMS ANY AND ALL LIABILITY OR LEGAL RESPONSIBILITY FOR USE OR RELIANCE UPON SAME.

Key/Legend

EPA = Environmental Protection Agency; TSCA = Toxic Substance Control Act; ACGIH = American Conference of Governmental Industrial Hygienists; IARC = International Agency for Research on Cancer; NIOSH = National Institute for Occupational Safety and Health; NTP = National Toxicology Program; OSHA = Occupational Safety and Health Administration; NJTSR = New Jersey Trade Secret Registry.