

# Material Safety Data Sheet

24 Hour Assistance:  
1-847-367-7700  
ROC.

## Section 1 - Chemical Product / Company Information

Product Name: Danger Orange  
Identification Number: 208269  
Product Use/Class: Multi Purpose Aerosol  
Supplier: Orgill Incorporated  
2100 Latham Street  
Memphis, TN 38109  
USA  
Preparer: Department, Regulatory

Revision Date: 11/26/2002

Manufacturer: ROC Sales Inc.  
8105 95th St.  
Pleasant Prairie, WI 53158  
USA

## Section 2 - Composition / Information On Ingredients

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Weight % Less Than</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH TLV-STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>
Acetone	67-64-1	40.0	500 PPM	750 PPM	750 PPM	N.E.
Liquified Petroleum Gas	68476-85-7	25.0	1000 PPM	N.E.	1000 PPM	N.E.
Toluene	108-88-3	10.0	50 PPM	N.E.	200 PPM	300 PPM
Naphtha	8032-32-4	10.0	300 PPM	N.E.	N.E.	N.E.
Xylene	1330-20-7	5.0	100PPM	150PPM	100PPM	N.E.
Titanium Dioxide	13463-67-7	5.0	10 mg/m3	N.E.	10 mg/m3	N.E.
Ethylbenzene	100-41-4	5.0	100 PPM	125 PPM	100 PPM	N.E.
Aromatic Hydrocarbon	64742-95-6	5.0	N.E.	N.E.	N.E.	N.E.

## Section 3 - Hazards Identification

\*\*\* Emergency Overview \*\*\*: Contents Under Pressure. Harmful if inhaled. May affect the brain or nervous system causing dizziness, headache or nausea. Vapors may cause flash fire or explosion. Extremely flammable liquid and vapor. Harmful if swallowed.

Effects Of Overexposure - Eye Contact: Causes eye irritation.

Effects Of Overexposure - Skin Contact: Prolonged or repeated contact may cause skin irritation. Substance may cause slight skin irritation.

Effects Of Overexposure - Inhalation: High vapor concentrations are irritating to the eyes, nose, throat and lungs. Avoid breathing vapors or mists. High gas, vapor, mist or dust concentrations may be harmful if inhaled. Harmful if inhaled.

Effects Of Overexposure - Ingestion: Aspiration hazard if swallowed; can enter lungs and cause damage. Substance may be harmful if swallowed.

Effects Of Overexposure - Chronic Hazards: IARC lists Ethylbenzene as a possible human carcinogen (group 2B). May cause central nervous system disorder (e.g.,narcosis involving a loss of coordination, weakness,

fatigue, mental confusion, and blurred vision) and/or damage. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Overexposure to xylene in laboratory animals has been associated with liver abnormalities, kidney, lung, spleen, eye and blood damage as well as reproductive disorders. Effects in humans, due to chronic overexposure, have included liver, cardiac abnormalities and nervous system damage. Overexposure to toluene in laboratory animals has been associated with liver abnormalities, kidney, lung and spleen damage. Effects in humans have included liver and cardiac abnormalities.

Primary Route(s) Of Entry: Skin Contact, Skin Absorption, Inhalation, Eye Contact

## **Section 4 - First Aid Measures**

First Aid - Eye Contact: Hold eyelids apart and flush with plenty of water for at least 15 minutes. Get medical attention.

First Aid - Skin Contact: Wash with soap and water. Get medical attention if irritation develops or persists.

First Aid - Inhalation: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

First Aid - Ingestion: Aspiration hazard: Do not induce vomiting or give anything by mouth because this material can enter the lungs and cause severe lung damage. Get immediate medical attention.

## **Section 5 - Fire Fighting Measures**

Flash Point: -156 F  
(Setaflash)

LOWER EXPLOSIVE LIMIT: 1.0 %  
UPPER EXPLOSIVE LIMIT : 12.8 %

Extinguishing Media: Dry Chemical, Foam, Water Fog

Unusual Fire And Explosion Hazards: Keep containers tightly closed. Vapors can travel to a source of ignition and flash back. Vapors may form explosive mixtures with air. FLASH POINT IS LESS THAN 20 DEG. F. - EXTREMELY FLAMMABLE LIQUID AND VAPOR! Closed containers may explode when exposed to extreme heat. Water spray may be ineffective. Perforation of the pressurized container may cause bursting of the can. Isolate from heat, electrical equipment, sparks and open flame.

Special Firefighting Procedures: Evacuate area and fight fire from a safe distance.

## **Section 6 - Accidental Release Measures**

Steps To Be Taken If Material Is Released Or Spilled: Dispose of according to local, state (provincial) and federal regulations. Do not incinerate closed containers. Remove all sources of ignition, ventilate area and remove with inert absorbent and non-sparking tools. Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust.

## **Section 7 - Handling And Storage**

Handling: Wash thoroughly after handling. Wash hands before eating. Use only in a well-ventilated area. Avoid breathing vapor or mist. Follow all MSDS/label precautions even after container is emptied because it may retain product residues.

Storage: Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Do not store above 120 degrees F. Store large quantities in buildings designed and protected for storage of NFPA Class I flammable liquids. Contents under pressure. Do not expose to heat or store above 120 degrees F.

## Section 8 - Exposure Controls / Personal Protection

**Engineering Controls:** Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof ventilation equipment.

**Respiratory Protection:** A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits.

Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection. A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

**Skin Protection:** Nitrile or Neoprene gloves may afford adequate skin protection. Use impervious gloves to prevent skin contact and absorption of this material through the skin.

**Eye Protection:** Use safety eyewear designed to protect against splash of liquids.

**Other protective equipment:** Refer to safety supervisor or industrial hygienist for further information regarding personal protective equipment and its application.

**Hygienic Practices:** Wash thoroughly with soap and water before eating, drinking or smoking.

## Section 9 - Physical And Chemical Properties

Boiling Range:	130 - 410 F	Vapor Density:	Heavier than Air
Odor:	Solvent Like	Odor Threshold:	ND
Appearance:	Orange Liquid	Evaporation Rate:	Faster than Ether
Solubility in H <sub>2</sub> O:	Slight		
Freeze Point:	ND	Specific Gravity:	0.753
Vapor Pressure:	ND	PH:	NE
Physical State:	Liquid		

(See section 16 for abbreviation legend)

## Section 10 - Stability And Reactivity

**Conditions To Avoid:** Avoid all possible sources of ignition. Avoid temperatures above 120 degrees F.

**Incompatibility:** Incompatible with strong oxidizing agents, strong acids and strong alkalis.

**Hazardous Decomposition:** When heated to decomposition it emits acrid smoke and irritating fumes. By open flame, carbon monoxide and carbon dioxide.

**Hazardous Polymerization:** Will not occur under normal conditions.

**Stability:** This product is stable under normal storage conditions.

## Section 11 - Toxicological Information

Product LD50: ND

**Chemical Name**

Acetone  
Liquified Petroleum Gas  
Toluene  
Naphtha  
Xylene  
Titanium Dioxide  
Ethylbenzene  
Aromatic Hydrocarbon

Product LC50: ND

**LD50**

RAT 5800MG/KG  
N.E.  
RAT 5000MG/KG  
>5 G/KG RAT  
RAT 4300MG/KG  
7500mg/kg Rats  
RAT 3500MG/KG  
4900mg/kg(rat)

**LC50**

RAT 50100MG/M^3 8H  
N.E.  
MOUSE 5320PPM 8HR  
  
RAT 5000PPM 4HR  
  
N.A.  
N.E.

**Section 12 - Ecological Information**

Ecological Information: Product is a mixture of listed components.

**Section 13 - Disposal Information**

Disposal Information: Dispose of material in accordance to local, state and federal regulations and ordinances. Do not allow to enter storm drains or sewer systems.

**Section 14 - Transportation Information**

DOT Proper Shipping Name: Aerosol  
DOT Technical Name: ---  
DOT Hazard Class: 2  
DOT UN/NA Number: UN 1950

Packing Group: ---  
Hazard Subclass: 1  
Resp. Guide Page: 126

**Section 15 - Regulatory Information**

**CERCLA - SARA Hazard Category**

This product has been reviewed according to the EPA "Hazard Categories" promulgated under Sections 311and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE HEALTH HAZARD, CHRONIC HEALTH HAZARD, FIRE HAZARD

**SARA Section 313:**

Listed below are the substances (if any) contained in this product that are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

**Chemical Name**

Toluene  
Xylene  
Ethylbenzene

**CAS Number**

108-88-3  
1330-20-7  
100-41-4

**Toxic Substances Control Act:**

Listed below are the substances (if any) contained in this product that are subject to the reporting requirements of TSCA 12(B) if exported from the United States:

**U.S. State Regulations: As follows -**

### **New Jersey Right-to-Know:**

The following materials are non-hazardous, but are among the top five components in this product.

<b><u>Chemical Name</u></b>	<b><u>CAS Number</u></b>
-----------------------------	--------------------------

Copolymer Alkyd Solids	<b>PROPRIETARY</b>
------------------------	--------------------

### **Pennsylvania Right-to-Know:**

The following non-hazardous ingredients are present in the product at greater than 3%.

<b><u>Chemical Name</u></b>	<b><u>CAS Number</u></b>
-----------------------------	--------------------------

Copolymer Alkyd Solids	<b>PROPRIETARY</b>
------------------------	--------------------

### **California Proposition 65:**

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

<b><u>Chemical Name</u></b>	<b><u>CAS Number</u></b>
-----------------------------	--------------------------

Silicon Dioxide (Quartz)	<b>14808-60-7</b>
--------------------------	-------------------

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

<b><u>Chemical Name</u></b>	<b><u>CAS Number</u></b>
-----------------------------	--------------------------

Toluene	<b>108-88-3</b>
---------	-----------------

### **International Regulations: As follows -**

#### **CANADIAN WHMIS:**

This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

**CANADIAN WHMIS CLASS:** AB5 D2A D2B

## **Section 16 - Other Information**

#### **HMIS Ratings:**

Health: 2\*

Flammability: 4

Reactivity: 0

Personal Protection: X

**VOLATILE ORGANIC COMPOUNDS, g/l:** 545

**REASON FOR REVISION:** Regulatory Update

**Legend:** N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The information contained on this MSDS has been checked and should be accurate. However, it is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.