

**ATC - Air Tool Conditioner** 

MSDS Number: ATC - Aerosol

Revision Date: 02/23/06

Page 1 of 5

#### PRODUCT AND COMPANY IDENTIFICATION

Product Name:ATC - Air Tool ConditionerRevision Date:02/23/06MSDS Number:ATC - AerosolProduct Code:ATC-TS, 8-ATC-S, 16-ATC

Manufacturer: The Blaster Chemical Companies, Inc. 8500 Sweet Valley Drive Valley View, Ohio 44125

> (216) 901-5800 (216) 901-5801 fax www.blasterproducts.com

2

1

#### **COMPOSITION/INFORMATION ON INGREDIENTS**

#### Ingredients:

Cas #	Chemical Name	Perc.
8042475 8032324 67630 9003138 68649423 124389	Isopropylalcohol	40-55% 20-30% 10-20% <10% <10% <2%

**3** HAZARDS IDENTIFICATION

Route of Entry: Target Organs:	Eyes, skin, inhalation, ingestion
Inhalation:	Inhalation of spray mist may cause irritation to the respiratory tract.
Skin Contact:	Repeated or prolonged contact with skin may cause mild irritation and possibly dermatitis.
Eye Contact:	Likely to cause immediate or delayed irritation. Irritation will show as redness and/or swelling of the eyes.
Ingestion:	Ingestion may cause irritation to the mouth, esophagus and stomach.

May aggravate a pre-existing skin and respiratory disorders.

**Physical Hazard:** Aerosol containers are pressurized (even when empty!) Do not expose to temperatures above 120° F. Do not puncture or burn can. Failure to observe these precautions may result in rapid and violent decompression of the container producing projectiles and atomization of the liquid contents.

**Notice:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.



# ATC - Air Tool Conditioner

#### MSDS Number: ATC - Aerosol

Revision Date: 02/23/06

Page 2 of 5

4	FIRST AID MEASURES
Inhalation:	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Continuie to monitor. Get medical attention.
Skin Contact:	Remove contaminated clothing immediately! Wash skin with soap and water. If irritation develops, seek medical attention.
Eye Contact:	Flush eye(s) with water for 15 minutes. Get medical attention. If eye irritation presists, obtain medical treatment.
Ingestion:	If conscious, immediately give the person two large glasses of water. Do not induce vomiting. Get medical attention immediately.

FIRE FI

FIRE FIGHTING MEASURES

Flashpoint: 58° F (TCC)

Unusual Fire & Explosion Hazard: Level 3 Aerosols - Contents Under Pressure

Extinguishing Media: Dry chemical. Carbon dioxide, halon or foam.

6

7

5

#### ACCIDENTAL RELEASE MEASURES

Leaking aerosol cans should be put into suitable container until the internal pressure has dissipated. Use suitable absorbents to collect liquid product. Consult regulations for the disposal of the container, liquid and absorbents.

## HANDLING AND STORAGE

Handling Precautions:Use in accordance with good industrial workplace practices. Avoid unnecessary contact. Wash<br/>thoroughly after handling. Use with good ventalation.Storage Requirements:Store in a dry place away from excessive heat. Store containers with lids on and properly<br/>labeled.

Do not store at temperatures above 120 degrees F.



ATC - Air Tool Conditioner

MSDS Number: ATC - Aerosol

Revision Date: 02/23/06

Page 3 of 5

#### 8 **EXPOSURE CONTROLS/PERSONAL PROTECTION Engineering Controls:** Eye wash stations and emergency showers should be immediately available. **Protective Equipment:** Eyes and Face: Standard safety glasses with splash shields typically offer adequate protection. Where excessive splashing or spraying is possible, a face shield should be used. Do not wear contacts. Skin and clothing: Excessive contact should be avoided. Nitrile gloves, boots and aprons will provide adequate protection when contact cannot be avoided. Remove and wash any contaminated clothing immediately. Wash thoroughly after handling. Respiratory: Good general ventilation should be sufficient to control airborne levels. Maintain airborne concentrations below OSHA established exposure limits of ingredients in Section 2. Use NIOSH approved respirator if ventilation is not adequate enough to maintain levels below these limits. Exposure Guidelines/Other: The Blaster Chemical Companies takes not responsibility for determining what measures are required for personal protection in any specific application. This information should be used with discretion.

9	PHYSICAL AND CHEMIC	CAL PROPERTIES	
Appearance: Physical State:	red, transparent, thin liquid	Boiling Point:	180 F
Odor:	typical solvent-like	Freezing/Melting Pt.:	Not Determined
pH:	Not Determined	Solubility:	nil
Vapor Pressure:	Not Determined	Spec Grav./Density:	0.83 - 0.85
Vapor Density:	>1 (air = 1)		
Heat Value:	Not Determined		
VOC: Evap. Rate:	Not Determined >1 (NBA=1)		
Bulk Density:	Not Determined		
Octanol: Molecular Weight Particle Size:			
Softening Point:	Not Applicable Not Applicable		
Viscosity: Percent Volatile:	Not Determined Not Determined		
Sat. Vap. Concent Molecular Formul			



## **ATC - Air Tool Conditioner**

#### MSDS Number: ATC - Aerosol

11

Revision Date: 02/23/06

Page	4	of	5
I aye	-		0

10	STABILITY AND REACTIVITY	
Stability:		This product is stable.
Conditions to avoid:		Avoid excessive heat, sources of ingition and excessive water.
Materials to avoid (in	compatability):	Avoid contact with strong oxidizing agents and strong reducing agents (strong acids or bases.) Avoid mixture with water.
Hazardous Decompo	sition products:	Combustion will product carbon monoxide, carbon dioxide and nitrogen-oxygen compounds
Hazardous Polymeriz	zation:	Will not occur.

### TOXICOLOGICAL INFORMATION

Toxicological information on this product as a mixture has not been determined. See Section 15 for reportable ingredients.

12 ECOLOGICAL INFORMATION

Ecological information on this product as a mixture has not been determined.

# 13 DISPOSAL CONSIDERATIONS

Used or unused product should be disposed of in accordance with local, state and federal regulations. Some special regulations may exist for the disposal of aerosol containers.

Empty containers may contain residucal pressure and contents. They should be handled with the same precautions as the product.

14 TR

**TRANSPORT INFORMATION** 

#### Dept. of Transportation (DOT):

This product, as it leaves Blaster's facilities, meets the definitions set forth in CFR 49 part 173.150c as a "consumer commodity." Allowing for certain exceptions (173.156) for domestic surface (ground) shipments.

Proper shipping name: Consumer Commodity Hazard class: ORM-D

#### International (IMDT-IATA):

Proper shipping name:Aerosols, Limited QuantitiesHazard class:2 Compressed GasUN Number:1950



ATC - Air Tool Conditioner

MSDS Number: ATC - Aerosol

Revision Date: 02/23/06

Page 5 of 5

### **REGULATORY INFORMATION**

COMPONENT / (CAS/PERC) / CODES

\*VM & P Naphtha (8032324 20-30%) OSHAWAC, PA, TXAIR

\*Isopropyl alcohol (67630 10-20%) MASS, NJHS, NRC, OSHAWAC, PA, SARA313, TXAIR

\*Carbon dioxide (propellant) (124389 <2%) MASS, OSHAWAC, PA, TXAIR

REGULATORY KEY DESCRIPTIONS

OSHAWAC = OSHA Workplace Air Contaminants PA = PA Right-To-Know List of Hazardous Substances TXAIR = TX Air Contaminants with Health Effects Screening Level

MASS = MA Massachusetts Hazardous Substances List NJHS = NJ Right-to-Know Hazardous Substances NRC = Nationally Recognized Carcinogens SARA313 = SARA 313 Title III Toxic Chemicals

16

15

#### **OTHER INFORMATION**

#### Manufacturer's Disclaimer:

To the best of our knowledge, the information containedherein is accurate. However, neither The Blaster Chemical Companies nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exists.

#### **HMIS** Ratings

Health:	2
Fire:	3
Reactivity	0

END OF MSDS DOCUMENT