

MATERIAL SAFETY DATA SHEET 57100  
KELLOGGS PROFESSIONAL PRODUCTS, INC.

SECTION 1 – CHEMICAL PRODUCT AND COMPANY INFORMATION

PRODUCT NAME: FOOD GRADE PURE SILICONE LUBRICANT 57100 IDENTIFICATION NUMBER 6262-A DATE PRINTED: 12/16/08  
PRODUCT CLASS: FOOD GRADE SILICONE PREPARER: CUSTOMER SERVICE  
SUPPLIER/DISTRIBUTOR: KELLOGG'S PROFESSIONAL PRODUCTS, INC.  
MANUFACTURED FOR 325 PEARL STREET  
SANDUSKY, OH 44870  
EMERGENCY TELEPHONE: 419-625-6551 M – F 8:30AM – 5:00PM

SECTION 2 – COMPOSITION/INFORMATION ON INGREDIENTS

ITEM:	CHEMICAL/ COMMON NAME	CAS NUMBER	WT/WT % (LESS THAN)
01	PROPANE/SOBUTANE/N-BUTANE	68476-86-8	45.0%
02	HYDROTREATED KEROSENE	64742-47-8	35.0%
02	N-HEPTANE	142-82-5	20.0%
03	2-PROPANONE	64-64-1	10.0%

EXPOSURE LIMITS

ITEM	ACGIH		OSHA		COMPANY	SKIN
	TLV – TWA	TLV – STEL	PEL – TWA	PEL – CEILING	TLV – TWA	
01	1000 PPM	N.E.	800 PPM	N.E.	N.E.	YES
02	N.E	N.E.	N.E	N.E	N.E.	NO
03	400 PPM	500 PPM	400 PPM	500 PPM	N.E	YES
04	750 PPM	1000 PPM	750 PPM	N.E	N.E	NO

\* See section #16 for abbreviation legend.

SECTION 3 –HAZARDOUS IDENTIFICATION

\*\*\* EMERGENCY OVERVIEW \*\*\* Vapors irritating to eyes and respiratory tract. Vapors may cause flash fire or explosion.

EFFECTS OF OVEREXPOSURE

**EYE CONTACT:** Liquid, aerosols and vapors of this product are irritating and can cause pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.  
**SKIN CONTACT:** Prolonged or repeated contact can result in defatting / drying of the skin which may result in skin irritation and dermatitis (rash).  
**INHALATION:** Headaches, dizziness, nausea, decreased blood pressure, changes in heart rate and cyanosis may result from over-exposure to vapor or skin exposure. Prolonged inhalation may be harmful.  
**INGESTION:** This material may be harmful or fatal if swallowed. If a "corrosive" product, may cause severe and permanent damage to mouth, throat and stomach.  
**CHRONIC HAZARDS:** Overexposure may cause nervous system damage, lung damage or kidney damage.

PRIMARY ROUTE (S) OF ENTRY: SKIN CONTACT SKIN ABSORPTION INHALATION EYE CONTACT

SECTION 4 – FIRST AID MEASURES

**FIRST AID - EYE CONTACT:** Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.  
**FIRST AID - SKIN CONTACT:** Immediately flush skin with plenty of water. Remove clothing. Get medical attention immediately. Wash clothing separately before reuse.  
**FIRST AID – INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.  
**FIRST AID – INGESTION:** Get medical attention immediately. If swallowed, do NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth go an unconscious person.

## SECTION 5 – FIRE FIGHTING MEASURES

FLASH POINT -156 F

LOWER EXPLOSIVE LIMIT: 1.2 %  
UPPER EXPLOSIVE LIMIT: 12.8 %

AUTOIGNITION TEMPERATURE: ND      EXTINGUISHING MEDIA: CO2 ALCOHOL DRY CHEMICAL      FOAM      WATER      FOG

## MATERIAL SAFETY DATA SHEET 57100 KELLOGGS PROFESSIONAL PRODUCTS, INC.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Vapors can travel to a source of ignition and flash back. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty drums should be completely drained, properly bunged and promptly returned to a drum re-conditioner, or properly disposed.

**SPECIAL FIRE FIGHTING PROCEDURES:** Containers can build up pressure if exposed to heat (fire). As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear.

## SECTION 6 – ACCIDENTAL RELEASE MEASURES

**IF PRODUCT IS RELEASED / SPILLED:** Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container.

## SECTION 7 – HANDLING AND STORAGE

**HANDLING:** Wash thoroughly after handling.

**STORAGE:** Keep away from heat, sparks and flame. Keep from freezing.

## SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

**ENGINEERING CONTROLS:** Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product.

**RESPIRATORY PROTECTION:** A NIOSH / MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

**PROTECTIVE EQUIPMENT; STANDARD INDUSTRIAL CLOTHING STANDARDS SHOULD BE FOLLOWED.**

**SKIN PROTECTION:** Where contact is likely, wear chemical resistant gloves, a chemical suit, rubber boots, and chemical safety goggles plus a face shield.

**EYE PROTECTION:** Wear safety glasses with side shields (or goggles) and a face shield.

**HYGIENIC PRACTICES:** Wash hands before eating. Remove contaminated clothing and wash before reuse. Use only in a well ventilated area. Follow all MSDS / label precautions even after container is emptied because they may retain product residues. Avoid prolonged or repeated contact with skin. Avoid breathing vapors from heated material. Avoid contact with eyes, skin, and clothing.

## SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE:	-43 - 209° F	VAPOR DENSITY:	Is heavier than air
ODOR:	SOLVENT	ODOR THRESHOLD:	ND
APPEARANCE:	CLEAR	EVAPORATION RATE:	Is faster than Butyl Acetate
SOLUBILITY IN H2O:	NEGLECTIBLE		
FREEZE POINT:	ND	SPECIFIC GRAVITY:	0.6803
VAPOR PRESSURE:	ND	pH @ 0.0 %:	NA
PHYSICAL STATE:	AEROSOL	VISCOSITY:	NA

Coefficient of Water/Oil Distribution: Negligible



**TOXIC SUBSTANCES CONTROL ACT:** This product contains the following chemical substances subject to the reporting requirements of TSCA 12 (B) if exported from the United States:

CHEMICAL NAME	CAS NUMBER
N-HEPTANE	142-82-5
DIMETHYLSILOXANE	63148-62-9

MATERIAL SAFETY DATA SHEET 57100  
KELLOGGS PROFESSIONAL PRODUCTS, INC.

SECTION 15 – REGULATORY INFORMATION (CONTINUED)

**U.S. STATE REGULATIONS AS FOLLOWS:**

**NEW JERSEY RIGHT-TO-KNOW:** The following materials are non-hazardous, but are among the top five components in this product:

CHEMICAL NAME	CAS NUMBER
DIMETHYLSILOXANE	63148-62-9

**PENNSYLVANIA RIGHT-TO-KNOW:** The following non-hazardous ingredients are present in the product at greater than 3%:

CHEMICAL NAME	CAS NUMBER
DIMETHYLSILOXANE	63148-62-9

**CALIFORNIA PROPOSITION 65: WARNING -** The chemical (s) noted below and contained in this product, are known to the state of California to cause cancer, birth defects or other reproductive harm:

**NO PROPOSITION 65 CHEMICALS EXIST IN THIS PRODUCT.**

**INTERNATIONAL REGULATIONS AS FOLLOWS:**

**CANADIAN WHMIS:** This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings

**CANADIAL WHMIS CLASS:** No information available.

SECTION 16 – OTHER INFORMATION

HMIS RATINGS –	HEALTH: 2	FLAMMABILITY:	REACTIVITY:
<i>LEGEND:</i>	<i>N.A.- Not Applicable</i>	<i>N.E. – Not Established,</i>	<i>N.D – Not Determined</i>

Previous MSDS revision date: 12/16/08

\* The information contained on this MSDS has been checked and should be accurate. However, it is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.