

# Material Safety Data Sheet

24 Hour Assistance:  
1-847-367-7700  
ROC.

## Section 1 - Chemical Product / Company Information

Product Name: ORGILL RP RED OXIDE PRIMER 6PK  
12OZ SSPR Revision Date: 11/04/2009

Identification Number: 208313

Product Use/Class: Primer/Aerosol

Supplier: Orgill Incorporated  
2100 Lathan Street  
Memphis, TN 38109  
USA

Manufacturer: ROC Sales Inc.  
8105 95th Street  
Pleasant Prairie, WI 53158  
USA

Preparer: Regulatory Department

## Section 2 - Composition / Information On Ingredients

| Chemical Name                  | CAS Number  | Weight % | Less Than ACGIH TLV-TWA | ACGIH TLV-STELOSHA PEL -TWA | OSHA PEL -CEILING      |
|--------------------------------|-------------|----------|-------------------------|-----------------------------|------------------------|
| Liquefied Petroleum Gas        | 68476-86-8  | 30.0     | N.E.                    | N.E.                        | N.E.                   |
| Acetone                        | 67-64-1     | 30.0     | 500 ppm                 | 750 ppm                     | 1000 ppm               |
| Modified Alkyd Resin           | PROPRIETARY | 10.0     | N.E.                    | N.E.                        | N.E.                   |
| Toluene                        | 108-88-3    | 10.0     | 20 ppm                  | N.E.                        | 200 ppm                |
| Mineral Spirits                | 64742-88-7  | 10.0     | 100 ppm                 | N.E.                        | 100 ppm                |
| Magnesium Silicate             | 14807-96-6  | 5.0      | 2 mg/m3                 | N.E.                        | 0.1 mg/m3 (Respirable) |
| Xylene                         | 1330-20-7   | 5.0      | 100 ppm                 | 150 ppm                     | 100 ppm                |
| Aliphatic Hydrocarbon          | 64742-89-8  | 5.0      | N.E.                    | N.E.                        | 300 ppm                |
| n-Butyl Acetate                | 123-86-4    | 5.0      | 150 ppm                 | 200 ppm                     | 150 ppm                |
| Ethylbenzene                   | 100-41-4    | 5.0      | 100 ppm                 | 125 ppm                     | 100 ppm                |
| Quartz (Crystalline Silica)    | 14808-60-7  | 1.0      | 0.025 mg/m3             | N.E.                        | 2.4 mppcf (Respirable) |
| Methyl Ethyl Ketoxime          | 96-29-7     | 0.1      | N.E.                    | N.E.                        | N.E.                   |
| Solvent Naptha, Light Aromatic | 64742-95-6  | 0.1      | N.E.                    | N.E.                        | N.E.                   |

## Section 3 - Hazards Identification

\*\*\* Emergency Overview \*\*\*: Contents Under Pressure. Harmful if inhaled. May affect the brain or nervous system causing dizziness, headache or nausea. Vapors may cause flash fire or explosion. Harmful if swallowed. Extremely flammable liquid and vapor.

Effects Of Overexposure - Eye Contact: Causes eye irritation.

Effects Of Overexposure - Skin Contact: Prolonged or repeated contact may cause skin irritation. Substance may cause slight skin irritation.

Effects Of Overexposure - Inhalation: High vapor concentrations are irritating to the eyes, nose, throat and lungs. Avoid breathing vapors or mists. High gas, vapor, mist or dust concentrations may be harmful if inhaled. Harmful if inhaled.

Effects Of Overexposure - Ingestion: Aspiration hazard if swallowed; can enter lungs and cause damage. Substance may be harmful if swallowed.

Effects Of Overexposure - Chronic Hazards: IARC lists Ethylbenzene as a possible human carcinogen (group 2B). May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion, and blurred vision) and/or damage. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Overexposure to xylene in laboratory animals has been associated with liver abnormalities, kidney, lung, spleen, eye and blood damage as well as reproductive disorders. Effects in humans, due to chronic overexposure, have included liver, cardiac abnormalities and nervous system damage.

Contains crystalline silica as silicon dioxide. Excessive inhalation of respirable crystalline silica dust may cause lung disease, silicosis or lung cancer. Significant exposure is not anticipated during brush or trowel application or drying. Risk of overexposure depends on the duration and level of exposure to dust from repeated sanding of surfaces, mechanical abrasion or spray mist and actual concentration of crystalline silica in the formula. Crystalline silica is listed as Group 1 "carcinogenic to humans" by the International Agency for Research on Cancer (IARC), and Group 2 "reasonably anticipated to be a carcinogen" by the National Toxicology Program (NTP).

Primary Route(s) Of Entry: Skin Contact, Skin Absorption, Inhalation, Ingestion, Eye Contact

## Section 4 - First Aid Measures

First Aid - Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

First Aid - Skin Contact: Wash with soap and water. Get medical attention if irritation develops or persists.

First Aid - Inhalation: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

First Aid - Ingestion: Aspiration hazard: Do not induce vomiting or give anything by mouth because this material can enter the lungs and cause severe lung damage. Get immediate medical attention.

## Section 5 - Fire Fighting Measures

Flash Point: -156 F  
(Setaflash)

Lower Explosive Limit: 0.7 %  
Upper Explosive Limit : 13.1 %

Extinguishing Media: Film Forming Foam, Carbon Dioxide, Dry Chemical, Water Fog

Unusual Fire And Explosion Hazards: Water spray may be ineffective. Closed containers may explode when exposed to extreme heat. Vapors may form explosive mixtures with air. Vapors can travel to a source of ignition and flash back. FLASH POINT IS LESS THAN 20 °. F. - EXTREMELY FLAMMABLE LIQUID AND VAPOR! Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Perforation of the pressurized container may cause bursting of the can.

Special Firefighting Procedures: Evacuate area and fight fire from a safe distance.

## Section 6 - Accidental Release Measures

Steps To Be Taken If Material Is Released Or Spilled: Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Dispose of according to local, state (provincial) and federal regulations. Do not incinerate closed containers. Remove all sources of ignition, ventilate area and remove with inert absorbent and non-sparking tools.

## Section 7 - Handling And Storage

Handling: Wash thoroughly after handling. Follow all MSDS/label precautions even after container is emptied because it may retain product residues. Avoid breathing vapor or mist. Use only in a well-ventilated area. Wash hands before eating.

Storage: Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Do not store above 120 ° F. Store large quantities in buildings designed and protected for storage of NFPA Class I flammable liquids. Contents under pressure. Do not expose to heat or store above 120 ° F.

## Section 8 - Exposure Controls / Personal Protection

Engineering Controls: Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof ventilation equipment.

Respiratory Protection: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use. A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits.

Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or in any other circumstances where air purifying respirators may not provide adequate protection.

Skin Protection: Use impervious gloves to prevent skin contact and absorption of this material through the skin. Nitrile or Neoprene gloves may afford adequate skin protection.

Eye Protection: Use safety eyewear designed to protect against splash of liquids.

Other protective equipment: Refer to safety supervisor or industrial hygienist for further information regarding personal protective equipment and its application.

Hygienic Practices: Wash thoroughly with soap and water before eating, drinking or smoking.

## Section 9 - Physical And Chemical Properties

|                                 |                  |                   |                   |
|---------------------------------|------------------|-------------------|-------------------|
| Boiling Range:                  | -34 - 999 F      | Vapor Density:    | Heavier than Air  |
| Odor:                           | Solvetn Like     | Odor Threshold:   | ND                |
| Appearance:                     | Aerosolized Mist | Evaporation Rate: | Faster than Ether |
| Solubility in H <sub>2</sub> O: | Slight           |                   |                   |
| Freeze Point:                   | ND               | Specific Gravity: | 0.784             |
| Vapor Pressure:                 | ND               | PH:               | NE                |
| Physical State:                 | Liquid           |                   |                   |

(See section 16 for abbreviation legend)

## Section 10 - Stability And Reactivity

Conditions To Avoid: Avoid temperatures above 120 ° F. Avoid all possible sources of ignition.

Incompatibility: Incompatible with strong oxidizing agents, strong acids and strong alkalies.

Hazardous Decomposition: When heated to decomposition, it emits acrid smoke and irritating fumes. By open flame, carbon monoxide and carbon dioxide.

Hazardous Polymerization: Will not occur under normal conditions.

Stability: This product is stable under normal storage conditions.

## Section 11 - Toxicological Information

Product LD50: ND

Product LC50: ND

| <b>Chemical Name</b>           | <b>LD50</b>             | <b>LC50</b>                         |
|--------------------------------|-------------------------|-------------------------------------|
| Liquefied Petroleum Gas        | N.E.                    | N.E.                                |
| Acetone                        | 5800 mg/kg (Rat)        | 50100 mg/m3 (Rat, 8Hr)              |
| Modified Alkyd Resin           | N.E.                    | N.E.                                |
| Toluene                        | 636 mg/kg (Rat, Oral)   | > 26700 ppm (Rat, Inhalation, 1 Hr) |
| Mineral Spirits                | >8 mg/kg (Rat, Oral)    | >1400 ppm (Rat, Inhalation, 4Hr)    |
| Magnesium Silicate             | N.E.                    | TCLo: 11 mg/m3 (Inhalation)         |
| Xylene                         | 4300 mg/kg (Rat, Oral)  | 5000 ppm (Rat, Inhalation, 4Hr)     |
| Aliphatic Hydrocarbon          | >5000 mg/kg (Rat, Oral) | N.E.                                |
| n-Butyl Acetate                | 13100 mg/kg (Rat, Oral) | 2000 ppm (Rat, Inhalation, 4 Hr)    |
| Ethylbenzene                   | 3500 mg/kg (Rat, Oral)  | N.E.                                |
| Quartz (Crystalline Silica)    | N.E.                    | N.E.                                |
| Methyl Ethyl Ketoxime          | 3680 mg/kg (Rat)        | >4.8 mg/L (Rat)                     |
| Solvent Naptha, Light Aromatic | 4700 mg/kg (Rat, Oral)  | 3670 mg/kg (Rat, Inhalation)        |

## Section 12 - Ecological Information

Ecological Information: Product is a mixture of listed components.

## Section 13 - Disposal Information

Disposal Information: Dispose of material in accordance to local, state and federal regulations and ordinances. Do not allow to enter storm drains or sewer systems.

## Section 14 - Transportation Information

|                           |          |                   |      |
|---------------------------|----------|-------------------|------|
| DOT Proper Shipping Name: | Aerosols | Packing Group:    | N.A. |
| DOT Technical Name:       | N.A.     | Hazard Subclass:  | N.A. |
| DOT Hazard Class:         | 2.1      | Resp. Guide Page: | 126  |
| DOT UN/NA Number:         | UN 1950  |                   |      |

## Section 15 - Regulatory Information

### CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE HEALTH HAZARD, CHRONIC HEALTH HAZARD, FIRE HAZARD, PRESSURIZED GAS HAZARD

**SARA Section 313:**

Listed below are the substances (if any) contained in this product that are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

| <b><u>Chemical Name</u></b> | <b><u>CAS Number</u></b> |
|-----------------------------|--------------------------|
| Toluene                     | 108-88-3                 |
| Xylene                      | 1330-20-7                |
| Ethylbenzene                | 100-41-4                 |

**Toxic Substances Control Act:**

Listed below are the substances (if any) contained in this product that are subject to the reporting requirements of TSCA 12(B) if exported from the United States:

**U.S. State Regulations: As follows -****New Jersey Right-to-Know:**

The following materials are non-hazardous, but are among the top five components in this product.

None

**Pennsylvania Right-to-Know:**

The following non-hazardous ingredients are present in the product at greater than 3%.

| <b><u>Chemical Name</u></b> | <b><u>CAS Number</u></b> |
|-----------------------------|--------------------------|
| Iron Oxide                  | 1309-37-1                |

**California Proposition 65:**

WARNING! This product contains a chemical(s) known by the State of California to cause cancer.

WARNING! This product contains a chemical(s) known to the State of California to cause birth defects or other reproductive harm.

**International Regulations: As follows -****CANADIAN WHMIS:**

This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

**CANADIAN WHMIS CLASS:** AB5 D2A D2B

**Section 16 - Other Information****HMIS Ratings:**

Health: 2\*

Flammability: 4

Reactivity: 0

Personal Protection: X

**REASON FOR REVISION:** Regulatory Update

**Legend:** N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The information contained on this MSDS has been checked and should be accurate. However, it is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.