

Issuing Date 27-Oct 2014

Revision Date 20-Oct-2014

Revision Number 1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product SDS Name Steel Reinforced Epoxy Resin - Syringe - Part A

J-B Weld FG SKU Part Numbers Covered

50165, 50165-F, 50176, 50176-F

J-B Weld Product Names Covered

J-B Weld[™] Syringe, KwikWeld[™] Syringe

J-B Weld Product Type

Epoxy

Recommended use of the chemical and restrictions on use

Recommended UseGeneral Purpose AdhesiveUses advised againstNo information available

Details of the supplier of the safety data sheet

Supplier NameJ-B WELD COMPANY,LLCSupplier Address1130 COMO STSULPHUR SPRINGS, TX 75482USA

Emergency Telephone Numbers Transportation Emergencies: Chemtrec (24 hour transportation emergency response info): 800-424-9300 or 703-527-3887

Poison/Medical Emergencies: Poison Control Centers (24 hour emergency poison / medical response info): 800-222-1222

Supplier Email

info@jbweld.com

Supplier Phone Number 903-885-7696

2. HAZARDS IDENTIFICATION

OSHA/HCS statusThis material is considered hazardous by the OSHA Hazard Communication Standard
(29 CFR 1910.1200).Classification of the
substance or mixtureSKIN CORROSION/IRRITATION - Category 2GHS label elementsSKIN SENSITIZATION - Category 1B

Hazard pictograms Signal word Hazard statements

Precautionary statements



Warning! Causes skin and eye irritation. May cause an allergic skin reaction.

Prevention	Wear protective gloves. Wear eye or face protection. Avoid breathing dust. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.
Response	IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
Storage	Not applicable.
Disposal	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazards not otherwise classified	None known.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Substance/mixture

Mixture

Ingredient name	% by weight	CAS number
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin	60 - 100	25068-38-6
carbon black respirable	0.1 - 1	1333-86-4

Occupational exposure limits, if available, are listed in Section 8.

4. FIRST AID MEASURES					
Description of necessary first aid measures					
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.				
Skin contact	Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.				
Eye contact	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.				
Ingestion	Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.				
Most important symptoms/e Potential acute health effe					
r otomiai acute nealth ener					

Inhalation

No known significant effects or critical hazards.



Skin contact	Causes skin irritation. May cause an allergic skin reaction		
Eye contact	Causes serious eye irritation.		
Ingestion	Irritating to mouth, throat and stomach.		
Over-exposure signs/sympto	oms		
Inhalation	No specific data.		
Skin contact	Adverse symptoms may include the following: irritation redness		
Eye contact	Adverse symptoms may include the following: pain or irritation watering redness		
	No specific data.		

Ingestion Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments No specific treatment.

See toxicological information (Section 11)

5. FIRE-FIGHTING MEASURES Extinguishing media Use an extinguishing agent suitable for the surrounding fire. Suitable extinguishing media None known. **Unsuitable extinguishing** media Specific hazards arising No specific fire or explosion hazard. from the chemical National Fire Protection Association (U.S.A.) Flammability Health Instability/Reactivity **Special Hazardous thermal** Decomposition products may include the following materials: decomposition products carbon dioxide carbon monoxide halogenated compounds metal oxide/oxides **Special protective actions** Promptly isolate the scene by removing all persons from the vicinity of the incident if for fire-fighters there is a fire. No action shall be taken involving any personal risk or without suitable training. **Special protective equipment** Fire-fighters should wear appropriate protective equipment and self-contained breathing for fire-fighters apparatus (SCBA) with a full face-piece operated in positive pressure mode.



6. ACCIDENTAL RELEASE MEASURES

•••	
Personal precautions, protective	ve equipment and emergency procedures
For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".
Environmental precautions Methods and materials for cont	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). tainment and cleaning up
Small spill	Move containers from spill area. Avoid dust generation. Using a vacuum with HEPA filter will reduce dust dispersal. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.
Large spill	Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.
	7. HANDLING AND STORAGE
Conditions for safe storage, including any incompatibilities	Do not store above the following temperature: 35°C (95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.
Precautions for safe handling	
Protective measures	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.



8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Occupational exposure limits

Ingredient name	C	CAS #	Exposure limits	
carbon black respirable	1	1333-86-4	OSHA PEL 1989 (United States, 3/1989). TWA: 3.5 mg/m ³ 8 hours. ACGIH TLV (United States, 6/2013). TWA: 3 mg/m ³ 8 hours. Form: Inhalable fraction NIOSH REL (United States, 10/2013). TWA: 3.5 mg/m ³ 10 hours. TWA: 0.1 mg of PAHs/cm ³ 10 hours. OSHA PEL (United States, 2/2013). TWA: 3.5 mg/m ³ 8 hours.	
Appropriate engineering controls	cont with	rol worker exp exposure limit neering contro	tion requirements. Good general ventilation should be sufficient to posure to airborne contaminants. If this product contains ingredients ts, use process enclosures, local exhaust ventilation or other ols to keep worker exposure below any recommended or statutory	
Environmental exposure controls	they case will b	comply with the scrub	entilation or work process equipment should be checked to ensure the requirements of environmental protection legislation. In some bers, filters or engineering modifications to the process equipment to reduce emissions to acceptable levels.	
Individual protection measured	<u>sures</u>			
Hygiene measures Respiratory protection	 Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the 			
	selected re	espirator.		
Skin protection Hand protection	at all times necessary use that th time to bre manufactu	s when handlir . Considering le gloves are s eakthrough for irers. In the ca	ervious gloves complying with an approved standard should be worn ing chemical products if a risk assessment indicates this is the parameters specified by the glove manufacturer, check during still retaining their protective properties. It should be noted that the any glove material may be different for different glove use of mixtures, consisting of several substances, the protection time accurately estimated.	
Body protection	Personal p	protective equi and the risks	pment for the body should be selected based on the task being involved and should be approved by a specialist before handling	
Other skin protection	Appropriat on the task	e footwear an k being perforr	d any additional skin protection measures should be selected based med and the risks involved and should be approved by a specialist duct.	
Eye/face protection	before handling this product. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.			



9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Solid.
Color	Black.
Odor	Ethereal.
Odor threshold	Not available.
рН	Not available.
Melting point	Not available.
Boiling point	Not available.
Flash point	[Product does not sustain combustion.]
Evaporation rate	Not available.
Flammability (solid, gas)	Flammable in the presence of the following materials or conditions: open flames, sparks and static discharge. Not available.
Lower and upper explosive (flammable) limits Vapor pressure Vapor density Relative density Solubility Solubility in water	Not available. Not available. 1.199 Not available. Not available.
Auto-ignition temperature	Not available. >200°C (>392°F)
Decomposition temperature	Not available.
Viscosity	
VOC (% content)	<3%

10. STABILITY AND REA	CTIVITY
-----------------------	---------

Reactivity	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	The product is stable.
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	No specific data.
Incompatible materials	No specific data.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.



11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Product/ingredient name	Result		Species I		Dos	e	Exposure	
carbon black respirable	LD50 Oral		Rat >154		>1540	00 mg/kg	-	
rritation/Corrosion					I			
Product/ingredient name	Result	Spec	ies	Score		Exposure	Observation	
reaction product: bisphenol- A(epichlorhydrin); epoxy resin	Eyes - Mild irritant	Rabb	it	-		100 milligrams	-	
	Skin - Moderate irritant	Rabb	it	-		24 hours 500 microliters	-	
	Skin - Severe irritant	Rabb	it	-		24 hours 2 milligrams	-	

Sensitization No

specific data.

Mutagenicity No

specific data.

Carcinogenicity No

specific data.

C	lass	ific	atior	

Product/ingredient name	OSHA	IARC	NTP
carbon black respirable	-	2B	-

Reproductive toxicity No

specific data.

Teratogenicity No

specific data.

Specific target organ toxicity (single exposure) No specific data.

Specific target organ toxicity (repeated exposure) No specific data. Aspiration hazard No specific data.

Not available.

routes of exposure Potential acute health effects

Information on the likely

r otoritiar aoato rioattir orrooto	
Eye contact	Causes serious eye irritation.
Inhalation	No known significant effects or critical hazards.
Skin contact	Causes skin irritation. May cause an allergic skin reaction.
Ingestion	Irritating to mouth, throat and stomach.



Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	No specific data.
Skin contact	Adverse symptoms may include the following: irritation redness
Ingestion	No specific data.
•	and also chronic effects from short and long term exposure
Short term exposure	and also enrolle encots from short and long term exposure
Potential immediate effects	Not available.
Potential delayed effects	available. Not available.
Long term exposure	
Potential immediate effects	Not available.
Potential delayed effects	Not available.
Potential chronic health effec	
specific data.	
General	Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	No known significant effects or critical hazards.
Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	No known significant effects or critical hazards.
Developmental effects	No known significant effects or critical hazards.
Fertility effects	No known significant effects or critical hazards.
Numerical measures of toxicity	-
Acute toxicity estimates No specific data.	
	12. ECOLOGICAL INFORMATION

Toxicity

No specific data.

Persistence and degradability No

specific data.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
reaction product: bisphenol- A(epichlorhydrin); epoxy resin	2.64 to 3.78	31	low



Mobility in s	oil
Soil/water p	artition
coefficient	(Koc)

Not available.

Other adverse effects

No known significant effects or critical hazards.

13. DISPOSAL CONSIDERATIONS

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

RCRA classification

Not available.

14. TRANSPORT INFORMATION

	DOT Classification	TDG Classification	Mexico Classification	IMDG	ΙΑΤΑ
UN Number UN proper shipping name	UN3077 Environmentally hazardous substance, solid, n.o.s. (reaction product: bisphenol-A- (epichlorhydrin); epoxy resin). Marine pollutant	UN3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (reaction product: bisphenol-A- (epichlorhydrin); epoxy resin). Marine pollutant.	UN3077 SUBSTANCIA SOLIDA POTENCIALMENTE PELIGROSA PARA EL MEDIO AMBIENTE, N.E.P. (reaction product: bisphenol-A- (epichlorhydrin); epoxy resin). Marine pollutant	UN3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (reaction product: bisphenol-A- (epichlorhydrin); epoxy resin). Marine pollutant	UN3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (reaction product: bisphenol-A- (epichlorhydrin); epoxy resin)
Transport hazard class(es)	9	9	9	9	9
Packing group					
Environmental hazards	Yes.	Yes.	Yes.	Yes.	Yes
Additional information	<u>Limited quantity</u> Yes.	Explosive Limit and Limited Quantity Index 5	<u>Special</u> provisions 179, 274	<u>Emergency</u> <u>schedules (EmS)</u> F-A, S-F	Passenger and Cargo Aircraft Quantity limitation: 400 kg



<u>Special</u> <u>provisions</u> 8, 146, 335, B54, IB8, IP3, N20, T1, TP33	Special provisions		Packaging instructions: 956 Cargo Aircraft Only Quantity limitation: 400 kg Packaging instructions: 956 Limited Quantities – Passenger Aircraft Quantity limitation: 30 kg Packaging instructions:
			Y956

Special precautions for user Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

15. REGULATORY INFORMATION

U.S. Federal regulations TSCA 8(a) PAIR: Siloxanes and Silicones, di-Me, reaction products with silica TSCA 8(a) CDR Exempt/Partial exemption: Not determined United States inventory (TSCA 8b): All components are listed or exempted

Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)	Not listed
Clean Air Act Section 602 Class I Substances	Not listed

Clean Air Act Section 602 Not listed **Class II Substances**

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ

SARA 311/312

Not applicable.

Classification

Immediate (acute) health hazard

Composition/information on ingredients

Name	%	Fire hazard	Sudden release of pressure		Immediate (acute) health hazard	Delayed (chronic) health hazard
reaction product: bisphenol- A(epichlorhydrin); epoxy resin	60 - 100	No.	No.	No.	Yes.	No.
carbon black respirable	0.1 - 1	No.	No.	No.	No.	Yes.



State regulations	None of the components are listed.
Massachusetts	None of the components are listed.
New York	The following components are listed: CARBON
New Jersey	BLACK
Pennsylvania	The following components are listed: CARBON BLACK
Minnesota Hazardous	None of the components are listed.
Substances	

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

Ingredient name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
carbon black respirable	Yes.	No.	No.	No.
International regulations International lists	exempted. China inventory (IE Japan inventory: No Korea inventory: All Ialaysia Inventory (Iew Zealand Invent	y (AICS): All cor CSC): All componen ot determined. components are lis (EHS Register): Not ory of Chemicals (I ry (PICCS): All comp	t determined. NZIOC) : Not determined ponents are listed or exem	ed. I.

Substances of very high concern

None of the components are listed.

	16. OTHER INFORMATION
Key to abbreviations	ATE = Acute Toxicity Estimate
	BCF = Bioconcentration Factor
	GHS = Globally Harmonized System of Classification and Labelling of Chemicals
	IATA = International Air Transport Association
	IBC = Intermediate Bulk Container
	IMDG = International Maritime Dangerous Goods
	LogPow = logarithm of the octanol/water partition coefficient
	MARPOL 73/78 = International Convention for the Prevention of Pollution From
	Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
	UN = United Nations

Notice to reader

NON-WARRANTY: The information presented in this publication is based upon the research and experience of J-B Weld Company. No representation or warranty is made, however, concerning the accuracy or completeness of the information presented in this publication. J-B Weld Company makes no warranty or representation of any kind, express or implied, including without limitation any warranty of merchantability or fitness for any particular purpose, and no warranty or representation shall be implied by law or otherwise. Any products sold by J-B Weld Company are not warranted as suitable for any particular purpose to the buyer. The suitability of any products for any purpose particular to the buyer is for the buyer to determine. J-B Weld Company assumes no responsibility for the selection of products suitable to the particular purposes of any particular buyer. J-B Weld Company shall in no event be liable for any special, incidental, or consequential damages.

End of Safety Data Sheet





Issuing Date 27-Oct 2014

Revision Date 20-Oct-2014

Revision Number 1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product SDS Name Steel Reinforced Epoxy Hardener – Fast Cure - Syringe - Part B

J-B Weld FG SKU Part Numbers Covered

50176, 50176-F

J-B Weld Product Names Covered

KwikWeld™ Syringe

J-B Weld Product Type

Ероху

Recommended use of the chemical and restrictions on use			
Recommended Use	General Purpose Adhesive		
Uses advised against	No information available		
Details of the supplier of the safety	/ data sheet		
Supplier Name	J-B WELD COMPANY,LLC		
Supplier Address	1130 COMO ST SULPHUR SPRINGS, TX 75482 USA		
Emergency Telephone Numbers	Transportation Emergencies: Chemtrec (24 hour transportation emergency response info): 800-424-9300 or 703-527-3887		
	Poison/Medical Emergencies: Poison Control Centers (24 hour emergency poison / medical response info): 800-222-1222		
Supplier Email	info@jbweld.com		
Supplier Phone Number	903-885-7696		

	2. HAZARDS IDENTIFICATION
OSHA/HCS status	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the	ACUTE TOXICITY: ORAL - Category 4
substance or mixture GHS label elements	ACUTE TOXICITY: SKIN - Category 4



Hazard pictograms Signal word

Hazard statements	Harmful if swallowed or in contact with skin.
Precautionary statements	
Prevention	Wear protective gloves. Wear protective clothing. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling.
Response	IF SWALLOWED: Call a POISON CENTER or physician if you feel unwell. Rinse mouth. IF ON SKIN: Wash with plenty of soap and water. Call a POISON CENTER or physician if you feel unwell. Wash contaminated clothing before reuse.
Storage	Not applicable.
Disposal	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazards not otherwise classified	None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance/mixture

Ingredient name	% by weight	CAS number
2,4,6-tris(dimethylaminomethyl)phenol	5 - 10	90-72-2
titanium dioxide	0.1 - 1	13463-67-7
On a second the second second limited of a second second limited with the One of the O		

Occupational exposure limits, if available, are listed in Section 8.

Mixture

4. FIRST AID MEASURES

Description of necessary	
first aid measures	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not
Inhalation	breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth- to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention if adverse health effects persist or are severe. If necessary, call a poison center or physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Eye contact	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
Ingestion	Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health	effects
Inhalation	Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
Skin contact	Harmful in contact with skin.
Eye contact	No known significant effects or critical hazards.
Ingestion	Harmful if swallowed.



Over-exposure signs/sy	<u>/mptoms</u>	
Inhalation	No specific data.	
Skin contact	No specific data.	
Eye contact	No specific data.	
Ingestion Indication of immediate	No specific data. medical attention and special treatment needed, if necessary	
Notes to physician	In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.	
Specific treatments	No specific treatment.	

See toxicological information (Section 11)

	5. FIRE-FIGHTING MEASURES
Extinguishing media	Use an extinguishing agent suitable for the surrounding fire.
Suitable extinguishing media Unsuitable extinguishing media	None known.
Specific hazards arising from the chemical	No specific fire or explosion hazard.
National Fire Protection Assoc	iation (U.S.A.)
Health 200	Flammability Instability/Reactivity Special
Hazardous thermal decomposition products	Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides sulfur oxides metal oxide/oxides
Special protective actions for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable
Special protective equipment for fire-fighters	training. Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures



For non-emergency personnel For emergency responders	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".		
Environmental precautions Methods and materials for cont	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).		
Small spill	Move containers from spill area. Avoid dust generation. Using a vacuum with HEPA		
Large spill	filter will reduce dust dispersal. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.		
7. HANDLING AND STORAGE			
Conditions for safe storage, including any incompatibilities	Do not store above the following temperature: 35°C (95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.		
Precautions for safe handling			
Protective measures Advice on general occupational hygiene	Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. Eating, drinking and smoking should be prohibited in areas where this		

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters Occupational exposure limits

Ingredient name

CAS #

Exposure limits



titanium dioxide	13463-67-7	ACGIH TLV (United States, 3/2012). TWA: 10 mg/m ³ 8 hours. OSHA PEL 1989 (United States, 3/1989). TWA: 10 mg/m ³ 8 hours. Form: Total dust OSHA PEL (United States, 6/2010). TWA: 15 mg/m ³ 8 hours. Form: Total dust
Appropriate engineering controls	No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.	
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.	
Individual protection measures Hygiene measures	S Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.	
Respiratory protection	Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.	
Skin protection		
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.	
Body protection	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.	
Other skin protection	selected based of	vear and any additional skin protection measures should be n the task being performed and the risks involved and should be ecialist before handling this product.
Eye/face protection	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side- shields.	



9. PHYSICAL AND CHEMICAL PROPERTIES

Physical States	Solid.
Color	White.
Odor	Pungent. Sulfurous. {Strong]
Odor threshold	Not available.
рН	Not available.
Melting point	Not available.
Boiling point	Not available.
Flash point	Closed cup: >93.3°C (>199.9°F)[Setaflash.] [Product does not sustain combustion.]
Evaporation rate	Not available.
Flammability (solid, gas)	Flammable in the presence of the following materials or conditions: open flames, sparks and static discharge.
Lower and upper explosive (flammable) limited	Not available.
Vapor pressure	Not available
Vapor density	Not available.
Relative density	1.2
Solubility	Not available.
Solubility in water	Not available.
Auto-ignition temperatures	Not available.
Decomposition temperature	>200°C(>392°F)
Viscosity	Not available
VOC (% content)	<3%

	10. STABILITY AND REACTIVITY
Reactivity	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	The product is stable.
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	No specific data.
Incompatible materials	No specific data.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.



11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Acute	toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2,4,6-tris (dimethylaminomethyl)phenol	LD50 Dermal	Rat	1280 mg/kg	-
	LD50 Oral	Rat	1200 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
2,4,6-tris (dimethylaminomethyl)phenol	Eyes - Severe irritant	Rabbit	-	24 hours 50 Micrograms	-
	Skin - Mild irritant	Rat	-	0.025 Mililiters	-
	Skin - Severe irritant	Rat	-	0.25 Mililiters	-
	Skin - Severe irritant	Rabbit	-	24 hours 2 milligrams	-
titanium dioxide	Skin - Mild irritant	Human	-	72 hours 300 Micrograms Intermittent	-

Sensitization

No specific data.

Mutagenicity No

specific data.

Carcinogenicity

No specific data.

Classification

Product/ingredient name	OSHA	IARC	NTP
titanium dioxide	-	2B	-

Reproductive toxicity

No specific data.

Teratogenicity

No specific data.

Specific target organ toxicity (single exposure) No specific data.

Specific target organ toxicity (repeated exposure)

No specific data.

Aspiration hazard

No specific data.

Information on the likely

routes of exposure

Not available.

Potential acute health effects

Eye contact

No known significant effects or critical hazards.



Inhalation	Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.						
Skin contact	Harmful in contact with skin.						
Ingestion	Harmful if swallowed.						
	cal, chemical and toxicological charact	eristics					
Eye contact	No specific data.						
Inhalation	No specific data.						
Skin contact	No specific data.						
Ingestion	No specific data.						
Delayed and immediate effects	and also chronic effects from short and	d long term exposure					
Short term exposure							
Potential immediate	Not						
effects	available.						
Potential delayed effects	Not						
	available.						
Long term exposure	Not						
Potential immediate	available.						
effects							
Potential delayed effects	Not						
	available.						
Potential chronic health effect	t <u>s</u>						
No specific data.							
General	No known significant effects or critical ha						
Carcinogenicity	No known significant effects or critical ha						
Mutagenicity	No known significant effects or critical ha						
Teratogenicity	No known significant effects or critical ha	zards.					
Developmental effects	No known significant effects or critical ha	zards.					
Fertility effects	No known significant effects or critical hazards.						
Numerical measures of toxicity	-						
Acute toxicity estimates							
Route		ATE value					
Oral		1239.2 mg/kg					
Dermal		1321.8 mg/kg					
	12. ECOLOGICAL INFOR	MATION					
Toxicity							

Product/ingredient name	Result	Species	Exposure
titanium dioxide	Acute LC50 1000000 µg/l Marine water	Fish - Fundulus heteroclitus	96 hours

Persistence and degradability No specific data.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2,4,6-tris (dimethylaminomethyl)phenol	0.219	-	low
titanium dioxide	-	352	low



Soil/water partition coefficient (Koc)

Not available.

Other adverse effects

No known significant effects or critical hazards.

13. DISPOSAL CONSIDERATIONS

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Not available.

RCRA classification

14. TRANSPORT INFORMATION						
	DOT Classification	TDG Classification	Mexico Classification	IMDG	ΙΑΤΑ	
UN Number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.	
UN proper shipping name	-	-	-	-	-	
Transport hazard class(es)	-	-	-	-	-	
Packing group	-	-	-	-	-	
Environmental hazards	No.	No.	No.	No.	No.	

Special precautions for user

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.



				NFORM			
.S. Federal regulations	•	-			-Me, reaction p		silica
	•		•	•	: Not determin		
	United St	ates inven	ntory (TSC)	A 8b): All con	nponents are li	sted or exem	pted.
Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)	Not listed						
Clean Air Act Section 602 Class I Substances	Not listed						
Clean Air Act Section 602 Class II Substances <u>SARA 302/304</u>	Not listed						
Composition/information or	n ingredient	<u>s</u>					
No products were found.							
SARA 304 RQ	Not applic	able.					
SARA 311/312							
Classification	Immediate	e (acute) he	ealth hazar	d			
Composition/information or	n ingredient	S					
Name		%	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
2,4,6-		5 - 10	No.	No.	No.	Yes.	No.
tris(dimethylaminomethyl)p titanium dioxide	henol	0.1 - 1	No.	No.	No.	No.	Yes.
State regulations	The foll	owing com	ponents are	e listed [.] BARI	IUM SULFATE	:	
Massachusetts		-	onents are				
New York		•			IUM SULFATE		
New Jersey	The following components are listed: BARIUM SULFATE; SULFURIC ACID, BARIUM SALT (1:1); TITANIUM DIOXIDE; TITANIUM OXIDE (TiO2)						
	The foll	owing com	ponents are	e listed: BAR	IUM SULFATE	; TITANIUM	OXIDE
Pennsylvania	(TIO2)						
Minnesota Hazardous	None of	f the compo	onents are	listed.			
Substances							
<u>California Prop. 65</u>							
WARNING: This product cont Ingredient name	ains a chem	ical known Cancer			a to cause can No significant		

Ingredient name		Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
titanium dioxide		Yes.	No.	No.	No.
Canada inventory International regulations International lists	Australia exempted China inv exempted Japan in Korea inv	a inventory d. ventory (IECS d. ventory: Not o ventory: Not o	SC) : All componen determined.		or



New Zealand Inventory of Chemicals (NZIoC): Not determined. Philippines inventory (PICCS): Not

determined. Taiwan inventory (CSNN): Not determined.

Substances of very high concern None of the components are listed.

	16. OTHER INFORMATION
Key to abbreviations	ATE = Acute Toxicity Estimate
	BCF = Bioconcentration Factor
	GHS = Globally Harmonized System of Classification and Labelling of Chemicals
	IATA = International Air Transport Association
	IBC = Intermediate Bulk Container
	IMDG = International Maritime Dangerous Goods
	LogPow = logarithm of the octanol/water partition coefficient
	MARPOL 73/78 = International Convention for the Prevention of Pollution From
	Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
	UN = United Nations

Notice to reader

NON-WARRANTY: The information presented in this publication is based upon the research and experience of J-B Weld Company. No representation or warranty is made, however, concerning the accuracy or completeness of the information presented in this publication. J-B Weld Company makes no warranty or representation of any kind, express or implied, including without limitation any warranty of merchantability or fitness for any particular purpose, and no warranty or representation shall be implied by law or otherwise. Any products sold by J-B Weld Company are not warranted as suitable for any particular purpose to the buyer. The suitability of any products for any purpose particular to the buyer is for the buyer to determine. J-B Weld Company assumes no responsibility for the selection of products suitable to the particular purposes of any particular buyer. J-B Weld Company shall in no event be liable for any special, incidental, or consequential damages.

End of Safety Data Sheet

