

Technical Data Bulletin





SureGrip [®] Border Adhesive For Painted Surfaces is Ready-To-Use, clear adhesive formulated for hanging all pre-pasted borders and non-pasted borders over painted or primed surfaces.

- For hanging any pre-pasted border
- Provides excellent adhesion
- Dries Clear, non-staining

Selection Data

Generic Type – Starch-based adhesive.

Recommended Uses – Use to apply pre-pasted and non-pasted paper-backed borders over painted or primed surfaces. Refer to the "ZINSSER SureGrip Adhesive Selection Chart" online at <u>www.rustoleum.com</u> for detailed recommendations.

Not Recommended For – This product is not intended for hanging pre-pasted or non-pasted borders over existing vinyl wallcovering or extremely rough surfaces such as concrete blocks or stucco. See "**Existing Vinyl Wallcovering or Rough Surfaces**" on page 2 for recommended for hanging borders over bare or painted drywall.

Application Data

Surface Preparation – All walls must be clean, dry, smooth and sound – free of dust, grease, wax, oil, old wallcovering adhesive, mold and mildew and other residue. If old wallcovering exists, remove it with **DIF**[®] **Wallpaper Stripper**. Seal loose paint or damaged drywall and skim coats with **GARDZ**[®] **High Performance Sealer** as needed.

Prime un-painted surfaces with SHIELDZ[®] Universal Wallcovering Primer or SHIELDZ[®] Clear Acrylic Wall Size. Before proceeding with an unusual conditions, consult your wallcovering or adhesive supplier.

Application – Use only when temperature is above 50° F. For non-pasted borders use full strength. For pre-pasted borders, then with a maximum of 4 oz. of water per quart. Using a roller or brush, apply liberally to the back of border. Book and hang according to border manufacturer's instructions.

Mold & Mildew - Eliminate pre-existing mold and mildew by washing the affected area with a solution of ³/₄ of Clorox[®] Ultra Bleach to 1 gallon of clean water. Wear protection to prevent skin and eye contact. Quickly wash off any solution that comes in contact with your skin. Do not add ammonia or other cleaning products to the bleach solution. Rinse surface with clean water. Allow surface to dry thoroughly before applying wallcovering.

Drywall - Wipe down with a damp cloth to remove residual joint compound dust prior to priming.

Plaster – New plaster must age at least 90 days before hanging wallcovering. Prime prior to installation.

Glossy Surfaces – Glossy paint, paneling, metal, glass, plastic, etc. should be primed with either SHIELDZ[®] Universal Wallcovering Primer, SHIELDZ Universal PLUS Wallcovering Primer, SHIELDZ Clear Acrylic Wall Size or SHIELDZ Oil-Base Wallcovering Primer prior to wallcovering installation. Metal surfaces should be primed with rust inhibiting Bulls Eye 1-2-3[®] Primer.

Existing Vinyl Wallcovering or Rough Surfaces- This product is not intended for hanging borders over existing wallcovering or extremely rough surfaces such as concrete blocks or stucco. For installations over wallcovering, use either, **SureGrip Border** Adhesive For Wallpapered Surfaces. SureGrip[®] Universal Wallcovering Adhesive or PREPZ[®] Pre-Pasted Border Prep & Adhesive, or SureGrip 127 Vinyl Over Vinyl Wallcovering Adhesive. **Textiles and Delicate Borders** – Take special care to keep the adhesive off the face of the wallpaper. Some wallpaper can be stained by water alone. Test for stain resistance prior to the installation and hang according to manufacturer's instructions.

Coverage - One quart of adhesive will hang up to 8 to 12 border spools. Spread rate may differ with various backings.

Dry Time – Drying time will vary depending on the border type, temperature, ventilation and humidity of the room.

Cleanup – Remove excess adhesive on or around the border immediately with clean water. Additional effort may be required if adhesive is allowed to contact the surface of embossed or textured vinyl. Close container tightly after each use.

Tool Cleanup – Clean tools with warm water.

Storage/Shelf/Disposal – **Protect from freezing**. Always keep the container tightly closed and store in a cool dry place at temperature between 40°F to 100°F. Normal storage life is one year. The disposal of excess or left over product should conform to local laws regarding water-based products.

Caution – Avoid contact with eyes and skin. Wear eye and skin protection. In case of eye contact, flush eyes with plenty of water for at least 15 minutes. in case of skin contact, wash thoroughly with soap and water. Do not take internally. If swallowed contact a physician or Poison Control Center. Use with adequate ventilation. **Keep Out of Reach Of Children.**

Limited Warranty – This product will perform as claimed if applied according to our directions. The directions apply to most applications, but may not cover special conditions, applications, techniques and/or surfaces. If you have a question, check with your dealer or contact Rust-Oleum Corporation, Vernon Hills, IL. Warranty is limited to replacement or refunded value of product actually used when supported by proof of purchase if such product proves defective within one year from date of manufacture.

Size	Item No.	Product UPC	Carton Code	Case Dimensions	Case Pack	Case Wt. Lbs	Case Vol. In.	Pallet Pack	Pallet Size
Quart	69684	0 47719 69684 2	60 047719 69684 1	15.5" x 10.25" x 5.75"	6	15	.49	81	40" x 48"

PHYSICAL & PERFORMANCE DATA					
Appearance Dry	Clear				
Odor	Mild				
% Solids	23.5% +/1%				
Viscosity	24,000 -28,000 cps				
Thinning	Thin up to 4 oz. per quart for pre-pasted borders				
Coverage	8-12 spools (May vary depending on porosity and application method)				
Pasting Machine	Recommended				
Cleanup	With water				
Recommended Application Range	50°F to 100°F				
Recommended Storage Temperature	40°F to 100°F				
Freeze/Thaw Stable	Yes				
Flammability	Non-flammable, water based				
Shelf Life	1 year				
Mold & Mildew Resistance	Good –Contains mold & mildew inhibitors				
Removal	Wet Strip				
VOC's	Less than 5%				
Toxicity	Safe, pH Neutral				

Keep out of reach of children

Read and carefully follow all information on this Technical Data Bulletin, on the product label and the material safety data sheet for this product. To the best of our knowledge, the data contained herein are true and accurate at the date of issuance and are subject to change without prior notice. User must contact Rust-Oleum to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. We guarantee our products to conform to Rust-Oleum's quality control and assume no responsibility for coverage, performance or injuries from use. Visit Zinsser.com for our most up-to-date technical data bulletins.

> Rust-Oleum Corporation, 11 Hawthorn Parkway, Vernon Hills, IL 60061 An RPM Company Phone: 847•367•7700 www.rustoleum.com