

11" Round Spin Light™

LED

22 Watt 1600lm Round Flushmount Specifications



The ETi 11" Spin Light™ retrofits a common lampholder into a flushmount fixture. The installation is as easy as screwing in a light bulb -- yet the Spin Light offers exceptional performance, while reducing energy and maintenance costs when compared with conventional light sources. Using only 22 watts of power to deliver 1600 lumens and lasting more than 10 times longer, the Spin Light is a high quality replacement for incandescent bulbs or fixtures. Available in 4000K CCT and UL listed for use in damp locations, the Spin Light has a warranty of 5 years. Suitable for installations from - 4° F to 104° F.


KEY FEATURES & BENEFITS

- Retrofits a lampholder into a flushmount fixture
- Simple to install - Screws into an existing lampholder
- 22 Watts - Low Power & High Performance
- 1600 lumens
- Rated life 50,000 hours (45.6 years)
- 4000K CCT/80 CRI
- UL Rated for Damp Locations



This light source meets restrictions on hazardous substances.

FIXTURE DIMENSIONS



SKU# 54652141

Dimension A = 11.0"

Dimension B = 4.2"

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, please see www.etiled.us/fcc15b

APPLICATION INFORMATION

Designed to be used anywhere a standard incandescent lamp or fixture is used. Typically used in basements, utility rooms, garages, laundry rooms, and closets. The Spin Light carries a 5 year warranty.



855-384-7754 www.etissl.com

11" Round Spin Light™

LED

SPECIFICATION DATA

Project _____

Item Number _____

Prepared by _____ Date _____

ORDERING INFORMATION

Item Number	Description	Wattage	Input Voltage (VAC)	Average Rated Life ¹	Typical Lumens ²	CCT ³	CRI ⁴	Power Factor	R9	Duv	CBCP	Beam	Operating Frequency
54652141	LED 22w FLUSH-MOUNT 840120 NDIM	22	120	50,000	1600	4000K	80	>.99	54	-2.99	424	120°	60Hz
¹ Hours lifetime with 70% lumen maintenance													
² Thermally stable typical lumens (±10%)													
³ Thermally stable CCT (±10%)													
⁴ Color rendering index/Ra													

SHIPPING INFORMATION

Item Number	Item UPC	Item Dimensions (H x L x W)	Item Weight (lbs)	Inner Pack Qty	Inner Carton Bar Code	Inner Carton Dimensions (H x L x W)	Inner Pack Weight (lbs)	Master Pack Qty	Master Carton Bar Code	Master Dimensions (H x L x W)	Master Pack Weight (lbs)
54652141	849489 000145	12.2" x 12.1" x 4.8"	1.9	1	N/A	12.2" x 19.8" x 12.5"	9	4	50849489 000140	12.9" x 20.4" x 13.2"	10.4



LED lighting facts®
A Program of the U.S. DOE

Light Output (Lumens) 1600
Watts 22
Lumens per Watt (Efficacy) 72.73

Color Accuracy
Color Rendering Index (CRI) 80

Light Color
Color Rendering Index (CRI) 4000 (Bright White)

2700K 3000K 4500K 6500K

All results are according to IESNA LM-79-2008, Approved Method for the Electrical and Photometric Testing of Solid-State Lighting. The U.S. Department of Energy (DOE) verifies product test data and results.
Visit www.lightingfacts.com for the Label Reference Guide.
Registration Number: W084-763L3Y (12/22/2014)
Model Number: 546521XX00-041-50
Type: Luminaire - Troffer/Grid Ceiling

North America Headquarters
720 Corporate Woods Parkway
Vernon Hills, IL 60061

855-384-7754 www.etissl.com