

MATERIAL SAFETY DATA SHEET  
May be used to comply with  
OSHA's Hazard Communication Standard,  
29 CFR 1910.1200. Standard must be  
consulted for specific requirements.

U.S DEPARTMENT OF LABOR  
Occupational Safety and Health Administration  
(Non-Mandatory Form)  
Form Approved  
OMB.No. 1218-0072

IDENTITY (As used on Label and List)

**MIX-I-GO One-Shot**

**SECTION I**

Manufacturer's Name: Bell Performance, Inc.  
Address  
1340 Bennett Drive, Longwood, FL 32750

Emergency Telephone Number: CHEMTREC: USA: 800-424-9300  
INT'L: 703-527-3887 (COLLECT)  
Telephone Number for information: (407) 831-5021

Date prepared: (optional)

Signature of Preparer (optional)

**SECTION II - Hazardous Ingredients/Identity Information**

<u>Ingredients</u>		<u>CAS #</u>	<u>TWA</u>	<u>STEL</u>	<u>PEL</u>	<u>STEL</u>
Stoddard Solvent Additives	8052-41-3	100ppm 75ppm				

A Stoddard solvent base containing as proprietary properties a surfactant, an upper lubricant, and non-metallic combustion modifiers.

**SECTION III - Physical/Chemical Characteristics**

Boiling Point:	318-460 deg F	Specific Gravity (H2O = 1):	0.885
Vapor Pressure:	2.0	Melting Point:	N/Av
Vapor Density(AIR = 1)	5.5	Evaporation Rate: (n-BuAC=1)	0.01
		(Ether=1)	70

Solubility in Water: Low

Appearance and Odor: Amber color solution having a slight characteristic odor.

**SECTION IV - Fire and Explosion Hazard Data**

**Flash Point (Method Used):** (Pensky-Martens) 120°F  
**Flammable Limits:** LEL: 1.0 UEL: 6.0

**Flammability Classification (OSHA 29 CFR 1910.1200):** Class III Combustible Liquid

**Extinguishing Media:** Foam, carbon dioxide or dry chemical fire fighting apparatus. Water may be unsuitable except as a cooling agent for fire-exposed containers.

**Special Fire Fighting Procedures:** Self-contained breathing apparatus is recommended for fire fighters. Water may be unsuitable as an extinguishing media, but helpful in keeping adjacent containers cool.

**Unusual Fire and Explosion Hazards:** Combustible liquid. Keep work areas free of hot metal surfaces and other sources of ignition. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

OSHA 174, Sept. 1985  
NPFA (NATIONAL FIRE PROTECTION ASSOCIATION STANDARD)  
Health Hazard: 2 Flammability: 2 Reactivity: 0

---

## SECTION V - Reactivity Data

---

**Stability:** Stable

**Incompatibility (materials to avoid):** This product is incompatible with strong oxidizing agents, strong acids or bases and selected amines.

**Hazardous Decomposition or Byproducts:** Thermal decomposition in the presence of air may yield carbon monoxide and/or carbon dioxide.

**Hazardous Polymerization:** Will not occur

**Conditions to Avoid:** Heat, open flame and other ignition sources

---

## SECTION VI - Health Hazard Data

---

**Route(s) of Entry:** Inhalation? Yes    Skin? Yes    Ingestion? Yes

**Carcinogenicity:**        NTP? No        OSHA Regulated? No

                                  IARC Monographs? No

### Signs and Symptoms of Exposure:

#### Medical Conditions Generally Aggravated by Exposure:

*Eyes:* This product may be an eye irritant.

*Skin:* May cause skin irritation upon prolonged or repeated contacts.

*Kidney/Liver:* Individuals with preexisting diseases of the kidney or liver may have increase susceptibility to the toxicity of excessive exposure

**Chronic Exposure Effects:** Prolonged exposure may contribute to respiratory tract irritation or central nervous system depression in high concentrations. Over-exposure to high atmospheric concentrations may produce central nervous depression, headache, dizziness, incoordination, nausea and loss of appetite. Aspiration may cause lung damage due to chemical pneumonia.

#### Emergency and First Aid Procedures:

*Eye Contact:* Flush with water for at least 15 minutes and seek immediate medical attention.

*Skin Contact:* Wash with soap and large quantities of water. Seek medical attention if irritation from contact persists.

*Inhalation:* If breathing difficulties, dizziness, or lightheadedness occur when working in areas with high vapor concentrations, victim should seek air free of vapors. If breathing stops, begin artificial respiration and seek immediate medical advice and/or attention.

*Ingestion:* DO NOT INDUCE VOMITING. Allow victim to rinse his mouth and then drink 2 to 4 cupfuls of water. Never give anything by mouth to an unconscious person. Seek immediate medical advice and/or attention.

---

## SECTION VII - Precautions for Safe Handling and Use

---

### Steps to be taken in Case Material is Released or Spilled:

**Ecotoxicological information:** The ecological characteristics of this product have not been fully investigated. The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters. Do not discharge product unmonitored into the environment.

**Chemical fate information:** There is no data available on the product itself.

**Handling for disposal:** Handle according to recommendations below.

**Safe Handling Procedures:** Keep sources of ignition and hot metal surfaces isolated from the spill. Flush spilled material into suitable retaining areas or containers with large quantities of water. Small amounts of spilled material may be absorbed into an appropriate absorbent.

**Methods of disposal:** Dispose of product in accordance with local, county, state and federal regulations.

**Precautions to be taken in Storing:** Keep product container cool, dry and away from sources of ignition. Store in an area with adequate ventilation.

**Other Precautions:** Personnel should avoid inhalation of vapors, should product splash on a person remove saturated clothing and flush contaminated area. Launder clothing before reuse.

---

## **SECTION VIII - Control Measures**

---

**Respiratory Protection:** The use of respiratory protection depends on vapor concentration above the time-weighted TLV; Use a NIOSH approved cartridge respirator or gas mask.

**Ventilation and Engineering Controls:** Provide sufficient ventilation mechanical and/or local exhaust to maintain exposure below TLV's

**Skin protection and other protective equipment:** The use of Nitrile rubber gloves is advised to prevent skin irritation in sensitive individuals.

**Eye/Face Protection:** Use goggles or face shields to safeguard against potential eye contact.

**General hygiene considerations:** Keep work area clean. Clean up spills immediately.

---

## **SECTION IX – US Federal Regulations**

---

**TSCA Inventory Status:** Reported/Included

---

Bell Performance (REV-01/08)