



MATERIAL SAFETY DATA SHEET

Page 1 of 5

Sikaflex® Mortar Fix

HMIS

HEALTH	*2
FLAMMABILITY	1
REACTIVITY	0
PERSONAL PROTECTION	C

1. Product And Company Identification

Supplier

Sika Corporation
201 Polito Ave
Lyndhurst, NJ 07071

Company Contact: EHS Department
Telephone Number: 201-933-8800
FAX Number: 201-933-9379
Web Site: www.sikausa.com

Manufacturer

Sika Corporation
201 Polito Ave
Lyndhurst, NJ 07071

Company Contact: EHS Department
Telephone Number: 201-933-8800
FAX Number: 201-933-9379
Web Site: www.sikausa.com

Supplier Emergency Contacts & Phone Number

CHEMTREC: 800-424-9300
INTERNATIONAL: 703-527-3887

Manufacturer Emergency Contacts & Phone Number

CHEMTREC: 800-424-9300
INTERNATIONAL: 703-527-3887

Issue Date: 03/11/2005

Product Name: Sikaflex® Mortar Fix
Chemical Family: Polyurethane
Chemical Formula: RMF-3138
MSDS Number: 3497
Product Code: 043T547

2. Composition/Information On Ingredients

Ingredient Name	CAS Number		Percent Of Total Weight
POLYISOCYANATE PREPOLYMER	Trade Secret		
XYLENE (MIXED ISOMERS)	1330-20-7	<	4

3. Hazards Identification

Eye Hazards

Causes eye irritation.

Skin Hazards

May cause skin irritation. Prolonged and/or repeated skin contact may cause an allergic reaction/sensitization.

Ingestion Hazards

May be harmful if swallowed.

Inhalation Hazards

May cause nose, throat, and lung irritation. May cause an allergic respiratory reaction / sensitization after prolonged or repeated contact. Reports have associated repeated and prolonged exposure to some of the chemicals in this product with permanent brain, liver, kidney, and Central Nervous System damage. Headaches

Sikaflex® Mortar Fix

3. Hazards Identification - Continued

Inhalation Hazards - Continued

and dizziness may result.

4. First Aid Measures

Eye

In case of contact, hold eyelids apart and immediately flush eyes with plenty of tepid water for at least 15 minutes. Get medical attention immediately if irritation develops and persists.

Skin

In case of contact, immediately flush skin with soap and plenty of tepid water for at least 15 minutes. Get medical attention immediately if irritation (redness, rash, blistering) develops and persists.

Ingestion

If victim is fully conscious do not induce vomiting, give one or two cups of water or milk to drink. Call a physician or a poison control center immediately.

Inhalation

Remove to fresh air. If not breathing, give artificial respiration, seek medical attention.

5. Fire Fighting Measures

Flash Point: >200 °F

Autoignition Point: N/AV °F

Fire And Explosion Hazards

During a fire, irritating and/or toxic gases and aerosols from the decomposition/combustion products may be present.

Extinguishing Media

In case of fire, use water spray (fog) foam, dry chemical, or CO₂.

Fire Fighting Instructions

In the event of a fire, firefighters should wear full protective clothing and NIOSH-approved self-contained breathing apparatus with a full facepiece operated in the pressure demand or other positive pressure mode.

6. Accidental Release Measures

Avoid release to the environment. Use appropriate Personal Protective Equipment (PPE). Contain spill and collect with absorbent material and transfer into suitable containers. Do not flush to sewer or allow to enter waterways. Ventilate enclosed area.

7. Handling And Storage

Handling And Storage Precautions

Keep out of reach of children. Store in a cool, dry, well ventilated area. Keep containers tightly closed.

Handling Precautions

Do not smoke. Use only in well ventilated areas. Condition to 65-85F before using. Use only with ventilation sufficient to reduce potential exposures (air borne levels of dust, fumes, vapors, etc.) to below recommended exposure limits.

Storage Precautions

Do not store near excessive heat. Store in tightly closed containers and protect from moisture and foreign material. Ideal storage temperature is less than 75F. If maximum storage temperature is exceeded, material may prematurely polymerize without hazard.

Work/Hygienic Practices

Wash thoroughly with soap and water after handling.

Sikaflex® Mortar Fix

8. Exposure Controls/Personal Protection

Engineering Controls

Use of a system of local and/or general exhaust is recommended to keep employee below applicable exposure limits. Refer to the current edition of "Industrial Ventilation: A Manual of Recommended Practice" published by the American Conference of Governmental Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems.

Eye/Face Protection

Safety glasses with side shields or goggles.

Skin Protection

Chemical-resistant gloves. Lab coat or other work clothing to prevent skin exposure (Long sleeve shirt and long pants). Launder before reuse.

Respiratory Protection

A respirator protection program that meets 29 CFR 1910.134 requirement must be followed whenever workplace conditions warrant a respirator's use. In areas where the Permissible Exposure Limits are exceeded, use a properly fitted NIOSH-approved respirator.

Other/General Protection

Wash thoroughly after handling.

Ingredient(s) - Exposure Limits

XYLENE (MIXED ISOMERS)
ACGIH TLV-STEL 150 ppm
ACGIH TLV-TWA 100 ppm
OSHA PEL-TWA 100 ppm

9. Physical And Chemical Properties

Appearance

Textured mastic (solid) in various colors

Odor

Aromatic odor

Chemical Type: Mixture

Physical State: Solid

Melting Point: N/AV °F

Boiling Point: N/AV °F

Specific Gravity: 1.40 grams/cm³

Percent VOCs: < 4%

Packing Density: 11.68 pounds/gallon

Vapor Pressure: N/AV

Vapor Density: > Air

Solubility: N/AV

Evaporation Rate: Slower than ether

VOC Content: 42 grams / liter

10. Stability And Reactivity

Stability: Stable

Hazardous Polymerization: Will not occur

Conditions To Avoid (Stability)

Open flame

Incompatible Materials

Water, Alcohol, Amines

Sikaflex® Mortar Fix

10. Stability And Reactivity - Continued

Hazardous Decomposition Products

Carbon Dioxide, Carbon Monoxide, and Oxides of Nitrogen, Smoke, Fumes

Conditions To Avoid (Polymerization)

None known

11. Toxicological Information

Conditions Aggravated By Exposure

Eye disease, skin disorders and allergies, chronic respiratory conditions.

12. Ecological Information

No Data Available...

13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations. Waste generators must determine whether a discarded material is classified as a hazardous waste. USEPA guidelines for the classification determination are listed in 40 CFR Parts 261.3. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

14. Transport Information

Proper Shipping Name

Not regulated by the USDOT.

15. Regulatory Information

U.S. Regulatory Information

All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

SARA Hazard Classes

Acute Health Hazard
Chronic Health Hazard

SARA Title III - Section 313 Supplier Notification

This product contains the following toxic chemicals that are subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act (EPCRA) of 1986 and of 40 CFR 372.

XYLENE (MIXED ISOMERS) (1330-20-7) <4 %

This information must be included on all MSDSs that are copied and distributed for this material.

Ingredient(s) - U.S. Regulatory Information

XYLENE (MIXED ISOMERS)
SARA Title III - Section 313 Form "R"/TRI Reportable Chemical

Ingredient(s) - State Regulations

XYLENE (MIXED ISOMERS)
New Jersey - Workplace Hazard
New Jersey - Environmental Hazard
New Jersey - Special Hazard
Pennsylvania - Workplace Hazard
Pennsylvania - Environmental Hazard
Massachusetts - Hazardous Substance
New York City - Hazardous Substance

Sikaflex® Mortar Fix

16. Other Information

HMIS Rating

Health: *2

Fire: 1

Reactivity: 0

PPE: C

Revision/Preparer Information

MSDS Preparer: EHS Department

MSDS Preparer Phone Number: 201 933 8800

Disclaimer

The data in this Material Safety Data Sheet relates only to the specific material herein and does not relate to use in combination with any other material or in any process. The information set forth herein is based on technical data that Sika believes to be reliable as of the date hereof. Since conditions of use are outside our control, we make no warranties, express or implied and assume no liability in connection with any use of this information. Nothing herein is to be taken as a license to operate under or a recommendation to infringe any patents.

Sika Corporation