

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Christy's® ROOT-BAN™ Drain Pipe Adhesive **SYNONYMS:**

PRODUCT USE: Synthetic Rubber Based Adhesive

SUPPLIER and MANUFACTURER: Christy Enterprises, Inc.
655 East Ball Road, Anaheim, CA 92805-5910
Tel. 1-714-507-3300 (North America)
Tel. 1-714-507-3300 (International)

EMERGENCY: Transportation/Medical issues: Tel. 800.535.5053 INFOTRAC

SECTION 2 - HAZARDS IDENTIFICATION

GHS CLASSIFICATION:

Health	Environmental	Physical
Acute Toxicity: Category 2	Acute Toxicity: None Known	Flammable Liquid/Aerosol/Gas: Category 2
Skin Corrosion/Irritation: Category 2	Chronic Toxicity: None Known	
Skin Sensitization: YES		
Eye: Category 2A		

Signal Word: **DANGER**



WHMIS CLASSIFICATION: CONTROLLED PRODUCT
CLASS B, DIVISION 2 CLASS D, DIVISION 2B

Hazard Statements	Precautionary Statements (See Section 15 for all advisory and required precautions)
H225 Highly flammable liquid and vapour	P210 Keep away from heat, hot surfaces, open flames and other ignition sources. No smoking
H305 May be harmful if swallowed and enters airways	P261 Avoid breathing dust/ fume/gas/mist/vapours/spray
H315 Causes skin irritation	P264 Wash hands thoroughly after handling.
H319 Causes serious eye irritation	P271 Use only outdoors or in a well-ventilated area.
H336 May cause drowsiness or dizziness	P280 Wear protective gloves/ protective/ clothing/ eye protection/ face protection
	P301+P310 IF SWALLOWED immediately call a POISON CONTROL CENTER or doctor/physician
	P304 + P340 IF INHALED: remove person to fresh air and keep comfortable for breathing.
	P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P312 Call a POISON CENTER/ doctor if you feel unwell.
	P331 Do NOT induce vomiting
	P332+P337+P313 If skin or eye irritation occurs: Get medical advice/ attention
	P362+P364 Take off contaminated clothes and wash it before reuse.
	P405 Store locked up
	P403+P233+P235 Store in a well-ventilated place. Keep container tightly closed. Keep cool
	P501 Dispose of contents/container in accordance with local regulations.

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

	CAS#	EINECS #	REACH	CONCENTRATION
			Pre-registration Number	% by Weight
Rosin Based Resin	8050-26-8			13-30
Acetone	67-64-1	200-662-2	05-2116297713-35-0000	10-40
Heptane*	142-82-5			20-60
Globalprene SBS	9003-55-8			5-30

All of the constituents of this adhesive product are listed on the TSCA inventory of chemical substances maintained by the US EPA, or are exempt from that listing.
*This chemical is subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 (40CFR372).

SECTION 4 - FIRST AID MEASURES

Contact with eyes: Flush eyes immediately with plenty of water for 15 minutes and seek medical advice immediately.

Skin contact: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water. If irritation develops, seek medical advice.

Inhalation: Remove to fresh air. If breathing is stopped, give artificial respiration. If breathing is difficult, give oxygen. Seek medical advice.

Ingestion: Rinse mouth with water. Give 1 or 2 glasses of water or milk to dilute. Do not induce vomiting. Seek medical advice immediately.

SECTION 5 - FIREFIGHTING MEASURES

Suitable Extinguishing Media: Dry chemical powder, carbon dioxide gas, foam, Halon, water fog. **HMIS** **NFPA** **0-Minimal**

Unsuitable Extinguishing Media: Water spray or stream. **Health** **2** **2** **1-Slight**

Exposure Hazards: Carbon monoxide, carbon dioxide, hydrogen chloride and smoke **Flammability** **3** **3** **2-Moderate**

Combustion Products: Carbon monoxide, carbon dioxide, hydrogen chloride and smoke **Reactivity** **1** **1** **3-Serious**

Protection for Firefighters: Self-contained breathing apparatus or full-face positive pressure airline masks. **4-Severe**

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal precautions: Keep away from heat, sparks and open flame.
Provide sufficient ventilation, use explosion-proof exhaust ventilation equipment or wear suitable respiratory protective equipment.
Prevent contact with skin or eyes (see section 8).

Environmental Precautions: Prevent product or liquids contaminated with product from entering sewers, drains, soil or open water course.

Methods for Cleaning up: Clean up with sand or other inert absorbent material. Transfer to a closable metal container

Materials not to be used for clean up: Aluminum or plastic containers

SECTION 7 - HANDLING AND STORAGE

Handling: Avoid breathing of vapor, avoid contact with eyes, skin and clothing.
Keep away from ignition sources, use only electrically grounded handling equipment and ensure adequate ventilation/fume exhaust hoods.
Do not eat; drink or smoke while handling.

Storage: Store in ventilated room or shade below 27°C (80°F) and away from direct sunlight.
Keep away from ignition sources and incompatible materials: caustics, ammonia, inorganic acids, chlorinated compounds, strong oxidizers and isocyanates.
Follow all precautionary information on container label, product bulletins and solvent cementing literature.

SECTION 8 - PRECAUTIONS TO CONTROL EXPOSURE / PERSONAL PROTECTION

EXPOSURE LIMITS:	Component	ACGIH TLV	ACGIH STEL	OSHA PEL	OSHA STEL:
	Acetone	500 ppm	750 ppm	750 ppm	1000 ppm
	Heptane	200 ppm		300 ppm	500 ppm

Engineering Controls: If ventilated cabinet, enclosure or fume hood is necessary, average airflow should be at least 100 FPM (50.8 cm/sec).

Monitoring: Maintain breathing zone airborne concentrations below exposure limits.

Personal Protective Equipment (PPE):

Eye Protection: Avoid contact with eyes, wear splash proof chemical goggles, face shield, safety glasses (spectacles) with brow guards and side shields, etc. as may be appropriate for the exposure.

Skin Protection: Prevent contact with the skin as much as possible. Polyethylene or PVA coated rubber gloves should be used for frequent immersion.
Use of latex/nitrile surgical gloves or solvent-resistant barrier cream should provide adequate protection when normal adhesive application practices and procedures are used for making structural bonds.

Respiratory Protection: Prevent inhalation of the solvents. Use in a well-ventilated room. Open doors and/or windows to ensure airflow and air changes. Use local exhaust ventilation to remove airborne contaminants from employee breathing zone and to keep contaminants below levels listed above.
With normal use, the Exposure Limit Value will not usually be reached. When limits approached, use respiratory protection equipment.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Green, regular syrupy liquid
Odor: Ethereal
P.H. Not Applicable
Melting/Freezing Point: -95°C (-139°F) Based on first freezing component: Acetone
Boiling Point: 57°C (133°F) Based on first boiling component: Acetone
Flash Point: -4°C (24.8°F) T.C.C. based on heptane
Specific Gravity @23°C ± 2° (73°F ± 3.6°) Typical 0.833 ± 0.01
Solubility: Solvent portion completely soluble in water. Resin portion separates out.
Partition Coefficient n-octanol/water: Not Available
Auto-ignition Temperature: 203°C (399°F): T.C.C. Based on heptane
Decomposition Temperature: Not Applicable
VOC Content : When applied as directed, per SCAQMD Rule 1168, Test Method 316A, VOC content is: ≤250 g/l.

Odor Threshold: N/D
Boiling Range: 57°C (133°F) to 98°C (208°F)
Evaporation Rate: > 1.0 (BUAC = 1)
Flammability: Category I
Flammability Limits: LEL: 2%
 UEL: 11.8%
Vapor Pressure: 181 mm Hg @ 20°C (68°F): Acetone
Vapor Density: <2 (Air = 1)
Other Data: Viscosity: Regular bodied

SECTION 10 - STABILITY AND REACTIVITY

Stability: Stable
Hazardous decomposition products: None in normal use. When forced to burn, this product gives off carbon monoxide (CO), carbon dioxide (CO₂), hydrogen chloride (HCl) and smoke.
Conditions to avoid: Keep away from heat, sparks, open flame and other ignition sources.
Incompatible Materials: Caustics, ammonia, inorganic acids, chlorinated compounds, strong oxidizers and isocyanates.

SECTION 11 - TOXICOLOGICAL INFORMATION

Likely Routes of Exposure: Inhalation, Eye and Skin Contact

Acute symptoms and effects:

Inhalation: Severe overexposure may result in nausea, dizziness, headache. Can cause drowsiness, irritation of eyes and nasal passages.
Eye Contact: Vapors slightly uncomfortable. Overexposure may result in severe eye injury with corneal or conjunctival inflammation on contact with the liquid.
Skin Contact: Liquid contact may remove natural skin oils resulting in skin irritation. Dermatitis may occur with prolonged contact.
Ingestion: May cause nausea, vomiting, diarrhea and mental sluggishness.

Chronic (long-term) effects:

None known to humans

Toxicity:

LD₅₀

LC₅₀

Acetone Oral: 9.75 g/kg (rat), Dermal 20 g/kg (rabbit) Inhalation LCLO 4 hrs. 16,000 PPM (rat)

Heptane Oral: 5170 mg/kg (rat) Inhalation LCLO: 4 hrs. 7.63 mg/l (rat)

Reproductive Effects	Teratogenicity	Mutagenicity	Embryotoxicity	Sensitization to Product	Synergistic Products
Not Applicable	Not Applicable	Poss.	Not Applicable	Not Applicable	Not Available

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity: No known significant effects or critical hazards
Mobility: In normal use, emission of volatile organic compounds (VOC's) to the air takes place. Typically at a rate of ≤ 250 Grams/Liter.
 Minimal other adverse effects include possible ground water contamination from release to soil, sewers, drains or water course.
Degradability: Biodegradable
Bioaccumulation: Minimal to none.

SECTION 13 - WASTE DISPOSAL CONSIDERATIONS

Follow local and national regulations. Consult disposal expert. Can be disposed of by controlled incineration. May be allowed to dry and disposed of as trash. Excessive quantities should not be permitted to enter drains, sewers or water courses. Empty containers should be air dried before disposing.

SECTION 14 - TRANSPORT INFORMATION**DOT, IATA, ADR, IMO/IMDG SHIPPING INFORMATION**

Proper Shipping Name: Adhesives DOT/IMDG EXCEPTION: Case quantities of cement in containers of less than one liter may be shipped as LIMITED QUANTITY when properly labeled and marked.
Hazard Class: 3
Secondary Risk: None ICAO/IATA May be shipped by air as CONSUMER COMMODITY, ID 8000 when properly packaged, labeled and marked.
Identification Number: UN 1133
Packing Group: II
Label Required: Flammable Liquid
Marine Pollutant: NO

TDG INFORMATION
TDG CLASS: FLAMMABLE LIQUID 3
SHIPPING NAME: ADHESIVES (ACETONE)
UN NUMBER: 1133, PG II

SECTION 15 - REGULATORY INFORMATION

Precautionary Label Information: Highly Flammable, Irritant
Symbols: F, Xi
Risk Phrases: R-11 Highly Flammable
 R-20 Harmful by inhalation
 R-21 Harmful in contact with skin.
 R-22 Harmful if swallowed.

Safety Phrases: S-2 Keep out of reach of children.
 S-7 Keep container tightly closed when not in use.
 S-9 Keep container in a well-ventilated place.
 S-15/16 Keep away from heat and sources of ignition. No smoking.
 S-23 Do not breathe vapor.

Ingredient Listings: USA TSCA, Europe EINECS, Canada DSL, Australia AICS, Korea ECL/TCCL, Japan MITI (ENCS)
 R-36/37/38 Irritating to eyes, respiratory system and skin.
 R-41 Risk of serious damage to the eyes.
 R-43 May cause sensitization by skin contact.

S-24/25 Avoid contact with skin and eyes.
 S-29 Do not empty into drains.
 S-37 Wear suitable gloves.
 S-45 If seeking medical advice show physician label or SDS.
 S-51 Use only in well ventilated areas.
 S-46 If swallowed, seek medical advice immediately and show this container or label

SECTION 16 - OTHER INFORMATION

Specification Information:
Department issuing data sheet: Environmental Health & Safety
e-mail address: <EHSinfo@tchristy.com>
Training necessary: Yes, training in practices and procedures contained in product literature.
Reissue date / reason for reissue: NOV 2014/ Original
Intended Use of Product: Contact adhesive for polyethylene, HDPE and Styrene drain pipe and fittings.

All ingredients are compliant with the requirements of the European Directive on RoHS (Restriction of Hazardous Substances).

This product is intended for use by skilled individuals at their own risk. The information contained herein is based on data considered accurate based on current state of knowledge and experience. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof.