

Material Safety Data Sheet

Certified Products, Inc
1075 County Road 427 N.
Longwood, FL 32750
407-830-7775

1. Chemical Product and Company Identification

Product Name: **SUPERSLICK SLICK STUFF**

General Use:

Product Code:

2. Composition/Information on Ingredients

	<u>Wt. %</u>	<u>Case #</u>
Proprietary Blend of Base Oils,		513-77-9, 5989-27-5
Inhibitors, Solvents and Additives.	65%	64741-88-4, 64742-52-5
Hydrocarbon Propellant-Propane/ Isobutane	35%	64742-53-6
		78-28-5, 74-98-6

Comments: Ingredients not identified are proprietary or non-hazardous. Values are not specifications.

3. Hazards Identifications

Warning: **Extremely Flammable.** Causes Substantial but temporary eye injury. Contents Under Pressure. Keep away from heat and open flames. Do not expose Temperatures above 130 degrees F. May cause respiratory tract irritation. May be harmful if swallowed. Avoid breathing vapors and spray mists of this product. DO NOT puncture or incinerate container.

Potential Health Effects

Eyes: Causes substantial but temporary eye irritation, redness, tearing and blurred Vision.

Skin: Can cause skin irritation

Ingestion: Can cause stomach irritation, resulting in nausea, cramps and vomiting.

Inhalation: Excessive inhalation can cause nasal and respiratory irritation. May produce dizziness or headaches.

4. First Aid Measures

Eyes: Remove contact lenses and immediately flush eyes with large amounts of cool water for at least 5-10 min. If irritation persists, get medical attention

Skin: Remove contaminated clothing and wash affected areas with soap and water. If irritation persists, get medical attention. Wash clothing separately before reuse.

Ingestion: If swallowed call a physician or poison control center and seek medical attention immediately. DO NOT induce vomiting

Never give anything by mouth to an unconscious person.

Inhalation: Remove affected person to fresh air. Seek medical attention if needed

5. Fire Fighting Measures

Flammable Class:

This aerosol is classified as **EXTREMELY FLAMMABLE** by the flame extension test method described in 16 CFR 1500.45.

Extinguishing Media:

Foam, carbon dioxide or dry chemical.

Hazardous Combustion Products:

Under fire conditions this product will support combustion and may decompose to give off toxic gases such as carbon monoxide, carbon dioxide and sulfur oxides. Contents react violently with iodine pentafluoride in Tetrafluoroethylene. Can react with strong oxidizing agents generating heat.

Explosion Hazards:

Contents under pressure. Exposure to temperatures above 130 degrees F/54.4 C can cause bursting.

Fire Fighting Procedures:

Treat as an oil fire. Use a full-faced self-contained breathing apparatus along with full protective gear. Keep nearby containers and equipment cool with a water stream.

6. Accidental Release Measures

Small Spill:

Shut off ignition sources. Stop release, if possible with out risk. Dike or contain release, if possible, and if immediate response can prevent further damage or danger. Isolate and control access to the release area. Take actions to reduce vapors. Absorb with appropriate absorbent. Clean spill area of residues and absorbent.

Large Spill:

Shut off ignition sources. Stop release, if possible with out risk. Dike or contain release, if possible, and if immediate response can prevent further damage or danger. Isolate and control access to the release area. Take actions to reduce vapors. Collect product into drums, etc, via drains, pumps, etc. Absorb with appropriate absorbent. Clean spill area of residues and absorbent.

7. Handling and Storage

General Procedures

Do not use near heat, open flame or any ignition source
