MATERIAL SAFETY DATA SHEET

For Lithium Polymer Rechargeable Battery PT603040 750mAh 3.7V of Pow-tech

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT IDENTIFICATION

Powtech Lithium-polymer cell PT603040 750mAh Powtech PT603040 750mAh 3.7V Lithium-polymer Battery (Equivalent Lithium content: 28g/pc, and 2.775Wh

MANUFACTURER

Shenzhen Pow-tech New Power Co., Ltd.

Room 1102, Xinhua insurance Mansions, Mintian Road, Central District, Shenzhen, China

Tel: (+86)755-82721259, Fax: (+86)755-82721250

Email: pub@szpowtech.com.cn, Web site: http://www.szpowtech.com.cn

2. COMPOSITION INFORMATION

%	CAS NUMBER
30-40%	12190-79-3
15-20%	7782-42-5
10-15%	21324-40-3
5-10%	7440-50-8
5-10%	7429-90-5
0.5-2%	24937-79-9
5-10%	7440-02-0
15-20%	7439-89-6
0.5-1%	9002-88-4
	30-40% 15-20% 10-15% 5-10% 5-10% 0.5-2% 5-10% 15-20%

3. HAZARDS IDENTIFICATION

Emergency Overview

May explode in a fire, which could release hydrogen fluoride gas and smoke.

Use extinguishing media suitable for materials burning in fire



File No.PT603040-750--2015

2015-3-12

PRIMARY ROUTES OF ENTRY

Skin contact, Skin absorption, Eye contact, Inhalation, and Ingestion: NO

Skin contact	No
Skin absorption	No
Eye contact	No
Inhalation	No
Ingestion	No

SIGNS AND SYMPTOMS OF EXPOSURE

Skin contact	No effect under routine handling and use
Skin absorption	No effect under routine handling and use
Eye contact	No effect under routine handling and use
Inhalation .	No effect under routine handling and use
Ingestion	No effect under routine handling and use
Reported as Carcinogen	Not applicable

4. FIRE FIGHTING MEASURES

GENERAL HAZARD

Cell is not flammable but internal organic material will burn if the cell is incinerated.

Combustion products include, but are not limited to hydrogen fluoride, carbon monoxide and carbon dioxide.

EXTINGUISHING MEDIA

Use extinguishing media suitable for the materials that are burning.

SPECIAL FIREFIGHTING INSTRUCTIONS

If possible, remove cell(s) from fire fighting area. If heated above 130°C, cell(s) may Swell/explode/vent.

FIREFIGHTING EQUIPMENT

Use NIOSH/MSHA approved full-face self-contained breathing apparatus (SCBA) with full protective gear.

5. ACCIDENTAL RELEASE MEASURES

ON LAND

Place material into suitable containers and call local fire/police department.

IN WATER

If possible, remove from water and call local fire/police department.



File No.PT603040-750--2015

2015-3-12

6. HANDLING AND STORAGE

HANDLING

No special protective clothing required for handling individual cells.

STORAGE

Store in a cool, dry place

7. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS

Keep away from heat and open flame. Store in a cool dry place

PERSONAL PROTECTION

Respirator:

Not required during normal operations, SCBA required in the event of a fire

Eye/face protection:

Not required beyond safety practices of employer.

Gloves:

Not required for handling of cells.

Foot protection:

Steel toed shoes recommended for large container handling.

8. PHYSICAL AND CHEMICAL PROPERTIES

State	Solid
Odor	N/A
PH	N/A
Vapor density	N/A
Boiling point	N/A
Solubility in water	Insoluble
Specific gravity	N/A
Density	N/A

9. STABILITY AND REACTIVITY

REACTIVITY

None during normal operating or handling conditions.

INCOMPATIBILITIES

None (during normal operation). Avoid exposure to heat, open flame, and corrosives

HAZARDOUS DECOMPOSITION PRODUCTS

None (during normal operating conditions). If cells are opened, hydrogen fluoride and carbon monoxide may be released.

CONDITIONS TO AVOID



File No.PT603040-750--2015

2015-3-12

Avoid exposure to heat and open flame. Do not puncture, crush or incinerate.

10. TOXICOLOGICAL INFORMATION

This product does not elicit toxicological properties during routine handling and use.

Sensitization	No
Acute toxicity	No
Teratogenicity	No
Reproductive toxicity	No

This product does not contain any kinds of the following substances and halogen-type flame retardants including Chlorine and Bromide type harmful flame retardants which are listed in appendix of TCO documents and relevant international ECO requirements.

A Transaction of the Control of the	
Polybromated Biphenyls	(PBB)
Polybromated Biphenyl Ethers	(PBBE)
Polybromater Biphenyl Oxides	(PBBO)
Polybromated Diphenylethers	(PBDE)
Polychlorinated Biphenyl	(PCB)
Polychlorinated Diphenylethers	(PCDE)
Tetrabromphisphenol A	(TBBPA)
Asbestos, Antimonytrioxide, Dioxine	1

None of the following substances will be exposed, leaked, or emitted during transportation, storage or any operation and any temperature condition:

	Chlorinated Fluorohydrocarbon (FCKW)
	Acrylonitride
	Styrol
	Phenol
	Benzol
	Mercury of great less than 0.0001 wt% for alkaline battery
Mercury of great less than 0.0005 wt% for other battery	
Lithium content of great less than 0.5g/cell, 1.5g/battery	
	Cadmium, lead, and other harmful heavy metal

This product does not contain mercury, cadmium and lithium-metal.

Mercury content	N/A
Lithium-metal	N/A
Cadmium content	N/A



File No.PT603040-750--2015

2015-3-12

CAUTION

If the cells are opened through misuse or damage, discard immediately. Internal components of cell are irritants and sensitizers

11. ECOLOGICAL INFORMATION

Some materials within the cell are bio-accumulative. Under normal conditions, these materials are contained and pose no risk to persons or the surrounding environment.

12. DISPOSAL CONSIDERATIONS

CALIFORNIA REGULATED DEBRIS

RCRA Waste Code: Non-regulated

Dispose of according to all federal, state, and local regulations.

13. REGULATORY INFORMATION

OSHA hazard communication standard (29 CFR 1910.1200)

□ Hazardous

Non-hazardous

14. TRANSPORT INFORMATION

Lithium ion batteries containing no more than 20Wh/cell and 100 Wh /battery pack can be treated as "Non-dangerous goods" under the United Nations Recommendations on the Transport of Dangerous Goods, provided that packaging is strong and prevent the products from short-circuit.

With regard to air transport, the following regulations are cited and considered:

- I) The International Civil Aviation Organization (ICAO) Technical Instructions (2015-2016 Edition)
- II) 2015 International Air Transport Association (IATA) Dangerous Goods Regulations ((56th ed.) SECTION I & II of PI965/PI966/PI967),
- III) The International Maritime Dangerous Goods (IMDG) Code: special provision 188,
- IV) The US Hazardous Materials Regulation (HMR) pursuant to a final rule issued by RSPA (Part 49 CFR Sections 100-185),
- V) The Office of Hazardous Materials Safety within the US Department of Transportation's (DOT) Research and Special Programs Administration (RSPA), and
- VI) The UN classification number: Class 9 3480.

Our products are properly classified, described, packaged, marked, and labeled, and are in proper condition for transportation according to all the applicable international and national governmental regulations, not limited to the above mentioned. We further certify that the enclosed products have been tested and fulfilled the requirements and conditions in accordance with UN Recommendations (T1~T8) on the Transport of Dangerous Goods



File No.PT603040-750--2015

2015-3-12

Model Regulations and the Manual of Testes and Criteria that can be treated as "Non-Dangerous Goods"

Manual of Test and Criteria(38.3 Lithium battery)			
	Test Item	Test Results	Remark
T1	Altitude Simulation	Pass	
T2	Thermal Test	Pass	
Т3	Vibration	Pass	
T4	Shock	Pass	
T5	External Short Circuit	Pass	
Т6	Impact	Pass	
T7	Overcharge	Pass	For Pack Only
T8	Forced Discharge	Pass	For Cell Only

15. EMERGENCY AND FIRST AID MEASURES

INHALATION, EYE CONTACT, and SKIN CONTACT: Not a health hazard.

INGESTION

If swallowed, obtain medical attention immediately.

CAUTION

If exposure to internal materials within cell due to damaged outer casing, the following actions are recommended.

INHALATION

Leave area immediately and seek medical attention.

EYE CONTACT

Rinse eyes with water for 15 minutes and seek medical attention.

SKIN CONTACT

Wash area thoroughly with soap and water and seek medical attention.

INGESTION

Drink milk/water and induce vomiting; seek medical attention

16. OTHER INFORMATION

For further information, please contact Shenzhen powtech New Power Co., Ltd. sales representative.

Note:

This Sheet is provided as technical information only. The information and recommendations set forth are made in good faith and believed to be accurate as of the date of preparation. Shenzhen powtech New Power Co. Ltd. makes no warranty, expressed or implied, with respect to this information and disclaims all liabilities from reliance on it.