

Product

9396132 BLUE PAINT MOD 1 Crisp Waters

Print Date

10/27/2015

Page 1 (9)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name

: 9396132 BLUE PAINT MOD 1

Code

: Crisp Waters

Product Use Description

: Fragrance Compound

Company

: Scentco, LLC

93 Genesis Pkwy

Thomasville, GA 31792

Telephone

229-227-0737

Emergency telephone number

: 877-723-6826

SECTION 2 HAZARDS IDENTIFICATION

GHS-Classification

Flammable liquids, Category 4 Skin irritation, Category 2 Eye irritation, Category 2A Skin sensitisation, Category I

GHS-Labelling

Symbol(s)

Signal word

: Warning

Hazard statements

: H227: Combustible liquid. H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

Version

: 2

Revision Date



Product

9396132 BLUE PAINT MOD 1 Crisp Waters

Print Date

10/27/2015

Page 2 (9)

H319: Causes serious eye irritation.

Precautionary statements

P302 + P352: IF ON SKIN: Wash with plenty of soap and water.
P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P264: Wash skin thoroughly after handling.

P280: Wear protective gloves/ eye protection/ face protection.

Carcinogenicity:

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature

: Fragrance for consumer product

Fragrance Compound: A multi component mixture of fragrance ingredients. The specific chemical identities of the ingredients not listed herein are considered by Scentco to be Trade Secrets and are withheld in accordance with the provisions of 1910.1200 of Title29 of the U.S. Code of Federal Regulations.

SECTION 4. FIRST AID MEASURES

First aid procedures

Inhalation

: Remove from exposure site to fresh air and keep at rest. Obtain

Version

: 2

Revision Date



Product

9396132 BLUE PAINT MOD 1 Crisp Waters

Print Date

10/27/2015

Page 3 (9)

medical advice.

Skin contact

: Remove contaminated clothes. Wash thoroughly with water (and

soap). Contact physician if symptoms persist.

Eye contact

: Flush immediately with water for at least 15 minutes. Contact

physician if symptoms persist.

Ingestion

: Rinse mouth with water and obtain medical advice.

SECTION 5. FIREFIGHTING MEASURES

Flammable properties

Flash point

: 199.40 °F (93.00 °C)

Fire fighting

Suitable extinguishing media

: Use water spray, dry chemical, carbon dioxide or appropriate foam.

Protective equipment and precautions for firefighters

Special protective equipment for

firefighters

: Wear NIOSH approved self-contained breathing apparatus and full

protective clothing when fighting fires involving chemicals. Use

water spray to cool containers exposed to fire.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions

: Avoid inhalation and contact with skin and eyes. A self-contained

breathing apparatus is recommended in case of a major spill.

Environmental precautions

: Keep away from drains, surface- and groundwater and soil.

Version

: 2

Revision Date



Product

9396132 BLUE PAINT MOD 1 Crisp Waters

Print Date

10/27/2015

Page 4 (9)

Methods for containment / Methods for cleaning up

: Clean up spillage promptly. Remove ignition sources. Provide adequate ventilation. Avoid excessive inhalation of vapours. Gross spillages should be contained by use of sand or inert powder and disposed of according to the local regulations.

SECTION 7. HANDLING AND STORAGE

Handling

: Avoid excessive inhalation of concentrated vapors. Follow good manufacturing practices for housekeeping and personal hygiene. Wash any exposed skin immediately after any chemical contact, before breaks and meals, and at the end of each work period. Contaminated clothing and shoes should be thoroughly cleaned before re-use.

If appropriate, procedures used during the handling of this material should also be used when cleaning equipment or removing residual chemicals from tanks or other containers, especially when steam or hot water is used, as this may increase vapor concentrations in the workplace air. Where chemicals are openly handled, access should be restricted to properly trained employees.

Keep all heated processes at the lowest necessary temperature in order to minimize emissions of volatile chemicals into the air.

Advice on protection against fire and explosion

Keep away from ignition sources and naked flame.

Requirements for storage areas and containers

Store in a cool, dry, ventilated area away from heat sources.

Keep containers upright and tightly closed when not in use.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

C		r	
Components	Listed by	Value type	17
	2.5.24 0)	Value type	Exposure
		· -	1 11 1.2 5
			limit(s)
			(0)

Version

: 2

Revision Date



Product

9396132 BLUE PAINT MOD 1 Crisp Waters

Print Date

10/27/2015

Page 5 (9)

2,4-Pentanediol, 2- methyl-	USA. ACGIH Threshold Limit Values (TLV)	Ceiling limit	25 ppm
2,4-Pentanediol, 2- methyl-	USA. NIOSH Recommended Exposure Limits	Ceiling value not be exceeded at any time.	25 ppm 125 mg/m3
2,4-Pentanediol, 2- methyI-	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000	Ceiling limit	25 ppm 125 mg/m3

Engineering measures

Engineering measures

: Where feasible, isolate mixing rooms and other areas where this material is used or openly handled. Maintain these areas under negative air pressure relative to the rest of the plant.

Where feasible, use closed systems to transfer and process this

material

Personal protective equipment

Eye protection

: Use tight-fitting goggles, face shield or safety glasses with side shields if eye contact might occur.

Hand protection

: Avoid skin contact. Use chemically resistant gloves.

Respiratory protection

: Use local exhaust ventilation around open tanks and other open sources of potential exposures in order to avoid excessive inhalation, including places where this material is openly weighed or measured. In addition, use general dilution ventilation of the work area to eliminate or reduce possible worker exposures.

No respiratory protection is required during normal operations in a workplace where engineering controls such as adequate ventilation, etc. are sufficient.

If engineering controls and safe work practices are not sufficient, an approved, properly fitted respirator with organic vapor cartridges or canisters and particulate filters should be used:

a) while engineering controls and appropriate safe work practices and/or procedures are being implemented; or

Version

Revision Date

: 2



Product

9396132 BLUE PAINT MOD 1 Crisp Waters

Print Date

10/27/2015

Page 6 (9)

b)during short term maintenance procedures when engineering controls are not in normal operation or are not sufficient; or c)if normal operational workplace vapor concentration in the air is increased due to heat:

d)during emergencies; or

e)if engineering controls and operational practices are not sufficient to reduce airborne concentrations below an established occupational exposure limit.

Hygiene measures

: To the extent deemed appropriate, implement pre-placement and regularly scheduled ascertainment of symptoms and spirometry testing of lung function for workers who are regularly exposed to this material.

To the extent deemed appropriate, use an experienced air sampling expert to identify and measure volatile chemicals that could be present in the workplace air to determine potential exposures and to ensure the continuing effectiveness of engineering controls and operational practices to minimize exposure.

Protective measures

: In December 2003, the National Institute for Occupational Safety and Health ("NIOSH") published an Alert on preventing lung disease in workers who use or make flavorings [NIOSH Publication Number 2004-110].

In August 2004, the United States Flavor and Extract Manufacturers Association (FEMA) issued a report entitled "Respiratory Safety in the Flavor Manufacturing Workplace".

Both of these reports provide recommendations for reducing employee exposure and for medical surveillance in the workplace. The recommendations in these reports are generally applicable to the use of any chemical in the workplace and you are strongly urged to review both of these reports.

The report published by FEMA also contains a list of "high priority" chemicals. If any of these chemicals are present in this product at a concentration >= 1.0% due to an intentional addition by Scentco, the chemical(s) will be identified in this safety data sheet.

Version

Revision Date

: 2



Product

9396132 BLUE PAINT MOD 1 Crisp Waters

Print Date

10/27/2015

Page 7 (9)

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state

:-liquid-

Colour

: colorless

Odour

: conforms to standard

Safety data

Flash point

: 199.40 °F (93.00 °C)

Vapour pressure

: .12 hPa (0.12 hPa) Note: Calculated

Relative density (20 °C)

: 0.9270 - 0.9370

SECTION 10. STABILITY AND REACTIVITY

Conditions to avoid

: Remarks: Direct sources of heat.

Chemical stability

: Remarks: Presents no significant reactivity hazard, by itself or in

contact with water. Avoid contact with strong acids, alkali or

oxidizing agents.

Hazardous decomposition products

: Note: Carbon monoxide and unidentified organic compounds may

be formed during combustion.

SECTION 11. TOXICOLOGICAL INFORMATION

Toxicological information

Version

: 2

Revision Date



Product

9396132 BLUE PAINT MOD 1 Crisp Waters

Print Date

10/27/2015

Page 8 (9)

Further information

: There is no data available for this product. The health hazards are assessed based on the ingredients in this preparation and their concentrations.

SECTION 12. ECOLOGICAL INFORMATION

Ecological information

Additional ecological information

: Avoid contamination of soil, ground and surface water.

SECTION 13. DISPOSAL CONSIDERATIONS

Contaminated packaging

: Place material into sealed containers and dispose of in accordance

with local, state and federal regulations.

SECTION 14. TRANSPORT INFORMATION

DOT

Not dangerous goods

IATA

Not dangerous goods

IMDG

Not dangerous goods

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards

: Fire Hazard

Acute Health Hazard Chronic Health Hazard

Reportable Quantity

.

Version

: 2

Revision Date



Product

9396132 BLUE PAINT MOD 1 Crisp Waters

Print Date

10/27/2015

Page 9 (9)

HMIS Classification

: Health hazard: 2

Chronic Health Hazard: *

Flammability: 2

Physical and chemical hazards: 0

SECTION 16. OTHER INFORMATION

Further information

The information in this MSDS was obtained from current and reliable sources. However the data is provided without any warrant, expressed or implied, regarding its correctness or accuracy. Since the use, handling, storage and disposal of this product are beyond Scentco's control, it is the responsibility of the user both to determine safe conditions for the use of this product and to assume liability of loss, damage, or expense arising out of the product's improper use. No warranty expressed or implied regarding the product described herein shall be created by or inferred from any statement or omission in this MSDS. Various Federal, State or Provincial agencies may have specific regulations concerning the transportation, handling, storage, use, or disposal of this product which may not be reflected in this MSDS. The user should review these regulations to ensure full compliance.

Version

Revision Date

: 2