

**MATERIAL SAFETY DATA SHEED 57580  
KELLOGG'S PROFESSIONAL PRODUCTS, INC.**

**SECTION 1 – CHEMICAL PRODUCT AND COMPANY INFORMATION**

**PRODUCT NAME:** HEAVY DUTY CARB CLEANER 57580    **IDENTIFICATION NUMBER:** 0650-B    **DATE PRINTED:** 05/05/05  
**PRODUCT USE/CLASS:** CARB CLEANER    **PREPARER:** CUSTOMER SERVICE  
**SUPPLIER/DISTRIBUTOR:** KELLOGG'S PROFESSIONAL PRODUCTS, INC.  
**MANUFACTURED FOR:** 325 PEARL STREET  
SANDUSKY, OH 44870  
**EMERGENCY TELEPHONE:** 419-625-6551    M – F 8:30AM – 5:00PM

**SECTION 2 – COMPOSITION/INFORMATION ON INGREDIENTS**

ITEM:	CHEMICAL/ COMMON NAME	CAS NUMBER	WT/WT % (LESS THAN)
01	2 – PROPANONE	67-64-1	55.0%
02	N-HEPTANE	142-82-5	25.0%
03	DIMETHYLBENZENE	1330-20-7	20.0%
04	CARBON DIOXIDE	124-38-9	10.0%
05	ETHYLBENZENE	100-41-4	5.0%

**EXPOSURE LIMITS**

ITEM	ACGIH		OSHA		COMPANY	SKIN
	TLV – TWA	TLV – STEL	PEL – TWA	PEL – CEILING	TLV – TWA	
01	750 PPM	1000 PPM	750 PPM	N.E.	N.E.	NO
02	400 PPM	500 PPM	400 PPM	500 PPM	N.E.	YES
03	100 PPM	150 PPM	100 PPM	N.E.	N.E.	NO
04	5000 PPM	30000PPM	5000 PPM	N.E.	N.E.	YES
05	100 PPM	125 PPM	100 PPM	N.E.	N.E.	YES

(See Section 16 for abbreviation legend.)

**SECTION 3 – HAZARDOUS IDENTIFICATION**

**\*\*\* EMERGENCY OVERVIEW \*\*\***    Vapors irritating to eyes and respiratory tract. Vapors may cause flash fire or explosion.

**EFFECTS OF OVEREXPOSURE**

**EYE CONTACT:**            Liquid, aerosols and vapors of this product are irritating and can cause pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.

**SKIN CONTACT:**           Prolonged or repeated contact can result in defatting / drying of the skin which may result in skin irritation and dermatitis (rash).

**INHALATION:**            Harmful if inhaled. Headaches, dizziness, nausea, decreased blood pressure, changes in heart rate and cyanosis may result from over-exposure to vapor or skin exposure. Prolonged inhalation may be harmful.

**INGESTION:**              Not hazardous in normal industrial use. This material may be harmful or fatal if swallowed. If a "corrosive" product, may cause severe and permanent damage to mouth, throat and stomach.

**CHRONIC HAZARDS:**      Overexposure may cause nervous system damage, lung damage or kidney damage.

**PRIMARY ROUTE (S) OF ENTRY:**    **SKIN CONTACT    SKIN ABSORPTION            INHALATION            INGESTION            EYE CONTACT**

**SECTION 4 – FIRST AID MEASURES**

**FIRST AID - EYE CONTACT:**            Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

**FIRST AID - SKIN CONTACT:**            Immediately flush skin with plenty of water. Remove clothing. Get medical attention immediately. Wash clothing separately before reuse.

**FIRST AID – INHALATION:**            Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

**FIRST AID – INGESTION:**            Get medical attention immediately. If swallowed, do **NOT** induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

MATERIAL SAFETY DATA SHEET 57580  
KELLOGG'S PROFESSIONAL PRODUCTS, INC.

SECTION 5 – FIRE FIGHTING MEASURES

FLASH POINT -156 F  
(SETAFLASH CLOSED CUP)

LOWER EXPLOSIVE LIMIT: 0.8 %  
UPPER EXPLOSIVE LIMIT: 12.8 %

AUTOIGNITION TEMPERATURE: ND EXTINGUISHING MEDIA: CO2 ALCOHOL FOAM DRY CHEMICAL FOAM WATER FOG

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Vapors can travel to a source of ignition and flash back. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty drums should be completely drained, properly bunged and promptly returned to a drum re-conditioner, or properly disposed.

**SPECIAL FIRE FIGHTING PROCEDURES:** Containers can build up pressure if exposed to heat (fire). As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

**IF PRODUCT IS RELEASED / SPILLED:** Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container.

SECTION 7 – HANDLING and STORAGE

**HANDLING:** Wash hands thoroughly after handling product.

**STORAGE:** Keep away from heat, sparks and flame. Keep from freezing. Store in cool dry area away from direct sunlight.

SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

**ENGINEERING CONTROLS:** Local exhaust ventilation may be necessary to control any air contaminants to within their TLV s during the use of this product.

**RESPIRATORY PROTECTION:** A NIOSH / MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

**PROTECTIVE INDUSTRIAL EQUIPMENT / CLOTHING STANDARDS SHOULD BE FOLLOWED.**

**SKIN PROTECTION:** Where contact is likely, wear chemical resistant gloves, a chemical suit, rubber boots, and chemical safety goggles plus a face shield.

**EYE PROTECTION:** Wear safety glasses with side shields (or goggles) and a face shield.

**HYGIENIC PRACTICES:** Wash hands before eating. Remove contaminated clothing and wash before reuse. Use only in a well ventilated area. Follow all MSDS / label precautions even after container is emptied because they may retain product residues. Avoid prolonged or repeated contact with skin. Avoid breathing vapors from heated material. Avoid contact with eyes, skin, and clothing.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE:	132 - 284° F	VAPOR DENSITY:	Is heavier than air
ODOR:	SOLVENT	ODOR THRESHOLD:	ND
APPEARANCE:	SEMI-OPAQUE	EVAPORATION RATE:	Is faster than Butyl Acetate
SOLUBILITY IN H2O:	NEGLIGIBLE		
FREEZE POINT:	32°	SPECIFIC GRAVITY:	0.8300
VAPOR PRESSURE:	50 – 60	PH @ 0.0 %:	NA
PHYSICAL STATE:	LIQUID	VISCOSITY:	NA



**MATERIAL SAFETY DATA SHEET 57580  
KELLOGG'S PROFESSIONAL PRODUCTS, INC.**

**IMMEDIATE HEALTH HAZARD**

**CHRONIC HEALTH HAZARD**

**FIRE HAZARD**

**PRESSURIZED GAS HAZARD**

SARA SECTION 313: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

CHEMICAL NAME	CAS NUMBER	WT/WT% IS LESS THAN
DIMETHYLBENZENE	1330-20-7	20.0%
ETHYLBENZENE	100-41-4	5.0 %

**TOXIC SUBSTANCES CONTROL ACT:** This product contains the following chemical substances subject to the reporting requirements of TSCA 12 (B) if exported from the United States:

CHEMICAL NAME	CAS NUMBER
N-HEPTANE	142-82-5

**UNITED STATE REGULATIONS AS FOLLOWS:**

**NEW JERSEY RIGHT-TO-KNOW:** The following materials are non-hazardous, but are among the top five components in this product:

CHEMICAL NAME	CAS NUMBER
No non-hazardous materials are among the top five ingredients..	

**PENNSYLVANIA RIGHT-TO-KNOW:** The following non-hazardous ingredients are present in the product at greater than 3%:

CHEMICAL NAME	CAS NUMBER
No non-hazardous ingredients are present at greater than 3%.	

**CALIFORNIA PROPOSITION 65: WARNING -** The chemical (s) noted below and contained in this product, are known to the state of California to cause cancer, birth defects or other reproductive harm:

CHEMICAL NAME	CAS NUMBER
TOLUENE	108-88-33

**INTERNATIONAL REGULATIONS AS FOLLOWS:**

**CANADIAN WHMIS:** This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings

**CANADIAL WHMIS CLASS:** No information available.

**SECTION 16 – OTHER INFORMATION**

HMIS RATINGS – HEALTH: 3 FLAMMABILITY: 4 REACTIVITY: 0

PREVIOUS MSDS REVISION DATE: 04/26/05 REASON FOR REVISION: NEW FORMAT

VOLATILE ORGANIC COMPOUNDS (VOCs): 2.81 lbs/gal 337 grams/liter

LEGEND: N.A.- Not Applicable N.E. – Not Established, N.D – Not Determined

\* The information contained on this MSDS has been checked and should be accurate. However, it is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.