

# Material Safety Data Sheet

## For Coatings, Resins and Related Materials

NOTE: CHEMTREC, CANUTEC and National Response Center emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals

24 Hour Emergency: 1-800-123-4567 CHEMTREC: 1-800-424-9300

National Response in Canada CANUTEC: 613-996-6666

Outside U.S. and Canada Chemtrec: 202-483-7616

### Section 1 - Chemical Product / Company Information

Product Name:	DEFTOIL MARINE TEAKWOOD FINISH	Revision Date:	01/10/2006
Identification Number:	182	Print Date:	04/21/2006
Product Use/Class:	MIXED OILS		
Manufacturer:	Deft, Inc. (CAGE CODE 33461) 17451 Von Karman Ave Irvine, Ca. 92614	Information Phone:	(949) 474-0400
		Emergency Phone:	(800) 424-9300

### Section 2 - Hazards Identification

\*\*\* Emergency Overview \*\*\*: Combustible liquid. Amber solution with mild odor. Harmful by inhalation, in contact with skin, and if swallowed. Contact with eyes or skin causes irritation.

**Effects Of Overexposure - Eye Contact:** Damage may occur to the cornea or lens of the eye. Direct eye contact may cause irritation. Exposure to liquid, aerosol, or vapors may cause irritation, tearing, redness, and swelling accompanied by a stinging sensation.

**Effects Of Overexposure - Skin Contact:** Symptoms may include swelling, redness, and rash. Prolonged and repeated skin contact may cause dermatitis, drying, and defatting due to the solvent properties. Direct skin contact may cause irritation.

**Effects Of Overexposure - Inhalation:** Inhalation may cause headaches, difficult breathing, and loss of consciousness. Respiratory depression, failure, or death may result from overexposure. Inhalation may cause irritation to the respiratory tract (nose, mouth, mucous membranes) & acute nervous system depression characterized by the following progressive steps: headache, dizziness, staggering gait, confusion, unconsciousness, or coma.

**Effects Of Overexposure - Ingestion:** Ingestion may cause gastrointestinal irritation, abdominal pain, nausea, vomiting and diarrhea. Vomiting may cause aspiration of the solvent, resulting in chemical pneumonitis. May result in possible corrosive action in the mouth, stomach tissue and digestive tract. Ingestion may cause a burning sensation in the mouth and esophagus.

**Effects Of Overexposure - Chronic Hazards:** A component(s) has been shown to cause blood abnormalities, lower activity of certain immune system cells, effects the hearing, mild reversible liver effects, central nervous damage, and cataracts in laboratory animals. Prolonged contact will cause drying and cracking of the skin, due to defatting action. Skin sensitization, asthma or other allergic responses may develop. Listed as a Carcinogen: NTP? : No, IARC Monographs? : No, OSHA regulated? : No.

**Primary Route(s) Of Entry:** Skin Contact, Skin Absorption, Inhalation, Ingestion, Eye Contact

### Section 3 - Composition / Information On Ingredients

Component	CAS Number	Weight % Reporting Ranges
MINERAL SPIRITS	8052-41-3	15-40
AROMATIC HYDROCARBON	64742-95-6	3-7
1,2,4 TRIMETHYLBENZENE	95-63-6	0.5-1.5

THE ABOVE LISTED PRODUCTS ARE ON THE TSCA INVENTORY LIST. ALSO ANY UNLISTED INGREDIENTS.

### Section 4 - First Aid Measures

**First Aid - Eye Contact:** Hold eyelids open to rinse out the entire eye. If material gets into eyes, flush with water immediately for 15 minutes. Consult a physician. If eyes are irritated from airborne exposure, move to fresh air.

**First Aid - Skin Contact:** In case of contact, immediately flush skin with plenty of water and wash affected areas thoroughly with soap and water. Remove contaminated clothing and shoes.

**First Aid - Inhalation:** Move to fresh air in case of accidental inhalation of vapors. Asthmatic type symptoms may develop and maybe immediate or delayed by several hours. In the case of inhalation of aerosol/mist consult a physician, if necessary.

**First Aid - Ingestion:** Do not induce vomiting. Do not give anything to an unconscious person. Obtain medical help.

### Section 5 - Fire Fighting Measures

Flash Point (°F): 110 TCC

LOWER EXPLOSIVE LIMIT (%): 0.9 UPPER EXPLOSIVE LIMIT (%): 7.0

Extinguishing Media: Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Fog, Water Spray

Unusual Fire And Explosion Hazards: Toxic gases may form when product burns. Remove all sources of ignition. Fire or intense heat may cause violent rupture of packages. Vapors can form an ignitable mixture with air. Vapors can flow along surfaces to a distant ignition source and flashback. Keep containers tightly closed. Isolate from heat, sparks, electrical equipment and open flame. Application to hot surfaces requires special precautions.

Special Firefighting Procedures: Cool fire-exposed containers using water spray. Firefighters should wear full protective clothing. In the event of fire, wear self-contained breathing apparatus.

### Section 6 - Accidental Release Measures

Steps To Be Taken If Material Is Released Or Spilled: Evacuate all non-essential personnel. Remove all sources of ignition. Ventilate area. Contain and remove spilled material with inert absorbent and non-sparking tools. Use personal protective equipment as necessary. Dike to prevent entering any sewer or waterway.

### Section 7 - Handling and Storage

Handling: Do not drill, solder, pressurize, grind, cut, weld, or braze empty container. Do not expose empty container to static electricity, heat, flame, sparks, or any source of ignition. Use only in ventilated areas. Open doors and windows. CAUTION! SPONTANEOUS COMBUSTION This product will cause spontaneous combustion (starts burning without apparent causes) when rags, paper, spray filters, steelwool, sawdust, or other material soaked or contaminated with this product is improperly disposed. Place contaminated waste materials in a container filled with water. Make sure all contaminated material is completely submerged under the water. Close the container with its proper and securely fit lid. Keep product and empty container away from heat and sources of ignition. Handle in accordance with good industrial hygiene and safety practice.

Storage: Store in buildings designed to comply with OSHA 1910.106. Do not store with oxidizers. Avoid storing near high temperatures, fire, open flames, and spark sources. Keep containers upright to prevent leakage and tightly closed in a dry, cool and well-ventilated place.

### Section 8 - Exposure Controls / Personal Protection

Component	ACGIH TLV	ACGIH STEL	OSHA PEL	OSHA STEL
MINERAL SPIRITS	100 ppm	N.E.	500 ppm	N.E.
AROMATIC HYDROCARBON	100 ppm	N.E.	N.E.	N.E.
1,2,4 TRIMETHYLBENZENE	25 ppm	150 mg/m3	100 ppm	N.E.

Engineering Controls: Local ventilation of emission sources may be necessary to maintain ambient concentrations below permissible OSHA exposure limits. Remove all ignition sources (heat, sparks, flame, and hot surfaces).

Respiratory Protection: A respirator that is recommended or approved for use in an organic vapor environment (air purifying or fresh air supplied) is necessary. Observe OSHA regulations for respirator use. Ventilation should be provided to keep exposure levels below the OSHA permissible limits.

Skin Protection: Chemical-resistant gloves (cotton, neoprene, rubber, polyethylene) should be used to prevent skin contact.

Eye Protection: Wear safety eyewear (safety glasses, safety glasses with side-shields, chemical goggles, or face shields) to prevent eye contact.

Other protective equipment: Long sleeve and long leg clothing is recommended. Remove and wash contaminated clothing before reuse or discard.

Hygienic Practices: Wash hands before breaks, eating, smoking, and at the end of the workday.

### Section 9 - Physical and Chemical Properties

Boiling Range (°F):	N.A. - N.A.	Vapor Density:	Heavier than air
Odor:	Mild odor	Odor Threshold:	N.D.
Appearance:	Amber solution	Evaporation Rate:	Faster than n-Butyl Acetate
Solubility in H2O:	Insoluble		
Freeze Point:	N.D.	Specific Gravity:	0.885
Vapor Pressure:	N.D.	PH:	N.A.
Physical State:	Liquid	Viscosity:	N.A.

(See section 16 for abbreviation legend)

### Section 10 - Stability and Reactivity

Conditions To Avoid: Do not breathe vapors or spray mist. Avoid high temperatures, sparks, or open flames.

Incompatibility: Keep away from strong oxidizing agents, heat and open flames.

Hazardous Decomposition: Thermal decomposition can lead to the generation and release of gases and vapors including carbon monoxide, carbon dioxide, oxides of nitrogen, and hydrocarbons.

Hazardous Polymerization: Will not occur.

Stability: Stable under recommended storage conditions.

**Section 11 - Toxicological Information**

Product LD50: N.E.

Product LC50: N.E.

**Section 12 - Ecological Information**

Ecological Information: No Information.

**Section 13 - Disposal Information**

Disposal Information: Dispose of waste in accordance with federal, state, and local environmental regulations. Empty containers will contain product residue and flammable vapors. Handle as hazardous material. Do not incinerate closed containers.

**Section 14 - Transportation Information**

DOT Proper Shipping Name:	Consumer Commodity	Packing Group:	N.A.
DOT Technical Name:	N.A.	Hazard Subclass:	N.A.
DOT Hazard Class:	ORM-D	Resp. Guide Page:	N.A.
DOT UN/NA Number:	N.A.		

**Section 15 - Regulatory Information****CERCLA - SARA Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories: IMMEDIATE HEALTH HAZARD, CHRONIC HEALTH HAZARD, FIRE HAZARD

**SARA Section 313:**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Component</u>	<u>CAS Number</u>	<u>Percent By Weight</u>
1,2,4 TRIMETHYLBENZENE	95-63-6	1.15

**Toxic Substances Control Act:**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

None

**U.S. State Regulations: As follows -  
New Jersey Right-to-Know:**

The following materials are non-hazardous, but are among the top five components in this product.

<u>Component</u>	<u>CAS Number</u>
BOILED LINSEED OIL	67746-08-1
VERY LONG OIL ALKYD	

**Pennsylvania Right-to-Know:**

The following non-hazardous ingredients are present in the product at greater than 3%.

<u>Component</u>	<u>CAS Number</u>
BOILED LINSEED OIL	67746-08-1
VERY LONG OIL ALKYD	

**California Proposition 65:**

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

<u>Component</u>	<u>CAS Number</u>
ETHYL BENZENE	100-41-4
ETHYL BENZENE	100-41-4
BENZENE	71-43-2
BENZENE	71-43-2

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

<u>Component</u>	<u>CAS Number</u>
TOLUENE	108-88-3
BENZENE	71-43-2
BENZENE	71-43-2

**International Regulations: As follows -**

**CANADIAN WHMIS:** This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

**CANADIAN WHMIS CLASS:** N.A.

**Section 16 - Other Information****HMIS Ratings:**

Health: 2

Flammability: 1

Reactivity: 0

Personal Protection: G

**VOLATILE ORGANIC COMPOUNDS, GR/LTR:** 341.6**VOLATILE ORGANIC COMPOUNDS, LB/GAL:** 2.9**VOLATILE ORGANIC COMPOUNDS MIXED, GR/LTR:** <= N.D.**VOLATILE ORGANIC COMPOUNDS MIXED, LB/GAL:** <= N.D.**REASON FOR REVISION:** New Computer System. Information in Sections 2, 3, 4, 5, 6, 7, 8, 14, 15, and 16 have been updated.**REGULATORY CODE:** 182**LAYOUT CODE:** A2004R**Legend:** N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The information contained on this MSDS has been checked and should be accurate. However, it is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.