

## **Specification:**

**AC Current:** 10AAC

**Microamps:** Yes

**AC Milliamps:** Yes

**AC Voltage:** 1000V

**Audible Continuity:** Yes

**Auto Ranging:** Yes

**Auto-Power Off:** Yes

**Backlight:** Yes

**Capacitance Test:** 1000 $\mu$ F

**DC Current:** 10A

**DC Microamps:** Yes

**DC Milliamps:** Yes

**DC Millivolts:** Yes

**DC Voltage:** 1000V

**Data Hold:** Yes

**Depth:** 2.1"(53.34 mm)

**Diode Test:** Yes

**Drop Protection:** 6.6'(2 m)

**Frequency/Duty Cycle:** 1Hz - 500 KHz

**Height:** 7"(177.8 mm)

**Included:** Carrying Case, Test Leads, Thermocouple, and Batteries

**Ingress Protection:** IP42

**LCD Display Count:** 4000

**Lead Warning:** Yes

**Magnetic Mount:** Available as Accessory

**Max/Min:** Yes

**Number of Batteries:** 2 x AAA

**Ohms (Resistance):** 40MO

**Overall Length:** 3.54"

**Range Hold:** Yes

**Safety Rating:** CAT IV 600V

**Temperature Range:** 0° - 1000°F (-18° - 538°C)

**Width:** 3.54"(89.91 mm)