

SimpleFix® Ceramic Tile & Fixture Caulk

1 Product Name

SimpleFix® Ceramic Tile & Fixture Caulk

2 Manufacturer

Custom Building Products
 Technical Services
 10400 Pioneer Boulevard, Unit 3
 Santa Fe Springs, CA 90670
 Customer Support: 800-272-8786
 Technical Services: 800-282-8786
 Fax: 800- 200-7765
 Email: contactus@cbpmail.net
custombuildingproducts.com



3 Product Description

For caulking around sinks, tubs, showers and where tile meets tile or another surface. Also adheres bath fixtures and loose tile. Do not use to install grab bars. Maximum joint width and depth should not exceed 1/4" (6 mm). Do not use in areas with constant water exposure. For interior use only.

Key Features

- Flexible
- Resists cracking

Suitable Substrates

- Around tubs, showers and sinks
- Bonds bath fixtures and loose tiles

Packaging

5.5 oz. (162.6 L) Tube

4 Technical Data

Technical Properties Chart

Not available.

Environmental Consideration

Custom® Building Products is committed to environmental responsibility in both products produced and in manufacturing practices. Use of this product can contribute towards LEED® v3 certification:

- Up to 2 points towards MR Credit 5, Regional Materials
- Up to 1 point towards IEQ Credit 4.1, Low-Emitting Materials – Adhesives & Sealants

5 Instructions

General Surface Prep

USE CHEMICAL-RESISTANT GLOVES, such as nitrile, when handling product.

Application of Product

For Caulking:

Surfaces should be clean, dry and free of all contamination. Knead tube with hands until soft. Cut tip off nozzle on a slant to desired opening size and squeeze into joint. Smooth with wet finger. Clean off excess caulk with soap and water before it cures.

For Use as an Adhesive:

Clean surface and back of tile or fixture. Cover at least 90% of tile or fixture back with material. Set tile or fixture holding in place with tape if necessary and let dry for at least 24 hours.

Drying Time

24 hours.

Cleaning of equipment

Clean tools and hands with water before material dries.

Storage

Keep from freezing.

Health Precautions

Contains Petroleum Distillates. If ingested, do not induce vomiting and call a physician immediately. Use with adequate ventilation. Nonflammable. KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY.

6 Availability & Cost

Location	Item Code	Size	Color	Package
USA	CTFC381	5.5 oz. (162.6 ml)	Bright White, Smooth	Tube
Canada	CCTFC381	5.5 oz. (162.6 ml)	Bright White, Smooth	Tube

7 Product Warranty

Custom® Building Products warrants to the original consumer purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. Custom's® sole liability under this warranty shall be limited to the replacement of the product. Some states, countries or territories do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with Custom's® printed instructions. Custom® makes no other warranties either expressed or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state or from one country/territory to another. This warranty is not transferrable.



CUSTOM®

SimpleFix® Ceramic Tile & Fixture Caulk

8 Product Maintenance

Clean with a neutral cleaner such as Aquamix AquaKleen or Tilelab Grout & Tile Cleaner

9 Technical Services Information

For technical assistance, contact Custom technical services at 800-282-8786 or visit custombuildingproducts.com.

10 Filing System

Additional product information is available from the manufacturer upon request.

Related Products

SimplePrep® Pre-Mixed Floor Patch

SimpleSet® Pre-Mixed Thin-Set Mortar

SimpleFix® Pre-Mixed Adhesive & Grout

SimpleGrout® Pre-Mixed Grout