

Safety Data Sheet

Issue date 02-Sep-2016 Version 1

1. Identification of the Substance/Preparation and of the Company/Undertaking

Product Identifier

Product name DECORATING MAGIC SPRAY GLITTER SILVER (BONUS SIZE)

Chemical name 7-7714-2

Other means of identification

Product code FG 499-3311-6 Synonyms Spray Glitter Silver

Recommended use of the chemical and restrictions on use

Recommended UseTo decorate artificial flowers, wreaths, pinecones, baskets, pottery, gift wrap, ribbons, bows,

costumes and seasonal decorations.

Uses advised against See directions for use on product's label.

Details of the supplier of the safety data sheet

Supplier Address
Chase Products Co.
2727 Gardner Road
Broadview, IL 60155
708-273-1121

Manufacturer Address
Chase Products Co.
2727 Gardner Road
Broadview, IL 60155
708-273-1121

Emergency Telephone Number

Company Phone Number 708-865-1000 **24 Hour Emergency Phone Number** 1-800-255-3924

Emergency telephone ChemTel 1-800-255-3924

2. Hazards Identification

Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
FLAMMABLE AEROSOLS	Category 1
Gases Under Pressure	liquefied gas

Label Elements

EMERGENCY OVERVIEW

DANGER

hazard statements

CAUSES SKIN IRRITATION
Causes serious eye irritation
May cause drowsiness or dizziness
May be fatal if swallowed and enters airways
EXTREMELY FLAMMABLE AEROSOL

Contains gas under pressure; may explode if heated



Appearance Clear liquid with colored plastic particles (glitter).

Physical State Aerosol

Odor Alcohol and petroleum solvent odor.

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves, protective clothing, eye protection and face protection.

Avoid breathing fumes, mist, vapors or spray.

Use only outdoors or in a well-ventilated area

Keep away from heat, sparks, open flames and hot surfaces. — No smoking

Pressurized container: Do not pierce or burn, even after use

Do not spray on an open flame or other ignition source

Precautionary Statements - Response

Specific treatment: See additional cautionary statements on this label.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of soap and water

If skin irritation occurs: Get medical advice/attention

Take off contaminated clothing and wash before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor if you feel unwell

IF SWALLOWED: Immediately call a POISON CENTER or doctor

Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other Information

- Very toxic to aquatic life with long lasting effects
- · Very toxic to aquatic life
- 1.68% of the mixture consists of ingredient(s) of unknown toxicity

3. Composition/information on Ingredients

Synonyms Spray Glitter Silver.
Chemical Family MIXTURES.
Formula 7-7714-2

Chemical name	CAS No	weight-%	Trade secret
Heptane	142-82-5	30-35	*
Ethyl alcohol	64-17-5	30-25	*
n-butane	106-97-8	20-25	*
Propane	74-98-6	5-10	*

^{*} The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First aid measures

FIRST AID MEASURES

Eye Contact Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact

lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control

center or doctor for treatment advice.

Skin contact Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20

minutes. Call a poison control center or doctor for treatment advise.

Inhalation If overcome by vapor, move person to fresh air. If person is not breathing, call 911 or an

ambulance, then provide artifical respiration, preferably mouth-to-mouth, if possible. Call a

poison control center or doctor for further treatment advise.

Ingestion Ingestion from an aerosol product is unlikely to occur. Contains petroleum distillates.

Harmful if swallowed. If accidentally swallowed, do not induce vomiting, call physician

immediately.

Most important symptoms and effects, both acute and delayed

Symptoms Acute: Prolonged inhalation of concentrated vapor or mist may cause headaches, dizziness

and nausea. Prolonged and repeated contact with skin may cause irritation and reddening.

Contact with eyes causes irritation.

Indication of any immediate medical attention and special treatment needed

Note to physicians Contains petroleum distillates, do not induce vomiting because of aspiration neumonia

hazard.

5. Fire-fighting measures

Suitable extinguishing media

Dry chemical, CO2 or water spray.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

This product is under pressure. Water spray may be used to cool cans in the vicinity of fire or excessive heat to prevent the explosion of the cans.

Hazardous combustion products Thermal decomposition may release carbon monoxide and carbon dioxide.

Explosion data

Sensitivity to Mechanical Impact Contents under pressure, keep away from heat and open flame.

Sensitivity to Static Discharge Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity).

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For emergency responders Remove all sources of ignition.

Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Provide adequate ventilation to area being treated. Soak up spills with chemically inert,

absorbent material.

Methods for cleaning upClean contaminated surface thoroughly.

7. Handling and Storage

Precautions for safe handling

Advice on safe handling Do not deliberately inhale vapor or spray mist. Avoid getting spray into eyes. Keep out of

reach of children.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity). AEROSOL STORAGE LEVEL III (NFPA-30B).

Incompatible Materials Avoid heat, open flame and contact with strong oxidizers.

8. Exposure Controls/Personal Protection

Control parameters

Exposure guidelines See occupational exposure limits listed below.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Heptane	STEL: 500 ppm	TWA: 500 ppm	IDLH: 750 ppm
142-82-5	TWA: 400 ppm	TWA: 2000 mg/m ³	Ceiling: 440 ppm 15 min
		(vacated) TWA: 400 ppm	Ceiling: 1800 mg/m ³ 15 min
		(vacated) TWA: 1600 mg/m ³	TWA: 85 ppm
		(vacated) STEL: 500 ppm	TWA: 350 mg/m ³
		(vacated) STEL: 2000 mg/m ³	_
Ethyl alcohol	STEL: 1000 ppm	TWA: 1000 ppm	IDLH: 3300 ppm
64-17-5		TWA: 1900 mg/m ³	TWA: 1000 ppm
		(vacated) TWA: 1000 ppm	TWA: 1900 mg/m ³
		(vacated) TWA: 1900 mg/m ³	_
n-butane	STEL: 1000 ppm	(vacated) TWA: 800 ppm	TWA: 800 ppm
106-97-8		(vacated) TWA: 1900 mg/m ³	TWA: 1900 mg/m ³
Propane	: See Appendix F: Minimal	TWA: 1000 ppm	IDLH: 2100 ppm
74-98-6	Oxygen Content	TWA: 1800 mg/m ³	TWA: 1000 ppm
		(vacated) TWA: 1000 ppm	TWA: 1800 mg/m ³
		(vacated) TWA: 1800 mg/m ³	_

Appropriate engineering controls

Individual protection measures, such as personal protective equipment

Eye/face Protection Conventional eyeglasses to guard against splashing.

Skin and Body Protection Nitrile rubber gloves required.

Respiratory protection Use in a well-ventilated area ONLY. WHEN USING INDOORS, KEEP WINDOWS AND

DOORS OPEN UNTIL FUMES DISSIPATE.

General hygiene considerations Wash hands thoroughly after handling.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Physical State Aerosol

Appearance Clear liquid with colored plastic Odor Alcohol and petroleum

particles (glitter). solvent odor.

ColorOdor thresholdNo information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pHNot applicableSolvent-based product.Melting point/freezing pointNot applicableNo information availableBoiling point/boiling rangeHeptane 195 °F/ 91 °CNo information availableFlash PointNot Available. This is an aerosolNo information available

product for which Flame Projection is over 18 inches with 8 in flashback. Temperatures above 120 F may cause

cans to burst.

Evaporation Rate Faster than butyl acetate No information available

Flammability (solid, gas)

Flammability Limits in Air

No information available
No information available

Upper flammability limits Not available Lower Flammability Limit Not available

Vapor pressure No information available

Vapor DensityNo information availableRelative Density0.744 g/ml concentrateNo information availableWater solubilitypartially solubleNo information available

Solubility in other solvents
Partition coefficient
Autoignition Temperature
Decomposition temperature
Kinematic viscosity
No information available
No information available
No information available
No information available

Dynamic viscosity

No information available

Explosive propertiesNo information availableOxidizing propertiesNo information available

Other Information

Softening point No information available Molecular weight No information available

 VOC content (%)
 97.41%

 Density
 6.20 lb/gal

Bulk Density

No information available

10. Stability and Reactivity

Reactivity

Not applicable No data available

Chemical stability

Stable.

Possibility of hazardous reactions

Temperatures above 130 °F may cause cans to burst with force.

hazardous polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Temperatures above 122 °F (50 °C).

Incompatible Materials

Avoid heat, open flame and contact with strong oxidizers.

Hazardous decomposition products

Thermal decomposition may yield gases like carbon monoxide and carbon dioxide.

11. Toxicological Information

Information on likely routes of exposure

Product InformationThis product has not been tested as whole. See below for information on ingredients.

Inhalation No data available.

Eye Contact No data available.

Skin contact No data available.

Ingestion No data available.

Chemical name	Oral LD50	dermal LD50	Inhalation LC50
Heptane	-	= 3000 mg/kg (Rabbit)	= 103 g/m³ (Rat) 4 h
142-82-5			
Ethyl alcohol	= 7060 mg/kg (Rat)	-	= 124.7 mg/L (Rat) 4 h
64-17-5			
n-butane	-	-	= 658 g/m³ (Rat) 4 h
106-97-8			, ,
Propane	-	-	= 658 mg/L (Rat) 4 h
74-98-6			_ ` '

Information on toxicological effects

Symptoms Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation May cause skin irritation and reddening after prolonged or repeated contact with skin.

Serious eye damage/eye irritation Irritating to eyes.

irritation May cause skin and eye irritation.

corrosivity Not applicable.

sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity Over exposure to petroleum solvents has been associated with nervous system damage.

Reproductive toxicity
STOT - single exposure
STOT - repeated exposure
Aspiration Hazard
No information available.
No information available.
No information available.

Numerical measures of toxicity - Product Information

Unknown acute toxicity 1.68% of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document $\,$.

ATEmix (oral) 15483 mg/kg
ATEmix (dermal) 6821 mg/kg
ATEmix (inhalation-gas) 1397188 mg/l
ATEmix (inhalation-dust/mist) 143 mg/l
ATEmix (inhalation-vapor) 262 mg/l

12. Ecological Information

This product contains a chemical which, although not listed, meets the IMDG criteria for being a marine pollutant.

ecotoxicity

32.59% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
Heptane 142-82-5		375.0: 96 h Cichlid fish mg/L LC50		10: 24 h Daphnia magna mg/L EC50
Ethyl alcohol 64-17-5		13400 - 15100: 96 h Pimephales promelas mg/L LC50 flow-through 100: 96 h Pimephales promelas mg/L LC50 static 12.0 - 16.0: 96 h Oncorhynchus mykiss mL/L LC50 static	EC50 = 35470 mg/L 5 min	10800: 24 h Daphnia magna mg/L EC50 9268 - 14221: 48 h Daphnia magna mg/L LC50 2: 48 h Daphnia magna mg/L EC50 Static

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical name	Partition coefficient
Heptane 142-82-5	4.66
Ethyl alcohol 64-17-5	-0.32
n-butane 106-97-8	2.89
Propane 74-98-6	2.3

Other adverse effects No information available

13. Disposal Considerations

Waste treatment methods

Disposal of wastesDispose of in accordance with federal, state and local regulations.

Contaminated packaging Pressurized container: Do not pierce or burn, even after use. Do not puncture or incinerate

container. If empty: Place in trash or offer for recycling if available. If partly filled: Call your

local solid waste agency for disposal instructions.

Chemical name	California Hazardous Waste Status
Heptane	Toxic
142-82-5	Ignitable
Ethyl alcohol	Toxic
64-17-5	Ignitable

14. Transport Information

DOT

UN/ID no Limited Quantity
Proper Shipping Name Consumer Commodity
Hazard Class ORM-D

Inches and United the Inches

Marine pollutant This product contains a chemical which, although not listed, meets the IMDG criteria for

being a marine pollutant.

15. Regulatory information

International Inventories

TSCA All ingredients of this product are listed or are excluded from listing under the U.S. Toxic

Subtances Control Act (TSCA) Chemical Substance Inventory.

All ingredients are listed or are excluded from listing on the DSL.

Legend:

DSL

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute Health Hazard	yes
Chronic Health Hazard	No
Fire Hazard	yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Heptane 142-82-5	X	X	Х
Ethyl alcohol 64-17-5	X	X	X
n-butane 106-97-8	X	X	X
Propane 74-98-6	X	X	Х

U.S. EPA Label information

EPA Pesticide registration number Not applicable

16. Other information

NFPA Health Hazards 2 Flammability 4 Instability 1 Physical and chemical

properties Not applicable

HMIS Health Hazards 2 Flammability 4 Physical hazards 1 Personal Protection B

Eyes and hands

protection

Prepared by Regulatory Department

Issue date 02-Sep-2016

Revision note

This SDS supersedes a previous MSDS dated January 17, 2011.

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet
