



SAFETY DATA SHEET

Revision date 25-Aug-2015

Version 2

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Code 080.0006505

Product Name MOW SPAR VOC SATIN

Other means of identification

No information available

Recommended use of the chemical and restrictions on use

Paint, Coatings

Details of the supplier of the safety data sheet

See section 16 for more information

The Valspar Corporation
PO Box 1461
Minneapolis, MN 55440

E-mail address msds@valspar.com

Emergency telephone number

United States of America 1-888-345-5732

American Samoa, Guam, Northern Mariana Islands, Puerto Rico, U.S. Virgin Islands 1-800-255-3924

Section 2: HAZARDS IDENTIFICATION

Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Carcinogenicity	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration toxicity	Category 1
Flammable liquids	Category 3

Label elements

Product Code 080.0006505

Page 1 / 10

AGHS - USA OSHA SDS



Signal word

DANGER

HAZARD STATEMENTS

Flammable liquid and vapor
Causes skin irritation
Causes serious eye irritation
May cause an allergic skin reaction
Suspected of causing cancer
Suspected of damaging fertility or the unborn child
Causes damage to organs through prolonged or repeated exposure
May be fatal if swallowed and enters airways

PREVENTION

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Wash face, hands and any exposed skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Do not breathe dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

RESPONSE

IF exposed or concerned: Get medical advice/attention.

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin

If skin irritation or rash occurs: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. Wash contaminated clothing before reuse.

Inhalation

IF INHALED: Call a POISON CENTER or doctor if you feel unwell.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

Fire

In case of fire: Use CO₂, dry chemical, or foam for extinction.

STORAGE

Store locked up. Store in a well-ventilated place. Keep cool.

DISPOSAL

Dispose of contents/containers in accordance with local regulations.

HAZARDS NOT OTHERWISE CLASSIFIED (HNOC)

Not applicable.

OTHER HAZARDS

Toxic to aquatic life with long lasting effects. spontaneously combustible material. Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials should be soaked in water and placed in a closed metal container before disposal. Not applicable.

UNKNOWN ACUTE TOXICITY

0% of the mixture consists of ingredient(s) of unknown toxicity.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	weight-%
---------------	--------	----------

Product Code 080.0006505

Page 2 / 10

AGHS - USA OSHA SDS

Petroleum distillates, hydrotreated light	64742-47-8	10 - 25
Stoddard solvent	8052-41-3	5 - 10
Dipentene	138-86-3	5 - 10
Xylenes	1330-20-7	1 - 3
2-Butanone, oxime	96-29-7	1 - 3
Ethylbenzene	100-41-4	0.3 - 1
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	136-52-7	0.1 - 0.3
Zirconium ethyl hexoate	22464-99-9	0.1 - 0.3

*The exact percentage (concentration) of composition has been withheld as a trade secret.

Section 4: FIRST AID MEASURES

First Aid Measures

General advice

IF exposed or concerned: Get medical advice/attention.

Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin Contact

If skin irritation or rash occurs: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. Wash contaminated clothing before reuse.

Inhalation

IF INHALED: Call a POISON CENTER or doctor if you feel unwell.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

Section 5: FIRE FIGHTING MEASURES

Suitable extinguishing media

Dry chemical, CO₂, water spray or alcohol-resistant foam.

Not to be used for safety reasons: Strong water jet

Specific hazards arising from the chemical

Burning produces heavy smoke. Fire may produce irritating and/or toxic gases. In the event of fire and/or explosion do not breathe fumes. May cause sensitization by skin contact. spontaneously combustible material. Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials should be soaked in water and placed in a closed metal container before disposal. Keep product and empty container away from heat and sources of ignition.

Special protective equipment for fire-fighters

Wear self-contained breathing apparatus and protective suit. Cool containers with flooding quantities of water until well after fire is out. Do not allow run-off from fire-fighting to enter drains or water courses.

Section 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions

Avoid breathing vapors or mists. Remove all sources of ignition. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas. Take precautionary measures against static discharges.

For emergency responders

Use personal protection recommended in Section 8.

Environmental precautions

Do not allow into any sewer, on the ground or into any body of water. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Prevent further leakage or spillage if safe to do so. Local authorities should be advised if significant spillages cannot be contained.

Methods and material for containment and cleaning up

Methods for containment

Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Dispose of waste product or used containers according to local regulations. Clean with detergents. Avoid solvent cleaners. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. Take up mechanically, placing in appropriate containers for disposal.

Section 7: HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentration higher than the occupational exposure limits. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Use personal protection recommended in Section 8. Never use pressure to empty container. Comply with the health and safety at work laws. Prevent product from entering drains. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Use only with adequate ventilation. Do not breathe dust/fume/gas/mist/vapors/spray. Use only in well-ventilated areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded. Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials should be soaked in water and placed in a closed metal container before disposal.

General Hygiene Considerations

When using do not eat, drink or smoke. Wash contaminated clothing before reuse. Avoid contact with skin, eyes or clothing.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep/store only in original container. Store in accordance with local regulations. Keep unauthorized personnel away. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed in a dry and well-ventilated place. Keep tightly closed in a dry and cool place.

Incompatible materials

Strong bases. Strong oxidizing agents. Strong acids.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Limits

If S* appears in the OEL table, it indicates this chemical contains a skin notation.

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Stoddard solvent 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m ³	IDLH: 20000 mg/m ³ Ceiling: 1800 mg/m ³ 15 min TWA: 350 mg/m ³

Xylenes 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³	
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³
Zirconium ethyl hexoate 22464-99-9	STEL: 10 mg/m ³ Zr TWA: 5 mg/m ³ Zr	TWA: 5 mg/m ³ Zr	IDLH: 25 mg/m ³ Zr TWA: 5 mg/m ³ except Zirconium tetrachloride Zr STEL: 10 mg/m ³ Zr

Appropriate engineering controls

Engineering Controls

Ensure adequate ventilation, especially in confined areas. Provide local exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tight sealing safety goggles.

Skin and body protection

Wear anti-static clothing made of natural fiber or of high temperature resistant synthetic fiber. Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Wear suitable protective clothing.

Hand Protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical / chemical damage and poor maintenance. Wear protective gloves.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Thermal Protection

No information available

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	liquid
Appearance	No information available
Odor	Solvent
Color	clear
Odor Threshold	No information available
pH value	No information available
Melting point/freezing point	No information available
Boiling point / boiling range	No information available °C / °F
flash point	38 °C / 100 °F
evaporation rate	No information available
Flammability (solid, gas)	No information available
Flammability Limit in Air	
Upper flammability limit:	No information available
Lower flammability limit:	No information available
Vapor Pressure	No information available
vapor density	No information available
Density (lbs per US gallon)	7.9
specific gravity	.95
Solubility(ies)	No information available

Partition coefficient	No information available
Autoignition temperature	No information available
Decomposition temperature	No information available
Kinematic viscosity	No information available
Dynamic viscosity	No information available

Other information

Section 10: STABILITY AND REACTIVITY

Reactivity	No information available.
Chemical stability	Stable under normal conditions.
Possibility of Hazardous Reactions	None under normal processing.
Hazardous polymerization	None under normal processing.
Conditions to avoid	Heat, flames and sparks.
Incompatible materials	Strong bases. Strong oxidizing agents. Strong acids.
Hazardous Decomposition Products	Carbon monoxide. Carbon dioxide (CO2).

Section 11: TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Eye contact

Causes serious eye irritation

Skin Contact

Causes skin irritation

May cause an allergic skin reaction

Ingestion

May be fatal if swallowed and enters airways

Inhalation

Not applicable

Numerical measures of toxicity - Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Petroleum distillates, hydrotreated light 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h
Stoddard solvent 8052-41-3	-	-	-
Dipentene 138-86-3	-	-	-
Xylenes 1330-20-7	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h
2-Butanone, oxime 96-29-7	= 930 mg/kg (Rat)	= 0.2 mg/kg (Rabbit)	= 20 mg/L (Rat) 4 h
Ethylbenzene 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.2 mg/L (Rat) 4 h
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1) 136-52-7	-	-	-
Zirconium ethyl hexoate 22464-99-9	-	-	-

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (dermal) 32648 Mg/kg

ATEmix (inhalation-dust/mist) 88.8 mg/l

Product Code 080.0006505

Page 6 / 10

AGHS - USA OSHA SDS

ATEmix (inhalation-vapor) 651 mg/l

UNKNOWN ACUTE TOXICITY 0% of the mixture consists of ingredient(s) of unknown toxicity.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Chemical Name	ACGIH	IARC	NTP	OSHA
Ethylbenzene 100-41-4	A3	Group 2B		X
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1) 136-52-7		Group 2B		X

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen.

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans.

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present.

Skin corrosion/irritation	Causes skin irritation
Serious eye damage/eye irritation	Causes serious eye irritation
Skin sensitization	May cause an allergic skin reaction
Respiratory sensitization	Not applicable
Germ cell mutagenicity	Not applicable
Carcinogenicity	Suspected of causing cancer
Reproductive Toxicity	Suspected of damaging fertility or the unborn child
Specific target organ toxicity (single exposure)	Not applicable
Specific target organ toxicity (repeated exposure)	Causes damage to organs through prolonged or repeated exposure
Aspiration hazard	Not applicable

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Environmental precautions Prevent product from entering drains.

Marine pollutant This material meets the definition of a marine pollutant

Persistence and degradability

No information available

Bioaccumulation

No information available

Mobility

No information available

Other adverse effects

No information available

Section 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging Improper disposal or reuse of this container may be dangerous and illegal. Empty containers must be scrapped or reconditioned.

Section 14: TRANSPORT INFORMATION

Product Code 080.0006505

Page 7 / 10

AGHS - USA OSHA SDS

14.1 UN/ID no	DOT UN1263	IMDG UN1263	IATA UN1263
14.2 Proper shipping name	Paint	Paint	Paint
14.3 Hazard Class	COMBUSTIBLE LIQUID	3	3
14.4 Packing Group	III	III	III
14.5 Environmental hazard Yes			
Marine pollutant This material meets the definition of a marine pollutant			
Marine pollutant Petroleum distillates, hydrotreated light , Stoddard solvent			
14.6 Special Provisions	B1, B52, IB3, T2, TP1, TP29	163, 223, 955	A3, A72
	Emergency Response Guide Number 128	EmS-No F-E, S-E	
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code			No information available

Section 15: REGULATORY INFORMATION

International Inventories

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory	All components are listed or exempt from listing.
DSL - Canadian Domestic Substances List	All components are listed or exempt from listing.

US Federal Regulations

Chemical Name	SARA 313 - Threshold Values %	Hazardous air pollutants (HAPs) content
Xylenes 1330-20-7 1 - 3	1	Present
Ethylbenzene 100-41-4 0.3 - 1	0.1	Present
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1) 136-52-7 0.1 - 0.3	1	Present

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylenes 1330-20-7	100 lb			X
Ethylbenzene 100-41-4	1000 lb	X	X	X

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Xylenes 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
Ethylbenzene 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

US State Regulations

Rule 66 status of product

Photochemically reactive.

California Proposition 65

WARNING! This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

U.S. EPA Label information

EPA Pesticide registration number Not applicable

U.S. State Right-to-Know Regulations

Chemical Name
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Petroleum distillates, hydrotreated light 64742-47-8
Stoddard solvent 8052-41-3
Dipentene 138-86-3
Proprietary Inert
Xylenes 1330-20-7
2-Butanone, oxime 96-29-7
Ethylbenzene 100-41-4
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1) 136-52-7
Zirconium ethyl hexoate 22464-99-9

Section 16: OTHER INFORMATION

HMIS

Health hazards	3*
<i>* = Chronic Health Hazard</i>	
Flammability	2
Physical hazards	0
Personal Protection	X

Supplier Address

Valspar Consumer Headquarters 8725 W. Higgins Rd. Suite 1000 Chicago, IL 60631 773-628-5500	The Valspar Corporation 4999 36th St. Grand Rapids, MI 49512 800-253-3957	Valspar Plasti-Kote 1636 Shawsone Dr. Mississauga, Ontario L4W 1N7 905-671-8333
--	--	--

Prepared By Product Stewardship

Revision date 25-Aug-2015
Revision Note No information available

Product Code 080.0006505

Page 9 / 10
 AGHS - USA OSHA SDS

Disclaimer

The information on this Safety Data Sheet (SDS) is based on the present state of our knowledge, current national legislation and guidelines. As the specific conditions of use of the product are outside the supplier's knowledge and control the user is responsible for ensuring that the requirements of relevant legislation are complied with. This SDS should not be construed as any guarantee of the technical performance or suitability for particular applications. **UNLESS SUPPLIER AGREES OTHERWISE IN WRITING, SUPPLIER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPPLIER WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.**

End of Safety Data Sheet