



Revision Number: 002.3

Issue date: 12/13/2016

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: OSI® GS-121 Gutter & Seam Sealant **IDH number:** 827681
Product type: White Sealant
Restriction of Use: None identified **Region:** United States
Company address: **Contact information:**
 Henkel Corporation Telephone: +1 (800) 624-7767
 One Henkel Way MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY
 Rocky Hill, Connecticut 06067 Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING: FLAMMABLE LIQUID AND VAPOR.
 CAUSES SKIN IRRITATION.
 CAUSES SERIOUS EYE IRRITATION.
 MAY CAUSE DROWSINESS OR DIZZINESS.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	3
SKIN IRRITATION	2
EYE IRRITATION	2A
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3

PICTOGRAM(S)



Precautionary Statements

Prevention: Keep away from heat, sparks, open flames, hot surfaces - no smoking. Keep container tightly closed. No release into water. Use explosion-proof equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves, eye protection, and face protection.

Response: If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing. In case of fire: Use foam, dry chemical or carbon dioxide to extinguish.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Limestone	1317-65-3	40 - 50
Stoddard solvent, <0.1% Benzene	8052-41-3	20 - 30
Titanium dioxide	13463-67-7	1 - 5
1,2,4-Trimethylbenzene	95-63-6	1 - 5
Naphthalene	91-20-3	0.1 - 1
Quartz (SiO ₂)	14808-60-7	0.1 - 1
Ethylbenzene	100-41-4	0.1 - 1

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation:	If inhaled, immediately remove the affected person to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. If symptoms develop and persist, get medical attention.
Skin contact:	Rinse with running water and soap. Apply replenishing cream. Change all contaminated clothing.
Eye contact:	In case of contact with the eyes, rinse immediately with plenty of water for 15 minutes, and seek immediate medical attention.
Ingestion:	Do not induce vomiting, seek medical advice immediately.
Symptoms:	See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Foam, dry chemical or carbon dioxide. In case of fire, keep containers cool with water spray.
Special firefighting procedures:	Wear a self-contained breathing apparatus with a full face piece operated in pressure-demand or other positive pressure mode. Wear full protective clothing.
Unusual fire or explosion hazards:	Closed containers may explode when exposed to extreme heat. Vapors may form explosive mixtures with air. Vapors are heavier than air and may travel along floor to an ignition source.
Hazardous combustion products:	Carbon dioxide. Carbon monoxide.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Eliminate all sources of ignition or flammables that may come into contact with a spill of this material. Ventilate area.
Clean-up methods:	Absorb spill with inert material. Shovel material into appropriate container for disposal. Wear suitable protective clothing, gloves and eye/face protection.

7. HANDLING AND STORAGE

Handling: Do not pressurize, cut, heat or weld containers. Empty product containers may contain product residue. Do not reuse empty containers. Use only in well-ventilated areas. Keep out of the reach of children.

Storage: Keep away from heat, spark and flame. Keep containers closed when not in use.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Limestone	10 mg/m ³ TWA Total dust.	5 mg/m ³ PEL Respirable fraction. 15 mg/m ³ PEL Total dust.	None	None
Stoddard solvent, <0.1% Benzene	100 ppm TWA	500 ppm (2,900 mg/m ³) PEL	None	None
Titanium dioxide	10 mg/m ³ TWA	15 mg/m ³ PEL Total dust. 15 MPPCF TWA Respirable fraction. 15 mg/m ³ TWA Total dust. 50 MPPCF TWA Total dust. 5 mg/m ³ TWA Respirable fraction.	None	None
1,2,4-Trimethylbenzene	25 ppm TWA	None	None	None
Naphthalene	10 ppm TWA (SKIN)	10 ppm (50 mg/m ³) PEL	None	None
Quartz (SiO ₂)	0.025 mg/m ³ TWA Respirable fraction.	2.4 MPPCF TWA Respirable. 0.1 mg/m ³ TWA Respirable. 0.05 mg/m ³ PEL	None	None
Ethylbenzene	20 ppm TWA	100 ppm (435 mg/m ³) PEL	None	None

Engineering controls: Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination below occupational exposure limits.

Respiratory protection: Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists. When workplace hazards warrant the use of a respirator, appropriate respirators must be used, and a program that follows 29 CFR 1910.134 must be followed.

Eye/face protection: Safety goggles or safety glasses with side shields.

Skin protection: Use impermeable gloves and protective clothing as necessary to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid
Color: white
Odor: slightly, of solvent
Odor threshold: Not available.

pH:	Not applicable
Vapor pressure:	10 mm hg (25 °C (77°F))
Boiling point/range:	149 - 154 °C (300.2 - 309.2 °F)(solvent)
Melting point/ range:	Not available.
Specific gravity:	1.342
Vapor density:	Heavier than air
Flash point:	40.56 °C (105.01 °F) no method
Flammable/Explosive limits - lower:	1 %
Flammable/Explosive limits - upper:	6 %
Autoignition temperature:	Not available.
Flammability:	Not applicable
Evaporation rate:	0.08 (Butyl acetate = 1)
Solubility in water:	Insoluble
Partition coefficient (n-octanol/water):	Not available.
VOC content:	28 %; 368 g/l (by weight, calculated using CARB method; g/L less water, less exempts calculated using SCAQMD method)
Viscosity:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Carbon dioxide, carbon monoxide and irritating and/or toxic gases and particulate may be generated by thermal decomposition or combustion.
Incompatible materials:	Strong oxidizing agents.
Reactivity:	Not available.
Conditions to avoid:	Heat, flames, sparks and other sources of ignition.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:	Inhalation, Skin contact
-------------------------------------	--------------------------

Potential Health Effects/Symptoms

Inhalation: Irritates the nose, throat and respiratory system. Abrasion of cured material such as by sanding or grinding could release respirable particles of silica quartz, a cancer hazard by inhalation. Normal use of this product causes no such release. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Skin contact: Prolonged and/or repeated skin contact with this product may cause irritation/dermatitis.

Eye contact: Contact with eyes can cause eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Ingestion: Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Limestone	None	Nuisance dust
Stoddard solvent, <0.1% Benzene	None	Central nervous system, Irritant
Titanium dioxide	None	Irritant, Respiratory, Some evidence of carcinogenicity
1,2,4-Trimethylbenzene	Oral LD50 (Rat) = 6.0 g/kg Dermal LD50 (Rabbit) = > 3,160 mg/kg	Central nervous system, Irritant, Respiratory
Naphthalene	Oral LD50 (Rat) = 490 mg/kg Oral LD50 (Rat) = 2.6 g/kg Oral LD50 (Rat) = 2,200 mg/kg Oral LD50 (Rat) = 2,400 mg/kg Dermal LD50 (Rat) = > 20 g/kg Dermal LD50 (Rabbit) = > 2.0 g/kg	Blood, Central nervous system, Eyes, Irritant
Quartz (SiO ₂)	None	Immune system, Lung, Some evidence of carcinogenicity
Ethylbenzene	Oral LD50 (Rat) = 5.46 g/kg Oral LD50 (Rat) = 3,500 mg/kg Dermal LD50 (Rabbit) = 17,800 mg/kg	Irritant, Central nervous system

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Limestone	No	No	No
Stoddard solvent, <0.1% Benzene	No	No	No
Titanium dioxide	No	Group 2B	No
1,2,4-Trimethylbenzene	No	No	No
Naphthalene	Reasonably Anticipated to be a Human Carcinogen.	Group 2B	No
Quartz (SiO ₂)	Known To Be Human Carcinogen.	Group 1	No
Ethylbenzene	No	Group 2B	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:	Dispose of according to Federal, State and local governmental regulations.
Hazardous waste number:	It is the responsibility of the user to determine if an item is hazardous as defined in the Resource Conservation and Recovery Act (RCRA) at the time of disposal. Product uses, transformations, mixtures, processes, etc., may render the resulting material hazardous, under the criteria of ignitability, corrosivity, reactivity and toxicity characteristics of the Toxicity Characteristics Leaching Procedure (TCLP) 40 CFR 261.20-24.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:	Adhesives
Hazard class or division:	3
Identification number:	UN 1133
Packing group:	III

International Air Transportation (ICAO/IATA)

Proper shipping name:	Adhesives
Hazard class or division:	3
Identification number:	UN 1133
Packing group:	III

Water Transportation (IMO/IMDG)

Proper shipping name:	ADHESIVES
Hazard class or division:	3
Identification number:	UN 1133
Packing group:	III

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12 (b) Export Notification:	None above reporting de minimis
CERCLA/SARA Section 302 EHS:	None above reporting de minimis.
CERCLA/SARA Section 311/312:	Immediate Health, Delayed Health, Fire
CERCLA/SARA Section 313:	This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372): 1,2,4-Trimethylbenzene (CAS# 95-63-6). Naphthalene (CAS# 91-20-3). Ethylbenzene (CAS# 100-41-4).
California Proposition 65:	This product contains a chemical known to the State of California to cause birth defects or other reproductive harm. This product contains a chemical known in the State of California to cause cancer.

Canada Regulatory Information

CEPA DSL/NDSL Status:	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.
------------------------------	---

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: This Safety Data Sheet contains changes from the previous version in Section(s): 2, 3

Prepared by: Mary Ellen Roddy, Sr. Regulatory Affairs Specialist

Issue date: 12/13/2016

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.