

**MSDS for: LN-990****Revised: 12-Feb-2009****SECTION 1:**

PRODUCT IDENTIFIER: LN-990 QUICK-GRIP LATEX ADHESIVE  
DATE OF PREPARATION: JANUARY 28, 2008  
PRODUCT USE: ADHESIVE/CAULK  
MANUFACTURED BY: AKZO NOBEL  
15885 WEST SPRAGUE ROAD  
STRONGSVILLE, OHIO 44136, U.S.A.

AKZO NOBEL (CANADA)  
8200 KEELE STREET  
CONCORD, ONTARIO L4K 2A5, CANADA

EMERGENCY AND MSDS TELEPHONE NUMBER: 1-800-545-2643

MSDS PREPARED BY: PRODUCT SAFETY AND COMPLIANCE DEPARTMENT  
AKZO NOBEL NORTH AMERICA

**SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS**

| <b>INGREDIENT</b>  | <b>WT. %</b> |
|--|--------------|
| CHEMICAL NAME: ACRYLIC COPOLYMER<br>COMMON NAME: ACRYLIC COPOLYMER<br>CAS NUMBER: CONFIDENTIAL   | 1-5          |
| CHEMICAL NAME: LIMESTONE<br>COMMON NAME: LIMESTONE<br>CAS NUMBER: 1317-65-3  | 30-40        |
| CHEMICAL NAME: QUARTZ<br>COMMON NAME: QUARTZ<br>CAS NUMBER: 14808-60-7   | 0.1-1.0      |
| CHEMICAL NAME: 2-PROPENOIC ACID, POLYMER WITH BUTYL<br>2-PROPENOATE AND ETHENYLBENZENE<br>COMMON NAME: ACRYLIC LATEX<br>CAS NUMBER: 25586-20-3 | 30-40        |
| CHEMICAL NAME: FORMALDEHYDE LT<br>COMMON NAME: FORMALDEHYDE<br>CAS NUMBER: 50-00-0   | 0.01         |
| CHEMICAL NAME: 1,2-PROPANEDIOL<br>COMMON NAME: PROPYLENE GLYCOL<br>CAS NUMBER: 57-55-6   | 1-5          |
| CHEMICAL NAME: WATER<br>COMMON NAME: WATER<br>CAS NUMBER: 7732-18-5  | 30-40        |

### **SECTION 3: HAZARDS IDENTIFICATION**

PRIMARY ROUTE(S) OF EXPOSURE: INHALATION, SKIN CONTACT, EYE CONTACT, INGESTION

#### **EFFECTS OF OVEREXPOSURE**

**INHALATION:** IRRITATION OF RESPIRATORY TRACT. PROLONGED INHALATION MAY LEAD TO HEADACHE, NAUSEA.

**SKIN CONTACT:** IRRITATION OF SKIN. PROLONGED OR REPEATED CONTACT CAN CAUSE DERMATITIS. POSSIBLE SENSITIZATION TO SKIN. SKIN CONTACT MAY RESULT IN DERMAL ABSORPTION OF COMPONENT(S) OF THIS PRODUCT WHICH MAY CAUSE HEADACHE, NAUSEA, CENTRAL NERVOUS SYSTEM DEPRESSION.

**EYE CONTACT:** IRRITATION OF EYES. PROLONGED OR REPEATED CONTACT CAN CAUSE TEARING OF EYES, REDNESS OF EYES.

**INGESTION:** INGESTION MAY CAUSE NAUSEA, VOMITING, GASTRO-INTESTINAL DISTURBANCES, ABDOMINAL PAIN, CENTRAL NERVOUS SYSTEM DEPRESSION, KIDNEY DAMAGE.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: EYE, SKIN, RESPIRATORY DISORDERS

### **SECTION 4: FIRST-AID MEASURES**

**INHALATION:** REMOVE TO FRESH AIR. RESTORE AND SUPPORT CONTINUED BREATHING. GET EMERGENCY MEDICAL ATTENTION. HAVE TRAINED PERSON GIVE OXYGEN IF NECESSARY. GET MEDICAL HELP FOR ANY BREATHING DIFFICULTY.

**SKIN CONTACT:** WASH THOROUGHLY WITH SOAP AND WATER. IF ANY PRODUCT REMAINS, GENTLY RUB PETROLEUM JELLY, VEGETABLE OR MINERAL/BABY OIL ONTO SKIN. REPEATED APPLICATIONS MAY BE NEEDED. REMOVE CONTAMINATED CLOTHING. WASH CONTAMINATED CLOTHING BEFORE RE-USE.

**EYE CONTACT:** FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER, ESPECIALLY UNDER LIDS FOR AT LEAST 15 MINUTES. IF IRRITATION OR OTHER EFFECTS PERSIST, OBTAIN MEDICAL TREATMENT.

**INGESTION:** IF SWALLOWED, OBTAIN MEDICAL TREATMENT IMMEDIATELY.

### **SECTION 5: FIRE-FIGHTING MEASURES**

FLASH POINT (SETA): ABOVE 200F/93C LOWER EXPLOSIVE LIMIT: NOT AVAILABLE  
UPPER EXPLOSIVE LIMIT: NOT AVAILABLE

FIRE EXTINGUISHING MEDIA: DRY CHEMICAL OR FOAM, WATER FOG, CARBON DIOXIDE

## UNUSUAL FIRE AND EXPLOSION HAZARDS

CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT OR FIRE. VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL LONG DISTANCES TO A SOURCE OF IGNITION AND FLASH BACK. VAPORS CAN FORM EXPLOSIVE MIXTURES IN AIR AT ELEVATED TEMPERATURES. CLOSED CONTAINERS MAY BURST IF EXPOSED TO EXTREME HEAT OR FIRE.

## FIRE FIGHTING PROCEDURES

WATER MAY BE USED TO COOL AND PROTECT EXPOSED CONTAINERS. FIREFIGHTERS SHOULD USE FULL PROTECTIVE CLOTHING, EYE PROTECTION, AND SELF-CONTAINED BREATHING APPARATUS.

## HAZARDOUS DECOMPOSITION OR COMBUSTION PRODUCTS

CARBON MONOXIDE, CARBON DIOXIDE, OXIDES OF NITROGEN,  
OXIDES OF SULFUR, TOXIC GASES, PROPIONALDEHYDE, OXIDES OF CALCIUM

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

COMPLY WITH ALL APPLICABLE HEALTH AND ENVIRONMENTAL REGULATIONS. VENTILATE AREA. SPILLS MAY BE COLLECTED WITH ABSORBENT MATERIALS. EVACUATE ALL UNNECESSARY PERSONNEL. PLACE COLLECTED MATERIAL IN PROPER CONTAINER. SPILLED MATERIAL IS EXTREMELY SLIPPERY.

LARGE SPILLS: SHUT OFF LEAK IF SAFE TO DO SO. DIKE AND CONTAIN SPILL. PUMP TO STORAGE OR SALVAGE VESSELS. USE ABSORBENT TO PICK UP EXCESS RESIDUE. KEEP SALVAGEABLE MATERIAL AND RINSE WATER OUT OF SEWERS AND WATER COURSES.

SMALL SPILLS: USE ABSORBENT TO PICK UP RESIDUE AND DISPOSE OF PROPERLY.

## SECTION 7: HANDLING AND STORAGE

STORE BELOW 100F (38C). KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME. KEEP FROM FREEZING.

### OTHER PRECAUTIONS

USE ONLY WITH ADEQUATE VENTILATION. DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN. AVOID CONTACT WITH SKIN AND EYES, AND BREATHING OF VAPORS. WASH HANDS THOROUGHLY AFTER HANDLING, ESPECIALLY BEFORE EATING OR SMOKING. KEEP CONTAINERS TIGHTLY CLOSED AND UPRIGHT WHEN NOT IN USE.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

COMMON NAME: LIMESTONE  
CAS NUMBER: 1317-65-3  
ACGIH(TWA): 10 MG/M3 OSHA(TWA): 5 MG/M3

COMMON NAME: QUARTZ  
CAS NUMBER: 14808-60-7  
ACGIH(TWA): 0.025 MG/M3 OSHA(TWA): 0.1 MG/M3

COMMON NAME: FORMALDEHYDE  
CAS NUMBER: 50-00-0  
OSHA(TWA): 0.75 PPM  
ACGIH(STEL): C 0.3 PPM OSHA(STEL): 2 PPM

#### RESPIRATORY PROTECTION

CONTROL ENVIRONMENTAL CONCENTRATIONS BELOW APPLICABLE EXPOSURE STANDARDS WHEN USING THIS MATERIAL. WHEN RESPIRATORY PROTECTION IS DETERMINED TO BE NECESSARY, USE A NIOSH/MSHA (CANADIAN Z94.4) APPROVED ELASTOMERIC SEALING-SURFACE FACEPIECE RESPIRATOR OUTFITTED WITH ORGANIC VAPOR CARTRIDGES AND PAINT SPRAY (DUST/MIST) PREFILTERS. DETERMINE THE PROPER LEVEL OF PROTECTION BY CONDUCTING APPROPRIATE AIR MONITORING. CONSULT 29CFR1910.134 FOR SELECTION OF RESPIRATORS (CANADIAN Z94.4).

#### VENTILATION

PROVIDE DILUTION VENTILATION OR LOCAL EXHAUST TO PREVENT BUILD-UP OF VAPORS.

#### PERSONAL PROTECTIVE EQUIPMENT

EYE WASH, SAFETY SHOWER, SAFETY GLASSES OR GOGGLES,  
IMPERVIOUS GLOVES, IMPERVIOUS CLOTHING

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

|                      |                 |                      |                 |
|----------------------|-----------------|----------------------|-----------------|
| VAPOR PRESSURE:      | NOT AVAILABLE   | SPECIFIC GRAVITY:    | 1.307           |
| BOILING RANGE (F/C): | 212-212/100-100 | WEIGHT PER GALLON:   | 10.89/13.08 IMP |
| APPEARANCE:          | WHITE           | %VOLATILE BY VOLUME: | 44.26           |
| PHYSICAL STATE:      | PASTE           | PH:                  | 8.10            |
| SOLUBLE IN WATER:    | Y               |                      |                 |

### SECTION 10: STABILITY AND REACTIVITY

UNDER NORMAL CONDITIONS: STABLE (SEE SECTION 5 FIRE FIGHTING MEASURES)

MATERIALS TO AVOID: OXIDIZERS, ACIDS, BASES, AMMONIUM SALTS,  
NITRIC ACID, HYDROFLUORIC ACID

#### CONDITIONS TO AVOID:

ELEVATED TEMPERATURES, CONTACT WITH OXIDIZING AGENT,  
FREEZING, EXTREMES IN TEMPERATURE

#### HAZARDOUS POLYMERIZATION:

WILL NOT OCCUR

**SECTION 11: TOXICOLOGICAL INFORMATION**

COMMON NAME: ACRYLIC COPOLYMER  
CAS NUMBER: CONFIDENTIAL  
CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO

COMMON NAME: LIMESTONE  
CAS NUMBER: 1317-65-3  
CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO  
LD50: 6450.00 MG/KG ORL RAT

COMMON NAME: QUARTZ  
CAS NUMBER: 14808-60-7  
CARCINOGENICITY LISTED BY: NTP YES IARC YES 1 OSHA NO ACGIH YES A2

COMMON NAME: FORMALDEHYDE  
CAS NUMBER: 50-00-0  
CARCINOGENICITY LISTED BY: NTP YES IARC YES 1 OSHA YES ACGIH YES A2  
LD50: 100.00 MG/KG ORL RAT  
LC50: 203.00 MG/M3 IHL PIG

COMMON NAME: PROPYLENE GLYCOL  
CAS NUMBER: 57-55-6  
CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO  
LD50: 20.00 GM/KG ORL RAT  
LD50: 20.80 GM/KG SKN RBT

**SUPPLEMENTAL HEALTH INFORMATION**

NO ADDITIONAL EFFECTS ARE ANTICIPATED

CARCINOGENICITY: CONTAINS FORMALDEHYDE, A POTENTIAL CANCER HAZARD. RATS EXPOSED TO FORMALDEHYDE VIA INHALATION DEVELOPED CANCER OF THE NASAL CAVITY. EVIDENCE IN HUMANS IS LIMITED (NASAL AND NASOPHARYNGEAL CANCER). FORMALDEHYDE IS LISTED AS A CARCINOGEN BY OSHA, PROBABLE HUMAN CARCINOGEN (GROUP 2A) BY IARC, AND ANTICIPATED HUMAN CARCINOGEN BY NTP. OVEREXPOSURE CAN CAUSE EYE, SKIN, AND RESPIRATORY TRACT IRRITATION, AND SKIN AND RESPIRATORY SENSITIZATION. CONTAINS CRYSTALLINE SILICA WHICH IS CONSIDERED A HAZARD BY INHALATION. IARC HAS CLASSIFIED CRYSTALLINE SILICA AS CARCINOGENIC TO HUMANS (GROUP 1). CRYSTALLINE SILICA IS ALSO A KNOWN CAUSE OF SILICOSIS, A NONCANCEROUS LUNG DISEASE. THE NATIONAL TOXICOLOGY PROGRAM (NTP) HAS CLASSIFIED CRYSTALLINE SILICA AS A KNOWN HUMAN CARCINOGEN.

REPRODUCTIVE EFFECTS: NO REPRODUCTIVE EFFECTS ARE ANTICIPATED

MUTAGENICITY: NO MUTAGENIC EFFECTS ARE ANTICIPATED

TERATOGENICITY: NO TERATOGENIC EFFECTS ARE ANTICIPATED

**SECTION 12: ECOLOGICAL INFORMATION**

NO ECOLOGICAL TESTING HAS BEEN DONE BY AKZO NOBEL ON THIS PRODUCT AS A WHOLE.

**SECTION 13: DISPOSAL CONSIDERATIONS**

WASTE DISPOSAL: DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS. AVOID DISCHARGE TO NATURAL WATERS.

**SECTION 14: TRANSPORT INFORMATION**

DOT: ADHESIVE  
IMDG: NOT AVAILABLE  
IATA: NOT AVAILABLE  
TDG: NOT AVAILABLE

**SECTION 15: REGULATORY INFORMATION**

|                           |             |             |                 |                      |                  |
|---------------------------|-------------|-------------|-----------------|----------------------|------------------|
|                           | SARA<br>302 | SARA<br>313 | CERCLA<br>302.4 | HAZ AIR<br>POLLUTANT | MARINE<br>POLTNT |
| CAS NUMBER: 50-00-0       | YES         | YES         | YES             | YES                  | NO               |
| COMMON NAME: FORMALDEHYDE |             |             |                 |                      |                  |

AS OF THE DATE OF THIS MSDS, ALL OF THE COMPONENTS IN THIS PRODUCT ARE LISTED (OR ARE OTHERWISE EXEMPT FROM LISTING) ON THE TSCA INVENTORY. THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CPR (CONTROLLED PRODUCTS REGULATIONS) AND THE MSDS CONTAINS ALL THE INFORMATION REQUIRED BY THE CPR.

**SECTION 16: OTHER INFORMATION**

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA AVAILABLE AT THE TIME OF PREPARATION OF THIS DATA SHEET AND WHICH AKZO NOBEL BELIEVES TO BE RELIABLE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA. AKZO NOBEL SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS INFORMATION, OR OF ANY PRODUCT, METHOD OR APPARATUS MENTIONED AND YOU MUST MAKE YOUR OWN DETERMINATION OF ITS SUITABILITY AND COMPLETENESS FOR YOUR OWN USE, FOR THE PROTECTION OF THE ENVIRONMENT, AND THE HEALTH AND SAFETY OF YOUR EMPLOYEES AND USERS OF THIS MATERIAL. COMPLIES WITH OSHA HAZARD COMMUNICATION STANDARD 29CFR1910.1200.