



# MOLY-LIT™

## Anti-Seize Compound

### SAFETY DATA SHEET

#### SECTION 1: IDENTIFICATION

**Manufacturer:** Anti-Seize Technology  
2345 N. 17th Ave.  
Franklin Park, IL 60131  
Phone: 847-455-2300  
Toll Free: 800 991-1106  
Web: antiseize.com

**Information Phone Number:** 847-455-2300

**Emergency Phone Number:** Infotrac 24/7 Phone: 1-800-535-5053 (US & Canada)  
or 352-323-3500 (International)

**Product Use:** Anti-Seize Compound

**Restriction on Use:** None known

**SDS Date of Preparation:** December 2017

#### SECTION 2: HAZARDS IDENTIFICATION

**GHS Classification (Hazcom 2012):**

Not Hazardous

**Label Elements:**

Not hazardous in accordance with the OSHA Hazard Communication Standard (29CFR 1910.1200).

**Hazard Phrases:**

None

**Precautionary Phrases:**

None

**Other Hazards:** None

#### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	%
Trade Secret, non-hazardous	Proprietary	15-25

Molybdenum disulfide	1317-33-5	15-30
Graphite	7782-42-5	15-30
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	40-60
Rust inhibitor	Mixture	1-3

**The specific identity and/or exact percentage of composition has been withheld as a trade secret.**

#### SECTION 4: FIRST AID MEASURES

**Eye:** Flush eyes with water, holding the eyelids apart. Get medical attention if irritation develops or persists.

**Skin:** Wash thoroughly with plenty of water. Get medical attention if irritation persists.

**Inhalation:** Remove to fresh air and keep comfortable for breathing. If irritation occurs, get medical attention.

**Ingestion:** If large amounts ingested, seek medical attention.

**Most Important symptoms and effects, both acute and delayed:** None known.

**Indication of any immediate medical attention and special treatment needed:** Immediate medical attention generally not required.

#### SECTION 5: FIRE-FIGHTING MEASURES

**Suitable and Unsuitable Extinguishing Media:** Use foam, carbon dioxide or dry chemical.

**Special Hazards Arising from the Chemical:** This compound will not burn unless it is pre-heated. Water fog may be used to cool the containers but do not spray directly into large containers of burning liquids as frothing may occur. Dense smoke and noxious or toxic fumes may be generated in a fire. The thermal decomposition products may yield oxides of carbon and sulfur. Noxious or toxic fumes may be generated, some of which may be toxic or irritating.

**Special Equipment and Precautions for Fire-Fighters:** Wear NIOSH approved positive pressure, self-contained breathing apparatus and full protective clothing. Cool fire exposed containers with water.

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

**Personal Precautions, Protective Equipment and Emergency Procedures:** Wear appropriate personal protective equipment. Use caution: slip hazard.

**Environmental Hazards:** Report spills and releases as required to appropriate authorities.

**Methods and Material for Containment and Cleaning Up:** Because of its viscous nature, this product is not expected to leak or spill. Collect liquid spill with an inert absorbent material and place into a suitable container for disposal. Clean area thoroughly with mineral spirits.

#### SECTION 7: HANDLING AND STORAGE

**Precautions for Safe Handling:** Avoid contact with eyes. Avoid prolonged skin contact Do not transfer to unlabeled containers.

**Conditions for Safe Storage, Including any Incompatibilities:** Store away from extreme heat and open flames. Store away from oxidizers.

#### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Chemical Name	Exposure Limits
Molybdenum disulfide (as molybdenum and insoluble compounds, as Mo)	30 mg/m <sup>3</sup> TWA ACGIH TLV (inhalable) 3 mg/m <sup>3</sup> TWA ACGIH TLV (respirable) 15 mg/m <sup>3</sup> TWA OSHA PEL (total dust)
Graphite	2 mg/m <sup>3</sup> TWA ACGIH TLV (respirable) 15 mg/m <sup>3</sup> TWA OSHA PEL (total dust) 5 mg/m <sup>3</sup> TWA OSHA PEL (respirable fraction)
Distillates (petroleum), hydrotreated heavy naphthenic	5 mg/m <sup>3</sup> TWA ACHIH TLV (inhalable) 5 mg/m <sup>3</sup> TWA OSHA PEL
Rust inhibitor	None Established

**Appropriate Engineering Controls:** Use with adequate general or local exhaust ventilation to maintain exposure levels below the exposure limits. If the product is used at high temperatures, local exhaust ventilation may be required.

#### Individual Protection Measures:

**Respiratory Protection:** In operations where the occupational exposure limits are exceeded, a NIOSH approved respirator with organic vapor/particulate cartridges or supplied air respirator appropriate for the form and concentration of the contaminants should be used. Selection and use of respiratory equipment must be in accordance with OSHA 1910.134 and good industrial hygiene practice.

**Skin Protection:** Impervious gloves such as rubber or nitrile recommended where needed to avoid prolonged skin contact .

**Eye Protection:** Safety glasses or goggles recommended where needed to avoid eye contact.

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

<b>Appearance:</b> Bluish gray colored paste	<b>Vapor Density (air = 1):</b> Not available
<b>Odor:</b> Slight odor	<b>Specific Gravity:</b> 0.9
<b>Odor Threshold:</b> Not established	<b>Water Solubility:</b> Not soluble
<b>pH:</b> Not available	<b>Octanol/Water Partition Coefficient:</b> Not available
<b>Melting Point/Freezing Point:</b> Not available	<b>Autoignition Temperature:</b> Not available
<b>Boiling Point:</b> Not available	<b>Decomposition Temperature:</b> Not available
<b>Flash Point:</b> >340°F	<b>Viscosity:</b> Not available
<b>Evaporation Rate:</b> Not available	<b>Explosion Properties:</b> None
<b>Flammable Limits:</b> <b>LEL:</b> Not established <b>UEL:</b> Not established	<b>Oxidizing Properties:</b> Not oxidizing
<b>Vapor Pressure:</b> Not established	<b>Aerosol Fire Protection Level:</b> Not applicable
<b>VOC Content:</b> <0.5%	<b>Flammability (solid, gas):</b> Not available

**SECTION 10: STABILITY AND REACTIVITY**

**Reactivity:** Not reactive under normal conditions of use.

**Chemical Stability:** Stable under normal storage and handling conditions.

**Possibility of Hazardous Reactions:** None known

**Conditions to Avoid:** Use with strong oxidizing chemicals such as concentrated acids.

**Incompatible Materials:** Avoid strong oxidizing agents, bromates, chlorates and iodates.

**Hazardous Decomposition Products:** The thermal decomposition products may yield oxides

of carbon and sulfur. Noxious or toxic fumes may be generated, some of which may be toxic or irritating.

## SECTION 11: TOXICOLOGICAL INFORMATION

### Potential Health Effects:

**Eye:** May cause mild irritation.

**Skin:** Prolonged contact may cause irritation and drying of the skin.

**Inhalation:** No adverse effects expected at ambient temperatures. Inhalation of vapors and fumes from thermal decomposition may cause respiratory irritation and metal fume fever with symptoms of fever and chills.

**Ingestion:** Swallowing may cause gastrointestinal irritation, nausea, vomiting, diarrhea.

**Chronic Hazards:** Prolonged inhalation of thermal decomposition products may result in lung damage.

**Carcinogen Status:** None of the components of this product are listed as carcinogens by IARC, NTP or OSHA.

### Acute Toxicity Values:

Molybdenum disulfide: Oral rat LD50 > 2000 mg/kg, inhalation rat LC50 > 2.82 mg/L, dermal rat LD50 > 2000 mg/kg

Graphite: Oral rat LD50 > 2000 mg/kg, inhalation rat LC50 > 2 mg/L

Distillates (petroleum), hydrotreated heavy naphthenic: Oral rat LD50 > 5000 mg/kg, inhalation rat LC50: 2.18 mg/L, dermal rabbit LD50 > 2000 mg/kg

## SECTION 12: ECOLOGICAL INFORMATION

### Ecotoxicity:

Molybdenum disulfide: Pimephales promelas LC50: 609.1 mg/L/96hr

Graphite: Danio rerio LC50 > 100 mg/L/96hr

Distillates (petroleum), hydrotreated heavy naphthenic: Pimephales promelas LL50 > 100 mg/L/96hr.

**Persistence and Degradability:** No data available

**Bioaccumulative Potential:** No data available

**Mobility in Soil:** No data available

**Other Adverse Effects:** None known

### SECTION 13: DISPOSAL CONSIDERATIONS

Dispose in accordance with all local, regional and national regulations.

### SECTION 14: TRANSPORT INFORMATION

#### DOT

**Shipping Name:** Not regulated

**DOT Technical Name:** None

**DOT Hazard Class:** None

**UN Number:** None

**DOT Labels Required (49CFR172.101):** None

#### IMDG

**Shipping Description:** Not regulated

**ID Number:** None

**Hazard Class:** None

**Packing Group:** None

**Labels Required:** None

**Marking Required:** None

**Placards Required:** None

#### ICAO/IATA

**Shipping Description:** Not regulated

**ID Number:** None

**Hazard Class:** None

**Packing Group:** None

### SECTION 15: REGULATORY INFORMATION

**Safety, health, and environmental regulations specific for the product in question.**

**CERCLA Hazardous Substances (Section 103)/RQ:** This product is not subject to reporting requirements under CERCLA. However, many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

**SARA Hazard Category (311/312):** Not Hazardous

**SARA 313:** This product contains the following chemicals regulated under SARA Title III, section 313: None.

**EPA TSCA Inventory:** All of the components of this product are listed on the TSCA inventory.

**CALIFORNIA PROPOSITION 65:** This product is not known to contain listed chemicals.

## SECTION 16: OTHER INFORMATION

**Revision Summary:** New format to comply with OSHA Hazcom 2012

---

### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.