

# BATTERY PROTECTOR AND SEALER SAFETY DATA SHEET

Section 1- Product and Company Identification

Product Code: 17211

Manufacture/Supplier : Anti-Seize Technology 2345 N. 17<sup>th</sup> Ave. Franklin Park, IL 60131

Phone: 847-455-2300 Fax: 847-455-2371 Web: antiseize.com Emergency Phone, 24 hr: Infotrac @ 1-800-535-5053 ( US & Canada )

1-800-535-5053 (US & Canada) 1-352-323-3500 (International) **Web**: infotrac.net

Product Use: Designed to protect wet cell batteries from environmental elements

Date: May 19, 2015

**Section 2-Hazard Identification** 

## GHS Classification (Hazcom 2012):

Flammable Aerosol Category 1 Gas under pressure, Liquefied gas Skin Corrosion / irritation Category 3 Eye damage / irritation , Category 2B Aspiration hazard, Category 1

Label Elements:



Signal word:

Danger

Hazard Phrases: Extremely flammable aerosol Contains gas under pressure: may explode if heated May be fatal if swallowed and enters airways Causes mild skin irritation Causes mild eye irritation

#### **Precautionary Phrases:**

Keep away from heat/sparks/open flames/hot surfaces-No smoking Do not spray on an open flame or other ignition sources Pressurized container-Do not pierce or burn, even after use Wash thoroughly after handling Do NOT induce vomiting

#### **Response:**

**IF IN EYES:** Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do, continue rinsing. If eye irritation persists: Get medical attention.

IF ON SKIN: Wash with soap and water. If irritation persist: Get medical attention

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting

#### Storage:

Protect from sunlight. Store in well ventilated place. Do not expose to temperatures exceeding 50°C /122°F Store locked up

**Disposal:** Dispose of contents in accordance with local, regional and national regulations.

Section 3- Composition/ Information on Ingredients			
CHEMICAL	CAS NUMBER	PERCENT	
ACETONE	67-64-1	30-50	
TOLUENE	108-88-3	15-20	
PROPANE	74-98-6	10-15	
BUTANE	106-97-8	10-15	
ALKYD RESIN	mixture	5-10	
PETROLEUM DISTILLATE, VM&P NAPHTHA	64742-89-8	1-5	
2-BUTOXYETHANOL	111-76-2	1-5	

The specific identity and/or exact percentage of composition has been withheld as a trade secret

#### Section 4 – First Aid Measures

Eye: Immediately flush eyes with water, holding the eyelids apart. Get medical attention if irritation develops or persists.

Skin: I case of contact, wash thoroughly with plenty of water. Get medical attention if irritation persists.

Inhalation: Remove to fresh air and keep comfortable for breathing. If irritation occurs, get medical attention.

Ingestion: Aspiration Hazard. DO NOT induce vomiting. Get immediate medical attention.

**Most Important symptoms and effects, both acute and delayed:** Causes eye and skin irritation. Product is an aspiration hazard. May enter the lungs during swallowing or vomiting and cause lung damage. Inhalation may cause irritation, headache, dizziness and drowsiness.

Indication of any immediate medical attention and special treatment needed: Immediate medical attention required for ingestion.

#### Section 5 – Fire Fighting Measures

Suitable and Unsuitable Extinguishing Media: Use water spray or fog, foam, carbon dioxide or dry chemical.

Special Hazards Arising from the Chemical: Extremely flammable aerosol. Keep away from heat and open flames. Container may rupture or explode in the heat of a fire. Prolonged exposure to temperatures above 120°F may cause cans to burst. Combustion may produce carbon dioxide, carbon monoxide.

Special Equipment and Precautions for Fire-Fighters: Wear NIOSH approved positive pressure, self-contained breathing apparatus and full protective clothing. Cool fire exposed containers with water. Protect against bursting cans.

#### Section 6 – Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures: Wear appropriate personal protective equipment. Eliminate all sources of ignition with explosion-proof equipment. Ventilate area.

Environmental Hazards: Report spills and releases as required to appropriate authorities.

Methods and Material for Containment and Cleaning Up: Place leaking container into a suitable container and place in a well-ventilated area until the propellant has dissipated. Collect liquid spill with an inert absorbent material and place into a suitable container for disposal.

#### Section 7 – Handling and Storage

Precautions for Safe Handling: Avoid contact with eyes. Avoid breathing vapors and mists. Use with adequate ventilation. Keep away from heat sources. Contents under pressure. Do not puncture or incinerate container. Do not smoke while using.

Conditions for Safe Storage, Including any Incompatibilities: Store in a cool, well-ventilated area at temperatures below 120°F. Do not store in direct sunlight.

Section 8 – Exposure Controls / Personal Protection		
CHEMICAL NAME	EXPOSURE LIMITS	
ACETONE	OSHA PEL TWA 750ppm ACGIH TLV-TWA 500ppm	
TOLUENE	OSHA TWA 200ppm	
	ACGIH TWA 20ppm, 8 hr.	
PROPANE	ACGIH TWA 1000ppm	
BUTANE	ACGIH TWA 1000ppm	
ALKYD RESIN	Not established	
PETROLEUM DISTILLATE, VM&P NAPHTHA	OSHA TWA 500ppm	
	ACGIH TLV TWA 400ppm	
2-BUTOXYETHANOL	OSHA PEL –TWA 50ppm	
	ACGIH TLV-TWA 20ppm	

**Appropriate Engineering Controls:** Use with adequate general or local exhaust ventilation to maintain exposure levels below the exposure limits. If the product is used at high temperatures, local exhaust ventilation may be required.

#### Individual Protection Measures:

**Respiratory Protection:** In operations where the occupational exposure limits are exceeded, a NIOSH approved respirator with organic vapor/particulate cartridges or supplied air respirator appropriate for the form and concentration of the contaminants should be used. Selection and use of respiratory equipment must be in accordance with OSHA 1910.134 and good industrial hygiene practice.

**Skin Protection:** Impervious gloves such as rubber or nitrile recommended where needed to avoid prolonged skin contact .

Eye Protection: Safety glasses or goggles recommended where needed to avoid eye contact.

Appearance: Aerosol product	Vapor Density (air = 1): heavier than air	
Odor: mild	Specific Gravity: 0.7	
Odor Threshold: Not established	Water Solubility: Not determined	
pH: Not available	Octanol/Water Partition Coefficient: Not available	
Melting Point/Freezing Point: No Data	Autoignition Temperature: Not available	
Boiling Point: 56°C	Decomposition Temperature: Not available	
Flash Point: not determined	Viscosity: Not available	
Evaporation Rate: slower than ether	Explosion Properties: None	
Flammable Limits: LEL: Not established UEL: Not established	Oxidizing Properties: Not oxidizing	
Vapor Pressure: Not established	Aerosol Fire Protection Level: Not applicable	
VOC Content: no data	Flammability (solid, gas): gas, level 3 Aerosol	

### Section 9 – Physical and Chemical Properties

#### Section 10 – Stability and Reactivity

Reactivity: Not reactive under normal conditions of use.

Chemical Stability: Stable under normal storage and handling conditions.

Possibility of Hazardous Reactions: None known

Conditions to Avoid: Use with strong oxidizing chemicals such as concentrated acids.

Incompatible Materials: Avoid strong oxidizing agents and acids.

Hazardous Decomposition Products: The thermal decomposition products are highly dependent upon the combustion conditions. Noxious or toxic fumes may be generated, some of which may be toxic or irritating.

#### Section 11 – Toxicological Information

Long term Toxicological studies have not been conducted for this product

#### **Potential Health Effects:**

Eye: May cause mild irritation.

Skin: Prolonged contact may cause mild irritation of the skin.

**Inhalation:** No adverse effects expected at ambient temperatures. Inhalation of vapors and fumes from thermal decomposition may cause respiratory irritation .

Ingestion: Swallowing may cause gastrointestinal irritation, nausea, vomiting, diarrhea

Chronic Hazards: Prolonged inhalation of thermal decomposition products may result in lung damage.

Carcinogen Status: None of the components of this product are listed as carcinogens by IARC, NTP or OSHA.

#### Section 12 – Ecological Information

Long term ecological studies have not been conducted for this product

Ecotoxicity: No Data

Bioaccumulative Potential: No Data

Mobility in Soil: No Data

Other Adverse Effects: No Data

Section 13 – Disposal Consideration

**Waste disposal**: Dispose of in a responsible manner. Follow local, state and federal guidelines. Do not discharge into sewers or waterways. Incineration is the preferred method of disposal, although it may be landfilled at an approved facility.

#### Section 14- Transport Information

DOT Proper Shipping Name: UN1950, Aerosols, 2.1, Limited Quantity DOT Technical Name: None DOT Hazard Class: 2.1 UN Number: UN1950 DOT Labels Required (49CFR172.101): LTD QTY

IMDG Shipping Description: UN1950, Aerosols, 2.1, FP -17 C, Limited Quantity, Marine Pollutant ID Number: UN1950 Hazard Class: 2.1 Packing Group: None Labels Required: None Marking Required: Limited Quantity Mark Placards Required: Limited Quantity and Marine Pollutant Mark On Transport Containers

ICAO/IATA Proper shipping name: Aerosol, Flammable Hazard Class: 2.1 Identification Number: UN 1950 Packing Group: None

#### Section 15 – Regulatory Information

#### Safety, health, and environmental regulations specific for the product in question.

CERCLA Hazardous Substances (Section 103)/RQ: None

SARA Hazard Category (311/312): Fire Hazard, Pressure Hazard, Acute Health

SARA 313: This product contains the following chemicals regulated under SARA Title III, section 313: None

**EPA TSCA Inventory:** All of the components of this product are listed on the TSCA inventory.

CALIFORNIA PROPOSITION 65: This product is not known to contain listed chemicals.

#### Section 16 – Other Information:

The information contained herein is based on data considered accurate, however, no warranty is expressed or implied regarding the accuracy of the data or the results obtained from the use of his product. Therefore, because the product may be used under conditions beyond our control, we assume no liability for its use.