

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.03.2015

Revision: 13.03.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: Vulcanizing Cement**
- **Article number:** 14-004, 14-008, 14-009, 14-020, 14-032, 14-041, 14-511, 14-512, 15-026
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Rubber compounding
- **1.3 Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
31 Incorporated
100 Enterprise Dr.
Newcomerstown, OH 43832
Phone: (740) 498-8324
- **1.4 Emergency telephone number:**
ChemTel Inc.
(800)255-3924, +1 (813)248-0585

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
Classifications listed also are applicable to the OSHA GHS Hazard Communication Standard (29CFR1910.1200).
The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H400, H410.



flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



environment

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

(Contd. on page 2)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.03.2015


Revision: 13.03.2015

Trade name: **Vulcanizing Cement**


(Contd. of page 1)

STOT SE 3 H336 May cause drowsiness or dizziness.

· **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**

 Xn; Harmful

R65: Harmful: may cause lung damage if swallowed.

 Xi; Irritant


R38: Irritating to skin.

 Xi; Sensitising

R43: May cause sensitisation by skin contact.

 F; Highly flammable

R11: Highly flammable.

 N; Dangerous for the environment

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67: Vapours may cause drowsiness and dizziness.

· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The substance is classified and labelled according to the Globally Harmonized System within the United States (GHS).

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



This pictogram only applicable for EU regulations. Not for use in the United States (OSHA GHS).



GHS02 GHS07 GHS08 GHS09

· **Signal word** Danger

· **Hazard-determining components of labelling:**

heptane

Natural rubber latex

(Contd. on page 3)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.03.2015

Revision: 13.03.2015

Trade name: Vulcanizing Cement

(Contd. of page 2)

· **Hazard statements**

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H410.

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

H410 Very toxic to aquatic life with long lasting effects.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261 Avoid breathing mist/vapours/spray.

P280 Wear protective gloves / eye protection.

P233 Keep container tightly closed.

P264 Wash thoroughly after handling.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P370+P378 In case of fire: Use foam, powder, or carbon dioxide for extinction.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P331 Do NOT induce vomiting.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Hazard description:**

· **WHMIS-symbols:**

B2 - Flammable liquid

D2B - Toxic material causing other toxic effects



· **NFPA ratings (scale 0 - 4)**



Health = 2

Fire = 3

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



HEALTH 2 Health = 2

FIRE 3 Fire = 3

REACTIVITY 0 Reactivity = 0

· **HMIS Long Term Health Hazard Substances**

None of the ingredients are listed.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

(Contd. on page 4)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.03.2015

Revision: 13.03.2015

Trade name: Vulcanizing Cement

(Contd. of page 3)

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 142-82-5 EINECS: 205-563-8 Index number: 601-008-00-2	heptane Xn R65; Xi R38; F R11; N R50/53 R67 ----- Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Skin Irrit. 2, H315; STOT SE 3, H336	>70%
CAS: 9006-04-6 EINECS: 232-689-0	Natural rubber latex Xi R43 ----- Skin Sens. 1B, H317	10-20%

· Additional information:

For the wording of the listed risk phrases refer to section 16.

For the listed ingredients, the identity and exact percentages are being withheld as a trade secret.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Take affected persons out into the fresh air.

· After inhalation:

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

In case of irregular breathing or respiratory arrest provide artificial respiration.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately remove any clothing soiled by the product.

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Remove contact lenses if worn, if possible.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

A person vomiting while laying on their back should be turned onto their side.

(Contd. on page 5)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.03.2015

Revision: 13.03.2015

Trade name: Vulcanizing Cement

(Contd. of page 4)

· **4.2 Most important symptoms and effects, both acute and delayed**

Breathing difficulty
Dizziness
Coughing
Allergic reactions
Gastric or intestinal disorders when ingested.
Irritant to skin and mucous membranes.
Irritant to eyes.
Disorientation

· **Hazards**

Danger of pulmonary oedema.
Danger of pneumonia.
Danger of impaired breathing.
May be harmful in contact with skin.
May be harmful if inhaled.
Repeated exposure may cause skin dryness or cracking.
Vapours may cause drowsiness and dizziness.

· **4.3 Indication of any immediate medical attention and special treatment needed**

If swallowed, gastric irrigation with added, activated carbon.
If necessary oxygen respiration treatment.
If swallowed or in case of vomiting, danger of entering the lungs.
Later observation for pneumonia and pulmonary oedema.

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.

· **For safety reasons unsuitable extinguishing agents:** Water

· **5.2 Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

· **5.3 Advice for firefighters**

· **Protective equipment:**

Wear self-contained respiratory protective device.
Wear fully protective suit.

· **Additional information** Eliminate all ignition sources if safe to do so.

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

Protect from heat.

· **6.2 Environmental precautions:**

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

(Contd. on page 6)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.03.2015

Revision: 13.03.2015

Trade name: Vulcanizing Cement

(Contd. of page 5)

- **6.3 Methods and material for containment and cleaning up:**
Allow to solidify. Pick up mechanically.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Pick up mechanically.
Dispose contaminated material as waste according to item 13.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Prevent formation of aerosols.
Avoid splashes or spray in enclosed areas.
Use only in well ventilated areas.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Flammable gas-air mixtures may form in empty receptacles.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Provide ventilation for receptacles.
Avoid storage near extreme heat, ignition sources or open flame.
- **Information about storage in one common storage facility:**
Store away from foodstuffs.
Store away from oxidising agents.
- **Further information about storage conditions:**
Store in cool, dry conditions in well sealed receptacles.
Keep container tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

Ingredients with limit values that require monitoring at the workplace:	
142-82-5 heptane	
IOELV (EU)	Long-term value: 2085 mg/m ³ , 500 ppm
PEL (USA)	Long-term value: 2000 mg/m ³ , 500 ppm

(Contd. on page 7)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.03.2015

Revision: 13.03.2015

Trade name: Vulcanizing Cement

(Contd. of page 6)

REL (USA)	Long-term value: 350 mg/m ³ , 85 ppm Ceiling limit: 1800* mg/m ³ , 440* ppm *15-min
TLV (USA)	Short-term value: 2050 mg/m ³ , 500 ppm Long-term value: 1640 mg/m ³ , 400 ppm
EL (Canada)	Short-term value: 500 ppm Long-term value: 400 ppm
EV (Canada)	Short-term value: 2,045 mg/m ³ , 500 ppm Long-term value: 1,635 mg/m ³ , 400 ppm
9006-04-6 Natural rubber latex	
TLV (USA)	Long-term value: 0,0001* mg/m ³ Skin; (SEN) NIC-DSEN, RSEN;* inh. fraction
EL (Canada)	Long-term value: 0,001 mg/m ³ inhalable, Skin; S
EV (Canada)	Long-term value: 0,001 mg/m ³ as total proteins, inhalable, Skin
108-87-2 methylcyclohexane	
PEL (USA)	Long-term value: 2000 mg/m ³ , 500 ppm
REL (USA)	Long-term value: 1600 mg/m ³ , 400 ppm
TLV (USA)	Long-term value: 1610 mg/m ³ , 400 ppm
EL (Canada)	Long-term value: 400 ppm
EV (Canada)	Long-term value: 1,600 mg/m ³ , 400 ppm

- **DNELs** No further relevant information available.
- **PNECs** No further relevant information available.
- **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

· **Personal protective equipment:**

· **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· **Respiratory protection:**

Not required under normal conditions of use.

Use suitable respiratory protective device when high concentrations are present.

Use suitable respiratory protective device when aerosol or mist is formed.

For spills, respiratory protection may be advisable.

NIOSH or EN approved organic vapor respirator equipped with a dust/mist prefilter should be used.

· **Protection of hands:**



Protective gloves

(Contd. on page 8)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.03.2015

Revision: 13.03.2015

Trade name: Vulcanizing Cement

(Contd. of page 7)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Safety glasses

- **Body protection:** Protective work clothing

- **Limitation and supervision of exposure into the environment**

No further relevant information available.

- **Risk management measures**

See Section 7 for additional information.

No further relevant information available.

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:	Liquid
Colour:	Cloudy
Odour:	Solvent-like
Odour threshold:	Not determined.
pH-value:	Not determined.

- **Change in condition**

Melting point/Melting range:	Not Determined.
Boiling point/Boiling range:	93 °C (199 °F)

- **Flash point:** 0 °C (32 °F)

- **Flammability (solid, gaseous):** Not applicable.

- **Auto/Self-ignition temperature:** 215 °C (419 °F)

- **Decomposition temperature:** Not determined.

- **Self-igniting:** Product is not self-igniting.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

(Contd. on page 9)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.03.2015

Revision: 13.03.2015

Trade name: Vulcanizing Cement

(Contd. of page 8)

- **Explosion limits:**
 - Lower:** 1,1 Vol %
 - Upper:** 6,7 Vol %
- **Vapour pressure at 20 °C (68 °F):** 48 hPa (36 mm Hg)
- **Density at 20 °C (68 °F):** 0,77 g/cm³ (6,426 lbs/gal)
- **Relative density** Not determined.
- **Vapour density** Not determined.
- **Evaporation rate** Not determined.
- **Solubility in / Miscibility with water:** Not miscible or difficult to mix.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
 - Dynamic:** Not determined.
 - Kinematic:** Not determined.
- **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions**
Flammable.
Reacts violently with oxidising agents.
Used empty containers may contain product gases which form explosive mixtures with air.
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.
Toxic fumes may be released if heated above the decomposition point.
- **10.4 Conditions to avoid**
Keep away from heat and direct sunlight.
Keep ignition sources away - Do not smoke.
Store away from oxidising agents.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:**

· LD/LC50 values relevant for classification:		
142-82-5 heptane		
Oral	LD50	> 5000 mg/kg (rat) (Estimate)

(Contd. on page 10)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.03.2015

Revision: 13.03.2015

Trade name: Vulcanizing Cement

(Contd. of page 9)

Inhalative	LC50/4h	103 mg/l (rat)
------------	---------	----------------

- **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.

- **on the eye:** Irritating effect.

- **Sensitisation:** Sensitisation possible through skin contact.

- **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

Danger through skin adsorption.

Inhalation of concentrated vapours as well as oral intake will lead to anaesthesia-like conditions and headache, dizziness, etc.

Toxic and/or corrosive effects may be delayed up to 24 hours.

- **Acute effects (acute toxicity, irritation and corrosivity):**

May be harmful if swallowed.

May be harmful in contact with skin.

May be harmful if inhaled.

Vapours have narcotic effect.

May be fatal if swallowed and enters airways.

Causes skin and eye irritation.

- **Sensitisation:** May cause an allergic skin reaction.

- **Repeated dose toxicity:**

Repeated exposure may cause skin dryness or cracking.

Repeated exposures may result in skin and/or respiratory sensitivity.

SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:** Toxic for aquatic organisms

- **12.2 Persistence and degradability** Easily biodegradable

- **12.3 Bioaccumulative potential** No further relevant information available.

- **12.4 Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Due to available data on eliminability/decomposition and bioaccumulation potential a prolonged damage of the environment is unlikely.

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

- **12.5 Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **12.6 Other adverse effects** No further relevant information available.

(Contd. on page 11)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.03.2015

Revision: 13.03.2015

Trade name: Vulcanizing Cement

(Contd. of page 10)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN-Number

DOT, ADR, IMDG, IATA

UN1206

14.2 UN proper shipping name

DOT

Heptanes

ADR

1206 HEPTANES, ENVIRONMENTALLY
HAZARDOUS
HEPTANES

IMDG, IATA

14.3 Transport hazard class(es)

DOT



Class

3 Flammable liquids.

Label

3

ADR



Class

3 (F1) Flammable liquids.

Label

3

IMDG, IATA



Class

3 Flammable liquids.

Label

3

(Contd. on page 12)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.03.2015

Revision: 13.03.2015

Trade name: Vulcanizing Cement

(Contd. of page 11)

· 14.4 Packing group	II
· DOT, ADR, IMDG, IATA	
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· Special marking (ADR):	Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Danger code (Kemler):	33
· EMS Number:	F-E,S-D
· 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	

· ADR	
· Limited quantities (LQ)	1L
· Transport category	2
· Tunnel restriction code	D/E
· UN "Model Regulation":	UN1206, HEPTANES, ENVIRONMENTALLY HAZARDOUS, 3, II

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- United States (USA)
- SARA

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65 (California):

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· Carcinogenic Categories

· EPA (Environmental Protection Agency)

142-82-5 | heptane

D

(Contd. on page 13)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.03.2015

Revision: 13.03.2015

Trade name: Vulcanizing Cement

(Contd. of page 12)

· IARC (International Agency for Research on Cancer)

None of the ingredients are listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients are listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

· Canada

· Canadian Domestic Substances List (DSL)
--

All ingredients are listed.

· Canadian Ingredient Disclosure list (limit 0.1%)

None of the ingredients are listed.

· Canadian Ingredient Disclosure list (limit 1%)

142-82-5 heptane

· Other regulations, limitations and prohibitive regulations

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.
--

· Substances of very high concern (SVHC) according to REACH, Article 57
--

None of the ingredients are listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.
--

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H336 May cause drowsiness or dizziness.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.

R11 Highly flammable.

R38 Irritating to skin.

R43 May cause sensitisation by skin contact.
--

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.
--

R67 Vapours may cause drowsiness and dizziness.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
--

IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 14)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 13.03.2015

Revision: 13.03.2015

Trade name: Vulcanizing Cement

(Contd. of page 13)

DOT: US Department of Transportation
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
WHMIS: Workplace Hazardous Materials Information System (Canada)
VOC: Volatile Organic Compounds (USA, EU)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
Flam. Liq. 2: Flammable liquids, Hazard Category 2
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1
Skin Sens. 1B: Sensitisation - Skin, Hazard Category 1B
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
Asp. Tox. 1: Aspiration hazard, Hazard Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1

Sources

SDS Prepared by:
ChemTel Inc.
1305 North Florida Avenue
Tampa, Florida USA 33602-2902
Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573
Website: www.chemtelinc.com