MATERIAL SAFETY DATA SHEET

NOTE: BLANK SPACES ARE NOT I	PERMITT	ED. IF ANY ITE	EM IS NOT APPLICABLE,	THE SPACE MUS	T BE MARKED	TO INDICATE THAT.		
IDENTITY		PART NO.						
(As shown on Label or package) PLASTI DIP and PLASTI DIP U			UV (F-698, 819, 820)	IF APPLICAL	BLE			
SECTION I								
MANUFACTURER'S EMERGENCY PHONE No.								
NAME Plasti Dip Internati		USA only: 1-800-424-9300 INT'L: 703-527-3887						
ADDRESS (NUMBER, STREET, CITY	Y, STATE	AND ZIP CODE		REVISION# 0004				
3920 Pheasant Ridge Drive			,					
						MANUFACTURER'S PHONE		
Blaine, MN 55449				No. FOR INFORMATION 1-763-785-2156				
				DATE MSDS				
				WAS PREPARED May 25, 2007				
SECTION II - HAZARDOUS INGREI	DIENTS II	NFORMATION.	All Health Hazards which co	omprise 1% or gre	ater of the comp	osition and all		
carcinogens if 0.1% of the composition	or greater	•		-	_			
HAZARDOUS COMPONENTS CHE	MICAL	% Wt.	CAS NO.	OSHA	ACGIH	OTHER LIMITS		
and IDENTITY AND COMMON NA	ME (S)	(OPTIONAL)		PEL	TLV	RECOMMEND		
VM&P Naphtha		36.5 – 37.1	64742-89-8	300 ppm	300 ppm	None		
Hexane		18.2 – 18.6	110-54-3	500 ppm	50 ppm	None		
Toluene		14.6 – 14.8	108-88-3	200 ppm	50 ppm	None		
Methyl Ethyl Ketone		3.5 - 3.7	78-93-3	200 ppm	200 ppm	None		
Resins		25.8 – 27.1	N/A	N/A	N/A	None		
SECTION III - PHYSICAL / CHEMIC	CAL CHA			•	•	•		
BOILING		SPECIFIC GRAVITY (H ₂ 0 =1)		APPROXIMATE WEIGHT PER GALLON (LBS)				
POINT 149-285°F		0.79 - 0.83		6.60 – 6.90				
VAPOR PRESSURE	VAPOR	DENSITY		EVAPORATION RATE				
125 mmHg @ 20°C	(AIR = 1)	1) Heavier than air	r	(BUTYL ACE	(BUTYL ACETATE =1) >1.0			
SOLUBILITY IN WATER	% VOL	ATILE 72.8 – 74	1.8	OTHER				
Insoluble	VOC LBS./GAL 4.9-5.0			(IF ANY) None				
APPEARANCE								
AND ODOR Various colors, Honey	Like Subs	tance - Characteri	stic Odor					
SECTION IV-FIRE AND EXPLOSION	N HAZAR	D DATA						
FLASH POINT -10.0°F		Fl	LAMMABLE LIMITS	LEL	U	EL		
(METHOD USED) TCC				0.9				
EXTINGUISHING		•		•	•			
MEDIA Carbon Dioxide, Dry	Chemical,	or Foam						
SPECIAL FIRE								
FIGHTING PROCEDURES Self cont	tained brea	thing apparatus wi	th a full face piece, operated i	n pressure demand of	or other positive p	ressure mode.		
UNUSUAL FIRE AND								
EXPLOSION HAZARDS This material is flammable and may be ignited by heat, sparks, flame or static electricity.								
HAZARDOUS PRODUCTS FORMED BY								
FIRE OR THERMAL DECOMPOSITION Carbon Dioxide and/or Carbon Monoxide								
EXPLOSIVE LIMITS								
(% BY VOLUME IN AIR) 0.9 – 11.5								
SECTION V - OPTIONAL HAZARD RATINGS IDENTIFICATION								
HAZARD RATING			National Fire Protection	Association (NFP	A)			
4-EXTREME								
3-HIGH			FIRE <u>3</u> REACTIVITY <u>0</u> .					
2-MODERATE								
1-SLIGHT 0-INSIGNIFICANT			HEALTH 2 CDEC	HEALTH 2 SPECIAL HAZARDS None .				
**SEE SECTION IV			HEALTH 2 SPECIAL HAZARDS NOIR .					

SECTION VI - REACTIVIT	Y AND STABILITY DATA					
STABILITY UNSTA						
	rials to Avoid) Strong acids, bases, oxidizing		s with alkali metals and halogens.			
	ITION OR BY PRODUCTS Carbon Monoxid					
HAZARDOUS POLYMERIZATION	MAY OCCUR	CONDITIONS TO	AVOID eat, sparks, flame or static electricity.			
	WILL NOT OCCUR X	May be ignited by ne	at, sparks, fiame or static electricity.			
SECTION VII - HEALTH H		C INCECTIONS	NEG ENEGO VEG			
ROUTES OF ENTRY	INHALATION? YES SKIN? YE	S INGESTION?	? YES EYES? YES			
HEALTH ACUTE HAZARDS CHRONIC	X X					
CARCINOGENICITY: No	11					
SIGNS AND						
SYMPTOMS OF	Headache, Dizziness, Drowsiness, Fatigue,	Irregular Heartbeat, Sk	kin and Eye Irritation.			
EXPOSURE						
MEDICAL CONDITIONS G	ENERALLY AGGRAVATED BY EXPOSU	RE				
EMEDGENCY AND	In a still a Control Physician and Price Con	1 T				
EMERGENCY AND FIRST AID	Ingestion: Contact Physician or Poison Con Inhalation: Remove to fresh air. Administe		Description if No.			
PROCEDURES	Eye Contact: Flush with large amounts of w	,,,	1 ,			
I ROCEDURES	Skin: Wash with soap and water.	vater. If fifthation pers	ists, contact i hysician.			
SECTION VIII - PRECAUT	IONS FOR SAFE HANDLING AND USE					
SECTION VIII - I RECALCIA	OND FOR SHIE IMMODELING HIND COL					
STEPS TO BE TAKEN	Wipe up with floor absorbent. Transfer to h	ood. Prevent run-off	to sewers.			
IN CASE MATERIAL IS		o maintain exposure below PEL's. Use sand or other material to dam or contain				
RELEASED OR SPILLED	spills. If large spill, notify appropriate state					
		•				
WASTE DISPOSAL METHO	ODS Dispose of product in accordance with loc	al, county, state and fe	ederal regulations.			
PRECAUTIONS TO BE			losed. Use with adequate ventilation. Keep away from sparks, flame and heat			
TAKEN IN HANDLING	sources and store in a cool area. Avoid inha	lation of vapors and p	ersonal contact with liquid product.			
AND STORAGE	Use good personal hygiene practices.					
OTHER	Keen Container Closed When Not In Use	Containers should be d	licposed of in an environmentally safe manner in accordance			
PRECAUTIONS	Keep Container Closed When Not In Use. Containers should be disposed of in an environmentally safe manner in accordance					
PRECAUTIONS with Governmental Regulations. SECTION IX - CONTROL MEASURES						
	ION (SPECIFY TYPE) Depending on the Airbo	orne concentration	PROTECTIVE GLOVES			
	ite NIOSH approved cartridge or supplied air eq		Impervious Gloves			
VENTILATION LOCAL	EXHAUST Supplemental (if needed)	F	SPECIAL None			
	ANICAL (GENERAL) To maintain exposure	below PEL's	OTHER None			
EYE PROTECTION			OTHER PROTECTIVE CLOTHING OR EQUIPMENT			
Chemical splash goggles, or ap	proved eye protection.		Chemcial Apron/Eye bath/Safety Shower			
WORK HYGIENIC PRACTICES Wash thoroughly after handling.						
SECTION X - TRANSPORTATION INFORMATION						
DOT PROPER SHIPPING N	CLASS 3					
DOT UN NUMBER UN 113	39	DOT PACKING GROUP II				
IATA PROPER SHIPPING NAME Coating Solution		IATA HAZARD CLASS 3				
IATA UN NUMBER UN 113	9	IATA PACKING	GROUP II			
SECTION XI - 313 SUPPLIER NOTIFICATION						
THIS PRODUCT CONTAINS THE FOLLOWING CHEMICALS SUBJECT TO REPORTING REQUIREMENTS OF SECTION 313 OF THE						
		CT OF 1986, 40 CFF	R 372, (see table on page 1 for CAS # and percent by weight).			
Hexane, Toluene, and Methyl Ethyl Ketone WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALLEODNIA TO CALISE CANCED AND RIDTH						
WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS. OR OTHER REPRODUCTIVE HARM						

This is the "back" when printed in duplex. Page 2 of 2 pages if not duplex.

Prepared By:	Mark Kenow	